

## RF Exposure Evaluation

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## Test Result of RF Exposure Evaluation

Band	Frequency	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Verdict
2.4G	2441MHz	-17.2584	0.0188	-1.1	0.0000029	1.0	PASS
2.4G WIFI	2437MHz	17.9	61.66	0.5	0.0138	1.0	
5.2G WIFI	5180MHz	17.06	50.82	-2.4	0.0058	1.0	
5.3G WIFI	5280MHz	16.83	48.19	-0.7	0.0082	1.0	
5.6G WIFI	5500MHz	15.84	38.37	0.9	0.0094	1.0	
5.8G WIFI	5825MHz	18.7	74.13	-1.9	0.0095	1.0	

Where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10^{((\text{dBuV/m})/20)/10^6}$

d = measurement distance in meters (m) ---3m

Field strength =70.98dBuV/m @3m

Ant gain =0.3dBi, so gt =0.78

So pt =  $(E \times d)^2/30 \times gt = \{ [10^{79.06/20}/10^6 \times 3]^2/30 \times 0.78 \} \times 1000 \text{ mW} = 0.0188 \text{ mW}$

Remark:

For the maximum simultaneous transmission MPE:

2.4G+WIFI 2.4G/WIFI 5G: 0.0069 < 1

The max power density is less than MPE exempt limit, so it is compliance.