

TEST REPORT

Applicant: HANSHOW TECHNOLOGY CO.,LTD.

Address of Applicant: Building 1(IF podium building and 4F) and Building 5 (7F) in Jiaxing Photovolta High-tech Park, No.1288 Kanghe Rd., Xiuzhou District, Jiaxing, Zhejiang, China

Manufacturer: HANSHOW TECHNOLOGY CO.,LTD.

Address of Manufacturer: Building 1(IF podium building and 4F) and Building 5 (7F) in Jiaxing Photovolta High-tech Park, No.1288 Kanghe Rd., Xiuzhou District, Jiaxing, Zhejiang, China

Equipment Under Test (EUT)

Product Name: N5 Shelf Camera

Model No.: N5-FS, N5-FM, N5-FL

FCC ID: 2AYMH-N5

Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407

Date of sample receipt: March 26, 2025

Date of Test: April 16, 2025-May 30, 2025

Date of report issue: May 30, 2025

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:


Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	May 30, 2025	Original

Prepared By:




Date:

May 30, 2025

Project Engineer

Check By:



Reviewer

Date:

May 30, 2025

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	6
5.3 TEST FACILITY	6
5.4 TEST LOCATION	6
5.5 DESCRIPTION OF SUPPORT UNITS	6
5.6 DEVIATION FROM STANDARDS	6
5.7 ADDITIONAL INSTRUCTIONS	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA	9
7.1 ANTENNA REQUIREMENT:	9
7.2 EMISSION BANDWIDTH	10
7.3 MAXIMUM CONDUCTED OUTPUT POWER	11
7.4 POWER SPECTRAL DENSITY	12
7.5 BAND EDGE	13
7.6 RADIATED EMISSION	19
7.7 FREQUENCY STABILITY	36
8 TEST SETUP PHOTO	38
9 EUT CONSTRUCTIONAL DETAILS	38

4 Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203	PASS
AC Power Line Conducted Emission	FCC part 15.207	N/A
Emission Bandwidth	FCC part 15.407	PASS
Maximum Conducted Output Power	FCC part 15.407(a)(1)	PASS
Power Spectral Density	FCC part 15.407(a)(1)	PASS
Undesirable Emission	FCC part 15.407(b), 15.205/15.209	PASS
Radiated Emission	FCC part 15.205/15.209	PASS
Band Edge	FCC part 15.407(b)(1)	PASS
Frequency Stability	FCC part 15.407(g)	PASS

Remark:

Pass: The EUT complies with the essential requirements in the standard.

N/A: Not applicable.

4.1 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	N5 Shelf Camera				
Model No.:	N5-FS, N5-FM, N5-FL				
Test Model No:	N5-FS				
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color and model name for commercial purpose.					
Test sample(s) ID:	GTS2025030422-1				
Sample(s) Status:	Engineer sample				
S/N:	N5-FS				
Operation Frequency:	Band	Mode	Frequency Range (MHz)	Number of channels	
	U-NII Band I	IEEE 802.11a	5180-5240	4	
		IEEE 802.11n/ac/ax 20MHz	5180-5240	4	
	U-NII Band II-2A	IEEE 802.11a	5260-5320	4	
		IEEE 802.11n/ac/ax 20MHz	5260-5320	4	
	U-NII Band II-2C	IEEE 802.11a	5500-5700	11	
		IEEE 802.11n/ac/ax 20MHz	5500-5700	11	
Modulation technology:	OFDM				
Antenna Type:	FPC Antenna				
Antenna gain:	Band I: -2.4dBi Band II-2A: -0.7dBi Band II-2C: 0.9dBi				
Power supply:	DC 5-7.5V				

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

Channel list for 802.11a/n(HT20)/ac(HT20)/ax(HE20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	40	5200MHz	44	5220MHz	48	5240MHz
52	5260MHz	56	5280MHz	60	5300MHz	64	5320MHz
100	5500MHz	104	5520MHz	108	5540MHz	112	5560MHz
116	5580MHz	120	5600MHz	124	5620MHz	128	5640MHz
132	5660MHz	136	5680MHz	140	5700MHz		

5.2 Test mode

Transmitting mode	Keep the EUT in transmitting with modulation..
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11a/n/ac (HT20) /ax(HE20)	6/6.5 Mbps

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing .

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.4 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number
Lenovo Thinkpad	Notebook PC	4286-PE9	N/A

5.6 Deviation from Standards

None.

5.7 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 11, 2025	Apr. 10, 2026
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 12, 2025	Apr. 11, 2026
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 12, 2025	Apr. 11, 2026
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul. 02, 2024	Jul. 01, 2025
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.16, 2024	Nov.15, 2025
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2025	Apr. 10, 2026
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2025	Apr. 10, 2026
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2025	Apr. 10, 2026
11	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 11, 2025	Mar. 10, 2026
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2025	Apr. 10, 2026
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 13, 2024	Nov. 12, 2025
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2025	Apr. 10, 2026
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 15, 2025	Apr. 14, 2026
16	RE cable 1	GTS	N/A	GTS675	Jul. 02, 2024	Jul. 01, 2025
17	RE cable 2	GTS	N/A	GTS676	Jul. 02, 2024	Jul. 01, 2025
18	RE cable 3	GTS	N/A	GTS677	Jul. 02, 2024	Jul. 01, 2025
19	RE cable 4	GTS	N/A	GTS678	Jul. 02, 2024	Jul. 01, 2025
20	RE cable 5	GTS	N/A	GTS679	Jul. 02, 2024	Jul. 01, 2025
21	RE cable 6	GTS	N/A	GTS680	Jul. 02, 2024	Jul. 01, 2025
22	RE cable 7	GTS	N/A	GTS681	Jul. 05, 2024	Jul. 04, 2025
23	RE cable 8	GTS	N/A	GTS682	Jul. 05, 2024	Jul. 04, 2025
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 11, 2025	Apr. 10, 2026
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 12, 2025	Apr. 11, 2026
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 11, 2025	Apr. 10, 2026
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 11, 2025	Apr. 10, 2026
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Power Meter	Keysight	N1924A	GTS673	Apr. 11, 2025	Apr. 10, 2026
7	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 11, 2025	Apr. 10, 2026
8	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 11, 2025	Apr. 10, 2026
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 11, 2025	Apr. 10, 2026
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 15, 2025	Apr. 14, 2026
11	EXA Signal Analyzer	Keysight	N9010B	MY60241168	Nov. 02, 2024	Nov. 01, 2025


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Aug. 17, 2024	Aug. 16, 2025

7 Test results and Measurement Data

7.1 Antenna requirement:


Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The antenna is FPC antenna, reference to the appendix II for details	

7.2 Emission Bandwidth

Test Requirement :	FCC Part15 E Section 15.407
Test Method :	ANSI C63.10:2013 & KDB 789033 D02 v02r01
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test procedure:	According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix.

7.3 Maximum Conducted Output Power

Test Requirement	FCC Part15 E Section 15.407	
Test Method :	ANSI C63.10:2013 & KDB 789033 D02 v02r01	
Limit:	Frequency band (MHz)	Limit
	5150-5250	$\leq 1W(30dBm)$ for master device
		$\leq 250Mw(23.98dBm)$ for client device
	5250-5350	$\leq 250Mw(23.98dBm)$ for client device or $11dBm+10\log B^*$
	5470-5725	$\leq 250Mw(23.98dBm)$ for client device or $11dBm+10\log B^*$
Remark: *Where B is the 26Db emission bandwidth in MHz. The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.		
Test setup:		
Duty Cycle set up:	RBW=VBW=8MHz	
Test procedure:	Measurement using an RF average power meter (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied a) The EUT is configured to transmit continuously or to transmit with a constant duty cycle. b) At all times when the EUT is transmitting, it must be transmitting at its maximum power control level. c) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five. (ii) If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section B). (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter. (iv) Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10\log(1/0.25)$ if the duty cycle is 25 percent).	
Test Instruments:	Refer to section 6.0 for details	
Test mode:	Refer to section 5.2 for details	
Test results:	Pass	

Measurement Data: The detailed test data see Appendix.


7.4 Power Spectral Density

Test Requirement:	FCC Part15 E Section 15.407	
Test Method :	ANSI C63.10:2013 & KDB 789033 D02 v02r01	
Limit:	Frequency band (MHz)	Limit
	5150-5250	≤17dBm in 1MHz for master device
		≤11dBm in 1MHz for client device
	5250-5350	≤11dBm in 1MHz for client device
	5470-5725	≤11dBm in 1MHz for client device
Remark: The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.		
Test setup:		
Test procedure:	1) Create an average power spectrum for the EUT operating mode being tested by following the instructions in section E)2) for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power...". 2) Use the peak search function on the instrument to find the peak of the spectrum. 3) Make the following adjustments to the peak value of the spectrum, if applicable: a) If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum. b) If Method SA-3 Alternative was used and the linear mode was used in step E)2)g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging. 4) The result is the PSD.	
Test Instruments:	Refer to section 6.0 for details	
Test mode:	Refer to section 5.2 for details	
Test results:	Pass	

Measurement Data: The detailed test data see Appendix.

7.5 Band Edge

Test Requirement:	FCC Part15 E Section 15.407 and 5.205																								
Test Method:	ANSI C63.10:2013																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>120KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>AV</td><td>1MHz</td><td>3MHz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	AV	1MHz	3MHz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	AV	1MHz	3MHz	Average Value																					
Limit:	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>68.2</td><td>Peak Value</td></tr></table> Undesirable emission limits: (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band. (3) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	68.2	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	68.2	Peak Value																							
Test Procedure:	a. The EUT was placed on the top of a rotating table 1.5 m above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.																								

Test setup:	For radiated emissions above 1GHz 
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
4. According to KDB 789033 D02 v02r01 section G) 1) (d), for For measurements above 1000 MHz @ 3m distance, the limit of field strength is computed as follows:
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2;$
For example, if EIRP = -27dBm
 $E[\text{dBuV/m}] = -27 + 95.2 = 68.2\text{dBuV/m}.$

Measurement Data:

Worse case mode:		802.11a		Test Frequency:		5180MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5150	49.86	-3.63	46.23	68.2	-21.97	peak	H
5150	43.31	-3.63	39.68	54	-14.32	AVG	H
5150	52.35	-3.63	48.72	68.2	-19.48	peak	V
5150	41.86	-3.63	38.23	54	-15.77	AVG	V
Worse case mode:		802.11a		Test Frequency:		5320MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5350	51.08	-3.59	47.49	68.2	-20.71	peak	H
5350	42.70	-3.59	39.11	54	-14.89	AVG	H
5350	45.99	-3.59	42.40	68.2	-25.80	peak	V
5350	41.12	-3.59	37.53	54	-16.47	AVG	V
Worse case mode:		802.11a		Test Frequency:		5500MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5460	51.13	-3.54	47.59	68.2	-20.61	peak	H
5460	41.69	-3.54	38.15	54	-15.85	AVG	H
5460	46.89	-3.54	43.35	68.2	-24.85	peak	V
5460	41.26	-3.54	37.72	54	-16.28	AVG	V
Worse case mode:		802.11a		Test Frequency:		5700MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5725	45.98	-3.45	42.53	68.2	-25.67	peak	H
5725	41.04	-3.45	37.59	54	-16.41	AVG	H
5725	49.18	-3.45	45.73	68.2	-22.47	peak	V
5725	41.75	-3.45	38.30	54	-15.70	AVG	V


Worse case mode:		802.11n(HT20)		Test Frequency:		5180MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5150	49.89	-3.63	46.26	68.2	-21.94	peak	H
5150	43.35	-3.63	39.72	54	-14.28	AVG	H
5150	52.38	-3.63	48.75	68.2	-19.45	peak	V
5150	41.91	-3.63	38.28	54	-15.72	AVG	V
Worse case mode:		802.11n(HT20)		Test Frequency:		5320MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5350	51.10	-3.59	47.51	68.2	-20.69	peak	H
5350	42.72	-3.59	39.13	54	-14.87	AVG	H
5350	46.01	-3.59	42.42	68.2	-25.78	peak	V
5350	41.14	-3.59	37.55	54	-16.45	AVG	V
Worse case mode:		802.11n(HT20)		Test Frequency:		5500MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5460	51.17	-3.54	47.63	68.2	-20.57	peak	H
5460	41.72	-3.54	38.18	54	-15.82	AVG	H
5460	46.93	-3.54	43.39	68.2	-24.81	peak	V
5460	41.29	-3.54	37.75	54	-16.25	AVG	V
Worse case mode:		802.11n(HT20)		Test Frequency:		5700MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5725	46.00	-3.45	42.55	68.2	-25.65	peak	H
5725	41.06	-3.45	37.61	54	-16.39	AVG	H
5725	49.20	-3.45	45.75	68.2	-22.45	peak	V
5725	41.77	-3.45	38.32	54	-15.68	AVG	V



Worse case mode:		802.11ac(HT20)		Test Frequency:		5180MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5150	49.43	-3.63	45.80	68.2	-22.40	peak	H
5150	42.73	-3.63	39.10	54	-14.90	AVG	H
5150	51.89	-3.63	48.26	68.2	-19.94	peak	V
5150	41.17	-3.63	37.54	54	-16.46	AVG	V
Worse case mode:		802.11ac(HT20)		Test Frequency:		5320MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5350	50.77	-3.59	47.18	68.2	-21.02	peak	H
5350	42.35	-3.59	38.76	54	-15.24	AVG	H
5350	45.65	-3.59	42.06	68.2	-26.14	peak	V
5350	40.73	-3.59	37.14	54	-16.86	AVG	V
Worse case mode:		802.11ac		Test Frequency:		5500MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5460	50.52	-3.54	46.98	68.2	-21.22	peak	H
5460	41.22	-3.54	37.68	54	-16.32	AVG	H
5460	46.19	-3.54	42.65	68.2	-25.55	peak	V
5460	40.70	-3.54	37.16	54	-16.84	AVG	V
Worse case mode:		802.11ac		Test Frequency:		5700MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5725	45.61	-3.45	42.16	68.2	-26.04	peak	H
5725	40.75	-3.45	37.30	54	-16.70	AVG	H
5725	48.77	-3.45	45.32	68.2	-22.88	peak	V
5725	41.44	-3.45	37.99	54	-16.01	AVG	V

Worse case mode:		802.11ax(HE20)		Test Frequency:		5180MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5150	49.51	-3.63	45.88	68.2	-22.32	peak	H
5150	42.81	-3.63	39.18	54	-14.82	AVG	H
5150	51.94	-3.63	48.31	68.2	-19.89	peak	V
5150	41.27	-3.63	37.64	54	-16.36	AVG	V
Worse case mode:		802.11ax(HE20)		Test Frequency:		5320MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5350	50.81	-3.59	47.22	68.2	-20.98	peak	H
5350	42.38	-3.59	38.79	54	-15.21	AVG	H
5350	45.68	-3.59	42.09	68.2	-26.11	peak	V
5350	40.77	-3.59	37.18	54	-16.82	AVG	V
Worse case mode:		802.11ax(HE20)		Test Frequency:		5500MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5460	50.60	-3.54	47.06	68.2	-21.14	peak	H
5460	41.27	-3.54	37.73	54	-16.27	AVG	H
5460	46.27	-3.54	42.73	68.2	-25.47	peak	V
5460	40.76	-3.54	37.22	54	-16.78	AVG	V
Worse case mode:		802.11ax(HE20)		Test Frequency:		5700MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
5725	45.65	-3.45	42.20	68.2	-26.00	peak	H
5725	40.78	-3.45	37.33	54	-16.67	AVG	H
5725	48.81	-3.45	45.36	68.2	-22.84	peak	V
5725	41.48	-3.45	38.03	54	-15.97	AVG	V

7.6 Radiated Emission

Test Requirement :	FCC Part15 C Section 15.209 and 15.205																												
Test Method :	ANSI C63.10: 2013																												
Test Frequency Range:	9kHz to 40GHz																												
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																												
Receiver setup:	Frequency	Detector	RBW	VBW	Value																								
	9kHz-150KHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value																								
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value																								
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value																								
	Above 1GHz	Peak	1MHz	3MHz	Peak Value																								
		AV	1MHz	3MHz	Average Value																								
Note: For Duty cycle ≥ 98%, average detector set as above For Duty cycle < 98%, average detector set as below: VBW ≥ 1 / T																													
Limit:	<table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100**</td><td>3</td></tr><tr><td>88-216</td><td>150**</td><td>3</td></tr><tr><td>216-960</td><td>200**</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table>					Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100**	3	88-216	150**	3	216-960	200**	3	Above 960	500	3
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																										
	0.009-0.490	2400/F(kHz)	300																										
	0.490-1.705	24000/F(kHz)	30																										
	1.705-30.0	30	30																										
	30-88	100**	3																										
	88-216	150**	3																										
	216-960	200**	3																										
	Above 960	500	3																										
	The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.																												
Test Procedure:	Substitution method was performed to determine the actual ERP emission levels of the EUT.																												
	The following test procedure as below:																												
	1>.Below 1GHz test procedure:																												
	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.																												
	2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.																												
	3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.																												
	4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.																												
	5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.																												
	6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using																												

	peak, quasi-peak or average method as specified and then reported in a data sheet. 2>.Above 1GHz test procedure: 1. On the test site as test setup graph above,the EUT shall be placed at the 0.8m support on the turntable and in the position closest to normal use as declared by the provider. 2. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter.The output of the test antenna shall be connected to the measuring receiver. 3. The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the transmitter under test. 4. The test antenna shall be raised and lowered from 1m to 4m until a maximum signal level is detected by the measuring receiver. Then the turntable should be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver. 5. Repeat step 4 for test frequency with the test antenna polarized horizontally. 6. Remove the transmitter and replace it with a substitution antenna 7. Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a nonradiating cable. With the antennas at both ends vertically polarized, and with the signal generator tuned to a particular test frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output. 8. Repeat step 7 with both antennas horizontally polarized for each test frequency. 9. Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps 7 and 8 by the power loss in the cable between the generator and the antenna, and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna by the following formula: $\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$ where: Pg is the generator output power into the substitution antenna.
Test setup:	For radiated emissions from 9kHz to 30MHz  For radiated emissions from 30MHz to 1GHz

	
For radiated emissions above 1GHz	
	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1012mbar
Test voltage:	AC 120V, 60Hz
Test results:	Pass

Remarks:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.


Measurement Data:

9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


30MHz~ 1GHz

Pre-scan all test modes, found worst case at 802.11a 5180MHz, and so only show the test result of it

Horizontal:

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
96.436	43.66	8.99	1.87	32.49	22.03	43.50	-21.47	QP
160.909	40.58	14.22	2.56	32.44	24.92	43.50	-18.58	QP
195.137	53.70	10.50	2.82	32.40	34.62	43.50	-8.88	QP
306.754	34.08	12.54	3.46	32.30	17.78	46.00	-28.22	QP
704.226	29.27	20.58	5.10	31.45	23.50	46.00	-22.50	QP
938.833	26.09	23.48	5.85	31.10	24.32	46.00	-21.68	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
63.092	48.26	11.49	1.54	32.35	28.94	40.00	-11.06	QP
86.200	54.48	9.08	1.73	32.44	32.85	40.00	-7.15	QP
100.934	54.51	9.39	1.94	32.50	33.34	43.50	-10.16	QP
160.909	43.49	14.22	2.56	32.44	27.83	43.50	-15.67	QP
188.413	52.99	10.76	2.77	32.41	34.11	43.50	-9.39	QP
706.700	33.00	20.63	5.11	31.44	27.30	46.00	-18.70	QP

Above 1GHz:

802.11a					Test Frequency: 5180MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	35.51	38.96	8.27	35.64	47.10	68.2	-21.10	Vertical
15540	34.45	38.4	10.57	35.35	48.07	68.2	-20.13	Vertical
10360	36.14	38.96	8.27	35.64	47.73	68.2	-20.47	Horizontal
15540	33.44	38.4	10.57	35.35	47.06	68.2	-21.14	Horizontal
10360	27.20	38.96	8.27	35.64	38.79	54	-15.21	Vertical
15540	28.18	38.4	10.57	35.35	41.80	54	-12.20	Vertical
10360	27.42	38.96	8.27	35.64	39.01	54	-14.99	Horizontal
15540	27.58	38.4	10.57	35.35	41.20	54	-12.80	Horizontal
802.11a					Test Frequency: 5200MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	35.93	39.01	8.29	35.67	47.56	68.2	-20.64	Vertical
15600	33.06	38.3	10.62	35.36	46.62	68.2	-21.58	Vertical
10400	36.61	39.01	8.29	35.67	48.24	68.2	-19.96	Horizontal
15600	32.29	38.3	10.62	35.36	45.85	68.2	-22.35	Horizontal
10400	26.09	39.01	8.29	35.67	37.72	54	-16.28	Vertical
15600	25.98	38.3	10.62	35.36	39.54	54	-14.46	Vertical
10400	24.80	39.01	8.29	35.67	36.43	54	-17.57	Horizontal
15600	25.06	38.3	10.62	35.36	38.62	54	-15.38	Horizontal
802.11a					Test Frequency: 5240MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	38.33	39.15	8.32	35.78	50.02	68.2	-18.18	Vertical
15720	33.49	38	10.72	35.37	46.84	68.2	-21.36	Vertical
10480	33.70	39.15	8.32	35.78	45.39	68.2	-22.81	Horizontal
15720	31.56	38	10.72	35.37	44.91	68.2	-23.29	Horizontal
10480	29.07	39.15	8.32	35.78	40.76	54	-13.24	Vertical
15720	27.15	38	10.72	35.37	40.50	54	-13.50	Vertical
10480	24.86	39.15	8.32	35.78	36.55	54	-17.45	Horizontal
15720	26.88	38	10.72	35.37	40.23	54	-13.77	Horizontal

802.11a					Test Frequency: 5260MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10520	36.82	39.2	8.34	35.82	48.54	68.2	-19.66	Vertical
15780	32.08	37.9	10.77	35.38	45.37	68.2	-22.83	Vertical
10520	36.30	39.2	8.34	35.82	48.02	68.2	-20.18	Horizontal
15780	30.79	37.9	10.77	35.38	44.08	68.2	-24.12	Horizontal
10520	29.88	39.2	8.34	35.82	41.60	54	-12.40	Vertical
15780	28.84	37.9	10.77	35.38	42.13	54	-11.87	Vertical
10520	26.53	39.2	8.34	35.82	38.25	54	-15.75	Horizontal
15780	25.51	37.9	10.77	35.38	38.80	54	-15.20	Horizontal

802.11a					Test Frequency: 5280MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10560	34.19	38.86	8.35	39.35	42.05	68.2	-26.15	Vertical
15840	35.98	38.2	10.82	39.6	45.40	68.2	-22.80	Vertical
10560	36.21	38.86	8.35	39.35	44.07	68.2	-24.13	Horizontal
15840	33.59	38.2	10.82	39.6	43.01	68.2	-25.19	Horizontal
10560	30.78	38.86	8.35	39.35	38.64	54	-15.36	Vertical
15840	25.94	38.2	10.82	39.6	35.36	54	-18.64	Vertical
10560	26.46	38.86	8.35	39.35	34.32	54	-19.68	Horizontal
15840	24.89	38.2	10.82	39.6	34.31	54	-19.69	Horizontal

802.11a					Test Frequency: 5320MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10640	37.14	39.22	8.38	35.96	48.78	68.2	-19.42	Vertical
15960	34.09	37.5	10.92	35.4	47.11	68.2	-21.09	Vertical
10640	36.16	39.22	8.38	35.96	47.80	68.2	-20.40	Horizontal
15960	31.27	37.5	10.92	35.4	44.29	68.2	-23.91	Horizontal
10640	26.71	39.22	8.38	35.96	38.35	54	-15.65	Vertical
15960	27.95	37.5	10.92	35.4	40.97	54	-13.03	Vertical
10640	27.59	39.22	8.38	35.96	39.23	54	-14.77	Horizontal
15960	23.48	37.5	10.92	35.4	36.50	54	-17.50	Horizontal

802.11a					Test Frequency: 5500MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11000	34.60	39.3	8.53	36.4	46.03	68.2	-22.17	Vertical
16500	34.42	39.3	11.06	35.87	48.91	68.2	-19.29	Vertical
11000	35.77	39.3	8.53	36.4	47.20	68.2	-21.00	Horizontal
16500	34.54	39.3	11.06	35.87	49.03	68.2	-19.17	Horizontal
11000	29.18	39.3	8.53	36.4	40.61	54	-13.39	Vertical
16500	28.76	39.3	11.06	35.87	43.25	54	-10.75	Vertical
11000	28.92	39.3	8.53	36.4	40.35	54	-13.65	Horizontal
16500	26.77	39.3	11.06	35.87	41.26	54	-12.74	Horizontal
802.11a					Test Frequency: 5580MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11160	34.93	39.33	8.6	36.37	46.49	68.2	-21.71	Vertical
16740	35.59	39.5	11.11	36.09	50.11	68.2	-18.09	Vertical
11160	33.22	39.33	8.6	36.37	44.78	68.2	-23.42	Horizontal
16740	32.20	39.5	11.11	36.09	46.72	68.2	-21.48	Horizontal
11160	27.67	39.33	8.6	36.37	39.23	54	-14.77	Vertical
16740	28.22	39.5	11.11	36.09	42.74	54	-11.26	Vertical
11160	28.78	39.33	8.6	36.37	40.34	54	-13.66	Horizontal
16740	24.07	39.5	11.11	36.09	38.59	54	-15.41	Horizontal
802.11a					Test Frequency: 5700MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11400	34.83	39.38	8.7	36.32	46.59	68.2	-21.61	Vertical
17100	32.53	40.22	11.26	36.29	47.72	68.2	-20.48	Vertical
11400	35.31	39.38	8.7	36.32	47.07	68.2	-21.13	Horizontal
17100	31.53	40.22	11.26	36.29	46.72	68.2	-21.48	Horizontal
11400	28.39	39.38	8.7	36.32	40.15	54	-13.85	Vertical
17100	25.26	40.22	11.26	36.29	40.45	54	-13.55	Vertical
11400	25.44	39.38	8.7	36.32	37.20	54	-16.80	Horizontal
17100	25.75	40.22	11.26	36.29	40.94	54	-13.06	Horizontal

802.11n(HT20)					Test Frequency: 5180MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	34.35	38.96	8.27	35.64	45.94	68.2	-22.26	Vertical
15540	33.64	38.4	10.57	35.35	47.26	68.2	-20.94	Vertical
10360	35.48	38.96	8.27	35.64	47.07	68.2	-21.13	Horizontal
15540	31.95	38.4	10.57	35.35	45.57	68.2	-22.63	Horizontal
10360	26.32	38.96	8.27	35.64	37.91	54	-16.09	Vertical
15540	27.41	38.4	10.57	35.35	41.03	54	-12.97	Vertical
10360	26.42	38.96	8.27	35.64	38.01	54	-15.99	Horizontal
15540	26.73	38.4	10.57	35.35	40.35	54	-13.65	Horizontal
802.11n(HT20)					Test Frequency: 5200MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	35.18	39.01	8.29	35.67	46.81	68.2	-21.39	Vertical
15600	32.26	38.3	10.62	35.36	45.82	68.2	-22.38	Vertical
10400	35.97	39.01	8.29	35.67	47.60	68.2	-20.60	Horizontal
15600	31.26	38.3	10.62	35.36	44.82	68.2	-23.38	Horizontal
10400	25.15	39.01	8.29	35.67	36.78	54	-17.22	Vertical
15600	25.31	38.3	10.62	35.36	38.87	54	-15.13	Vertical
10400	23.99	39.01	8.29	35.67	35.62	54	-18.38	Horizontal
15600	24.35	38.3	10.62	35.36	37.91	54	-16.09	Horizontal
802.11n(HT20)					Test Frequency: 5240MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	36.87	39.15	8.32	35.78	48.56	68.2	-19.64	Vertical
15720	32.59	38	10.72	35.37	45.94	68.2	-22.26	Vertical
10480	33.01	39.15	8.32	35.78	44.70	68.2	-23.50	Horizontal
15720	30.35	38	10.72	35.37	43.70	68.2	-24.50	Horizontal
10480	28.28	39.15	8.32	35.78	39.97	54	-14.03	Vertical
15720	26.38	38	10.72	35.37	39.73	54	-14.27	Vertical
10480	23.45	39.15	8.32	35.78	35.14	54	-18.86	Horizontal
15720	26.12	38	10.72	35.37	39.47	54	-14.53	Horizontal

802.11n(HT20)					Test Frequency: 5260MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10520	35.91	39.2	8.34	35.82	47.63	68.2	-20.57	Vertical
15780	31.21	37.9	10.77	35.38	44.50	68.2	-23.70	Vertical
10520	35.64	39.2	8.34	35.82	47.36	68.2	-20.84	Horizontal
15780	29.36	37.9	10.77	35.38	42.65	68.2	-25.55	Horizontal
10520	28.94	39.2	8.34	35.82	40.66	54	-13.34	Vertical
15780	28.15	37.9	10.77	35.38	41.44	54	-12.56	Vertical
10520	25.67	39.2	8.34	35.82	37.39	54	-16.61	Horizontal
15780	24.74	37.9	10.77	35.38	38.03	54	-15.97	Horizontal

802.11n(HT20)					Test Frequency: 5280MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10560	33.37	38.86	8.35	39.35	41.23	68.2	-26.97	Vertical
15840	34.96	38.2	10.82	39.6	44.38	68.2	-23.82	Vertical
10560	35.40	38.86	8.35	39.35	43.26	68.2	-24.94	Horizontal
15840	32.87	38.2	10.82	39.6	42.29	68.2	-25.91	Horizontal
10560	29.83	38.86	8.35	39.35	37.69	54	-16.31	Vertical
15840	25.16	38.2	10.82	39.6	34.58	54	-19.42	Vertical
10560	25.61	38.86	8.35	39.35	33.47	54	-20.53	Horizontal
15840	24.24	38.2	10.82	39.6	33.66	54	-20.34	Horizontal

802.11n(HT20)					Test Frequency: 5320MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10640	35.95	39.22	8.38	35.96	47.59	68.2	-20.61	Vertical
15960	33.32	37.5	10.92	35.4	46.34	68.2	-21.86	Vertical
10640	35.48	39.22	8.38	35.96	47.12	68.2	-21.08	Horizontal
15960	30.29	37.5	10.92	35.4	43.31	68.2	-24.89	Horizontal
10640	25.75	39.22	8.38	35.96	37.39	54	-16.61	Vertical
15960	27.18	37.5	10.92	35.4	40.20	54	-13.80	Vertical
10640	26.71	39.22	8.38	35.96	38.35	54	-15.65	Horizontal
15960	22.61	37.5	10.92	35.4	35.63	54	-18.37	Horizontal

802.11n(HT20)					Test Frequency: 5500MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11000	33.09	39.3	8.53	36.4	44.52	68.2	-23.68	Vertical
16500	33.56	39.3	11.06	35.87	48.05	68.2	-20.15	Vertical
11000	35.11	39.3	8.53	36.4	46.54	68.2	-21.66	Horizontal
16500	33.37	39.3	11.06	35.87	47.86	68.2	-20.34	Horizontal
11000	28.43	39.3	8.53	36.4	39.86	54	-14.14	Vertical
16500	28.08	39.3	11.06	35.87	42.57	54	-11.43	Vertical
11000	27.93	39.3	8.53	36.4	39.36	54	-14.64	Horizontal
16500	26.06	39.3	11.06	35.87	40.55	54	-13.45	Horizontal
802.11n(HT20)					Test Frequency: 5580MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11160	34.23	39.33	8.6	36.37	45.79	68.2	-22.41	Vertical
16740	34.44	39.5	11.11	36.09	48.96	68.2	-19.24	Vertical
11160	32.31	39.33	8.6	36.37	43.87	68.2	-24.33	Horizontal
16740	31.14	39.5	11.11	36.09	45.66	68.2	-22.54	Horizontal
11160	26.94	39.33	8.6	36.37	38.50	54	-15.50	Vertical
16740	27.49	39.5	11.11	36.09	42.01	54	-11.99	Vertical
11160	27.75	39.33	8.6	36.37	39.31	54	-14.69	Horizontal
16740	23.36	39.5	11.11	36.09	37.88	54	-16.12	Horizontal
802.11n(HT20)					Test Frequency: 5700MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11400	33.91	39.38	8.7	36.32	45.67	68.2	-22.53	Vertical
17100	31.82	40.22	11.26	36.29	47.01	68.2	-21.19	Vertical
11400	34.61	39.38	8.7	36.32	46.37	68.2	-21.83	Horizontal
17100	30.44	40.22	11.26	36.29	45.63	68.2	-22.57	Horizontal
11400	27.53	39.38	8.7	36.32	39.29	54	-14.71	Vertical
17100	24.51	40.22	11.26	36.29	39.70	54	-14.30	Vertical
11400	24.69	39.38	8.7	36.32	36.45	54	-17.55	Horizontal
17100	24.32	40.22	11.26	36.29	39.51	54	-14.49	Horizontal

802.11ac(HT20)	Test Frequency: 5180MHz
----------------	-------------------------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	35.52	38.96	8.27	35.64	47.11	68.2	-21.09	Vertical
15540	34.44	38.4	10.57	35.35	48.06	68.2	-20.14	Vertical
10360	36.12	38.96	8.27	35.64	47.71	68.2	-20.49	Horizontal
15540	32.96	38.4	10.57	35.35	46.58	68.2	-21.62	Horizontal
10360	27.05	38.96	8.27	35.64	38.64	54	-15.36	Vertical
15540	28.00	38.4	10.57	35.35	41.62	54	-12.38	Vertical
10360	27.51	38.96	8.27	35.64	39.10	54	-14.90	Horizontal
15540	27.51	38.4	10.57	35.35	41.13	54	-12.87	Horizontal
802.11ac(HT20)				Test Frequency: 5200MHz				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	36.49	39.01	8.29	35.67	48.12	68.2	-20.08	Vertical
15600	33.02	38.3	10.62	35.36	46.58	68.2	-21.62	Vertical
10400	36.56	39.01	8.29	35.67	48.19	68.2	-20.01	Horizontal
15600	32.22	38.3	10.62	35.36	45.78	68.2	-22.42	Horizontal
10400	25.84	39.01	8.29	35.67	37.47	54	-16.53	Vertical
15600	25.86	38.3	10.62	35.36	39.42	54	-14.58	Vertical
10400	24.66	39.01	8.29	35.67	36.29	54	-17.71	Horizontal
15600	24.89	38.3	10.62	35.36	38.45	54	-15.55	Horizontal
802.11ac(HT20)				Test Frequency: 5240MHz				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	37.52	39.15	8.32	35.78	49.21	68.2	-18.99	Vertical
15720	33.04	38	10.72	35.37	46.39	68.2	-21.81	Vertical
10480	33.36	39.15	8.32	35.78	45.05	68.2	-23.15	Horizontal
15720	30.90	38	10.72	35.37	44.25	68.2	-23.95	Horizontal
10480	28.69	39.15	8.32	35.78	40.38	54	-13.62	Vertical
15720	26.72	38	10.72	35.37	40.07	54	-13.93	Vertical
10480	24.05	39.15	8.32	35.78	35.74	54	-18.26	Horizontal
15720	26.56	38	10.72	35.37	39.91	54	-14.09	Horizontal

802.11ac(HT20)					Test Frequency: 5260MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10520	36.43	39.2	8.34	35.82	48.15	68.2	-20.05	Vertical
15780	31.66	37.9	10.77	35.38	44.95	68.2	-23.25	Vertical
10520	35.99	39.2	8.34	35.82	47.71	68.2	-20.49	Horizontal
15780	29.89	37.9	10.77	35.38	43.18	68.2	-25.02	Horizontal
10520	29.34	39.2	8.34	35.82	41.06	54	-12.94	Vertical
15780	28.48	37.9	10.77	35.38	41.77	54	-12.23	Vertical
10520	26.06	39.2	8.34	35.82	37.78	54	-16.22	Horizontal
15780	25.06	37.9	10.77	35.38	38.35	54	-15.65	Horizontal

802.11ac(HT20)					Test Frequency: 5280MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10560	33.79	38.86	8.35	39.35	41.65	68.2	-26.55	Vertical
15840	35.57	38.2	10.82	39.6	44.99	68.2	-23.21	Vertical
10560	35.87	38.86	8.35	39.35	43.73	68.2	-24.47	Horizontal
15840	33.27	38.2	10.82	39.6	42.69	68.2	-25.51	Horizontal
10560	30.29	38.86	8.35	39.35	38.15	54	-15.85	Vertical
15840	25.55	38.2	10.82	39.6	34.97	54	-19.03	Vertical
10560	26.13	38.86	8.35	39.35	33.99	54	-20.01	Horizontal
15840	24.65	38.2	10.82	39.6	34.07	54	-19.93	Horizontal

802.11ac(HT20)					Test Frequency: 5320MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10640	36.57	39.22	8.38	35.96	48.21	68.2	-19.99	Vertical
15960	33.73	37.5	10.92	35.4	46.75	68.2	-21.45	Vertical
10640	35.78	39.22	8.38	35.96	47.42	68.2	-20.78	Horizontal
15960	30.78	37.5	10.92	35.4	43.80	68.2	-24.40	Horizontal
10640	26.11	39.22	8.38	35.96	37.75	54	-16.25	Vertical
15960	27.47	37.5	10.92	35.4	40.49	54	-13.51	Vertical
10640	27.34	39.22	8.38	35.96	38.98	54	-15.02	Horizontal
15960	23.03	37.5	10.92	35.4	36.05	54	-17.95	Horizontal

802.11ac(HT20)					Test Frequency: 5500MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11000	33.69	39.3	8.53	36.4	45.12	68.2	-23.08	Vertical
16500	34.00	39.3	11.06	35.87	48.49	68.2	-19.71	Vertical
11000	35.44	39.3	8.53	36.4	46.87	68.2	-21.33	Horizontal
16500	33.89	39.3	11.06	35.87	48.38	68.2	-19.82	Horizontal
11000	28.82	39.3	8.53	36.4	40.25	54	-13.75	Vertical
16500	28.40	39.3	11.06	35.87	42.89	54	-11.11	Vertical
11000	28.33	39.3	8.53	36.4	39.76	54	-14.24	Horizontal
16500	26.39	39.3	11.06	35.87	40.88	54	-13.12	Horizontal
802.11ac(HT20)					Test Frequency: 5580MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11160	34.62	39.33	8.6	36.37	46.18	68.2	-22.02	Vertical
16740	35.03	39.5	11.11	36.09	49.55	68.2	-18.65	Vertical
11160	32.76	39.33	8.6	36.37	44.32	68.2	-23.88	Horizontal
16740	31.77	39.5	11.11	36.09	46.29	68.2	-21.91	Horizontal
11160	27.42	39.33	8.6	36.37	38.98	54	-15.02	Vertical
16740	27.87	39.5	11.11	36.09	42.39	54	-11.61	Vertical
11160	28.32	39.33	8.6	36.37	39.88	54	-14.12	Horizontal
16740	23.73	39.5	11.11	36.09	38.25	54	-15.75	Horizontal
802.11ac(HT20)					Test Frequency: 5700MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11400	34.51	39.38	8.7	36.32	46.27	68.2	-21.93	Vertical
17100	32.28	40.22	11.26	36.29	47.47	68.2	-20.73	Vertical
11400	34.96	39.38	8.7	36.32	46.72	68.2	-21.48	Horizontal
17100	30.97	40.22	11.26	36.29	46.16	68.2	-22.04	Horizontal
11400	27.94	39.38	8.7	36.32	39.70	54	-14.30	Vertical
17100	24.85	40.22	11.26	36.29	40.04	54	-13.96	Vertical
11400	25.05	39.38	8.7	36.32	36.81	54	-17.19	Horizontal
17100	24.87	40.22	11.26	36.29	40.06	54	-13.94	Horizontal

802.11ax(HE20)	Test Frequency: 5180MHz
----------------	-------------------------

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	35.79	38.96	8.27	35.64	47.38	68.2	-20.82	Vertical
15540	34.40	38.4	10.57	35.35	48.02	68.2	-20.18	Vertical
10360	36.12	38.96	8.27	35.64	47.71	68.2	-20.49	Horizontal
15540	33.13	38.4	10.57	35.35	46.75	68.2	-21.45	Horizontal
10360	27.09	38.96	8.27	35.64	38.68	54	-15.32	Vertical
15540	28.00	38.4	10.57	35.35	41.62	54	-12.38	Vertical
10360	27.64	38.96	8.27	35.64	39.23	54	-14.77	Horizontal
15540	27.56	38.4	10.57	35.35	41.18	54	-12.82	Horizontal
802.11ax(HE20)				Test Frequency: 5200MHz				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	36.67	39.01	8.29	35.67	48.30	68.2	-19.90	Vertical
15600	33.07	38.3	10.62	35.36	46.63	68.2	-21.57	Vertical
10400	36.56	39.01	8.29	35.67	48.19	68.2	-20.01	Horizontal
15600	32.39	38.3	10.62	35.36	45.95	68.2	-22.25	Horizontal
10400	25.88	39.01	8.29	35.67	37.51	54	-16.49	Vertical
15600	25.85	38.3	10.62	35.36	39.41	54	-14.59	Vertical
10400	24.68	39.01	8.29	35.67	36.31	54	-17.69	Horizontal
15600	24.88	38.3	10.62	35.36	38.44	54	-15.56	Horizontal
802.11ax(HE20)				Test Frequency: 5240MHz				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	38.10	39.15	8.32	35.78	49.79	68.2	-18.41	Vertical
15720	33.41	38	10.72	35.37	46.76	68.2	-21.44	Vertical
10480	33.58	39.15	8.32	35.78	45.27	68.2	-22.93	Horizontal
15720	31.45	38	10.72	35.37	44.80	68.2	-23.40	Horizontal
10480	28.99	39.15	8.32	35.78	40.68	54	-13.32	Vertical
15720	26.93	38	10.72	35.37	40.28	54	-13.72	Vertical
10480	24.66	39.15	8.32	35.78	36.35	54	-17.65	Horizontal
15720	26.87	38	10.72	35.37	40.22	54	-13.78	Horizontal

802.11ax(HE20)					Test Frequency: 5260MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10520	37.18	39.2	8.34	35.82	48.90	68.2	-19.30	Vertical
15780	32.13	37.9	10.77	35.38	45.42	68.2	-22.78	Vertical
10520	36.32	39.2	8.34	35.82	48.04	68.2	-20.16	Horizontal
15780	30.52	37.9	10.77	35.38	43.81	68.2	-24.39	Horizontal
10520	29.75	39.2	8.34	35.82	41.47	54	-12.53	Vertical
15780	28.80	37.9	10.77	35.38	42.09	54	-11.91	Vertical
10520	26.46	39.2	8.34	35.82	38.18	54	-15.82	Horizontal
15780	25.35	37.9	10.77	35.38	38.64	54	-15.36	Horizontal
802.11ax(HE20)					Test Frequency: 5280MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10560	34.12	38.86	8.35	39.35	41.98	68.2	-26.22	Vertical
15840	36.23	38.2	10.82	39.6	45.65	68.2	-22.55	Vertical
10560	36.28	38.86	8.35	39.35	44.14	68.2	-24.06	Horizontal
15840	33.59	38.2	10.82	39.6	43.01	68.2	-25.19	Horizontal
10560	30.67	38.86	8.35	39.35	38.53	54	-15.47	Vertical
15840	25.85	38.2	10.82	39.6	35.27	54	-18.73	Vertical
10560	26.58	38.86	8.35	39.35	34.44	54	-19.56	Horizontal
15840	24.98	38.2	10.82	39.6	34.40	54	-19.60	Horizontal
802.11ax(HE20)					Test Frequency: 5320MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10640	37.24	39.22	8.38	35.96	48.88	68.2	-19.32	Vertical
15960	34.19	37.5	10.92	35.4	47.21	68.2	-20.99	Vertical
10640	36.10	39.22	8.38	35.96	47.74	68.2	-20.46	Horizontal
15960	31.36	37.5	10.92	35.4	44.38	68.2	-23.82	Horizontal
10640	26.51	39.22	8.38	35.96	38.15	54	-15.85	Vertical
15960	27.76	37.5	10.92	35.4	40.78	54	-13.22	Vertical
10640	28.04	39.22	8.38	35.96	39.68	54	-14.32	Horizontal
15960	23.50	37.5	10.92	35.4	36.52	54	-17.48	Horizontal

802.11ax(HE20)					Test Frequency: 5500MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11000	34.37	39.3	8.53	36.4	45.80	68.2	-22.40	Vertical
16500	34.46	39.3	11.06	35.87	48.95	68.2	-19.25	Vertical
11000	35.76	39.3	8.53	36.4	47.19	68.2	-21.01	Horizontal
16500	34.48	39.3	11.06	35.87	48.97	68.2	-19.23	Horizontal
11000	29.21	39.3	8.53	36.4	40.64	54	-13.36	Vertical
16500	28.70	39.3	11.06	35.87	43.19	54	-10.81	Vertical
11000	28.74	39.3	8.53	36.4	40.17	54	-13.83	Horizontal
16500	26.69	39.3	11.06	35.87	41.18	54	-12.82	Horizontal
802.11ax(HE20)					Test Frequency: 5580MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11160	34.94	39.33	8.6	36.37	46.50	68.2	-21.70	Vertical
16740	35.66	39.5	11.11	36.09	50.18	68.2	-18.02	Vertical
11160	33.17	39.33	8.6	36.37	44.73	68.2	-23.47	Horizontal
16740	32.46	39.5	11.11	36.09	46.98	68.2	-21.22	Horizontal
11160	27.87	39.33	8.6	36.37	39.43	54	-14.57	Vertical
16740	28.20	39.5	11.11	36.09	42.72	54	-11.28	Vertical
11160	28.95	39.33	8.6	36.37	40.51	54	-13.49	Horizontal
16740	24.02	39.5	11.11	36.09	38.54	54	-15.46	Horizontal
802.11ax(HE20)					Test Frequency: 5700MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11400	35.21	39.38	8.7	36.32	46.97	68.2	-21.23	Vertical
17100	32.70	40.22	11.26	36.29	47.89	68.2	-20.31	Vertical
11400	35.28	39.38	8.7	36.32	47.04	68.2	-21.16	Horizontal
17100	31.56	40.22	11.26	36.29	46.75	68.2	-21.45	Horizontal
11400	28.34	39.38	8.7	36.32	40.10	54	-13.90	Vertical
17100	25.15	40.22	11.26	36.29	40.34	54	-13.66	Vertical
11400	25.39	39.38	8.7	36.32	37.15	54	-16.85	Horizontal
17100	25.53	40.22	11.26	36.29	40.72	54	-13.28	Horizontal

Notes:

1. Level = Read Level + Antenna Factor+ Cable loss- Preamp Factor.


Global United Technology Services Co., Ltd.

No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone,
Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960

2. The test trace is same as the ambient noise (the test frequency range: 18GHz~40GHz), therefore no data appear in the report.

7.7 Frequency stability

Test Requirement:	FCC Part15 C Section 15.407(g)
Test Method:	ANSI C63.10:2013, FCC Part 2.1055,
Limit:	Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified
Test Procedure:	The EUT was setup to ANSI C63.4, 2003; tested to 2.1055 for compliance to FCC Part 15.407(g) requirements.
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data:

Test Condition	Test Mode	Test Frequency [MHz]	Ant	Result [ppm]	Limit [ppm]	Verdict
NTNV	Carrier	5180	1	-5.92	<=20	PASS
		5190	1	-3.79	<=20	PASS
		5200	1	-5.60	<=20	PASS
		5210	1	-4.24	<=20	PASS
		5230	1	1.89	<=20	PASS
		5240	1	-3.67	<=20	PASS
		5260	1	-3.72	<=20	PASS
		5270	1	-3.89	<=20	PASS
		5280	1	-5.61	<=20	PASS
		5290	1	-2.65	<=20	PASS
		5310	1	-3.29	<=20	PASS
		5320	1	-4.11	<=20	PASS
		5500	1	-5.10	<=20	PASS
		5510	1	-4.54	<=20	PASS
		5530	1	-6.24	<=20	PASS
		5550	1	-8.13	<=20	PASS
		5580	1	-4.76	<=20	PASS
		5610	1	-3.95	<=20	PASS
		5670	1	-4.94	<=20	PASS
		5700	1	-8.63	<=20	PASS

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

---END---