

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Band	Frequency	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict
2.4G	2441MHz	-18.36	0.015	2.06	0.0000047	1.0	PASS
2.4G WIFI	2422MHz ANT 2	18.23	66.53	4.05	0.0334	1.0	
	2437MHz MIMO	18.03	63.53	7.12	0.0651	1.0	
5.2G WIFI	5210MHz ANT 2	17.33	54.08	3.52	0.0242	1.0	
	5210MHz MIMO	17.27	53.33	7.35	0.0576	1.0	
5.3G WIFI	5290MHz ANT 1	16.53	44.98	4.81	0.0270	1.0	
	5290MHz MIMO	16.91	49.09	6.93	0.0482	1.0	
5.6G WIFI	5700MHz ANT 2	17.31	53.83	3.6	0.0245	1.0	
	5610MHz MIMO	16.99	50.00	7.72	0.0588	1.0	
5.8G WIFI	5745MHz ANT 1	16.94	49.43	6.09	0.0399	1.0	
	5775MHz MIMO	18.01	63.24	7.61	0.0726	1.0	

where:

$$\text{EIRP (dBm)} = \text{E (dBuV/m)} - 95.2$$

E = Field Strength (dBuV/m)

$$\text{So output power} = \text{EIRP} - \text{Antenna gain} = 78.90 - 95.2 - 2.06 = -18.36$$

Simultaneous Transmission:

$$\sum_{k=1}^c \frac{\text{Evaluated}_k}{\text{Exposure Limit}_k}$$

$$2.4G + \text{WIFI } 2.4G = (0.0000047 / 1) + (0.0651/1) = 0.0651 < 1$$

$$2.4G + \text{WIFI } 5G = (0.0000047/1) + (0.0726/1) = 0.0726 < 1$$

The max power density is less than MPE exempt limit, so it is compliance.