

TEST REPORT

Applicant: HANSHOW TECHNOLOGY CO.,LTD.

Address of Applicant: Building 1(IF podium building and 4F) and Building 5 (7F) in
Jiaxing Photovolta High-tech Park, No. 1288 Kanghe Rd.,
Xiuzhou District, Jiaxing, Zhejiang, China

Manufacturer: HANSHOW TECHNOLOGY CO.,LTD.

**Address of
Manufacturer:** Building 1(IF podium building and 4F) and Building 5 (7F) in
Jiaxing Photovolta High-tech Park, No. 1288 Kanghe Rd.,
Xiuzhou District, Jiaxing, Zhejiang, China

Equipment Under Test (EUT)

Product Name: ESL Controller

Model No.: HS_C09961

FCC ID: 2AYMH-P9961

Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407

Date of sample receipt: April 30, 2025

Date of Test: April 30, 2025-June 10, 2025

Date of report issued: June 10, 2025

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:


Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Report No.	Version No.	Date	Description
GTS2024090177F04	00	October 25, 2024	Original
GTS2025040661F04	01	June 10, 2025	Class II permissive change

Prepared By:




Project Engineer

Date:

June 10, 2025

Check By:



Reviewer

Date:

June 10, 2025

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 TEST FACILITY	7
5.5 TEST LOCATION	7
5.6 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 BAND EDGE	14
7.3.1 Radiated Emission Method	14
7.4 SPURIOUS EMISSION	22
7.4.1 Radiated Emission Method	22
8 TEST SETUP PHOTO	31
9 EUT CONSTRUCTIONAL DETAILS	31

4 Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203	Pass
AC Power Line Conducted Emission	FCC part 15.207	Pass
Maximum Conducted Output Power	FCC part 15.407(a)(3)	N/A *
Channel Bandwidth and 99% Occupied Bandwidth	FCC part 15.407(e)	N/A *
Power Spectral Density	FCC part 15.407(a)(3)	N/A *
Band Edge	FCC part 15.407(b)(4)	Pass
Spurious Emission	FCC part 15.205/15.209/15.407(b)(4)	Pass
Frequency Stability	FCC part 15.407(g)	N/A *

Remarks:

1. Test according to ANSI C63.10:2013.
2. Pass: The EUT complies with the essential requirements in the standard.
3. N/A*: Not applicable. This's a Class II permissive change report, all of the changes are not effect to the RF performance, function and power. So the RF conducted test data directly reference the original report number GTS2024090177F04.

4.1 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	ESL Controller
Model No.:	HS_C09961
Test sample(s) ID:	GTS2025040661-1
Sample(s) Status:	Engineer sample
S/N:	927430061594116723
Operation Frequency:	802.11a/802.11n(HT20)/802.11ac(HT20):5745MHz~ 5825MHz 802.11n(HT40)/ 802.11ac(HT40): 5755MHz ~ 5795MHz 802.11ac(HT80): 5775MHz
Channel numbers:	802.11a/802.11n(HT20)/802.11ac(HT20): 5 802.11n(HT40)/ 802.11ac(HT40): 2 802.11ac(HT80): 1
Channel bandwidth:	802.11a/802.11n(HT20)/802.11ac(HT20): 20MHz 802.11n(HT40)/802.11ac(HT40): 40MHz 802.11ac(HT80): 80MHz
Modulation technology:	Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Internal Antenna
Antenna gain:	ANT 1: 6.09dBi ANT 2: 2.80dBi
Power supply:	DC 12.0V by Adapter Or DC 36V~57V by POE

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.
3. Both two power supply modes were tested and only reported the worst case adapter.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745MHz	151	5755MHz	153	5765MHz	155	5775MHz
157	5785MHz	159	5795MHz	161	5805MHz	163	5815MHz
165	5825MHz						

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)		
	802.11 a/n/ac(HT20))	802.11 n/ac(HT40)	802.11ac(HT80)
Lowest channel	5745	5755	
Middle channel	5785		5775
Highest channel	5825	5795	

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
-------------------	--

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate	Mode	Data rate
802.11a	6Mbps	802.11n/ac(HT40)	13Mbps
802.11n/ac(HT20)	6.5Mbps	802.11ac(HT80)	29.3Mbps

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
GTS	Adapter	K651-1205000D	N/A

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

- **CNAS (No. CNAS L5775)**

CNAS has accredited Global United Technology Services Co., Ltd., to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.6 Additional Instructions

Test Software	Special test software provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 11, 2025	Apr. 10, 2026
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 12, 2025	Apr. 11, 2026
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 12, 2025	Apr. 11, 2026
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul. 02, 2024	Jul. 01, 2025
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.16, 2024	Nov.15, 2025
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2025	Apr. 10, 2026
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2025	Apr. 10, 2026
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2025	Apr. 10, 2026
11	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 11, 2025	Mar. 10, 2026
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2025	Apr. 10, 2026
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 13, 2024	Nov. 12, 2025
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2025	Apr. 10, 2026
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 15, 2025	Apr. 14, 2026
16	RE cable 1	GTS	N/A	GTS675	Jul. 02, 2024	Jul. 01, 2025
17	RE cable 2	GTS	N/A	GTS676	Jul. 02, 2024	Jul. 01, 2025
18	RE cable 3	GTS	N/A	GTS677	Jul. 02, 2024	Jul. 01, 2025
19	RE cable 4	GTS	N/A	GTS678	Jul. 02, 2024	Jul. 01, 2025
20	RE cable 5	GTS	N/A	GTS679	Jul. 02, 2024	Jul. 01, 2025
21	RE cable 6	GTS	N/A	GTS680	Jul. 02, 2024	Jul. 01, 2025
22	RE cable 7	GTS	N/A	GTS681	Jul. 05, 2024	Jul. 04, 2025
23	RE cable 8	GTS	N/A	GTS682	Jul. 05, 2024	Jul. 04, 2025
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	Jul. 12, 2022	Jul. 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 12, 2025	Apr. 11, 2026
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	Apr. 11, 2025	Apr. 10, 2026
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	Thermo meter	JINCHUANG	GSP-8A	GTS642	Apr. 15, 2025	Apr. 14, 2026
6	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	Apr. 12, 2025	Apr. 11, 2026
7	ISN	SCHWARZBECK	NTFM 8158	GTS565	Apr. 11, 2025	Apr. 10, 2026
8	High voltage probe	SCHWARZBECK	TK9420	GTS537	Apr. 11, 2025	Apr. 10, 2026
9	Antenna end assembly	Weinschel	1870A	GTS560	Apr. 11, 2025	Apr. 10, 2026
10	EMI Test Software	AUDIX	E3-6.100622	GTS726	N/A	N/A
11	Current probe	CYBERTEK	EM5011	GTS698	Jan. 13, 2025	Jan. 12, 2026

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Aug. 17, 2024	Aug. 16, 2025

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
<i>15.203 requirement:</i> An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The antenna is Internal antenna, reference to the appendix II for details	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	150KHz to 30MHz						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto						
Limit:	Frequency range (MHz)		Limit (dBuV)				
			Quasi-peak		Average		
	0.15-0.5		66 to 56*		56 to 46*		
	0.5-5		56		46		
	5-30		60		50		
* Decreases with the logarithm of the frequency.							
Test setup:	Reference Plane 40cm LISN AUX Equipment E.U.T Test table/Insulation plane 80cm 40cm LISN Filter AC power EMI Receiver Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m						
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar	
Test voltage:	AC 120V, 60Hz						
Test results:	Pass						

Measurement data


Pre-scan all test modes, found worst case at 802.11ac(VHT80) 5775MHz@Ant 1, and so only show the test result of it.

Line:



Freq	Reading level	LISN/ISN factor	Cable loss	Level	Limit level	Over limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.15	23.98	10.01	0.01	44.00	65.78	-21.78	QP
0.15	8.84	10.01	0.01	28.86	55.78	-26.92	Average
0.33	22.79	9.63	0.01	42.43	59.53	-17.10	QP
0.33	16.95	9.63	0.01	36.59	49.53	-12.94	Average
0.81	20.77	9.76	0.02	40.55	56.00	-15.45	QP
0.81	11.21	9.76	0.02	30.99	46.00	-15.01	Average
3.90	18.59	9.40	0.06	38.05	56.00	-17.95	QP
3.90	8.78	9.40	0.06	28.24	46.00	-17.76	Average
4.45	18.80	9.59	0.06	38.45	56.00	-17.55	QP
4.45	9.22	9.59	0.06	28.87	46.00	-17.13	Average
22.42	18.03	9.88	0.19	38.10	60.00	-21.90	QP
22.42	8.05	9.88	0.19	28.12	50.00	-21.88	Average

Neutral:




Freq	Reading level	LISN/ISN factor	Cable loss	Level	Limit level	Over limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.16	23.64	9.90	0.01	43.55	65.56	-22.01	QP
0.16	9.48	9.90	0.01	29.39	55.56	-26.17	Average
0.31	21.53	9.75	0.01	41.29	60.06	-18.77	QP
0.31	14.20	9.75	0.01	33.96	50.06	-16.10	Average
0.78	13.06	9.93	0.02	33.01	56.00	-22.99	QP
0.78	5.50	9.93	0.02	25.45	46.00	-20.55	Average
4.38	16.31	9.73	0.06	36.10	56.00	-19.90	QP
4.38	6.58	9.73	0.06	26.37	46.00	-19.63	Average
12.06	17.72	9.79	0.13	37.64	60.00	-22.36	QP
12.06	9.94	9.79	0.13	29.86	50.00	-20.14	Average
19.33	14.23	9.84	0.18	34.25	60.00	-25.75	QP
19.33	7.21	9.84	0.18	27.23	50.00	-22.77	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Band edge

7.3.1 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	9kHz to 40GHz, only worse case is reported				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak RMS	1MHz 1MHz	3MHz 3MHz	Peak RMS
Limit:	All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.				
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.				

Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
4. According to KDB 789033 D02v02r01 section G) 1) d), for measurements above 1000 MHz @3m distance, the limit of field strength is computed as follows:
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2;$
 $E[\text{dBuV/m}] = -27 + 95.2 = 68.2\text{dBuV/m}.$
 $E[\text{dBuV/m}] = 10 + 95.2 = 105.2\text{dBuV/m}.$
 $E[\text{dBuV/m}] = 15.6 + 95.2 = 110.8\text{dBuV/m}.$
 $E[\text{dBuV/m}] = 27 + 95.2 = 122.2\text{dBuV/m}$

Measurement data:

All antennas have test, only the worst case ANT 1 report.

IEEE 802.11a								
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
5650	34.57	32.36	9.72	23.83	52.82	68.20	-15.38	Horizontal
5700	32.50	32.5	9.79	23.84	50.95	105.20	-54.25	Horizontal
5720	28.67	32.53	9.81	23.85	47.16	110.80	-63.64	Horizontal
5725	32.19	32.53	9.83	23.86	50.69	122.20	-71.51	Horizontal
5850	33.62	32.7	9.99	23.87	52.44	122.20	-69.76	Horizontal
5855	30.01	32.72	9.99	23.88	48.84	110.80	-61.96	Horizontal
5875	32.66	32.74	10.04	23.89	51.55	105.20	-53.65	Horizontal
5925	30.36	32.8	10.11	23.9	49.37	68.20	-18.83	Horizontal
5650	30.87	32.36	9.72	23.83	49.12	68.20	-19.08	Vertical
5700	27.51	32.5	9.79	23.84	45.96	105.20	-59.24	Vertical
5720	31.03	32.53	9.81	23.85	49.52	110.80	-61.28	Vertical
5725	32.06	32.53	9.83	23.86	50.56	122.20	-71.64	Vertical
5850	28.51	32.7	9.99	23.87	47.33	122.20	-74.87	Vertical
5855	33.39	32.72	9.99	23.88	52.22	110.80	-58.58	Vertical
5875	29.48	32.74	10.04	23.89	48.37	105.20	-56.83	Vertical
5925	31.01	32.8	10.11	23.9	50.02	68.20	-18.18	Vertical

IEEE 802.11n HT20								
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
5650	28.73	32.36	9.72	23.83	46.98	68.20	-21.22	Horizontal
5700	27.69	32.5	9.79	23.84	46.14	105.20	-59.06	Horizontal
5720	29.03	32.53	9.81	23.85	47.52	110.80	-63.28	Horizontal
5725	29.81	32.53	9.83	23.86	48.31	122.20	-73.89	Horizontal
5850	34.14	32.7	9.99	23.87	52.96	122.20	-69.24	Horizontal
5855	30.24	32.72	9.99	23.88	49.07	110.80	-61.73	Horizontal
5875	33.59	32.74	10.04	23.89	52.48	105.20	-52.72	Horizontal
5925	33.44	32.8	10.11	23.9	52.45	68.20	-15.75	Horizontal
5650	33.11	32.36	9.72	23.83	51.36	68.20	-16.84	Vertical
5700	32.48	32.5	9.79	23.84	50.93	105.20	-54.27	Vertical
5720	32.90	32.53	9.81	23.85	51.39	110.80	-59.41	Vertical
5725	30.58	32.53	9.83	23.86	49.08	122.20	-73.12	Vertical
5850	32.37	32.7	9.99	23.87	51.19	122.20	-71.01	Vertical
5855	33.58	32.72	9.99	23.88	52.41	110.80	-58.39	Vertical
5875	28.31	32.74	10.04	23.89	47.20	105.20	-58.00	Vertical
5925	34.48	32.8	10.11	23.9	53.49	68.20	-14.71	Vertical

IEEE 802.11ac HT20								
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
5650	31.54	32.36	9.72	23.83	49.79	68.20	-18.41	Horizontal
5700	31.47	32.5	9.79	23.84	49.92	105.20	-55.28	Horizontal
5720	32.95	32.53	9.81	23.85	51.44	110.80	-59.36	Horizontal
5725	32.83	32.53	9.83	23.86	51.33	122.20	-70.87	Horizontal
5850	31.78	32.7	9.99	23.87	50.60	122.20	-71.60	Horizontal
5855	32.65	32.72	9.99	23.88	51.48	110.80	-59.32	Horizontal
5875	32.82	32.74	10.04	23.89	51.71	105.20	-53.49	Horizontal
5925	31.89	32.8	10.11	23.9	50.90	68.20	-17.30	Horizontal
5650	29.81	32.36	9.72	23.83	48.06	68.20	-20.14	Vertical
5700	28.08	32.5	9.79	23.84	46.53	105.20	-58.67	Vertical
5720	29.20	32.53	9.81	23.85	47.69	110.80	-63.11	Vertical
5725	32.54	32.53	9.83	23.86	51.04	122.20	-71.16	Vertical
5850	28.26	32.7	9.99	23.87	47.08	122.20	-75.12	Vertical
5855	28.46	32.72	9.99	23.88	47.29	110.80	-63.51	Vertical
5875	31.97	32.74	10.04	23.89	50.86	105.20	-54.34	Vertical
5925	31.70	32.8	10.11	23.9	50.71	68.20	-17.49	Vertical


IEEE 802.11n HT40								
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
5650	31.51	32.36	9.72	23.83	49.76	68.20	-18.44	Horizontal
5700	30.72	32.5	9.79	23.84	49.17	105.20	-56.03	Horizontal
5720	31.00	32.53	9.81	23.85	49.49	110.80	-61.31	Horizontal
5725	31.93	32.53	9.83	23.86	50.43	122.20	-71.77	Horizontal
5850	28.44	32.7	9.99	23.87	47.26	122.20	-74.94	Horizontal
5855	33.27	32.72	9.99	23.88	52.10	110.80	-58.70	Horizontal
5875	29.81	32.74	10.04	23.89	48.70	105.20	-56.50	Horizontal
5925	31.09	32.8	10.11	23.9	50.10	68.20	-18.10	Horizontal
5650	33.50	32.36	9.72	23.83	51.75	68.20	-16.45	Vertical
5700	30.00	32.5	9.79	23.84	48.45	105.20	-56.75	Vertical
5720	29.72	32.53	9.81	23.85	48.21	110.80	-62.59	Vertical
5725	30.78	32.53	9.83	23.86	49.28	122.20	-72.92	Vertical
5850	34.21	32.7	9.99	23.87	53.03	122.20	-69.17	Vertical
5855	29.73	32.72	9.99	23.88	48.56	110.80	-62.24	Vertical
5875	29.83	32.74	10.04	23.89	48.72	105.20	-56.48	Vertical
5925	33.58	32.8	10.11	23.9	52.59	68.20	-15.61	Vertical


IEEE 802.11ac HT40								
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
5650	32.62	32.36	9.72	23.83	50.87	68.20	-17.33	Horizontal
5700	33.45	32.5	9.79	23.84	51.90	105.20	-53.30	Horizontal
5720	31.67	32.53	9.81	23.85	50.16	110.80	-60.64	Horizontal
5725	29.97	32.53	9.83	23.86	48.47	122.20	-73.73	Horizontal
5850	34.02	32.7	9.99	23.87	52.84	122.20	-69.36	Horizontal
5855	31.31	32.72	9.99	23.88	50.14	110.80	-60.66	Horizontal
5875	27.81	32.74	10.04	23.89	46.70	105.20	-58.50	Horizontal
5925	28.41	32.8	10.11	23.9	47.42	68.20	-20.78	Horizontal
5650	27.83	32.36	9.72	23.83	46.08	68.20	-22.12	Vertical
5700	33.00	32.5	9.79	23.84	51.45	105.20	-53.75	Vertical
5720	29.95	32.53	9.81	23.85	48.44	110.80	-62.36	Vertical
5725	34.09	32.53	9.83	23.86	52.59	122.20	-69.61	Vertical
5850	30.34	32.7	9.99	23.87	49.16	122.20	-73.04	Vertical
5855	32.15	32.72	9.99	23.88	50.98	110.80	-59.82	Vertical
5875	32.94	32.74	10.04	23.89	51.83	105.20	-53.37	Vertical
5925	29.68	32.8	10.11	23.9	48.69	68.20	-19.51	Vertical

IEEE 802.11ac HT80								
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
5650	33.76	32.36	9.72	23.83	52.01	68.20	-16.19	Horizontal
5700	27.68	32.5	9.79	23.84	46.13	105.20	-59.07	Horizontal
5720	34.39	32.53	9.81	23.85	52.88	110.80	-57.92	Horizontal
5725	27.42	32.53	9.83	23.86	45.92	122.20	-76.28	Horizontal
5850	32.64	32.7	9.99	23.87	51.46	122.20	-70.74	Horizontal
5855	27.46	32.72	9.99	23.88	46.29	110.80	-64.51	Horizontal
5875	27.75	32.74	10.04	23.89	46.64	105.20	-58.56	Horizontal
5925	32.20	32.8	10.11	23.9	51.21	68.20	-16.99	Horizontal
5650	27.90	32.36	9.72	23.83	46.15	68.20	-22.05	Vertical
5700	32.78	32.5	9.79	23.84	51.23	105.20	-53.97	Vertical
5720	33.55	32.53	9.81	23.85	52.04	110.80	-58.76	Vertical
5725	31.93	32.53	9.83	23.86	50.43	122.20	-71.77	Vertical
5850	30.70	32.7	9.99	23.87	49.52	122.20	-72.68	Vertical
5855	29.74	32.72	9.99	23.88	48.57	110.80	-62.23	Vertical
5875	28.23	32.74	10.04	23.89	47.12	105.20	-58.08	Vertical
5925	30.32	32.8	10.11	23.9	49.33	68.20	-18.87	Vertical


7.4 Spurious Emission

7.4.1 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209, Part 15E Section 15.407(b)(4)																												
Test Method:	ANSI C63.10:2013																												
Test Frequency Range:	9kHz to 40GHz																												
Test site:	Measurement Distance: 3m																												
Receiver setup:	Frequency	Detector	RBW	VBW	Value																								
	9kHz-150KHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value																								
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value																								
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value																								
	Above 1GHz	Peak	1MHz	3MHz	Peak Value																								
		AV	1MHz	3MHz	Average Value																								
Note: For Duty cycle ≥ 98%, average detector set as above For Duty cycle < 98%, average detector set as below: VBW ≥ 1 / T																													
Limit:	<table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100**</td><td>3</td></tr><tr><td>88-216</td><td>150**</td><td>3</td></tr><tr><td>216-960</td><td>200**</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table>					Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100**	3	88-216	150**	3	216-960	200**	3	Above 960	500	3
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																										
	0.009-0.490	2400/F(kHz)	300																										
	0.490-1.705	24000/F(kHz)	30																										
	1.705-30.0	30	30																										
	30-88	100**	3																										
	88-216	150**	3																										
	216-960	200**	3																										
	Above 960	500	3																										
	The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.																												
Test setup:	For radiated emissions from 9kHz to 30MHz																												
																													
For radiated emissions from 30MHz to1GHz																													



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remarks:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement Data:


9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Below 1GHz


Pre-scan all test modes, found worst case at 802.11ac(VHT80) 5775MHz@Ant 1, and so only show the test result of it.

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
171.995	35.79	13.30	2.65	32.43	19.31	43.50	-24.19	QP
250.301	46.13	10.51	3.17	32.35	27.46	46.00	-18.54	QP
375.939	42.53	14.22	3.78	32.26	28.27	46.00	-17.73	QP
501.179	36.16	16.82	4.20	32.20	24.98	46.00	-21.02	QP
625.078	39.49	19.60	4.75	31.74	32.10	46.00	-13.90	QP
875.247	33.23	22.80	5.67	31.10	30.60	46.00	-15.40	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
44.587	40.21	13.38	1.32	32.30	22.61	40.00	-17.39	QP
72.847	40.75	10.52	1.65	32.39	20.53	40.00	-19.47	QP
167.824	36.46	13.62	2.62	32.43	20.27	43.50	-23.23	QP
250.301	44.44	10.51	3.17	32.35	25.77	46.00	-20.23	QP
375.939	36.07	14.22	3.78	32.26	21.81	46.00	-24.19	QP
625.078	39.62	19.60	4.75	31.74	32.23	46.00	-13.77	QP

Above 1GHz:

All antennas have test, only the worst case ANT 1 report.

802.11a					Test Frequency: 5745MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11490	28.27	39.40	8.73	36.30	40.10	68.20	-28.10	Horizontal
17235	28.95	41.00	11.37	36.28	45.04	68.20	-23.16	Horizontal
11490	29.90	39.40	8.73	36.30	41.73	68.20	-26.47	Vertical
17235	29.32	41.00	11.37	36.28	45.41	68.20	-22.79	Vertical

802.11a					Test Frequency: 5785MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11570	27.88	39.28	8.77	36.29	39.64	68.20	-28.56	Horizontal
17355	31.42	41.52	11.48	36.26	48.16	68.20	-20.04	Horizontal
11570	32.43	39.28	8.77	36.29	44.19	68.20	-24.01	Vertical
17355	26.59	41.52	11.48	36.26	43.33	68.20	-24.87	Vertical

802.11a					Test Frequency: 5825MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11650	31.46	39.16	8.79	36.27	42.67	68.20	-25.53	Horizontal
17475	27.43	42.30	11.58	36.25	44.20	68.20	-24	Horizontal
11650	30.36	39.16	8.79	36.27	41.46	68.20	-26.74	Vertical
17475	26.84	42.30	11.58	36.25	44.04	68.20	-24.16	Vertical

802.11n(HT20)					Test Frequency: 5745MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11490	33.38	39.40	8.73	36.30	44.32	68.20	-23.88	Horizontal
17235	30.30	41.00	11.37	36.28	45.82	68.20	-22.38	Horizontal
11490	27.78	39.40	8.73	36.30	39.21	68.20	-28.99	Vertical
17235	31.65	41.00	11.37	36.28	46.99	68.20	-21.21	Vertical

802.11n(HT20)					Test Frequency: 5785MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11570	33.06	39.28	8.77	36.29	45.33	68.20	-22.87	Horizontal
17355	30.41	41.52	11.48	36.26	46.78	68.20	-21.42	Horizontal
11570	33.19	39.28	8.77	36.29	45.13	68.20	-23.07	Vertical
17355	26.55	41.52	11.48	36.26	42.74	68.20	-25.46	Vertical

802.11n(HT20)					Test Frequency: 5825MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11650	33.27	39.16	8.79	36.27	44.56	68.20	-23.64	Horizontal
17475	31.02	42.30	11.58	36.25	47.94	68.20	-20.26	Horizontal
11650	30.79	39.16	8.79	36.27	41.99	68.20	-26.21	Vertical
17475	30.23	42.30	11.58	36.25	47.50	68.20	-20.7	Vertical

802.11n(HT40)					Test Frequency: 5755MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11510	29.63	39.40	8.74	36.30	39.93	68.20	-28.27	Horizontal
17265	28.71	41.26	11.40	36.27	44.13	68.20	-24.07	Horizontal
11510	31.73	39.40	8.74	36.30	42.87	68.20	-25.33	Vertical
17265	26.89	41.26	11.40	36.27	41.98	68.20	-26.22	Vertical

802.11n(HT40)					Test Frequency: 5795MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11590	31.73	39.22	8.77	36.28	42.59	68.20	-25.61	Horizontal
17385	28.33	41.78	11.51	36.26	44.72	68.20	-23.48	Horizontal
11590	31.69	39.22	8.77	36.28	41.98	68.20	-26.22	Vertical
17385	30.07	41.78	11.51	36.26	46.16	68.20	-22.04	Vertical

802.11ac(HT20)					Test Frequency: 5745MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11490	31.19	39.40	8.73	36.30	42.35	68.20	-25.85	Horizontal
17235	28.80	41.00	11.37	36.28	43.67	68.20	-24.53	Horizontal
11490	30.65	39.40	8.73	36.30	41.65	68.20	-26.55	Vertical
17235	31.23	41.00	11.37	36.28	46.70	68.20	-21.5	Vertical

802.11ac(HT20)					Test Frequency: 5785MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11570	30.76	39.28	8.77	36.29	41.90	68.20	-26.3	Horizontal
17355	27.87	41.52	11.48	36.26	44.45	68.20	-23.75	Horizontal
11570	27.70	39.28	8.77	36.29	39.36	68.20	-28.84	Vertical
17355	31.40	41.52	11.48	36.26	47.52	68.20	-20.68	Vertical

802.11ac(HT20)					Test Frequency: 5825MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11650	31.21	39.16	8.79	36.27	42.74	68.20	-25.46	Horizontal
17475	29.04	42.30	11.58	36.25	46.57	68.20	-21.63	Horizontal
11650	27.80	39.16	8.79	36.27	39.41	68.20	-28.79	Vertical
17475	25.98	42.30	11.58	36.25	43.48	68.20	-24.72	Vertical

802.11ac(HT40)					Test Frequency: 5755MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11510	28.75	39.40	8.74	36.30	39.05	68.20	-29.15	Horizontal
17265	30.84	41.26	11.40	36.27	46.26	68.20	-21.94	Horizontal
11510	33.72	39.40	8.74	36.30	44.86	68.20	-23.34	Vertical
17265	31.84	41.26	11.40	36.27	46.93	68.20	-21.27	Vertical

802.11ac(HT40)					Test Frequency: 5795MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11590	34.20	39.22	8.77	36.28	45.29	68.20	-22.91	Horizontal
17385	25.67	41.78	11.51	36.26	42.56	68.20	-25.64	Horizontal
11590	30.73	39.22	8.77	36.28	42.35	68.20	-25.85	Vertical
17385	26.73	41.78	11.51	36.26	43.70	68.20	-24.5	Vertical

802.11ac(HT80)					Test Frequency: 5775MHz			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
11550	28.62	39.34	8.76	36.29	40.17	68.20	-28.03	Horizontal
17325	27.91	41.52	11.45	36.26	44.45	68.20	-23.75	Horizontal
11550	27.83	39.34	8.76	36.29	39.52	68.20	-28.68	Vertical
17325	25.92	41.52	11.45	36.26	42.41	68.20	-25.79	Vertical

Notes:

1. Level = Read Level + Antenna Factor+ Cable loss- Preamplifier Factor
2. The test trace is same as the ambient noise (the test frequency range: 18GHz~40GHz), therefore no data appear in the report.
3. If the test result on peak is lower than the limit more than 20dB, then average measurement needn't be performed.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----END-----