

FCC ID:2AYOQ-X2BT

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

According to KDB447498 D01 General RF Exposure Guidance V06

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

BT:
Measurement Result
Operation Frequency: 2402MHz~2480MHz
Power density limited: 1mW/ cm²
Antenna Type: PCB antenna
Antenna gain: 0dBi;
R=20cm
mW=10^{^(dBm/10)}
antenna gain Numeric=10^{^(dBi/10)}

Channel Freq. (MHz)	modulation	conducted pow er	Tune-up pow er (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up pow er		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	DH5	4.49	4±1	5	3.162	0.00	1.00	0.0006	1
2441		3.31	4±1	5	3.162	0.00	1.00	0.0006	1
2480		2.75	3±1	4	2.512	0.00	1.00	0.0005	1
2402	2DH5	6.05	6±1	7	5.012	0.00	1.00	0.0010	1
2441		6.73	6±1	7	5.012	0.00	1.00	0.0010	1
2480		5.53	6±1	7	5.012	0.00	1.00	0.0010	1
2402	3DH5	7.19	7±1	8	6.310	0.00	1.00	0.0013	1
2441		6.83	7±1	8	6.310	0.00	1.00	0.0013	1
2480		5.62	6±1	7	5.012	0.00	1.00	0.0010	1

Signature: 
Date: 2025-5-29

NAME AND TITLE (Please print or type): alex li/Manager
COMPANY (Please print or type): No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street,
Baoan District, Shenzhen, Guangdong, People's Republic of China