

TEST REPORT

Applicant Name: Shenzhen qianfenyi intelligent technology co., LTD.
Address: Room 2101, Building 3, Nanshan i Park Chongwen, 3370 Liuxian Avenue, Nanshan District, Shenzhen China 518000
Report Number: 2401T46527E-RF-00A
FCC ID: 2AYOTME-BOX01

Test Standard (s)

FCC PART 15.247;

Sample Description

Product Type: Meatmeet Pro Wireless Smart Meat Thermometer-Booster
Model No.: ME-BOX01
Multiple Model(s) No.: N/A
Trade Mark: N/A
Date Received: 2024-05-30
Issue Date: 2024-08-15

Test Result:

Pass▲

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Ekko Wu

Ekko Wu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
REQUIREMENTS AND TEST PROCEDURES	11
AC LINE CONDUCTED EMISSIONS.....	11
UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS	13
6 dB EMISSION BANDWIDTH.....	16
PEAK OUTPUT POWER MEASUREMENT	17
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	18
POWER SPECTRAL DENSITY	19
DUTY CYCLE	20
ANTENNA REQUIREMENT	21
TEST DATA AND RESULTS.....	22
AC LINE CONDUCTED EMISSIONS.....	22
UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS	25
6dB EMISSION BANDWIDTH.....	37
MAXIMUM CONDUCTED OUTPUT POWER	39
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	41
POWER SPECTRAL DENSITY	42
DUTY CYCLE	44
MAXIMUM PERMISSIBLE EXPOSURE (MPE)	46
EUT PHOTOGRAPHS	47
TEST SETUP PHOTOGRAPHS	48

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401T46527E-RF-00A	Original Report	2024-08-15

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	2402~2480MHz
Transmit Peak Power	6.95dBm
Modulation Technique	GFSK
Antenna Specification [#]	2.42dBi (provided by the applicant)
Voltage Range	DC 3.6V from battery or DC 5V from USB port
Sample serial number	2MC6-1 for Conducted and Radiated Emissions Test 2MC6-2 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A

Objective

This report is in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, 15.247 rules.

Test Methodology

All tests and measurements indicated in this document were performed in accordance ANSI C63.10-2013.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.94dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
...	...	...	...
...	...	...	...
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

EUT Exercise Software

Exercise Software [#]	EspRFTTestTool-v3.6-Manual.exe
Power Level [#]	maximum of 13

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Qianfenyi	Rechargeable probe	ME-TEMP01	Unknown
XED	Adapter	XED-UL050100CU	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Detachable AC Cable	1	Receptacle	LISN/AC Mains
Un-shielding Detachable USB Cable	1	Adapter	EUT

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC Line Conducted Emissions	PASS
FCC §15.205,§15.209,§15.247(d)	Radiated Spurious Emission	PASS
FCC §15.207(a)(2)	6 dB Emission Bandwidth	PASS
FCC §15.247(b)(1)	Maximum Conducted Output Power	PASS
FCC §15.247(d)	100 kHz Bandwidth of Frequency Band Edge	PASS
FCC §15.247(e)	Power Spectral Density	PASS
C63.10 §11.6	Duty Cycle	PASS
§1.1310 ,§2.1091	Maximum Permissible Exposure (MPE)	PASS
§15.203	Antenna Requirement	PASS

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2023/08/03	2024/08/02
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/01/16	2025/01/15
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Rohde & Schwarz	LISN	ENV216	101613	2024/01/16	2025/01/15
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2023/08/03	2024/08/02
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Sonoma instrument	Pre-amplifier	310N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Unknown	Cable	PNG214	1354	2024/05/21	2025/05/20
Unknown	Cable	2Y194	0735	2024/05/21	2025/05/20
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
COM-POWER	Pre-amplifier	PA-122	181919	2023/06/29	2024/06/28
A.H.System	Horn Antenna	SAS-200/571	135	2021/07/14	2024/07/13
Unknown	RF Cable	KMSE	0735	2023/10/08	2024/10/08
Unknown	RF Cable	UFA147	219661	2023/10/08	2024/10/07
SNSD	2.4G Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2023/08/03	2024/08/02
A.H.System	Pre-amplifier	PAM-1840VH	190	2023/08/02	2024/08/01
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyze	FSU26	200982	2023/12/18	2024/12/17
Unknown	10dB Attenuator	Unknown	F-03-EM065	2023/07/04	2024/07/03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


REQUIREMENTS AND TEST PROCEDURES

AC Line Conducted Emissions

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).


Unwanted Emission Frequencies and Restricted Bands

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;


EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.205, FCC 15.209, FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1-25 GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T_{on}$

Note: T_{on} is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

6 dB Emission Bandwidth

Standard Applicable

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

- Set RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. Procedure as below

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Peak Output Power Measurement


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.9.1.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.
4. Set the $RBW \geq DTS$ bandwidth.
5. Set the $VBW \geq [3 \times RBW]$.
6. Set $span \geq [3 \times RBW]$.
7. Sweep time = auto couple.
8. Detector = peak.
9. Trace mode = max hold.
10. Allow the trace to stabilize.
11. Use peak marker function to determine the peak amplitude level.



100 kHz Bandwidth of Frequency Band Edge

Applicable Standard


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Set the RBW =100 kHz.
 2. Set the VBW $\geq 3 \times$ RBW.
 3. Detector = peak
 4. Sweep time = auto couple.
 5. Trace mode=max hold
 6. All trace to fully stabilize
 7. Use the peak marker function to determine the maximum amplitude level.
- Ensure that amplitude of all unwanted emissions outside of the authorized frequency band(excluding restricted frequency bands) is attenuated by at least the minimum requirement specified in 11.11.
Report the three highest emissions relative to the limit.



Power Spectral Density

Applicable Standard


According to FCC §15.247(e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set analyzer center frequency to DTS channel center frequency
3. Set the span to 1.5 times the DTS bandwidth.
4. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
5. Set the VBW $\geq 3 \times \text{RBW}$.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum amplitude level within the RBW.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.




Duty Cycle

Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)



ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

According to FCC § 15.203, the applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISCED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached, the antenna gain[#] is 2.42dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Type	Antenna Gain [#]	Impedance
Monopole	2.42dBi	50Ω


Result: Compliant

TEST DATA AND RESULTS

AC Line Conducted Emissions

Environmental Conditions

Temperature (°C)	26	Relative Humidity (%)	71
ATM Pressure (kPa)	101	Test engineer	Macy.shi
Test date	2024.6.11		
EUT operation mode	Transmitting(Maximum output power mode, Middle Channel)		




Condition: Line

Project : 2401T46527E-RF

tester : Macy.shi

Note : BLE

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.16	12.60	33.58	10.87	10.11	55.38	-21.80	Average
2	0.16	22.38	43.36	10.87	10.11	65.38	-22.02	QP
3	0.26	11.64	32.44	10.71	10.09	51.34	-18.90	Average
4	0.26	18.31	39.11	10.71	10.09	61.34	-22.23	QP
5	0.48	11.25	31.89	10.51	10.13	46.32	-14.43	Average
6	0.48	20.94	41.58	10.51	10.13	56.32	-14.74	QP
7	1.51	11.35	32.03	10.52	10.16	46.00	-13.97	Average
8	1.51	17.75	38.43	10.52	10.16	56.00	-17.57	QP
9	2.62	10.42	31.07	10.48	10.17	46.00	-14.93	Average
10	2.62	15.88	36.53	10.48	10.17	56.00	-19.47	QP
11	5.62	8.77	29.37	10.42	10.18	50.00	-20.63	Average
12	5.62	14.87	35.47	10.42	10.18	60.00	-24.53	QP



Condition: Neutral

Project : 2401T46527E-RF


tester : Macy.shi

Note : BLE

		Read		LISN	Cable	Limit	Over	
	Freq	Level	Level	Factor	Loss	Line	Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.17	15.30	35.90	10.50	10.10	54.86	-18.96	Average
2	0.17	27.49	48.09	10.50	10.10	64.86	-16.77	QP
3	0.20	13.04	33.53	10.40	10.09	53.62	-20.09	Average
4	0.20	24.44	44.93	10.40	10.09	63.62	-18.69	QP
5	0.49	11.35	32.18	10.69	10.14	46.14	-13.96	Average
6	0.49	21.80	42.63	10.69	10.14	56.14	-13.51	QP
7	1.10	8.60	29.55	10.83	10.12	46.00	-16.45	Average
8	1.10	15.58	36.53	10.83	10.12	56.00	-19.47	QP
9	2.65	7.38	27.95	10.40	10.17	46.00	-18.05	Average
10	2.65	14.27	34.84	10.40	10.17	56.00	-21.16	QP
11	5.39	3.16	23.90	10.56	10.18	50.00	-26.10	Average
12	5.39	10.76	31.50	10.56	10.18	60.00	-28.50	QP


Unwanted Emission Frequencies and Restricted Bands**Environmental Conditions**

Temperature (°C)	25~25.6	Relative Humidity (%)	50
ATM Pressure (kPa):	101	Test engineer:	Anson Su & Sadow Tan
Test date:	2024.06.17-2024.06.24		
EUT operation mode:	Below 1GHz: Transmitting(Maximum output power mode, Middle Channel) Above 1GHz: Transmitting		
Note:	After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded. For the radiated spurious emission below 30MHz, the emissions are 20dB below the limit or the noise floor which are not recorded.		

Below 1GHz:

Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401T46527E-RF
Test Mode : BLE 1M
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.15	-11.62	23.21	11.59	40.00	-28.41	QP
2	98.36	-15.87	24.58	8.71	43.50	-34.79	QP
3	159.99	-13.97	37.96	23.99	43.50	-19.51	QP
4	332.52	-12.26	41.36	29.10	46.00	-16.90	QP
5	556.53	-7.99	28.39	20.40	46.00	-25.60	QP
6	887.22	-4.53	25.08	20.55	46.00	-25.45	QP




Site : Chamber A
 Condition : 3m Vertical
 Project Number: 2401T46527E-RF
 Test Mode : BLE 1M
 Tester : Anson Su

	Freq		Read		Limit	Over	Remark
	MHz	Factor	Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	41.26	-13.73	24.70	10.97	40.00	-29.03	QP
2	99.18	-17.09	24.55	7.46	43.50	-36.04	QP
3	207.03	-14.73	30.41	15.68	43.50	-27.82	QP
4	362.35	-11.92	35.69	23.77	46.00	-22.23	QP
5	499.21	-8.50	28.80	20.30	46.00	-25.70	QP
6	839.18	-5.19	26.11	20.92	46.00	-25.08	QP

Above 1GHz:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave					
GFSK							
Low Channel							
2383.46	54.14	PK	H	-2.93	51.21	74	-22.79
2383.46	39.83	AV	H	-2.93	36.9	54	-17.1
2354.4	54.68	PK	V	-2.93	51.75	74	-22.25
2354.4	39.22	AV	V	-2.93	36.29	54	-17.71
4804	52.74	PK	H	1.69	54.43	74	-19.57
4804	46.53	AV	H	1.69	48.22	54	-5.78
4804	52.34	PK	V	1.69	54.03	74	-19.97
4804	45.89	AV	V	1.69	47.58	54	-6.42
Middle Channel							
4880	51.99	PK	H	1.69	53.68	74	-20.32
4880	44	AV	H	1.69	45.69	54	-8.31
4880	51.27	PK	V	1.69	52.96	74	-21.04
4880	44.57	AV	V	1.69	46.26	54	-7.74
High Channel							
2484.51	61.27	PK	H	-3.17	58.1	74	-15.9
2484.51	47.26	AV	H	-3.17	44.09	54	-9.91
2483.89	61.57	PK	V	-3.17	58.4	74	-15.6
2483.89	47.6	AV	V	-3.17	44.43	54	-9.57
4960	49.54	PK	H	2.77	52.31	74	-21.69
4960	35.24	AV	H	2.77	38.01	54	-15.99
4960	52.86	PK	V	2.77	55.63	74	-18.37
4960	35.31	AV	V	2.77	38.08	54	-15.92

Test plots




Condition : Horizontal
Project No.: 2401T46527E-RF
Tester : Sadow Tan
Note : BLE 1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2484.511	-3.17	47.26	44.09	54.00	-9.91	Average
2	2484.511	-3.17	61.27	58.10	74.00	-15.90	peak




Condition : Vertical
Project No.: 2401T46527E-RF
Tester : Sadow Tan
Note : BLE 1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.892	-3.17	47.60	44.43	54.00	-9.57	Average
2	2483.892	-3.17	61.57	58.40	74.00	-15.60	peak




Condition : Horizontal
 Project No.: 2401T46527E-RF
 Tester : Sadow Tan
 Note : BLE 1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3594.250	-1.75	34.05	32.30	54.00	-21.70	Average
2	3594.250	-1.75	51.55	49.80	74.00	-24.20	Peak




Condition : Vertical
Project No.: 2401T46527E-RF
Tester : Sadow Tan
Note : BLE 1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3516.250	-1.72	35.69	33.97	54.00	-20.03	Average
2	3516.250	-1.71	51.20	49.49	74.00	-24.51	Peak




Condition : Horizontal
Project No.: 2401T46527E-RF
Tester : Sadow Tan
Note : BLE 1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4960.000	2.77	35.24	38.01	54.00	-15.99	Average
2	4960.000	2.77	49.54	52.31	74.00	-21.69	Peak
3	17916.000	24.02	22.13	46.15	54.00	-7.85	Average
4	17916.000	24.02	38.08	62.10	74.00	-11.90	Peak




Condition : Vertical
Project No.: 2401T46527E-RF
Tester : Sadow Tan
Note : BLE 1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4960.000	2.77	35.31	38.08	54.00	-15.92	Average
2	4960.000	2.77	52.86	55.63	74.00	-18.37	Peak
3	17994.750	24.58	21.55	46.13	54.00	-7.87	Average
4	17994.750	24.58	37.10	61.68	74.00	-12.32	Peak



Condition : Horizontal
Project No.: 2401T46527E-RF
Tester : Sadow Tan
Note : BLE 1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	22770.500	17.22	29.04	46.26	54.00	-7.74	Average
2	22770.500	17.22	42.28	59.50	74.00	-14.50	peak



Condition : Vertical
Project No.: 2401T46527E-RF
Tester : Sadow Tan
Note : BLE 1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	23585.130	17.52	28.76	46.28	54.00	-7.72	Average
2	23585.130	17.52	42.67	60.19	74.00	-13.81	peak

6dB Emission Bandwidth

Test Information:

Serial No.:	2MC6-2	Test Date:	2024/06/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Cheng	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	56	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	---------------------------	-----

BLE 1M

Mode	Value (MHz)	Limit (MHz)	Result
Low	0.665	0.5	Pass
Middle	0.669	0.5	Pass
High	0.667	0.5	Pass

Maximum Conducted Output Power

Test Information:

Serial No.:	2MC6-2	Test Date:	2024/06/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Cheng	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	56	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	---------------------------	-----

BLE 1M


Mode	Value (dBm)	Limit (dBm)	Result
Low	6.82	30.00	Pass
Middle	6.95	30.00	Pass
High	6.22	30.00	Pass

BLE 1M
Low




ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:42:13

Middle



ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:49:04

High



ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:54:24

100 kHz Bandwidth of Frequency Band Edge

Test Information:

Serial No.:	2MC6-2	Test Date:	2024/06/13~2024/06/28
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Cheng	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	56	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	---------------------------	-----

BLE 1M


Mode	Value (dB)	Limit (dB)	Result
Low	48.39	20.00	Pass
High	49.30	20.00	Pass

BLE 1M
Low



ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:45:44

High



ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 28-JUN-2024 15:55:16

Power Spectral Density

Test Information:

Serial No.:	2MC6-2	Test Date:	2024/06/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Cheng	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.5	Relative Humidity: (%)	56	ATM Pressure: (kPa)	101
----------------------	------	---------------------------	----	------------------------	-----

BLE 1M

Mode	Value (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-10.38	8.00	Pass
Middle	-10.13	8.00	Pass
High	-10.86	8.00	Pass


BLE 1M

Low




ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:44:21

Middle



ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:51:12

High



ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:56:31

Duty Cycle

Test Information:

Serial No.:	2MC6-2	Test Date:	2024/06/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Cheng	Test Result:	/

Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	56	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	---------------------------	-----


BLE 1M

Mode	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	1/Ton (Hz)	VBW Setting (kHz)
Low	100	100	100	/	0.01
Middle	100	100	100	/	0.01
High	100	100	100	/	0.01

Duty Cycle = Ton/(Ton+Toff)*100%


BLE 1M

Low




ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:41:33

Middle



ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:48:23

High



ProjectNo.:2401T46527E-RF Tester:Jim Cheng
Date: 13-JUN-2024 14:53:29

MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Result

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

For worst case:

Mode	Frequency (MHz)	Antenna Gain [#]		Max Tune-up Power [#]		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402-2480	2.42	1.75	7.0	5.01	20	0.0017	1.0
2.4G Wi-Fi	2412-2462	2.42	1.75	20.0	100.00	20	0.0348	1.0

Note:

1) The tune up conducted power and antenna gain was declared by the applicant.

2) The 2.4G Wi-Fi and BLE cannot transmit at same time.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

TR-EM-RF003

Page 46 of 48

Version 1.0 (2023/10/07)

EUT PHOTOGRAPHS

Please refer to the attachment 2401T46527E-RF External photo and 2401T46527E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2401T46527E-RF-A Test Setup photo.

******* END OF REPORT *******