

# TEST REPORT

Applicant Name: FCC: Shenzhen qianfenyi intelligent technology co., LTD.  
IC: Shenzhen Qianfenyi Intelligent Technology Co., LTD  
Address: FCC: Room 2101, Building 3, Nanshan i Park Chongwen, 3370 Liuxian Avenue, Nanshan District, Shenzhen China 518000  
IC: Room 2101, Building 3, Nanshan i Park Chongwen, 3370 Liuxian Avenue, Nanshan District Shenzhen 518000 China (Peoples Republic Of)  
Report Number: 2501S52654E-RFA  
FCC ID: 2AYOTME-BOX02  
IC: 26903-MEBOX02

**Test Standard (s)**

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2;  
RSS-247 ISSUE 3, AUGUST 2023

**Sample Description**


Product Type: Meatmeet S Pro Meat Thermometer  
Model No.: ME-BOX02  
Multiple Model(s) No.: N/A  
Trade Mark: N/A  
Date Received: 2025-04-14  
Issue Date: 2025-06-25

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

**Prepared and Checked By:**

Bruce Lin  
RF Engineer

**Approved By:**

Nancy Wang  
RF Supervisor

Note: The information marked\* is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.  
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.  
This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.  
This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

**Bay Area Compliance Laboratories Corp. (Shenzhen)**

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China  
Tel: +86-755-33320018    Fax: +86-755-33320008    [www.baclcorp.com.cn](http://www.baclcorp.com.cn)

## **TABLE OF CONTENTS**

<b>DOCUMENT REVISION HISTORY .....</b>	<b>3</b>
<b>GENERAL INFORMATION .....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION .....</b>	<b>6</b>
<b>SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>10</b>
<b>REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>12</b>
AC LINE CONDUCTED EMISSIONS.....	12
UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS .....	15
99% OCCUPIED BANDWIDTH & 6 dB EMISSION BANDWIDTH .....	18
PEAK OUTPUT POWER MEASUREMENT .....	20
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	21
POWER SPECTRAL DENSITY .....	22
DUTY CYCLE.....	23
<b>ANTENNA REQUIREMENT .....</b>	<b>24</b>
ANTENNA CONNECTOR CONSTRUCTION .....	25
<b>TEST DATA AND RESULTS .....</b>	<b>26</b>
AC LINE CONDUCTED EMISSIONS.....	26
UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS .....	29
RF CONDUCTED DATA .....	49
<b>RF EXPOSURE EVALUATION .....</b>	<b>50</b>
<b>EUT PHOTOGRAPHS .....</b>	<b>53</b>
<b>TEST SETUP PHOTOGRAPHS .....</b>	<b>54</b>
<b>APPENDIX.....</b>	<b>55</b>
APPENDIX A: DTS BANDWIDTH .....	55
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....	57
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER .....	59
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY .....	59
APPENDIX E: BAND EDGE MEASUREMENTS.....	61
APPENDIX F: DUTY CYCLE .....	62

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501S52654E-RFA	Original Report	2025-06-25

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>HVIN</b>	ME-BOX02
<b>FVIN</b>	N/A
<b>Frequency Range</b>	2402~2480MHz
<b>Maximum Conducted Output Peak Power</b>	7.00dBm
<b>Modulation Technique</b>	GFSK
<b>Antenna Specification<sup>#</sup></b>	2.42dBi (provided by the applicant)
<b>Voltage Range</b>	DC 3.6V from battery or DC 5V from USB Port
<b>Sample serial number</b>	318A-2 for Conducted and Radiated Emissions Test 318A-4 for RF Conducted Test (Assigned by BACL, Shenzhen)
<b>Sample/EUT Status</b>	Good condition
<b>Adapter Information</b>	N/A

### Objective

This report is in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, 15.247 rules and RSS-GEN Issue 5, February 2021 Amendment 2 and RSS-247 Issue 3, August 2023 of the Innovation, Science and Economic Development Canada rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices, RSS-GEN Issue 5, February 2021 Amendment 2 and RSS-247 Issue 3, August 2023.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
Power Spectral Density		0.90dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.63dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.64dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

### EUT Exercise Software

Exercise Software <sup>#</sup>	GRDirect Test Mode		
<b>Power Level<sup>#</sup></b>			
Mode	Low Channel	Middle Channel	High Channel
BLE 1M	-20	-20	-20

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

**Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
OUPU	Socket	PDU-OP1606K	6971041358020
XED	Adapter	XED-UL050100CU	Unknown
Huajin	Adapter	HJ-0501000E1-US	Unknown
Qianfenyi	Thermometer	ME-TEMP02	Unknown

**External I/O Cable**


Cable Description	Length (m)	From Port	To
Unshielded Un-detachable AC cable	1.2	Socket	LISN/AC Mains
Unshielded Detachable USB cable	1.0	EUT	Adapter
Unshielded Detachable USB cable	0.5	EUT	Adapter

**Block Diagram of Test Setup**


For Conducted Emissions:



For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



## SUMMARY OF TEST RESULTS

Test Rules	Test Rules	Description of Test	Result
FCC §15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
FCC §15.207 (a)	RSS-Gen §8.8	AC Line Conducted Emissions	Compliant
FCC §15.205, §15.209, §15.247(d)	RSS-GEN § 8.10 & RSS-247 § 5.5	Spurious Emissions	Compliant
FCC §15.247 (a)(2)	RSS- Gen§6.7 RSS-247 § 5.2 (a)	99% Occupied Bandwidth & 6 dB Emission Bandwidth	Compliant
FCC §15.247(b)(3)	RSS-247 § 5.4(d)	Maximum Conducted Output Power	Compliant
FCC §15.247(e)	RSS-247 § 5.2 (b)	Power Spectral Density	Compliant
FCC §15.247(d)	RSS-247 § 5.5	100 kHz Bandwidth of Frequency Band Edge	Compliant
C63.10 §11.6	C63.10 §11.6	Duty Cycle	/
FCC §1.1307(b) (3), §2.1091	/	MPE-Based Exemption	Compliant
/	RSS-102 § 6.6	Field reference level exposure exemption limits	Compliant

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2025/04/29	2026/04/28
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2025/04/29	2026/04/28
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
<b>Radiated Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310N	186238	2025/04/29	2026/04/28
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber Cable 1	F-03-EM236	2025/04/29	2026/04/28
Unknown	Cable	XH500C	J-10M-A	2025/04/29	2026/04/28
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
Unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2025/03/26	2026/03/25
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Unknown	RF Cable	XH750A-N	J-10M	2024/12/06	2025/12/05
JD	Filter Switch Unit	DT7220FSU	DS79906	2024/09/09	2025/09/08
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
A.H.System	Pre-amplifier	PAM-1840VH	190	2025/04/29	2026/04/28
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/12/18	2025/12/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>RF Conducted Test</b>					
Tonscend	RF control Unit	JS0806-2	19D8060154	2024/08/06	2025/08/05
Rohde & Schwarz	Spectrum Analyzer	FSV40	101473	2024/12/04	2025/12/03
ANRITSU	Microwave peak power sensor	MA24418A	12622	2025/04/29	2026/04/28
Unknown	10dB Attenuator	Unknown	F-03-EM065	2024/06/27	2025/06/26

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## REQUIREMENTS AND TEST PROCEDURES

### AC Line Conducted Emissions

#### Applicable Standard

FCC§15.207 (a) & RSS-GEN §8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50  $\mu$ H / 50  $\Omega$  line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

**Table 4 - AC Power Lines Conducted Emission Limits**


Frequency range (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 <sup>1</sup>	56 to 46 <sup>1</sup>
0.5 – 5	56	46
5 – 30	60	50

**Note 1:** The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- (a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- (b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

## EUT Setup



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 & RSS-247/RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

## Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).


## Unwanted Emission Frequencies and Restricted Bands

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205; RSS-247 §5.5, RSS-GEN §8.10.


### EUT Setup

#### 9 kHz-30MHz:



#### 30MHz-1GHz:



**Above 1GHz:**

The radiated emission tests were performed in the 3meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.205, FCC 15.209, FCC 15.247, RSS-Gen and RSS-247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak

1-25GHz:  
Pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	1 kHz	Peak
	<98%	1MHz	≥1/Ton	Peak

Final measurement for emission identified during pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	10 Hz	Peak
	<98%	1MHz	≥1/Ton	Peak

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

## Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit/Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit/Margin} = \text{Level} / \text{Corrected Amplitude} - \text{Limit}$$

$$\text{Level} / \text{Corrected Amplitude} = \text{Read Level} + \text{Factor}$$

## 99% Occupied Bandwidth & 6 dB Emission Bandwidth

### Standard Applicable

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

According to RSS-247 §5.2 a)

The minimum 6 dB bandwidth shall be 500 kHz.

According to RSS-Gen §6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).


## Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3& RSS-Gen §6.7

- a. Set RBW = 100 kHz.
- b. Set the VBW  $\geq [3 \times \text{RBW}]$ .
- c. Detector = peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize.
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. Procedure as below

- a. The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW (for RSS rules, VBW shall not be smaller than three times the RBW, unless otherwise specified by the applicable requirement).
- c. Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level.
- d. Step a) through step c) might require iteration to adjust within the specified range.
- e. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f. Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g. If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h. The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data maybe reported in addition to the plot(s).



## Peak Output Power Measurement

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.


According to RSS-247§5.4 d) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(e), the e.i.r.p. shall not exceed 4 W.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

Test method: ANSI C63.10-2020 clause 11.9.1.2 for peak power method.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss

## 100 kHz Bandwidth of Frequency Band Edge

### Applicable Standard

According to FCC §15.247(d).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


According to RSS-247 §5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Set the RBW =100 kHz.
2. Set the VBW  $\geq 3 \times$  RBW.
3. Detector = peak
4. Sweep time = auto couple.
5. Trace mode=max hold
6. All trace to fully stabilize
7. Use the peak marker function to determine the maximum amplitude level.  
Ensure that amplitude of all unwanted emissions outside of the authorized frequency band(excluding restricted frequency bands) is attenuated by at least the minimum requirement specified in 11.11.  
Report the three highest emissions relative to the limit.



## Power Spectral Density

### Applicable Standard

According to FCC §15.247(e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


According to RSS-247 §5.2 b):

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power)

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set analyzer center frequency to DTS channel center frequency
3. Set the span to 1.5 times the DTS bandwidth.
4. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
5. Set the VBW  $\geq 3 \times \text{RBW}$ .
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum amplitude level within the RBW.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss


## Duty Cycle

### Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set  $RBW \geq OBW$  if possible; otherwise, set  $RBW$  to the largest available value.
- 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both  $RBW$  and  $VBW$  are  $> 50/T$  and the number of sweep points across duration  $T$  exceeds 100. (For example, if  $VBW$  and/or  $RBW$  are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)



## ANTENNA REQUIREMENT

### Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

### **Antenna Connector Construction**

The EUT has one internal antenna arrangement which was permanently attached and the maximum antenna gain<sup>#</sup> is 2.42dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	Antenna Gain <sup>#</sup>	Impedance	Frequency Range
Monopole	2.42dBi	50Ω	2.4~2.48GHz

**Result: Compliant**


## TEST DATA AND RESULTS

### AC Line Conducted Emissions

#### Environmental Conditions


Temperature (°C)	26.8	Relative Humidity (%)	62
ATM Pressure (kPa)	100.3	Test engineer	Macy.shi
Test date	2025.5.10		
EUT operation mode	Transmitting (Maximum output power mode, Low channel)		

AC 120V 60 Hz, Line



Freq	MHz	Read	LISN	Cable	Limit	Over	Remark
		Level	Level	Factor	Loss	Line	
1	0.156	10.91	31.47	10.44	10.12	55.65	-24.18 Average
2	0.156	23.49	44.05	10.44	10.12	65.65	-21.60 QP
3	0.200	4.22	25.01	10.70	10.09	53.62	-28.61 Average
4	0.200	16.60	37.39	10.70	10.09	63.62	-26.23 QP
5	0.365	4.26	24.94	10.57	10.11	48.61	-23.67 Average
6	0.365	12.84	33.52	10.57	10.11	58.61	-25.09 QP
7	1.374	7.49	28.47	10.83	10.15	46.00	-17.53 Average
8	1.374	17.46	38.44	10.83	10.15	56.00	-17.56 QP
9	2.121	5.44	26.71	11.08	10.19	46.00	-19.29 Average
10	2.121	13.30	34.57	11.08	10.19	56.00	-21.43 QP
11	16.928	9.29	30.08	10.59	10.20	50.00	-19.92 Average
12	16.928	20.58	41.37	10.59	10.20	60.00	-18.63 QP

AC 120V 60 Hz, Neutral



	Freq	Read Level	LISN Level	Cable Factor	Limit Loss	Line Limit	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.156	8.54	29.12	10.46	10.12	55.65	-26.53	Average
2	0.156	21.08	41.66	10.46	10.12	65.65	-23.99	QP
3	0.213	2.32	23.19	10.78	10.09	53.10	-29.91	Average
4	0.213	11.51	32.38	10.78	10.09	63.10	-30.72	QP
5	0.433	7.15	27.81	10.55	10.11	47.20	-19.39	Average
6	0.433	14.76	35.42	10.55	10.11	57.20	-21.78	QP
7	0.647	6.93	27.64	10.58	10.13	46.00	-18.36	Average
8	0.647	16.00	36.71	10.58	10.13	56.00	-19.29	QP
9	2.765	2.67	23.69	10.84	10.18	46.00	-22.31	Average
10	2.765	11.69	32.71	10.84	10.18	56.00	-23.29	QP
11	16.226	8.28	29.01	10.52	10.21	50.00	-20.99	Average
12	16.226	19.21	39.94	10.52	10.21	60.00	-20.06	QP


## Unwanted Emission Frequencies and Restricted Bands

### Environmental Conditions

Temperature (°C)	24-26	Relative Humidity (%)	50-52
ATM Pressure (kPa):	101-102	Test engineer:	Anson su& Wing k ji
Test date:	2025.5.15-2025.5.26		
EUT operation mode:	Below 1GHz: Transmitting (Maximum output power mode, Low channel) Above 1GHz: Transmitting		
Note:	<ol style="list-style-type: none"><li>1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded.</li><li>2. For the radiated spurious emission below 1GHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.</li><li>3. The spurious emission from 9 kHz-30MHz of IC RSS-GEN standard, the unit of final result on the test plots are dB<math>\mu</math>V/m, so the limit should be added by 51,5 dB from dB<math>\mu</math>A/m to dB<math>\mu</math>V/m.</li><li>4. After pre-scan in the X, Y and Z axes of orientation, the worst case y-axis of orientation were recorded.</li></ol>		

**Below 1GHz:**


9kHz-150kHz



Site : Chamber A  
Condition : 3m  
Project Number : 2501S52654E-RF  
Test Mode : Transmitting  
Detector: Peak RBW/VBW: 0.3/1kHz  
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	0.010	32.25	25.58	57.83	127.38	-69.55	Peak
2	0.018	30.83	24.84	55.67	122.63	-66.96	Peak
3	0.031	28.38	29.01	57.39	117.73	-60.34	Peak
4	0.060	25.40	28.44	53.84	112.04	-58.20	Peak
5	0.090	22.69	28.00	50.69	108.51	-57.82	Peak
6	0.130	20.25	24.88	45.13	105.35	-60.22	Peak


150kHz-30MHz



Site : Chamber A  
Condition : 3m  
Project Number : 2501S52654E-RF  
Test Mode : Transmitting  
Detector: Peak RBW/VBW: 10/30kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	0.247	13.35	37.11	50.46	99.76 -49.30 Peak
2	0.703	3.89	44.86	48.75	70.59 -21.84 Peak
3	0.939	1.65	37.40	39.05	68.03 -28.98 Peak
4	1.408	0.06	35.51	35.57	64.44 -28.87 Peak
5	2.380	-1.81	32.91	31.10	69.54 -38.44 Peak
6	9.005	-2.90	34.12	31.22	69.54 -38.32 Peak


## 30MHz-1GHz\_Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2501S52654E-RF  
Test Mode : Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	120.07	-11.44	33.09	21.65	43.50	-21.85	Peak
2	156.66	-12.64	40.79	28.15	43.50	-15.35	Peak
3	168.49	-13.05	43.89	30.84	43.50	-12.66	Peak
4	226.50	-14.01	43.69	29.68	46.00	-16.32	Peak
5	339.29	-10.42	37.43	27.01	46.00	-18.99	Peak
6	444.07	-7.54	36.44	28.90	46.00	-17.10	Peak

## 30MHz-1GHz\_Verical



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2501S52654E-RF  
Test Mode : Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
		MHz	dB/m	dBuV	dBuV/m	dB
1	168.05	-13.00	35.24	22.24	43.50	-21.26 Peak
2	180.10	-13.65	34.13	20.48	43.50	-23.02 Peak
3	216.69	-14.20	32.71	18.51	46.00	-27.49 Peak
4	332.08	-10.61	35.77	25.16	46.00	-20.84 Peak
5	443.88	-7.55	33.90	26.35	46.00	-19.65 Peak
6	492.04	-5.97	31.04	25.07	46.00	-20.93 Peak

**Above 1GHz:**

Frequency (MHz)	Reading (dB $\mu$ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
<b>BLE 1M</b>							
Low Channel							
4804	55.23	PK	H	-7.79	47.44	74	-26.56
4804	57.04	PK	V	-7.79	49.25	74	-24.75
Middle Channel							
4880	55.77	PK	H	-7.59	48.18	74	-25.82
4880	57.08	PK	V	-7.59	49.49	74	-24.51
High Channel							
4960	56.04	PK	H	-7.56	48.48	74	-25.52
4960	55.45	PK	V	-7.56	47.89	74	-26.11

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.

**Test plots:****Band Edge**

Left Band edge Horizontal Peak



Condition : Horizontal

Project No. : 2501S52654E-RF


Tester : Wing K Ji

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : BLE\_1M\_2402

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	2386.141	-10.97	62.26	51.29	74.00 -22.71 Peak
2	2390.000	-10.98	60.34	49.36	74.00 -24.64 Peak


## Left Band edge\_Vertical\_Peak



Condition : Vertical  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2402

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	2338.132	-10.86	62.26	51.40	74.00	-22.60	Peak
2	2390.000	-10.98	60.23	49.25	74.00	-24.75	Peak


## Right Band edge\_Horizontal\_Peak



Condition : Horizontal  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

Freq Factor	MHz	dB/m	Read	Limit	Over	Remark
			Level	Level	Line	
1	2483.500	-10.97	71.53	60.56	74.00	-13.44 Peak
2	2483.558	-10.97	72.18	61.21	74.00	-12.79 Peak


## Right Band edge\_Horizontal\_Average



Condition : Horizontal  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Average reading: RBW:1MHz VBW:1kHz Detector:Peak  
Note : BLE\_1M\_2480

Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	2483.500	-10.97	61.40	50.43	54.00	-3.57	Average
2	2483.525	-10.97	61.45	50.48	54.00	-3.52	Average


## Right Band edge\_Vertical\_Peak



Condition : Vertical  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	2483.500	-10.97	71.49	60.52	74.00	-13.48	Peak
2	2483.610	-10.97	72.52	61.55	74.00	-12.45	Peak

## Right Band edge\_Vertical\_Average




Condition : Vertical  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Average reading: RBW:1MHz VBW:1kHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read		Limit		Over	Limit	Remark
		MHz	dB/m	dBuV	dBuV/m			
1	2483.500	-10.97	60.83	49.86	54.00	-4.14	Average	
2	2483.515	-10.97	60.85	49.88	54.00	-4.12	Average	

**Listed with the worst harmonic margin test plot**


1-4GHz\_Horizontal



Condition : Horizontal  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2440

Freq Factor	Read		Limit		Over	Remark
	MHz	dB/m	Level	dBuV/m	Line	dBuV/m
1	3367.671	-10.26	50.32	40.06	74.00	-33.94 Peak


## 1-4GHz\_Verical



Condition : Vertical  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2440

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	Level	dBuV	dBuV/m	
1	3917.115	1	-9.67	50.07	40.40	74.00	-33.60 Peak


## 4-18GHz\_Horizontal\_Peak



Condition : Horizontal  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2440

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	4880.000	-7.59	55.77	48.18	74.00	-25.82	Peak
2	17940.490	12.90	47.71	60.61	74.00	-13.39	Peak


## 4-18GHz\_Horizontal\_Average



Condition : Horizontal  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Average reading: RBW:1MHz VBW:3kHz Detector:Peak  
Note : BLE\_1M\_2440

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	17984.250	13.12	34.62	47.74	54.00	-6.26	Average


## 4-18GHz\_Vertical\_Peak



Condition : Vertical  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2440

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	4880.000	-7.59	57.08	49.49	74.00	-24.51	Peak
2	17986.000	13.13	46.97	60.10	74.00	-13.90	Peak


## 4-18GHz\_Vertical\_Average



Condition : Vertical  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Average reading: RBW:1MHz VBW:3kHz Detector:Peak  
Note : BLE\_1M\_2440

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	17994.750	13.17	34.71	47.88	54.00	-6.12	Average


## 18-25GHz\_Horizontal



Condition : Horizontal  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2440

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	19217.280	15.40	37.02	52.42	74.00	-21.58	peak

## 18-25GHz\_Vertical



Condition : Vertical  
Project No. : 2501S52654E-RF  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2440

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	19380.050	15.46	36.94	52.40	74.00	-21.60	peak

**RF Conducted data****Test Information:**

<b>Sample No.:</b>	318A-4	<b>Test Date:</b>	2025/05/28
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Navilite Cai	<b>Test Result:</b>	Pass

**Environmental Conditions:**

<b>Temperature:</b> (°C)	26.8	<b>Relative Humidity:</b> (%)	50.6	<b>ATM Pressure:</b> (kPa)	101.4
-----------------------------	------	--------------------------------------	------	-------------------------------	-------

The test data please refer to the Appendix.

## RF EXPOSURE EVALUATION

### MPE-Based Exemption

#### Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

#### MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R <sup>2</sup> .
1.34-30	3,450 R <sup>2</sup> /f <sup>2</sup> .
30-300	3.83 R <sup>2</sup> .
300-1,500	0.0128 R <sup>2</sup> f.
1,500-100,000	19.2R <sup>2</sup> .

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

**Result**

Mode	Frequency (MHz)	Tune up conducted power <sup>#</sup> (dBm)	Antenna Gain <sup>#</sup>		ERP		Evaluation Distance (m)	ERP Limit (mW)
			(dBi)	(dBd)	(dBm)	(mW)		
BLE	2402-2480	7.5	2.42	0.27	7.77	5.98	0.2	768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.  
2. 0dBd=2.15dBi

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant**

## Field reference level exposure exemption limits

### Applicable Standard

According to RSS-102 Issue 6§6.6:

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance)
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $1.31 \times 10^{-2}f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 5 W (adjusted for tune-up tolerance) In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the EIRP was derived.

### Calculated Data:

Mode	Frequency (MHz)	Maximum tune-up conducted power <sup>#</sup> (dBm)	Antenna Gain <sup>#</sup> (dBi)	Maximum tune-up EIRP		Evaluation Distance (m)	Limit (mW)
				(dBm)	(mW)		
BLE	2402-2480	7.5	2.42	9.92	9.82	0.2	2676

Note: The tune up conducted power<sup>#</sup> and antenna gain<sup>#</sup> was declared by the applicant.

### Result: Compliant

Note: To maintain compliance with the RF exposure guidelines, place the equipment at least 20cm from nearby persons.

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment 2501S52654E-RF External photo and 2501S52654E-RF Internal photo.

## **TEST SETUP PHOTOGRAPHS**

Please refer to the attachment 2501S52654E-RF Test Setup photo.


## APPENDIX


### Appendix A: DTS Bandwidth

#### Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.696	2401.636	2402.332	0.5	PASS
		2440	0.672	2439.644	2440.316	0.5	PASS
		2480	0.664	2479.644	2480.308	0.5	PASS

#### Test Graphs







## Appendix B: Occupied Channel Bandwidth

### Test Result

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.031	2401.4605	2402.4915	---	---
		2440	1.011	2439.4685	2440.4795	---	---
		2480	1.019	2479.4645	2480.4835	---	---

### Test Graphs





## Appendix C: Maximum conducted output power

### Test Result


Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power [dBm]	Conducted Limit[dBm]	EIRP[dBm]	IC EIRP Limit [dBm]	Verdict
BLE_1M	Ant1	2402	7.00	≤30	9.42	≤36	PASS
		2440	6.77	≤30	9.19	≤36	PASS
		2480	6.60	≤30	9.02	≤36	PASS


## Appendix D: Maximum power spectral density

### Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-2.56	≤8.00	PASS
		2440	-2.92	≤8.00	PASS
		2480	-3.08	≤8.00	PASS


### Test Graphs





## Appendix E: Band edge measurements

### Test Graphs




## Appendix F: Duty Cycle

### Test Result

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]	1/Ton[Hz]	VBW Setting [kHz]
BLE_1M	Ant1	2440	1.67	1.87	89.30	0.49	599	1

### Test Graphs



\*\*\*\*\* END OF REPORT \*\*\*\*\*