

Maximum Permissible Exposure Report

FCC ID: 2AYQN-SA1

Report No. : BTL-FCCP-3-2211G064
Equipment : Radio Alarm Clock
Model Name : SA1, SA2, SA3, SA4, SA5, SA6, SA7, SA8, SA9, SA10, SA11, SA12, SA13, SA14, SA15, SA16, SA17, SA18, SA19, SA20, SA21, SA22, SA23, SA24, SA25, SA26, SA27, SA28, SA29, SA30, SA31, SA32, SA33, SA34, SA35, SA36, SA37, SA38, SA39, SA40, SA41, SA42, SA43, SA44, SA45, SA46, SA47, SA48, SA49, SA50
Brand Name : EZVALO, EZVALO LITE, **EZVALO**, **EZVALO Lite**, **EZVALO LITE**
Applicant : Guangzhou EZVALO Technology Company Limited
Address : Unit 1503 and 1504, 15/F, 166 Huangpu Park West Road, Huangpu District, Guangzhou, China
FCC Rule Part(s) : FCC Guidelines for Human Exposure IEEE C95.1
Date of Receipt : 2022/12/09
Date of Test : 2023/1/7~2023/1/18
Issued Date : 2023/2/8

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by : Eric Lee
Eric Lee, Engineer



Approved by : Jerry Chuang
Jerry Chuang, Supervisor

BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-3-2211G064	R00	Original Report.	2023/2/8	Valid

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Type	Connector	Frequency (MHz)	Gain (dBi)
1	ZHUHAI JIELI TECHNOLOGY CO.,LTD	2.4G ANT	Internal	N/A	2400-2500	-0.58

The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

Maximum RF OUTPUT POWER

Mode	Maximum Power (dBm)
Bluetooth EDR	-2.82

Note: The values are adopted from test report: BTL-FCCP-1-2211G064.

CALCULATED RESULT

Band	Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Result
Bluetooth EDR	-0.58	0.8750	-2.82	0.5224	0.000091	1	Pass

Note:

1. The calculated distance is 20 cm.

End of Test Report