

MPE Report

Applicant : Sound Land Corporation

Product Name : No.32, Keji 1st Rd., Guishan Dist., Taoyuan City 33383, Taiwan

Trade Name : Sound Mixer

Model Number : Maker hart 

Applicable Standard : 47 CFR §2.1091

Received Date : Sep. 16, 2022

Issue Date : Nov. 23, 2022

Issued by

Approved By :

(Kris Pan)

Eurofins E&E Wireless Taiwan Co., Ltd.
No. 140-1, Changan Street, Bade District,
Taoyuan City 334025, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note:

1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
2. This report shall not be reproduced except in full, without the written approval of Eurofins E&E Wireless Taiwan Co., Ltd.
3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

Revision History

Rev.	Issued Date	Revisions	Revised By
00	Nov. 23, 2022	Initial Issue	Nicole Chu

Contents

1.	General Information	4
2.	Description of Equipment under Test (EUT)	5
3.	RF Exposure Limit	6
4.	RF Exposure Assessment.....	7
5.	Maximum Tune-up Power.....	9
6.	Test Result	9
7.	Conclusion.....	9

1. General Information

1.1 Reference Applicable Standard

Standard	Description	Version
IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	1992
47 CFR § 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.	-
47 CFR § 1.1310	Radiofrequency radiation exposure limits.	-
KDB 447498 D04	RF exposure procedures and equipment authorization policies for mobile and portable devices	v01

1.2 Testing Location

Site Name: Site Name: Eurofins E&E Wireless Taiwan Co., Ltd.

Site Address: ☒ No. 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan (R.O.C.)

Site Address: ☐ No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan (R.O.C.)

2. Description of Equipment under Test (EUT)

Applicant	Sound Land Corporation No.32, Keji 1st Rd., Guishan Dist., Taoyuan City 33383, Taiwan
Product Name	Sound Mixer
Trade Name	Maker hart 
Model Number	Just Combo V
FCC ID	2AYQY-COMBO-V
Frequency Range	Bluetooth : 2402 - 2480 MHz
Supported Modulations	Bluetooth : BR / EDR / LE
Device Category	Mobile

Note:

The above information of DUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Antenna Information					
Antenna	Brand	Model	Type	Frequency (MHz)	Max. Gain (dBi)
ASE	PSA	RFECA3216060A1T	Ceramic Antenna	2400 ~ 2483.5	2.0
Kirchhoff	TEXAS INSTRUMENTS	SWRA117D	PCB Antenna	2400 ~ 2483.5	5.3

3. RF Exposure Limit

For devices that operate at larger distances from persons, where there are minimal RF coupling interactions between a device and the user or nearby persons, RF exposure compliance using maximum permissible exposure (MPE) limits is applied. The limits for MPE is listed as below:

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824 / f	2.19 / f	(180 / f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F / 1,500	30
1,500-100,000	-	-	1.0	30
Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1,842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1,500	-	-	F / 300	6
1,500-100,000	-	-	5	6


f = frequency in MHz. * = Plane-wave equivalent power density.

4. RF Exposure Assessment

4.1 Exemption Evaluation

Exemption evaluation was performed according to the appendix A and B in KDB447498 D04.

The General Sequence for Determination of Procedure demonstrated in Figure A.1 of KDB447498 D04 was applied.



4.2 Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons."

Exposure evaluation

$$S_{eirp} = \frac{EIRP}{4\pi d^2} = \frac{PG}{4\pi d^2} (W / m^2)$$

Where

S: is the input power (W);

G: is the antenna gain;

d : is the distance between antennas and evaluation point (m).

5. Maximum Tune-up Power

Operate Band	Frequency (MHz)	ANT 0 (Kirchhoff)	ANT 1 (ASE)
Bluetooth	2402 - 2480	8.00	3.00
Bluetooth LE	2402 - 2480	-	6.00

6. Test Result

Band	Frequency (MHz)	Distance (cm) [R]	Tune-up Power (dBm) [P]	ANT Gain (dBi)	Numeric Gain [G]	Duty Cycle	Power with Duty cycle (mW) [P]x[G]	Power Density (mW/cm ²) [S]	Standalone Limit (mW/cm ²)	Antenna
Bluetooth	2402 - 2480	20.0	8.00	6.31	4.28	1	27.00	0.01	1.00	ANT 0
Bluetooth	2402 - 2480	20.0	6.00	3.98	2.50	1	9.95	0.002	1.00	ANT 1

Note:

1. The maximum power and gain were applied to evaluate MPE.
2. The Numeric Gain calculated by $10^{(\text{ant. Gain(dBi)} / 10)}$.

7. Conclusion

The result shows that this device is compliance with the exposure limits in 47 CFR §1.1310.

---END---