



FCC TEST REPORT

FCC ID:2AYQZ-V16

Applicant: Dongguan Yi Pai Ji He Electronic Co.Ltd
Address: 6th floor, No.96 Jinghai Middle Road, Chang'an Town Dongguan, Guangdong China
Manufacturer: Dongguan Yi Pai Ji He Electronic Co.Ltd
Address: 6th floor, No.96 Jinghai Middle Road, Chang'an Town Dongguan, Guangdong China
EUT: LCD projector
Trade Mark: N/A
Model Number: V16
Refer to page 7 for additional models
Date of Receipt: Jun. 30, 2025
Test Date: Jun. 30, 2025 - Jul. 10, 2025
Date of Report: Jul. 10, 2025
Prepared By: Shenzhen DL Testing Technology Co., Ltd.
Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China
Applicable Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013
Test Result: Pass
Report Number: DLE-250715006R

Prepared (Test Engineer): Dimon Tan

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents

	Page
1. VERSION	4
2. SUMMARY OF TEST RESULTS	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 TEST RESULT	14
4.2.1 RADIATED EMISSION LIMITS	18
4.2.2 TEST PROCEDURE	19
4.2.3 DEVIATION FROM TEST STANDARD	19
4.2.4 TEST SETUP	19
4.2.5 EUT OPERATING CONDITIONS	20
4.2.6 TEST RESULTS	20
5. RADIATED BAND EMISSIONMEASUREMENT	33
5.1 TEST REQUIREMENT	33
5.2 TEST PROCEDURE	33
5.3 DEVIATION FROM TEST STANDARD	34
5.4 TEST SETUP	34
5.5 EUT OPERATING CONDITIONS	34
5.6 TEST RESULT	35
6.1 APPLIED PROCEDURES / LIMIT	37
6.2 TEST PROCEDURE	37
6.3 DEVIATION FROM STANDARD	37
6.4 TEST SETUP	37



6.5 EUT OPERATION CONDITIONS	37
6.6 TEST RESULT	38
7. 6DB OCCUPIED BANDWIDTH	46
7.1 APPLIED PROCEDURES / LIMIT	46
7.2 TEST PROCEDURE	46
7.3 DEVIATION FROM STANDARD	46
7.4 TEST SETUP	46
7.5 EUT OPERATION CONDITIONS	46
7.6 TEST RESULT	47
8. PEAK OUTPUT POWER TEST	50
8.1 APPLIED PROCEDURES/LIMIT	50
8.2 TEST PROCEDURE	50
8.3 DEVIATION FROM STANDARD	50
8.4 TEST SETUP	50
8.5 EUT OPERATION CONDITIONS	50
8.6 TEST RESULT	51
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	52
9.1 APPLICABLE STANDARD	52
9.2 TEST PROCEDURE	52
9.3 DEVIATION FROM STANDARD	53
9.4 TEST SETUP	53
9.5 EUT OPERATION CONDITIONS	53
9.6 TEST RESULTS	53
10. DUTY CYCLE	60
10.1 APPLIED PROCEDURES / LIMIT	60
10.2 DEVIATION FROM STANDARD	60
10.3 TEST SETUP	60
10.4 TEST RESULTS	61
11. ANTENNA REQUIREMENT	64
12. TEST SETUP PHOTO	65
13. EUT CONSTRUCTIONAL DETAILS	65



1. VERSION

Report No.	Version	Description	Approved
DLE-250715006R	Rev.01	Initial issue of report	Jul. 10, 2025



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	6dB Occupied Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	
ANSI C63.10:2013	Duty cycle	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Test lab: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.:CN0118

ISED Registration number: 27485

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$ · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ · providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8dB
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59°C



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	LCD projector
Model No.:	V16
Model Different.:	The internal structure is the same, but the appearance color and bracket type are different
Serial No.:	V15, S1, S2, S3, S5, S6, S7, S8, S9, S10, S11, S12, S13, S15, S16, S17, S18, S19, S20, S21, S22, S23, S2 5, S26, S27, S28, S29, S30, S31, S32, S33, S35, S36, S37, S38, S39, S40, S41, S42, S43, S45, S46, S47, S48, S49, S50, S51, S52, S53, S55, S56, S57, S58, S59, S60, S61, S62, S63S65, S66, S67, S68, S69, S70, S71, S72, S73, S75, S76, S77, S78, S79, S80, S81, S82, S83, S85, S86, S8 7, S88, S89, S90, S91, S92, S93, S95, S96, S97, S98, S99, V1, V2, V3, V5, V6, V7, V8, V9, V10, V1 1, V12, V13, V16, V17, V18, V19, V20, V21, V22, V23, V25, V26, V27, V28, V29, V30, V31, V 32, V33, V35, V36, V37, V38, V39, V40, V41, V42, V43, V45, V46, V47, V48, V49, V50, V51, V52, V53, V55, V56, V57, V58, V59, V60, V61, V62, V63V65, V66, V67, V68, V69, V70, V71, V72, V73 , V75, V76, V77, V78, V79, V80, V81, V82, V83, V85, V86, V87, V88, V89, V90, V91, V92, V93, V9 5, V96, V97, V98, V99, RD-870S, RD-880, RD-880S, RD-890, RD-890S, sun707, YP20, YP20 B, YP25, YP25B, YP21, YP22, YP23, YP26, YP27, YP28, YP29, YP30, YP31, YP32, YP33, YP 35, YP36, YP37, YP38, YP39, YP50, YP51, YP52, YP53, YP55, YP56, YP57, YP58, YP59, YP60, YP61, YP62, YP63YP65, YP66, YP67, YP68, YP69, YP70, YP71, YP72, YP73, YP75, , YP76, YP77, YP78, YP79, YP80, YP81, YP82, YP83, YP85, YP86, YP87, YP88, YP89, YP90, YP91, YP92, YP93, YP95, YP96, YP97, YP98, YP99, YP500, YP510, YP520, YP530, YP540, YP550, YP560, YP570, YP580, YP590, YP600, YP610, YP620, YP630, YP650, YP660, YP670, YP680, YP690, YP700, YP710, YP720, YP970, YP750, YP760, YP770, YP780, YP790, YP800, YP810, YP820, YP830, YP840, YP850, YP860, YP870, YP880, YP890, YP900, V10P, V10PRO, V10PLUS, V10SE, V10M, V50P, V50PRO, V50PLUS, V50SE, V50M, V51P, V51PEO, V51PLUS, V51SE, V51M, S1, S1P, S1PRO, S1PLUS, S1SE, S1M, V5 3P, V53PRO, V53PLUS, V53SE, V53M, V51PRO
Hardware Version:	H1.0
Software Version:	S1.0
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/g/n20: 11 CH 802.11n40: 7 CH
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum(DSSS) 802.11g/n: Orthogonal Frequency Division Multiplexing(OFDM)



Data Rate	802.11b: 1/2/5.5/11Mbit/s 802.11g: 6/9/12/24/18/36/48/54Mbit/s 802.11n20/n40: MCS0-MCS7
Antenna Type:	Chip Antenna
Antenna gain:	2.95dBi
Power supply:	Input:15.0V  3.2A Power adapter: Input: 100-240V~, 50/60Hz, 1.2A Output: 15V  3.2A, 48W



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/g/n20	802.11n40
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. For battery operated equipment, the equipment tests shall be performed using a new battery.	


We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n20/n40	
Data rate	1Mbps	6Mbps	MCS0(HT0)	

Test Software	DRUT
Power level setup	Default




3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	LCD projector	N/A	V16	N/A	EUT
A-1	AC/DC Adapter	JFEC	JF050WR-15003 20UH	N/A	Auxiliary
A-2	AC/DC Adapter	N/A	CW48C1503200 SC	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) EUT is tested with new battery.



3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 01, 2024	Oct. 31, 2025
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 01, 2024	Oct. 31, 2025
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 01, 2024	Oct. 31, 2025
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 01, 2024	Oct. 31, 2025
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 01, 2024	Oct. 31, 2025
6	Amplifier (9kHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 01, 2024	Oct. 31, 2025
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 01, 2024	Oct. 31, 2025
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 01, 2024	Oct. 31, 2025
9	Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 01, 2024	Oct. 31, 2025
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 01, 2024	Oct. 31, 2025
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 01, 2024	Oct. 31, 2025
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 01, 2024	Oct. 31, 2025
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 01, 2024	Oct. 31, 2025
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 01, 2024	Oct. 31, 2025
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 01, 2024	Oct. 31, 2025
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 01, 2024	Oct. 31, 2025

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 01, 2024	Oct. 31, 2025
2	EMI Receiver	R&S	ESR	101421	Nov. 01, 2024	Oct. 31, 2025
3	LISN	R&S	ENV216	102417	Nov. 01, 2024	Oct. 31, 2025
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 01, 2024	Oct. 31, 2025

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 TEST RESULT

AC/DC Adapter:JF050WR-1500320UH

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	TX 802.11n20 - 2412MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1860	27.82	12.23	40.05	54.21	-14.16	AVG	P	
2	0.1864	35.84	12.22	48.06	64.20	-16.14	QP	P	
3	0.4605	37.46	10.72	48.18	56.68	-8.50	QP	P	
4	0.4605	28.44	10.72	39.16	46.68	-7.52	AVG	P	
5	1.8465	33.59	10.23	43.82	56.00	-12.18	QP	P	
6	1.8510	25.02	10.23	35.25	46.00	-10.75	AVG	P	
7	2.9580	36.43	9.95	46.38	56.00	-9.62	QP	P	
8	2.9580	28.15	9.95	38.10	46.00	-7.90	AVG	P	
9	3.3315	36.54	9.72	46.26	56.00	-9.74	QP	P	
10	3.3315	28.87	9.72	38.59	46.00	-7.41	AVG	P	
11	4.4385	28.21	9.01	37.22	46.00	-8.78	AVG	P	
12	4.4880	36.33	8.98	45.31	56.00	-10.69	QP	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Lism factor+ Cable loss factor + limiter factor.
5. Margin = Measurement Level-Limit.
6. The test data shows only the worst case TX 802.11n20 - 2412MHz.



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	N
Test Voltage:	AC 120V/60Hz	Test Mode:	TX 802.11n20 - 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1825	37.24	12.30	49.54	64.37	-14.83	QP	P	
2	0.1860	26.95	12.23	39.18	54.21	-15.03	AVG	P	
3	0.4564	23.72	10.74	34.46	46.76	-12.30	AVG	P	
4	0.4650	36.34	10.70	47.04	56.60	-9.56	QP	P	
5	1.8510	30.00	10.23	40.23	56.00	-15.77	QP	P	
6	1.8510	23.55	10.23	33.78	46.00	-12.22	AVG	P	
7	2.2244	31.32	10.13	41.45	56.00	-14.55	QP	P	
8	2.2244	24.21	10.13	34.34	46.00	-11.66	AVG	P	
9	3.8355	33.97	9.40	43.37	56.00	-12.63	QP	P	
10	3.8400	28.11	9.39	37.50	46.00	-8.50	AVG	P	
11	4.8705	28.12	8.73	36.85	46.00	-9.15	AVG	P	
12	4.8750	33.87	8.73	42.60	56.00	-13.40	QP	P	


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Lism factor+ Cable loss factor + limiter factor.
5. Margin = Measurement Level-Limit.
6. The test data shows only the worst case TX 802.11n20 - 2412MHz.



AC/DC Adapter: CW48C1503200SC

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	TX 802.11n20 - 2412MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2084	36.56	20.38	56.94	63.27	-6.33	QP	P	
2	0.2084	15.80	20.38	36.18	53.27	-17.09	AVG	P	
3	1.0632	30.38	20.30	50.68	56.00	-5.32	QP	P	
4	1.0632	17.86	20.30	38.16	46.00	-7.84	AVG	P	
5	1.6079	31.61	20.30	51.91	56.00	-4.09	QP	P	
6	1.6079	23.76	20.30	44.06	46.00	-1.94	AVG	P	
7	3.0705	31.14	20.33	51.47	56.00	-4.53	QP	P	
8	3.0750	23.22	20.33	43.55	46.00	-2.45	AVG	P	
9	4.8300	31.96	20.36	52.32	56.00	-3.68	QP	P	
10	4.8300	21.61	20.36	41.97	46.00	-4.03	AVG	P	
11	6.2925	35.30	20.38	55.68	60.00	-4.32	QP	P	
12	6.2925	25.53	20.38	45.91	50.00	-4.09	AVG	P	

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Reading level + Correct Factor.
- Correct Factor = Liss factor+ Cable loss factor + limiter factor.
- Margin = Measurement Level-Limit.
- The test data shows only the worst case TX 802.11n20 - 2412MHz.



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	N
Test Voltage:	AC 120V/60Hz	Test Mode:	TX 802.11n20 - 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.4380	29.43	20.31	49.74	57.10	-7.36	QP	P	
2	0.4380	20.59	20.31	40.90	47.10	-6.20	AVG	P	
3	1.3152	29.59	20.31	49.90	56.00	-6.10	QP	P	
4	1.3200	21.46	20.31	41.77	46.00	-4.23	AVG	P	
5	1.6124	29.80	20.30	50.10	56.00	-5.90	QP	P	
6	1.6124	20.52	20.30	40.82	46.00	-5.18	AVG	P	
7	3.6600	28.22	20.33	48.55	56.00	-7.45	QP	P	
8	3.6600	20.95	20.33	41.28	46.00	-4.72	AVG	P	
9	6.0045	35.89	20.37	56.26	60.00	-3.74	QP	P	
10	6.0045	24.54	20.37	44.91	50.00	-5.09	AVG	P	
11	9.0823	29.06	20.45	49.51	60.00	-10.49	QP	P	
12	9.2263	22.14	20.45	42.59	50.00	-7.41	AVG	P	

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Reading level + Correct Factor.
- Correct Factor = Lism factor+ Cable loss factor + limiter factor.
- Margin = Measurement Level-Limit.
- The test data shows only the worst case TX 802.11n20 - 2412MHz.



4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation


4.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz






(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



Between 30MHz – 1GHz

AC/DC Adapter:JF050WR-1500320UH

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 15V From Adapter AC 120V/60Hz	Test Mode :	TX 802.11n20 - 2412MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	112.5243	35.01	-19.04	15.97	43.50	-27.53	QP
2	189.7385	36.35	-18.30	18.05	43.50	-25.45	QP
3	513.6331	28.91	-11.24	17.67	46.00	-28.33	QP
4	677.5798	28.94	-7.18	21.76	46.00	-24.24	QP
5	922.5157	28.90	-6.52	22.38	46.00	-23.62	QP
6	996.4995	27.93	-4.94	22.99	54.00	-31.01	QP

Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin = Measurement Level-Limit.
7. The test data shows only the worst case TX 802.11n20 - 2412MHz.



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 15V From Adapter AC 120V/60Hz	Test Mode :	TX 802.11n20 - 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.9618	33.84	-18.28	15.56	40.00	-24.44	QP
2	204.2377	40.12	-20.63	19.49	43.50	-24.01	QP
3	508.2582	27.90	-11.26	16.64	46.00	-29.36	QP
4	627.2737	29.70	-7.72	21.98	46.00	-24.02	QP
5	872.1832	32.91	-1.53	31.38	46.00	-14.62	QP
6	986.0716	29.10	-0.29	28.81	54.00	-25.19	QP


Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin = Measurement Level-Limit.
7. The test data shows only the worst case TX 802.11n20 - 2412MHz.



AC/DC Adapter:CW48C1503200SC

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 15V From Adapter AC 120V/60Hz	Test Mode :	TX 802.11n20 - 2412MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.6201	32.43	-14.37	18.06	40.00	-21.94	QP
2	43.2014	30.46	-14.00	16.46	40.00	-23.54	QP
3	60.2800	31.44	-14.20	17.24	40.00	-22.76	QP
4	135.5061	34.71	-17.11	17.60	43.50	-25.90	QP
5	193.7726	38.47	-18.22	20.25	43.50	-23.25	QP
6	719.1992	29.57	-6.48	23.09	46.00	-22.91	QP

Remarks:

- An initial pre-scan was performed on the peak detector.
- Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Final Level = Reading level + Correct Factor.
- Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
- Margin = Measurement Level-Limit.
- The test data shows only the worst case TX 802.11n20 - 2412MHz.



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 15V From Adapter AC 120V/60Hz	Test Mode :	TX 802.11n20 - 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.0701	38.02	-18.16	19.86	40.00	-20.14	QP
2	36.8952	35.14	-17.21	17.93	40.00	-22.07	QP
3	85.8983	38.06	-21.53	16.53	40.00	-23.47	QP
4	126.7723	36.65	-21.06	15.59	43.50	-27.91	QP
5	207.8500	42.64	-20.26	22.38	43.50	-21.12	QP
6	925.7562	34.02	-0.29	33.73	46.00	-12.27	QP

Remarks:

8. An initial pre-scan was performed on the peak detector.
9. Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
10. The emission levels of other frequencies are very lower than the limit and not show in test report.
11. Final Level = Reading level + Correct Factor.
12. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
13. Margin = Measurement Level-Limit.
14. The test data shows only the worst case TX 802.11n20 - 2412MHz.



1GHz~25GHz

802.11b

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	51.84	30.55	5.77	24.66	51.72	74.00	-22.28	PK
V	4824.00	43.74	30.55	5.77	24.66	43.62	54.00	-10.38	AV
V	7236.00	54.54	30.33	6.32	24.55	55.08	74.00	-18.92	PK
V	7236.00	43.32	30.33	6.32	24.55	43.86	54.00	-10.14	AV
V	9648.00	52.08	30.85	7.45	24.69	53.37	74.00	-20.63	PK
V	9648.00	43.46	30.85	7.45	24.69	44.75	54.00	-9.25	AV
V	12060.00	51.28	31.02	8.99	25.57	54.82	74.00	-19.18	PK
V	12060.00	43.77	31.02	8.99	25.57	47.31	54.00	-6.69	AV
H	4824.00	51.60	30.55	5.77	24.66	51.48	74.00	-22.52	PK
H	4824.00	43.89	30.55	5.77	24.66	43.77	54.00	-10.23	AV
H	7236.00	50.77	30.33	6.32	24.55	51.31	74.00	-22.69	PK
H	7236.00	43.77	30.33	6.32	24.55	44.31	54.00	-9.69	AV
H	9648.00	53.65	30.85	7.45	24.69	54.94	74.00	-19.06	PK
H	9648.00	43.60	30.85	7.45	24.69	44.89	54.00	-9.11	AV
H	12060.00	52.30	31.02	8.99	25.57	55.84	74.00	-18.16	PK
H	12060.00	43.09	31.02	8.99	25.57	46.63	54.00	-7.37	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	51.17	30.55	5.77	24.66	51.05	74.00	-22.95	PK
V	4874.00	43.85	30.55	5.77	24.66	43.73	54.00	-10.27	AV
V	7311.00	52.15	30.33	6.32	24.55	52.69	74.00	-21.31	PK
V	7311.00	43.70	30.33	6.32	24.55	44.24	54.00	-9.76	AV
V	9748.00	53.06	30.85	7.45	24.69	54.35	74.00	-19.65	PK
V	9748.00	43.84	30.85	7.45	24.69	45.13	54.00	-8.87	AV
V	12185.00	54.26	31.02	8.99	25.57	57.80	74.00	-16.20	PK
V	12185.00	43.61	31.02	8.99	25.57	47.15	54.00	-6.85	AV
H	4874.00	54.23	30.55	5.77	24.66	54.11	74.00	-19.89	PK
H	4874.00	43.24	30.55	5.77	24.66	43.12	54.00	-10.88	AV
H	7311.00	52.00	30.33	6.32	24.55	52.54	74.00	-21.46	PK
H	7311.00	43.35	30.33	6.32	24.55	43.89	54.00	-10.11	AV
H	9748.00	51.10	30.85	7.45	24.69	52.39	74.00	-21.61	PK
H	9748.00	43.27	30.85	7.45	24.69	44.56	54.00	-9.44	AV
H	12185.00	53.70	31.02	8.99	25.57	57.24	74.00	-16.76	PK
H	12185.00	43.69	31.02	8.99	25.57	47.23	54.00	-6.77	AV



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
High Channel:2462MHz									
V	4924.00	52.22	30.55	5.77	24.66	52.10	74.00	-21.90	PK
V	4924.00	43.19	30.55	5.77	24.66	43.07	54.00	-10.93	AV
V	7386.00	52.24	30.33	6.32	24.55	52.78	74.00	-21.22	PK
V	7386.00	43.77	30.33	6.32	24.55	44.31	54.00	-9.69	AV
V	9848.00	50.34	30.85	7.45	24.69	51.63	74.00	-22.37	PK
V	9848.00	43.96	30.85	7.45	24.69	45.25	54.00	-8.75	AV
V	12310.00	54.02	31.02	8.99	25.57	57.56	74.00	-16.44	PK
V	12310.00	43.78	31.02	8.99	25.57	47.32	54.00	-6.68	AV
H	4924.00	51.72	30.55	5.77	24.66	51.60	74.00	-22.40	PK
H	4924.00	43.45	30.55	5.77	24.66	43.33	54.00	-10.67	AV
H	7386.00	51.13	30.33	6.32	24.55	51.67	74.00	-22.33	PK
H	7386.00	43.26	30.33	6.32	24.55	43.80	54.00	-10.20	AV
H	9848.00	53.10	30.85	7.45	24.69	54.39	74.00	-19.61	PK
H	9848.00	43.72	30.85	7.45	24.69	45.01	54.00	-8.99	AV
H	12310.00	54.36	31.02	8.99	25.57	57.90	74.00	-16.10	PK
H	12310.00	43.09	31.02	8.99	25.57	46.63	54.00	-7.37	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Low Channel:2412MHz									
V	4824.00	50.92	30.55	5.77	24.66	50.80	74.00	-23.20	PK
V	4824.00	43.58	30.55	5.77	24.66	43.46	54.00	-10.54	AV
V	7236.00	53.85	30.33	6.32	24.55	54.39	74.00	-19.61	PK
V	7236.00	43.74	30.33	6.32	24.55	44.28	54.00	-9.72	AV
V	9648.00	54.73	30.85	7.45	24.69	56.02	74.00	-17.98	PK
V	9648.00	43.16	30.85	7.45	24.69	44.45	54.00	-9.55	AV
V	12060.00	51.05	31.02	8.99	25.57	54.59	74.00	-19.41	PK
V	12060.00	43.23	31.02	8.99	25.57	46.77	54.00	-7.23	AV
H	4824.00	53.56	30.55	5.77	24.66	53.44	74.00	-20.56	PK
H	4824.00	43.24	30.55	5.77	24.66	43.12	54.00	-10.88	AV
H	7236.00	51.71	30.33	6.32	24.55	52.25	74.00	-21.75	PK
H	7236.00	43.18	30.33	6.32	24.55	43.72	54.00	-10.28	AV
H	9648.00	53.47	30.85	7.45	24.69	54.76	74.00	-19.24	PK
H	9648.00	43.08	30.85	7.45	24.69	44.37	54.00	-9.63	AV
H	12060.00	50.82	31.02	8.99	25.57	54.36	74.00	-19.64	PK
H	12060.00	43.52	31.02	8.99	25.57	47.06	54.00	-6.94	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Middle Channel:2437MHz									
V	4874.00	52.62	30.55	5.77	24.66	52.50	74.00	-21.50	PK
V	4874.00	43.76	30.55	5.77	24.66	43.64	54.00	-10.36	AV
V	7311.00	50.58	30.33	6.32	24.55	51.12	74.00	-22.88	PK
V	7311.00	43.58	30.33	6.32	24.55	44.12	54.00	-9.88	AV
V	9748.00	53.15	30.85	7.45	24.69	54.44	74.00	-19.56	PK
V	9748.00	43.22	30.85	7.45	24.69	44.51	54.00	-9.49	AV
V	12185.00	51.58	31.02	8.99	25.57	55.12	74.00	-18.88	PK
V	12185.00	43.59	31.02	8.99	25.57	47.13	54.00	-6.87	AV
H	4874.00	52.49	30.55	5.77	24.66	52.37	74.00	-21.63	PK
H	4874.00	43.50	30.55	5.77	24.66	43.38	54.00	-10.62	AV
H	7311.00	50.57	30.33	6.32	24.55	51.11	74.00	-22.89	PK
H	7311.00	43.33	30.33	6.32	24.55	43.87	54.00	-10.13	AV
H	9748.00	53.13	30.85	7.45	24.69	54.42	74.00	-19.58	PK
H	9748.00	43.64	30.85	7.45	24.69	44.93	54.00	-9.07	AV
H	12185.00	54.77	31.02	8.99	25.57	58.31	74.00	-15.69	PK
H	12185.00	43.42	31.02	8.99	25.57	46.96	54.00	-7.04	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	54.69	30.55	5.77	24.66	54.57	74.00	-19.43	PK
V	4924.00	43.75	30.55	5.77	24.66	43.63	54.00	-10.37	AV
V	7386.00	54.97	30.33	6.32	24.55	55.51	74.00	-18.49	PK
V	7386.00	43.70	30.33	6.32	24.55	44.24	54.00	-9.76	AV
V	9848.00	52.83	30.85	7.45	24.69	54.12	74.00	-19.88	PK
V	9848.00	43.92	30.85	7.45	24.69	45.21	54.00	-8.79	AV
V	12310.00	52.97	31.02	8.99	25.57	56.51	74.00	-17.49	PK
V	12310.00	43.47	31.02	8.99	25.57	47.01	54.00	-6.99	AV
H	4924.00	50.23	30.55	5.77	24.66	50.11	74.00	-23.89	PK
H	4924.00	43.34	30.55	5.77	24.66	43.22	54.00	-10.78	AV
H	7386.00	52.57	30.33	6.32	24.55	53.11	74.00	-20.89	PK
H	7386.00	43.76	30.33	6.32	24.55	44.30	54.00	-9.70	AV
H	9848.00	54.16	30.85	7.45	24.69	55.45	74.00	-18.55	PK
H	9848.00	43.22	30.85	7.45	24.69	44.51	54.00	-9.49	AV
H	12310.00	51.93	31.02	8.99	25.57	55.47	74.00	-18.53	PK
H	12310.00	43.87	31.02	8.99	25.57	47.41	54.00	-6.59	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Low Channel:2412MHz									
V	4824.00	54.36	30.55	5.77	24.66	54.24	74.00	-19.76	PK
V	4824.00	43.68	30.55	5.77	24.66	43.56	54.00	-10.44	AV
V	7236.00	54.88	30.33	6.32	24.55	55.42	74.00	-18.58	PK
V	7236.00	43.10	30.33	6.32	24.55	43.64	54.00	-10.36	AV
V	9648.00	50.98	30.85	7.45	24.69	52.27	74.00	-21.73	PK
V	9648.00	43.47	30.85	7.45	24.69	44.76	54.00	-9.24	AV
V	12060.00	54.94	31.02	8.99	25.57	58.48	74.00	-15.52	PK
V	12060.00	43.59	31.02	8.99	25.57	47.13	54.00	-6.87	AV
H	4824.00	54.07	30.55	5.77	24.66	53.95	74.00	-20.05	PK
H	4824.00	43.74	30.55	5.77	24.66	43.62	54.00	-10.38	AV
H	7236.00	53.65	30.33	6.32	24.55	54.19	74.00	-19.81	PK
H	7236.00	43.63	30.33	6.32	24.55	44.17	54.00	-9.83	AV
H	9648.00	54.83	30.85	7.45	24.69	56.12	74.00	-17.88	PK
H	9648.00	43.90	30.85	7.45	24.69	45.19	54.00	-8.81	AV
H	12060.00	52.37	31.02	8.99	25.57	55.91	74.00	-18.09	PK
H	12060.00	43.51	31.02	8.99	25.57	47.05	54.00	-6.95	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Middle Channel:2437MHz									
V	4874.00	51.87	30.55	5.77	24.66	51.75	74.00	-22.25	PK
V	4874.00	43.44	30.55	5.77	24.66	43.32	54.00	-10.68	AV
V	7311.00	54.82	30.33	6.32	24.55	55.36	74.00	-18.64	PK
V	7311.00	43.16	30.33	6.32	24.55	43.70	54.00	-10.30	AV
V	9748.00	54.70	30.85	7.45	24.69	55.99	74.00	-18.01	PK
V	9748.00	43.04	30.85	7.45	24.69	44.33	54.00	-9.67	AV
V	12185.00	53.98	31.02	8.99	25.57	57.52	74.00	-16.48	PK
V	12185.00	43.74	31.02	8.99	25.57	47.28	54.00	-6.72	AV
H	4874.00	54.90	30.55	5.77	24.66	54.78	74.00	-19.22	PK
H	4874.00	43.37	30.55	5.77	24.66	43.25	54.00	-10.75	AV
H	7311.00	53.63	30.33	6.32	24.55	54.17	74.00	-19.83	PK
H	7311.00	43.84	30.33	6.32	24.55	44.38	54.00	-9.62	AV
H	9748.00	53.49	30.85	7.45	24.69	54.78	74.00	-19.22	PK
H	9748.00	43.26	30.85	7.45	24.69	44.55	54.00	-9.45	AV
H	12185.00	51.58	31.02	8.99	25.57	55.12	74.00	-18.88	PK
H	12185.00	43.21	31.02	8.99	25.57	46.75	54.00	-7.25	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	51.45	30.55	5.77	24.66	51.33	74.00	-22.67	PK
V	4924.00	43.39	30.55	5.77	24.66	43.27	54.00	-10.73	AV
V	7386.00	53.23	30.33	6.32	24.55	53.77	74.00	-20.23	PK
V	7386.00	43.53	30.33	6.32	24.55	44.07	54.00	-9.93	AV
V	9848.00	51.38	30.85	7.45	24.69	52.67	74.00	-21.33	PK
V	9848.00	43.73	30.85	7.45	24.69	45.02	54.00	-8.98	AV
V	12310.00	50.22	31.02	8.99	25.57	53.76	74.00	-20.24	PK
V	12310.00	43.36	31.02	8.99	25.57	46.90	54.00	-7.10	AV
H	4924.00	53.09	30.55	5.77	24.66	52.97	74.00	-21.03	PK
H	4924.00	43.24	30.55	5.77	24.66	43.12	54.00	-10.88	AV
H	7386.00	50.15	30.33	6.32	24.55	50.69	74.00	-23.31	PK
H	7386.00	43.12	30.33	6.32	24.55	43.66	54.00	-10.34	AV
H	9848.00	51.04	30.85	7.45	24.69	52.33	74.00	-21.67	PK
H	9848.00	43.09	30.85	7.45	24.69	44.38	54.00	-9.62	AV
H	12310.00	54.58	31.02	8.99	25.57	58.12	74.00	-15.88	PK
H	12310.00	43.52	31.02	8.99	25.57	47.06	54.00	-6.94	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n40

Polar (H/V)	Frequenc y	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2422MHz									
V	4844.00	50.28	30.55	5.77	24.66	50.16	74.00	-23.84	PK
V	4844.00	43.38	30.55	5.77	24.66	43.26	54.00	-10.74	AV
V	7266.00	53.09	30.33	6.32	24.55	53.63	74.00	-20.37	PK
V	7266.00	43.20	30.33	6.32	24.55	43.74	54.00	-10.26	AV
V	9688.00	51.07	30.85	7.45	24.69	52.36	74.00	-21.64	PK
V	9688.00	43.21	30.85	7.45	24.69	44.50	54.00	-9.50	AV
V	12110.00	50.69	31.02	8.99	25.57	54.23	74.00	-19.77	PK
V	12110.00	43.52	31.02	8.99	25.57	47.06	54.00	-6.94	AV
H	4844.00	54.10	30.55	5.77	24.66	53.98	74.00	-20.02	PK
H	4844.00	43.58	30.55	5.77	24.66	43.46	54.00	-10.54	AV
H	7266.00	53.64	30.33	6.32	24.55	54.18	74.00	-19.82	PK
H	7266.00	43.18	30.33	6.32	24.55	43.72	54.00	-10.28	AV
H	9688.00	52.55	30.85	7.45	24.69	53.84	74.00	-20.16	PK
H	9688.00	43.03	30.85	7.45	24.69	44.32	54.00	-9.68	AV
H	12110.00	52.18	31.02	8.99	25.57	55.72	74.00	-18.28	PK
H	12110.00	43.20	31.02	8.99	25.57	46.74	54.00	-7.26	AV

Polar (H/V)	Frequenc y	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	51.72	30.55	5.77	24.66	51.60	74.00	-22.40	PK
V	4874.00	43.26	30.55	5.77	24.66	43.14	54.00	-10.86	AV
V	7311.00	54.16	30.33	6.32	24.55	54.70	74.00	-19.30	PK
V	7311.00	43.44	30.33	6.32	24.55	43.98	54.00	-10.02	AV
V	9748.00	53.20	30.85	7.45	24.69	54.49	74.00	-19.51	PK
V	9748.00	43.78	30.85	7.45	24.69	45.07	54.00	-8.93	AV
V	12185.00	51.65	31.02	8.99	25.57	55.19	74.00	-18.81	PK
V	12185.00	43.18	31.02	8.99	25.57	46.72	54.00	-7.28	AV
H	4874.00	54.17	30.55	5.77	24.66	54.05	74.00	-19.95	PK
H	4874.00	43.90	30.55	5.77	24.66	43.78	54.00	-10.22	AV
H	7311.00	54.03	30.33	6.32	24.55	54.57	74.00	-19.43	PK
H	7311.00	43.19	30.33	6.32	24.55	43.73	54.00	-10.27	AV
H	9748.00	54.97	30.85	7.45	24.69	56.26	74.00	-17.74	PK
H	9748.00	43.82	30.85	7.45	24.69	45.11	54.00	-8.89	AV
H	12185.00	53.69	31.02	8.99	25.57	57.23	74.00	-16.77	PK
H	12185.00	43.88	31.02	8.99	25.57	47.42	54.00	-6.58	AV



Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904.00	51.68	30.55	5.77	24.66	51.56	74.00	-22.44	PK
V	4904.00	43.43	30.55	5.77	24.66	43.31	54.00	-10.69	AV
V	7356.00	50.78	30.33	6.32	24.55	51.32	74.00	-22.68	PK
V	7356.00	43.83	30.33	6.32	24.55	44.37	54.00	-9.63	AV
V	9808.00	52.12	30.85	7.45	24.69	53.41	74.00	-20.59	PK
V	9808.00	43.41	30.85	7.45	24.69	44.70	54.00	-9.30	AV
V	12260.00	50.46	31.02	8.99	25.57	54.00	74.00	-20.00	PK
V	12260.00	43.73	31.02	8.99	25.57	47.27	54.00	-6.73	AV
H	4904.00	50.90	30.55	5.77	24.66	50.78	74.00	-23.22	PK
H	4904.00	43.12	30.55	5.77	24.66	43.00	54.00	-11.00	AV
H	7356.00	54.35	30.33	6.32	24.55	54.89	74.00	-19.11	PK
H	7356.00	43.03	30.33	6.32	24.55	43.57	54.00	-10.43	AV
H	9808.00	51.77	30.85	7.45	24.69	53.06	74.00	-20.94	PK
H	9808.00	43.55	30.85	7.45	24.69	44.84	54.00	-9.16	AV
H	12260.00	52.08	31.02	8.99	25.57	55.62	74.00	-18.38	PK
H	12260.00	43.61	31.02	8.99	25.57	47.15	54.00	-6.85	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



5. RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above	Peak	1MHz	3MHz	Peak
	1GHz	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported




5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.5 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dete ctor Type	Result
802.11b	LowChannel 2412MHz										
	H	2310.00	54.65	30.22	4.85	23.98	53.26	74.00	-20.74	PK	PASS
	H	2310.00	44.11	30.22	4.85	23.98	42.72	54.00	-11.28	AV	PASS
	H	2390.00	54.82	30.22	4.85	23.98	53.43	74.00	-20.57	PK	PASS
	H	2390.00	44.19	30.22	4.85	23.98	42.80	54.00	-11.20	AV	PASS
	V	2310.00	54.52	30.22	4.85	23.98	53.13	74.00	-20.87	PK	PASS
	V	2310.00	44.85	30.22	4.85	23.98	43.46	54.00	-10.54	AV	PASS
	V	2390.00	53.38	30.22	4.85	23.98	51.99	74.00	-22.01	PK	PASS
	V	2390.00	44.87	30.22	4.85	23.98	43.48	54.00	-10.52	AV	PASS
	HighChannel 2462MHz										
	H	2483.50	53.02	30.22	4.85	23.98	51.63	74.00	-22.37	PK	PASS
	H	2483.50	44.19	30.22	4.85	23.98	42.80	54.00	-11.20	AV	PASS
	H	2500.00	54.80	30.22	4.85	23.98	53.41	74.00	-20.59	PK	PASS
	H	2500.00	44.22	30.22	4.85	23.98	42.83	54.00	-11.17	AV	PASS
	V	2483.50	54.73	30.22	4.85	23.98	53.34	74.00	-20.66	PK	PASS
	V	2483.50	44.11	30.22	4.85	23.98	42.72	54.00	-11.28	AV	PASS
802.11g	V	2500.00	54.10	30.22	4.85	23.98	52.71	74.00	-21.29	PK	PASS
	V	2500.00	44.14	30.22	4.85	23.98	42.75	54.00	-11.25	AV	PASS
	LowChannel 2412MHz										
	H	2310.00	53.95	30.22	4.85	23.98	52.56	74.00	-21.44	PK	PASS
	H	2310.00	44.26	30.22	4.85	23.98	42.87	54.00	-11.13	AV	PASS
	H	2390.00	53.01	30.22	4.85	23.98	51.62	74.00	-22.38	PK	PASS
	H	2390.00	44.23	30.22	4.85	23.98	42.84	54.00	-11.16	AV	PASS
	V	2310.00	53.43	30.22	4.85	23.98	52.04	74.00	-21.96	PK	PASS
	V	2310.00	44.49	30.22	4.85	23.98	43.10	54.00	-10.90	AV	PASS
	V	2390.00	54.98	30.22	4.85	23.98	53.59	74.00	-20.41	PK	PASS
	V	2390.00	44.11	30.22	4.85	23.98	42.72	54.00	-11.28	AV	PASS
	High Channel 2462MHz										
	H	2483.50	54.86	30.22	4.85	23.98	53.47	74.00	-20.53	PK	PASS
	H	2483.50	44.76	30.22	4.85	23.98	43.37	54.00	-10.63	AV	PASS
	H	2500.00	53.09	30.22	4.85	23.98	51.70	74.00	-22.30	PK	PASS
	H	2500.00	44.74	30.22	4.85	23.98	43.35	54.00	-10.65	AV	PASS
	V	2483.50	54.11	30.22	4.85	23.98	52.72	74.00	-21.28	PK	PASS
	V	2483.50	44.47	30.22	4.85	23.98	43.08	54.00	-10.92	AV	PASS
	V	2500.00	53.73	30.22	4.85	23.98	52.34	74.00	-21.66	PK	PASS
	V	2500.00	44.30	30.22	4.85	23.98	42.91	54.00	-11.09	AV	PASS
Remark:											
Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit											



	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBu V/m)	Margin (dB)	Dete ctor Type	Result
802.11 n20	LowChannel 2412MHz										
	H	2310.00	53.07	30.22	4.85	23.98	51.68	74.00	-22.32	PK	PASS
	H	2310.00	44.75	30.22	4.85	23.98	43.36	54.00	-10.64	AV	PASS
	H	2390.00	53.01	30.22	4.85	23.98	51.62	74.00	-22.38	PK	PASS
	H	2390.00	44.22	30.22	4.85	23.98	42.83	54.00	-11.17	AV	PASS
	V	2310.00	53.39	30.22	4.85	23.98	52.00	74.00	-22.00	PK	PASS
	V	2310.00	44.92	30.22	4.85	23.98	43.53	54.00	-10.47	AV	PASS
	V	2390.00	53.71	30.22	4.85	23.98	52.32	74.00	-21.68	PK	PASS
	V	2390.00	44.83	30.22	4.85	23.98	43.44	54.00	-10.56	AV	PASS
	HighChannel 2462MHz										
	H	2483.50	53.10	30.22	4.85	23.98	51.71	74.00	-22.29	PK	PASS
	H	2483.50	44.85	30.22	4.85	23.98	43.46	54.00	-10.54	AV	PASS
	H	2500.00	54.04	30.22	4.85	23.98	52.65	74.00	-21.35	PK	PASS
	H	2500.00	44.81	30.22	4.85	23.98	43.42	54.00	-10.58	AV	PASS
	V	2483.50	53.37	30.22	4.85	23.98	51.98	74.00	-22.02	PK	PASS
	V	2483.50	44.33	30.22	4.85	23.98	42.94	54.00	-11.06	AV	PASS
	V	2500.00	53.71	30.22	4.85	23.98	52.32	74.00	-21.68	PK	PASS
	V	2500.00	44.06	30.22	4.85	23.98	42.67	54.00	-11.33	AV	PASS
802.11 n40	LowChannel 2422MHz										
	H	2310.00	53.24	30.22	4.85	23.98	51.85	74.00	-22.15	PK	PASS
	H	2310.00	44.43	30.22	4.85	23.98	43.04	54.00	-10.96	AV	PASS
	H	2390.00	53.21	30.22	4.85	23.98	51.82	74.00	-22.18	PK	PASS
	H	2390.00	44.31	30.22	4.85	23.98	42.92	54.00	-11.08	AV	PASS
	V	2310.00	53.88	30.22	4.85	23.98	52.49	74.00	-21.51	PK	PASS
	V	2310.00	44.79	30.22	4.85	23.98	43.40	54.00	-10.60	AV	PASS
	V	2390.00	53.41	30.22	4.85	23.98	52.02	74.00	-21.98	PK	PASS
	V	2390.00	44.42	30.22	4.85	23.98	43.03	54.00	-10.97	AV	PASS
	High Channel 2452MHz										
	H	2483.50	53.03	30.22	4.85	23.98	51.64	74.00	-22.36	PK	PASS
	H	2483.50	44.30	30.22	4.85	23.98	42.91	54.00	-11.09	AV	PASS
	H	2500.00	53.57	30.22	4.85	23.98	52.18	74.00	-21.82	PK	PASS
	H	2500.00	44.44	30.22	4.85	23.98	43.05	54.00	-10.95	AV	PASS
	V	2483.50	54.79	30.22	4.85	23.98	53.40	74.00	-20.60	PK	PASS
	V	2483.50	44.82	30.22	4.85	23.98	43.43	54.00	-10.57	AV	PASS
	V	2500.00	53.24	30.22	4.85	23.98	51.85	74.00	-22.15	PK	PASS
	V	2500.00	44.51	30.22	4.85	23.98	43.12	54.00	-10.88	AV	PASS
Remark:											
Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit											



6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS


6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 6.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULT

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 15V

Test Mode	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.11b	2412	-18.175	8	PASS
	2437	-18.768	8	PASS
	2462	-17.848	8	PASS





TX CH06




TX CH11






Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 15V

Test Mode	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.11g	2412	-23.371	8	PASS
	2437	-24.017	8	PASS
	2462	-22.634	8	PASS






TX CH06




TX CH11






Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 15V

Test Mode	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.11n20	2412	-24.881	8	PASS
	2437	-23.677	8	PASS
	2462	-24.926	8	PASS






TX CH06




TX CH11





Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 15V

Test Mode	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.11n40	2422	-27.08	8	PASS
	2437	-27.713	8	PASS
	2452	-28.072	8	PASS






TX CH06



TX CH09





7. 6DB OCCUPIED BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB Occupied Bandwidth)	2400-2483.5	PASS


7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 7.4 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULT

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 15V
Test Mode :	TX		

Test Mode	Test Channel (MHz)	6dB Occupied Bandwidth (MHz)	Limit (kHz)	Result
802.11b	2412	10.077	>500	Pass
	2437	10.106		
	2462	10.08		
802.11g	2412	16.294	>500	Pass
	2437	13.451		
	2462	13.203		
802.11n20	2412	16.922	>500	Pass
	2437	17.597		
	2462	17.327		
802.11n40	2422	27.904	>500	Pass
	2437	27.948		
	2452	28.228		





Test plot as follows:



802.11b

802.11g



Lowest channel



Middle channel



Highest channel








802.11n20

802.11n40



Lowest channel



Middle channel



Highest channel



**8. PEAK OUTPUT POWER TEST**

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT


FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP**8.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 8.4 Unless otherwise a special operating condition is specified in the follows during the testing.