




element

Quext

Radio Thermostat

**FCC 15.247:2022
Bluetooth LE DTS**

Report: F3EN0068.1, Issue Date: June 16, 2022



This report must not be used to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. Government. This Report shall not be reproduced, except in full without written approval of the laboratory.

EAR-Controlled Data - This document contains technical data whose export and reexport/retransfer is subject to control by the U.S. Department of Commerce under the Export Administration Act and the Export Administration Regulations. The Department of Commerce's prior written approval may be required for the export or re-export/retransfer of such technical data to any foreign person, foreign entity or foreign organization whether in the United States or abroad.

CERTIFICATE OF TEST



Last Date of Test: February 10, 2022
Quext
EUT: Radio Thermostat

Radio Equipment Testing

Standards

| Specification | Method |
|-----------------|------------------------------|
| FCC 15.209:2022 | |
| FCC 15.247:2022 | ANSI C63.10:2013, KDB 558074 |

Results

| Method Clause | Test Description | Applied | Results | Comments |
|----------------------------------|-------------------------------------|---------|---------|----------|
| 6.2 | Powerline Conducted Emissions | Yes | Pass | |
| 11.6 | Duty Cycle | Yes | Pass | |
| 11.8.2 | Occupied Bandwidth | Yes | Pass | |
| 11.9.1.1 | Output Power | Yes | Pass | |
| 11.9.1.1 | Equivalent Isotropic Radiated Power | Yes | Pass | |
| 11.10.2 | Power Spectral Density | Yes | Pass | |
| 11.11 | Band Edge Compliance | Yes | Pass | |
| 11.11 | Spurious Conducted Emissions | Yes | Pass | |
| 11.12.1, 11.13.2, 6.5, 6.6 | Spurious Radiated Emissions | Yes | Pass | |

Deviations From Test Standards

None

Approved By:

James Morris, Operations Manager

Product compliance is the responsibility of the client; therefore, the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test. This report reflects only those tests from the referenced standards shown in the certificate of test. It does not include inspection or verification of labels, identification, marking or user information. As indicated in the Statement of Work sent with the quotation, Element's standard process is to always use the latest published version of the test methods even when earlier versions are cited in the test specification. Issuance of a purchase order was de facto acceptance of this approach. Otherwise, the client would have advised Element in writing of the specific version of the test methods they wanted applied to the subject testing.

REVISION HISTORY



| Revision Number | Description | Date (yyyy-mm-dd) | Page Number |
|-----------------|-------------|----------------------|-------------|
| 00 | None | | |

ACCREDITATIONS AND AUTHORIZATIONS

United States

FCC - Designated by the FCC as a Telecommunications Certification Body (TCB). Certification chambers, Open Area Test Sites, and conducted measurement facilities are listed with the FCC.

A2LA - Each laboratory is accredited by A2LA to ISO / IEC 17025, and as a product certifier to ISO / IEC 17065 which allows Element to certify transmitters to FCC and IC specifications.

Canada

ISED - Recognized by Innovation, Science and Economic Development Canada as a Certification Body (CB) and as a CAB for the acceptance of test data.

European Union

European Commission – Recognized as an EU Notified Body validated for the EMCD and RED Directives.

United Kingdom

BEIS – Recognized by the UK as an Approved Body under the UK Radio Equipment and UK EMC Regulations.

Australia/New Zealand

ACMA - Recognized by ACMA as a CAB for the acceptance of test data.

Korea

MSIT / RRA - Recognized by KCC's RRA as a CAB for the acceptance of test data.

Japan

VCCI - Associate Member of the VCCI. Conducted and radiated measurement facilities are registered.

Taiwan

BSMI – Recognized by BSMI as a CAB for the acceptance of test data.

NCC - Recognized by NCC as a CAB for the acceptance of test data.

Singapore

IDA – Recognized by IDA as a CAB for the acceptance of test data.

Israel

MOC – Recognized by MOC as a CAB for the acceptance of test data.

Hong Kong

OFCA – Recognized by OFCA as a CAB for the acceptance of test data.

Vietnam

MIC – Recognized by MIC as a CAB for the acceptance of test data.

SCOPE

For details on the Scopes of our Accreditations, please visit:

[California](#)

[Minnesota](#)

[Oregon](#)


[Texas](#)

[Washington](#)

FACILITIES



| California | Minnesota | Oregon | Texas | Washington |
|---|---|--|--|---|
| Labs OC01-17 41 Tesla Irvine, CA 92618 (949) 861-8918 | Labs MN01-11 9349 W Broadway Ave. Brooklyn Park, MN 55445 (612) 638-5136 | Labs EV01-12 6775 NE Evergreen Pkwy #400 Hillsboro, OR 97124 (503) 844-4066 | Labs TX01-09 3801 E Plano Pkwy Plano, TX 75074 (469) 304-5255 | Labs NC01-05 19201 120th Ave NE Bothell, WA 98011 (425) 984-6600 |
| A2LA | | | | |
| Lab Code: 3310.04 | Lab Code: 3310.05 | Lab Code: 3310.02 | Lab Code: 3310.03 | Lab Code: 3310.06 |
| Innovation, Science and Economic Development Canada | | | | |
| 2834B-1, 2834B-3 | 2834E-1, 2834E-3 | 2834D-1 | 2834G-1 | 2834F-1 |
| BSMI | | | | |
| SL2-IN-E-1154R | SL2-IN-E-1152R | SL2-IN-E-1017 | SL2-IN-E-1158R | SL2-IN-E-1153R |
| VCCI | | | | |
| A-0029 | A-0109 | A-0108 | A-0201 | A-0110 |
| Recognized Phase I CAB for ISED, ACMA, BSMI, IDA, KCC/RRA, MIC, MOC, NCC, OFCA | | | | |
| US0158 | US0175 | US0017 | US0191 | US0157 |



MEASUREMENT UNCERTAINTY



Measurement Uncertainty

When a measurement is made, the result will be different from the true or theoretically correct value. The difference is the result of tolerances in the measurement system that cannot be completely eliminated. To the extent that technology allows us, it has been our aim to minimize this error. Measurement uncertainty is a statistical expression of measurement error qualified by a probability distribution.

A measurement uncertainty estimation has been performed for each test per our internal quality document QM205.4.6. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty (K=2) can be found in the table below. A lab specific value may also be found in the applicable test description section. Our measurement data meets or exceeds the measurement uncertainty requirements of the applicable specification; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for estimating measurement uncertainty are based upon ETSI TR 100 028 (or CISPR 16-4-2 as applicable), and are available upon request.

The following table represents the Measurement Uncertainty (MU) budgets for each of the tests that may be contained in this report.

| Test | + MU | - MU |
|---------------------------------------|---------|----------|
| Frequency Accuracy | 0.0007% | -0.0007% |
| Amplitude Accuracy (dB) | 1.2 dB | -1.2 dB |
| Conducted Power (dB) | 1.2 dB | -1.2 dB |
| Radiated Power via Substitution (dB) | 0.7 dB | -0.7 dB |
| Temperature (degrees C) | 0.7°C | -0.7°C |
| Humidity (% RH) | 2.5% RH | -2.5% RH |
| Voltage (AC) | 1.0% | -1.0% |
| Voltage (DC) | 0.7% | -0.7% |
| Field Strength (dB) | 5.1 dB | -5.1 dB |
| AC Powerline Conducted Emissions (dB) | 3.1 dB | -3.1 dB |


TEST SETUP BLOCK DIAGRAMS

Measurement Bandwidths

| Frequency Range (MHz) | Peak Data (kHz) | Quasi-Peak Data (kHz) | Average Data (kHz) |
|-----------------------|-----------------|-----------------------|--------------------|
| 0.01 - 0.15 | 1.0 | 0.2 | 0.2 |
| 0.15 - 30.0 | 10.0 | 9.0 | 9.0 |
| 30.0 - 1000 | 100.0 | 120.0 | 120.0 |
| Above 1000 | 1000.0 | N/A | 1000.0 |

Unless otherwise stated, measurements were made using the bandwidths and detectors specified. No video filter was used.


Antenna Port Conducted Measurements



Sample Calculation (logarithmic units)

$$\begin{array}{ccc} \text{Measured} & \text{Measured} & \text{Reference} \\ \text{Value} & = & \text{Level} \\ 71.2 & = & 42.6 \\ & & + \\ & & \text{Level} \\ & & \text{Offset} \\ & & 28.6 \end{array}$$

Near Field Test Fixture Measurements




Sample Calculation (logarithmic units)

$$\begin{array}{ccc} \text{Measured} & \text{Measured} & \text{Reference} \\ \text{Value} & = & \text{Level} \\ 71.2 & = & 42.6 \\ & & + \\ & & \text{Level} \\ & & \text{Offset} \\ & & 28.6 \end{array}$$

TEST SETUP BLOCK DIAGRAMS

Emissions Measurements



Sample Calculation (logarithmic units)

Radiated Emissions:

| | | | | | | |
|----------------------------|----------------|--------------|----------------|----------------------------|----------------------|----------------|
| | Factor | | | | | |
| Measured Level (Amplitude) | Antenna Factor | Cable Factor | Amplifier Gain | Distance Adjustment Factor | External Attenuation | Field Strength |
| 42.6 | + 28.6 | + 3.1 | - 40.8 | + 0.0 | + 0.0 | = 33.5 |


Conducted Emissions:

| | | | | |
|----------------------------|-------------------|--------------|----------------------|----------------|
| | Factor | | | |
| Measured Level (Amplitude) | Transducer Factor | Cable Factor | External Attenuation | Adjusted Level |
| 26.7 | + 0.3 | + 0.1 | = 20.0 | = 47.1 |

TEST SETUP BLOCK DIAGRAMS

Bore Sighting (>1GHz)

The diameter of the illumination area is the dimension of the line tangent to the EUT formed by 3 dB beamwidth of the measurement antenna at the measurement distance. At a 3 meter test distance, the diameter of the illumination area was 3.8 meters at 1 GHz and greater than 2.1 meters up to 6 GHz. Above 1 GHz, when required by the measurement standard, the antenna is pointed for both azimuth and elevation to maintain the receive antenna within the cone of radiation from the EUT. The specified measurement detectors were used for comparison of the emissions to the peak and average specification limits.



PRODUCT DESCRIPTION



Client and Equipment Under Test (EUT) Information

| | |
|---------------------------------|-----------------------------------|
| Company Name: | Quext |
| Address: | 5214 68 th St, Ste 201 |
| City, State, Zip: | Lubbock, TX 79424 |
| Test Requested By: | Tray Johnson |
| EUT: | Radio Thermostat |
| First Date of Test: | December 8, 2021 |
| Last Date of Test: | February 10, 2022 |
| Receipt Date of Samples: | December 3, 2021 |
| Equipment Design Stage: | Production |
| Equipment Condition: | No Damage |
| Purchase Authorization: | Verified |

Information Provided by the Party Requesting the Test

Functional Description of the EUT:

This is a physically and radio-controlled thermostat. It contains a LoRa radio (500kHz DTS and 125kHz Hybrid), a Z-wave radio and a Bluetooth Low Energy/Zigbee radio. The Bluetooth and Zigbee radio technologies share one antenna type and one antenna port.

Testing Objective:

To demonstrate compliance of the Bluetooth radio to FCC 15.247 requirements.

POWER SETTINGS AND ANTENNAS



The power settings, antenna gain value(s) and cable loss (if applicable) used for the testing contained in this report were provided by the customer and will affect the validity of the results. Element assumes no responsibility for the accuracy of this information.

ANTENNA GAIN (dBi)

| Type | Provided by: | Frequency Range (MHz) | Gain (dBi) |
|----------------------------|-----------------------------|-----------------------|------------|
| Surface mount Ceramic Chip | Unictron Technologies Corp. | 2400 - 2500 | -0.3 |

The EUT was tested using the power settings provided by the manufacturer:

SETTINGS FOR ALL TESTS IN THIS REPORT

| Modulation Types / Data Rates | Type | Channel | Frequency (MHz) | Power Setting |
|--|------|---------|-----------------|---------------|
| BLE 125 kbps, 500 kbps, 1 Mbps, 2 Mbps | DTS | 0 | 2402 | 8 dBm |
| | | 20 | 2440 | 7 dBm |
| | | 39 | 2480 | 8 dBm |

CONFIGURATIONS



Configuration F3EN0068- 2

| EUT | | | | |
|--------------------|---------------------|--------------------------|----------------------|--|
| Description | Manufacturer | Model/Part Number | Serial Number | |
| Radio Thermostat | Quext | Quext 1 | DUT4 | |

| Remote Equipment Outside of Test Setup Boundary | | | | |
|--|---------------------|--------------------------|----------------------|--|
| Description | Manufacturer | Model/Part Number | Serial Number | |
| AC/AC Transformer | None | None | None | |

| Cables | | | | | |
|-------------------|---------------|-------------------|----------------|---------------------|---------------------|
| Cable Type | Shield | Length (m) | Ferrite | Connection 1 | Connection 2 |
| 24VAC Cable | No | 1.4m | No | Radio Thermostat | AC/AC Transformer |
| 120VAC Cable | No | 1.0m | No | AC/AC Transformer | AC Mains |

CONFIGURATIONS



Configuration F3EN0068- 3

| Software/Firmware Running During Test | |
|---------------------------------------|----------|
| Description | Version |
| Tera Term | 1.0.0.26 |

| EUT | | | |
|------------------|--------------|-------------------|---------------|
| Description | Manufacturer | Model/Part Number | Serial Number |
| Radio Thermostat | Quext | Quext 1 | DUT1 |

| Peripherals in Test Setup Boundary | | | |
|------------------------------------|--------------|-------------------|---------------|
| Description | Manufacturer | Model/Part Number | Serial Number |
| Laptop | Lenovo | T450 | None |
| AC/DC Adapter (Laptop) | Lenovo | SK90200325 | None |
| AC/AC Transformer | None | None | None |
| Mouse (Laptop) | Logitech | 810-004116 | 1829HS0566P8 |

| Cables | | | | | |
|-----------------|--------|------------|---------|-------------------|--------------------------|
| Cable Type | Shield | Length (m) | Ferrite | Connection 1 | Connection 2 |
| USB to IO Cable | No | 1.2m | No | Radio Thermostat | Laptop |
| DC Cable | Yes | 2.1m | No | Laptop | AC/DC Adapter (Laptop) |
| AC Cable | No | 1.5m | No | AC Mains | AC/DC Adapter (Laptop) |
| 24VAC Cable | No | 1.4m | No | Radio Thermostat | AC/AC Transformer |
| 120VAC Cable | No | 1.0m | No | AC/AC Transformer | AC Mains / Not Energized |
| USB Mouse Cable | Yes | 1.5m | No | Laptop | Mouse (Laptop) |

CONFIGURATIONS



Configuration F3EN0068- 4

| EUT | | | | |
|--------------------|---------------------|--------------------------|----------------------|--|
| Description | Manufacturer | Model/Part Number | Serial Number | |
| Radio Thermostat | Quext | Quext 1 | DUT 11 | |

| Remote Equipment Outside of Test Setup Boundary | | | | |
|--|---------------------|--------------------------|----------------------|--|
| Description | Manufacturer | Model/Part Number | Serial Number | |
| AC/AC Transformer | None | None | None | |

| Cables | | | | | |
|-------------------|---------------|-------------------|----------------|---------------------|--------------------------|
| Cable Type | Shield | Length (m) | Ferrite | Connection 1 | Connection 2 |
| 24VACCable | No | 1.4m | No | Radio Thermostat | AC/AC Transformer |
| 120VAC Cable | No | 1.0m | No | AC/AC Transformer | AC Mains / Not Energized |

MODIFICATIONS

Equipment Modifications

| Item | Date | Test | Modification | Note | Disposition of EUT |
|------|------------|-------------------------------------|--------------------------------------|---|---|
| 1 | 2021-12-08 | Spurious Radiated Emissions | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 2 | 2022-01-06 | Powerline Conducted Emissions | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 3 | 2022-02-08 | Spurious Radiated Emissions | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 4 | 2022-02-10 | Duty Cycle | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 5 | 2022-02-10 | Occupied Bandwidth | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 6 | 2022-02-10 | Output Power | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 7 | 2022-02-10 | Equivalent Isotropic Radiated power | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 8 | 2022-02-10 | Power Spectral Density | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 9 | 2022-02-10 | Band Edge Compliance | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |
| 10 | 2022-02-10 | Spurious Conducted Emissions | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | Scheduled testing was completed. |

POWERLINE CONDUCTED EMISSIONS



TEST DESCRIPTION

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

| Description | Manufacturer | Model | ID | Last Cal. | Cal. Due |
|----------------------------------|-------------------|------------------|------|------------|------------|
| Receiver | Gauss Instruments | TDEMI 30M | ARL | 2021-03-23 | 2022-03-23 |
| LISN | Solar Electronics | 9252-50-R-24-BNC | LJK | 2021-08-06 | 2022-08-06 |
| Power Source/Analyzer | Hewlett Packard | 6841A | THC | NCR | NCR |
| Cable - Conducted Cable Assembly | Northwest EMC | TXA, HFC, TQU | TXAA | 2021-01-26 | 2022-01-26 |

MEASUREMENT UNCERTAINTY

| Description | | |
|--------------|--------|---------|
| Expanded k=2 | 3.1 dB | -3.1 dB |

CONFIGURATIONS INVESTIGATED

F3EN0068-2

MODES INVESTIGATED

Thermostat On, BLE Radio enabled, 1 Mbps modulation, mid-channel, all other radios disabled

POWERLINE CONDUCTED EMISSIONS



| | | | |
|-------------------|------------------|-----------------------|------------|
| EUT: | Radio Thermostat | Work Order: | F3EN0068 |
| Serial Number: | DUT4 | Date: | 2022-01-06 |
| Customer: | Quext | Temperature: | 23°C |
| Attendees: | None | Relative Humidity: | 22.6% |
| Customer Project: | None | Bar. Pressure (PMSL): | 1025 mb |
| Tested By: | Travis Glasser | Job Site: | TX01 |
| Power: | 110VAC/60Hz | Configuration: | F3EN0068-2 |

TEST SPECIFICATIONS

| | |
|-----------------|------------------|
| Specification: | Method: |
| FCC 15.207:2022 | ANSI C63.10:2013 |

TEST PARAMETERS

| | | | | | |
|--------|----|-------|-----------|-----------------------------|---|
| Run #: | 19 | Line: | High Line | Add. Ext. Attenuation (dB): | 0 |
|--------|----|-------|-----------|-----------------------------|---|

COMMENTS



None

EUT OPERATING MODES

Thermostat On, BLE Radio enabled, 1 Mbps modulation, mid-channel, all other radios disabled

DEVIATIONS FROM TEST STANDARD

None



POWERLINE CONDUCTED EMISSIONS



RESULTS - Run #19

Quasi Peak Data - vs - Quasi Peak Limit

| Freq (MHz) | Amp. (dBuV) | Factor (dB) | Adjusted (dBuV) | Spec. Limit (dBuV) | Margin (dB) |
|------------|-------------|-------------|-----------------|--------------------|-------------|
| 0.769 | 11.7 | 20.2 | 31.9 | 56.0 | -24.1 |
| 0.272 | 16.6 | 20.4 | 37.0 | 61.1 | -24.1 |
| 0.254 | 16.8 | 20.4 | 37.2 | 61.6 | -24.4 |
| 0.190 | 16.7 | 20.4 | 37.1 | 64.1 | -27.0 |
| 0.156 | 17.7 | 20.4 | 38.1 | 65.7 | -27.6 |
| 3.081 | 6.5 | 20.3 | 26.8 | 56.0 | -29.2 |
| 0.330 | 8.9 | 20.2 | 29.1 | 59.5 | -30.4 |
| 0.570 | 2.4 | 20.2 | 22.6 | 56.0 | -33.4 |
| 0.660 | 2.1 | 20.2 | 22.3 | 56.0 | -33.7 |
| 0.412 | 3.2 | 20.2 | 23.4 | 57.6 | -34.2 |
| 0.989 | 1.3 | 20.2 | 21.5 | 56.0 | -34.5 |
| 2.617 | 1.1 | 20.3 | 21.4 | 56.0 | -34.6 |
| 1.079 | 1.0 | 20.2 | 21.2 | 56.0 | -34.8 |
| 1.311 | 0.9 | 20.3 | 21.2 | 56.0 | -34.8 |
| 1.702 | 0.7 | 20.3 | 21.0 | 56.0 | -35.0 |
| 1.943 | 0.6 | 20.3 | 20.9 | 56.0 | -35.1 |
| 3.510 | 0.6 | 20.3 | 20.9 | 56.0 | -35.1 |
| 4.346 | 0.6 | 20.3 | 20.9 | 56.0 | -35.1 |
| 29.854 | 0.7 | 22.6 | 23.3 | 60.0 | -36.7 |
| 24.329 | -0.2 | 22.2 | 22.0 | 60.0 | -38.0 |
| 12.207 | 0.5 | 21.0 | 21.5 | 60.0 | -38.5 |
| 20.503 | -0.2 | 21.6 | 21.4 | 60.0 | -38.6 |
| 11.217 | 0.3 | 20.9 | 21.2 | 60.0 | -38.8 |
| 16.195 | -0.2 | 21.4 | 21.2 | 60.0 | -38.8 |
| 5.423 | 0.2 | 20.4 | 20.6 | 60.0 | -39.4 |

Average Data - vs - Average Limit

| Freq (MHz) | Amp. (dBuV) | Factor (dB) | Adjusted (dBuV) | Spec. Limit (dBuV) | Margin (dB) |
|------------|-------------|-------------|-----------------|--------------------|-------------|
| 0.769 | 7.1 | 20.2 | 27.3 | 46.0 | -18.7 |
| 0.272 | 11.9 | 20.4 | 32.3 | 51.1 | -18.8 |
| 0.238 | 12.2 | 20.4 | 32.6 | 52.1 | -19.5 |
| 0.222 | 12.5 | 20.4 | 32.9 | 52.8 | -19.9 |
| 0.156 | 14.0 | 20.4 | 34.4 | 55.7 | -21.3 |
| 3.098 | 0.8 | 20.3 | 21.1 | 46.0 | -24.9 |
| 0.330 | 3.3 | 20.2 | 23.5 | 49.5 | -26.0 |
| 0.570 | -3.5 | 20.2 | 16.7 | 46.0 | -29.3 |
| 0.660 | -3.9 | 20.2 | 16.3 | 46.0 | -29.7 |
| 0.412 | -2.8 | 20.2 | 17.4 | 47.6 | -30.2 |
| 0.991 | -4.7 | 20.2 | 15.5 | 46.0 | -30.5 |
| 2.614 | -4.9 | 20.3 | 15.4 | 46.0 | -30.6 |
| 1.310 | -5.1 | 20.3 | 15.2 | 46.0 | -30.8 |
| 1.311 | -5.2 | 20.3 | 15.1 | 46.0 | -30.9 |
| 1.596 | -5.5 | 20.3 | 14.8 | 46.0 | -31.2 |
| 2.155 | -5.5 | 20.3 | 14.8 | 46.0 | -31.2 |
| 3.510 | -5.5 | 20.3 | 14.8 | 46.0 | -31.2 |
| 4.349 | -5.6 | 20.3 | 14.7 | 46.0 | -31.3 |
| 29.937 | -5.2 | 22.6 | 17.4 | 50.0 | -32.6 |
| 24.244 | -6.3 | 22.2 | 15.9 | 50.0 | -34.1 |
| 12.288 | -5.5 | 21.0 | 15.5 | 50.0 | -34.5 |
| 19.949 | -6.4 | 21.6 | 15.2 | 50.0 | -34.8 |
| 11.215 | -5.8 | 20.9 | 15.1 | 50.0 | -34.9 |
| 16.079 | -6.4 | 21.4 | 15.0 | 50.0 | -35.0 |
| 6.034 | -5.8 | 20.4 | 14.6 | 50.0 | -35.4 |

CONCLUSION

Pass

Tested By

POWERLINE CONDUCTED EMISSIONS



| | | | |
|-------------------|------------------|-----------------------|------------|
| EUT: | Radio Thermostat | Work Order: | F3EN0068 |
| Serial Number: | DUT4 | Date: | 2022-01-06 |
| Customer: | Quext | Temperature: | 23°C |
| Attendees: | None | Relative Humidity: | 22.6% |
| Customer Project: | None | Bar. Pressure (PMSL): | 1025 mb |
| Tested By: | Travis Glasser | Job Site: | TX01 |
| Power: | 110VAC/60Hz | Configuration: | F3EN0068-2 |

TEST SPECIFICATIONS

| | |
|-----------------|------------------|
| Specification: | Method: |
| FCC 15.207:2022 | ANSI C63.10:2013 |

TEST PARAMETERS

| | | | | | |
|--------|----|-------|---------|-----------------------------|---|
| Run #: | 20 | Line: | Neutral | Add. Ext. Attenuation (dB): | 0 |
|--------|----|-------|---------|-----------------------------|---|

COMMENTS



None

EUT OPERATING MODES

Thermostat On, BLE Radio enabled, 1 Mbps modulation, mid-channel, all other radios disabled

DEVIATIONS FROM TEST STANDARD

None



POWERLINE CONDUCTED EMISSIONS

RESULTS - Run #20

Quasi Peak Data - vs - Quasi Peak Limit

| Freq (MHz) | Amp. (dBuV) | Factor (dB) | Adjusted (dBuV) | Spec. Limit (dBuV) | Margin (dB) |
|------------|-------------|-------------|-----------------|--------------------|-------------|
| 0.255 | 19.9 | 20.4 | 40.3 | 61.6 | -21.3 |
| 0.272 | 19.2 | 20.4 | 39.6 | 61.1 | -21.5 |
| 0.156 | 22.4 | 20.4 | 42.8 | 65.7 | -22.9 |
| 0.190 | 20.7 | 20.4 | 41.1 | 64.1 | -23.0 |
| 0.769 | 12.7 | 20.2 | 32.9 | 56.0 | -23.1 |
| 0.330 | 10.5 | 20.2 | 30.7 | 59.5 | -28.8 |
| 3.090 | 5.8 | 20.3 | 26.1 | 56.0 | -29.9 |
| 0.571 | 2.8 | 20.2 | 23.0 | 56.0 | -33.0 |
| 0.660 | 2.3 | 20.2 | 22.5 | 56.0 | -33.5 |
| 0.412 | 3.7 | 20.2 | 23.9 | 57.6 | -33.7 |
| 0.989 | 1.3 | 20.2 | 21.5 | 56.0 | -34.5 |
| 1.081 | 1.1 | 20.2 | 21.3 | 56.0 | -34.7 |
| 2.610 | 1.0 | 20.3 | 21.3 | 56.0 | -34.7 |
| 1.311 | 0.9 | 20.3 | 21.2 | 56.0 | -34.8 |
| 1.615 | 0.7 | 20.3 | 21.0 | 56.0 | -35.0 |
| 1.998 | 0.6 | 20.3 | 20.9 | 56.0 | -35.1 |
| 3.508 | 0.5 | 20.3 | 20.8 | 56.0 | -35.2 |
| 4.323 | 0.4 | 20.3 | 20.7 | 56.0 | -35.3 |
| 29.854 | 0.9 | 22.6 | 23.5 | 60.0 | -36.5 |
| 24.996 | -0.1 | 22.2 | 22.1 | 60.0 | -37.9 |
| 12.288 | 0.6 | 21.0 | 21.6 | 60.0 | -38.4 |
| 20.228 | -0.2 | 21.6 | 21.4 | 60.0 | -38.6 |
| 11.298 | 0.4 | 20.9 | 21.3 | 60.0 | -38.7 |
| 16.232 | -0.2 | 21.4 | 21.2 | 60.0 | -38.8 |
| 8.130 | 0.1 | 20.6 | 20.7 | 60.0 | -39.3 |

Average Data - vs - Average Limit

| Freq (MHz) | Amp. (dBuV) | Factor (dB) | Adjusted (dBuV) | Spec. Limit (dBuV) | Margin (dB) |
|------------|-------------|-------------|-----------------|--------------------|-------------|
| 0.272 | 14.7 | 20.4 | 35.1 | 51.1 | -16.0 |
| 0.156 | 18.8 | 20.4 | 39.2 | 55.7 | -16.5 |
| 0.223 | 15.7 | 20.4 | 36.1 | 52.7 | -16.6 |
| 0.190 | 16.2 | 20.4 | 36.6 | 54.1 | -17.5 |
| 0.769 | 7.9 | 20.2 | 28.1 | 46.0 | -17.9 |
| 0.330 | 5.2 | 20.2 | 25.4 | 49.5 | -24.1 |
| 3.098 | 0.1 | 20.3 | 20.4 | 46.0 | -25.6 |
| 0.570 | -3.3 | 20.2 | 16.9 | 46.0 | -29.1 |
| 0.660 | -3.7 | 20.2 | 16.5 | 46.0 | -29.5 |
| 0.412 | -2.3 | 20.2 | 17.9 | 47.6 | -29.7 |
| 0.989 | -4.7 | 20.2 | 15.5 | 46.0 | -30.5 |
| 1.079 | -5.0 | 20.2 | 15.2 | 46.0 | -30.8 |
| 2.596 | -5.1 | 20.3 | 15.2 | 46.0 | -30.8 |
| 1.311 | -5.2 | 20.3 | 15.1 | 46.0 | -30.9 |
| 1.622 | -5.4 | 20.3 | 14.9 | 46.0 | -31.1 |
| 1.954 | -5.5 | 20.3 | 14.8 | 46.0 | -31.2 |
| 3.510 | -5.6 | 20.3 | 14.7 | 46.0 | -31.3 |
| 4.335 | -5.7 | 20.3 | 14.6 | 46.0 | -31.4 |
| 29.856 | -5.0 | 22.6 | 17.6 | 50.0 | -32.4 |
| 23.751 | -6.2 | 22.1 | 15.9 | 50.0 | -34.1 |
| 12.205 | -5.5 | 21.0 | 15.5 | 50.0 | -34.5 |
| 11.298 | -5.6 | 20.9 | 15.3 | 50.0 | -34.7 |
| 18.978 | -6.3 | 21.5 | 15.2 | 50.0 | -34.8 |
| 16.519 | -6.3 | 21.4 | 15.1 | 50.0 | -34.9 |
| 7.781 | -6.0 | 20.6 | 14.6 | 50.0 | -35.4 |

CONCLUSION

Pass



Tested By

DUTY CYCLE



XMit 2020.12.30.0

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

| Description | Manufacturer | Model | ID | Last Cal. | Cal. Due |
|------------------------------|--------------------|------------------------|-----|------------|------------|
| Block - DC | Fairview Microwave | SD3379 | AMM | 2021-09-14 | 2022-09-14 |
| Generator - Signal | Agilent | N5182A | TIF | 2020-08-29 | 2023-08-29 |
| Analyzer - Spectrum Analyzer | Keysight | N9010A | AFN | 2022-01-19 | 2023-01-19 |
| Cable | UtiFlex Micro-Coax | UFD1150A-1-0720-200200 | TXJ | 2021-09-13 | 2022-09-13 |
| Attenuator | Fairview Microwave | SA18E 1913 | TZV | 2021-09-15 | 2022-09-15 |

TEST DESCRIPTION

The Duty Cycle (x) of the single channel operation of the radio as controlled by the provided test software was measured for each of the EUT operating modes.

There is no compliance requirement to be met by this test, so therefore no Pass / Fail criteria.

The measurements were made using a zero span on the spectrum analyzer to see the pulses in the time domain. The transmit power was set to its default maximum.

The duty cycle was calculated by dividing the transmission pulse duration (T) by the total period of a single on and total off time.

If the transmit duty cycle < 98 percent, burst gating may have been used during some of the other tests in this report to only take the measurement during the burst duration.

DUTY CYCLE



TbTx 2021.10.29.2 XMII 2020.12.30.0


| EUT: | Radio Thermostat | Work Order: | F3EN0068 | | | | |
|-------------------------------|------------------|-------------------|------------------|------------------|-----------|-----------|---------|
| Serial Number: | DUT 1 | Date: | 10-Feb-22 | | | | |
| Customer: | Quext | Temperature: | 21.2 °C | | | | |
| Attendees: | None | Humidity: | 24.1% RH | | | | |
| Project: | None | Barometric Pres.: | 1021 mbar | | | | |
| Tested by: | Brandon Hobbs | Power: | 110VAC/60Hz | | | | |
| TEST SPECIFICATIONS | | Test Method | ANSI C63.10:2013 | | | | |
| FCC 15.247:2022 | | | | | | | |
| COMMENTS | None | | | | | | |
| DEVIATIONS FROM TEST STANDARD | | | | | | | |
| None | | | | | | | |
| Configuration # | 3 | Signature | | | | | |
| | | Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| BLE/GFSK 125 kbps | | | | | | | |
| Low Channel, 2402 MHz | | 747.65 us | 1.25 ms | 1 | 59.8 | N/A | N/A |
| Low Channel, 2402 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| Mid Channel, 2440 MHz | | 745.39 us | 1.251 ms | 1 | 59.6 | N/A | N/A |
| Mid Channel, 2440 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| High Channel, 2480 MHz | | 747.52 us | 1.25 ms | 1 | 59.8 | N/A | N/A |
| High Channel, 2480 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| BLE/GFSK 500 kbps | | | | | | | |
| Low Channel, 2402 MHz | | 499.01 us | 1.249 ms | 1 | 40 | N/A | N/A |
| Low Channel, 2402 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| Mid Channel, 2440 MHz | | 493.69 us | 1.249 ms | 1 | 39.5 | N/A | N/A |
| Mid Channel, 2440 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| High Channel, 2480 MHz | | 494.35 us | 1.25 ms | 1 | 39.5 | N/A | N/A |
| High Channel, 2480 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| BLE/GFSK 1 Mbps | | | | | | | |
| Low Channel, 2402 MHz | | 96.609 us | 625 us | 1 | 15.5 | N/A | N/A |
| Low Channel, 2402 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| Mid Channel, 2440 MHz | | 96.663 us | 625.1 us | 1 | 15.5 | N/A | N/A |
| Mid Channel, 2440 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| High Channel, 2480 MHz | | 97.325 us | 625 us | 1 | 15.6 | N/A | N/A |
| High Channel, 2480 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| BLE/GFSK 2 Mbps | | | | | | | |
| Low Channel, 2402 MHz | | 59.292 us | 625.1 us | 1 | 9.5 | N/A | N/A |
| Low Channel, 2402 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| Mid Channel, 2440 MHz | | 58.475 us | 625.1 us | 1 | 9.4 | N/A | N/A |
| Mid Channel, 2440 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |
| High Channel, 2480 MHz | | 58.858 us | 625.1 us | 1 | 9.4 | N/A | N/A |
| High Channel, 2480 MHz | | N/A | N/A | 5 | N/A | N/A | N/A |

DUTY CYCLE




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, Low Channel, 2402 MHz | | | | | |
|--|---------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 747.65 us | 1.25 ms | 1 | 59.8 | N/A | N/A |



| BLE/GFSK 125 kbps, Low Channel, 2402 MHz | | | | | |
|--|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, Mid Channel, 2440 MHz | | | | | |
|--|----------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 745.39 us | 1.251 ms | 1 | 59.6 | N/A | N/A |



| BLE/GFSK 125 kbps, Mid Channel, 2440 MHz | | | | | |
|--|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbtTx 2021.10.29.2

XMit 2020.12.30.0

| BLE/GFSK 125 kbps, High Channel, 2480 MHz | | | | | | |
|---|---------|------------------|-----------|-----------|---------|--|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results | |
| 747.52 us | 1.25 ms | 1 | 59.8 | N/A | N/A | |



| BLE/GFSK 125 kbps, High Channel, 2480 MHz | | | | | | |
|---|--------|------------------|-----------|-----------|---------|-----|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results | |
| | N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 500 kbps, Low Channel, 2402 MHz | | | | | |
|--|----------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 499.01 us | 1.249 ms | 1 | 40 | N/A | N/A |



| BLE/GFSK 500 kbps, Low Channel, 2402 MHz | | | | | |
|--|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 500 kbps, Mid Channel, 2440 MHz | | | | | | |
|--|-------------|----------|------------------|-----------|-----------|---------|
| | Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| | 493.69 us | 1.249 ms | 1 | 39.5 | N/A | N/A |



| BLE/GFSK 500 kbps, Mid Channel, 2440 MHz | | | | | | |
|--|-------------|--------|------------------|-----------|-----------|---------|
| | Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| | N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 500 kbps, High Channel, 2480 MHz | | | | | |
|---|---------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 494.35 us | 1.25 ms | 1 | 39.5 | N/A | N/A |



| BLE/GFSK 500 kbps, High Channel, 2480 MHz | | | | | |
|---|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, Low Channel, 2402 MHz | | | | | |
|--|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 96.609 us | 625 us | 1 | 15.5 | N/A | N/A |



| BLE/GFSK 1 Mbps, Low Channel, 2402 MHz | | | | | |
|--|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbITx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, Mid Channel, 2440 MHz | | | | | |
|--|----------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 96.663 us | 625.1 us | 1 | 15.5 | N/A | N/A |



| BLE/GFSK 1 Mbps, Mid Channel, 2440 MHz | | | | | |
|--|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, High Channel, 2480 MHz | | | | | |
|---|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 97.325 us | 625 us | 1 | 15.6 | N/A | N/A |



| BLE/GFSK 1 Mbps, High Channel, 2480 MHz | | | | | |
|---|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbITx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 2 Mbps, Low Channel, 2402 MHz | | | | | |
|--|----------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 59.292 us | 625.1 us | 1 | 9.5 | N/A | N/A |



| BLE/GFSK 2 Mbps, Low Channel, 2402 MHz | | | | | |
|--|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |




DUTY CYCLE




TbITx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 2 Mbps, Mid Channel, 2440 MHz | | | | | |
|--|----------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 58.475 us | 625.1 us | 1 | 9.4 | N/A | N/A |



| BLE/GFSK 2 Mbps, Mid Channel, 2440 MHz | | | | | |
|--|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |



DUTY CYCLE




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 2 Mbps, High Channel, 2480 MHz | | | | | |
|---|----------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| 58.858 us | 625.1 us | 1 | 9.4 | N/A | N/A |



| BLE/GFSK 2 Mbps, High Channel, 2480 MHz | | | | | |
|---|--------|------------------|-----------|-----------|---------|
| Pulse Width | Period | Number of Pulses | Value (%) | Limit (%) | Results |
| N/A | N/A | 5 | N/A | N/A | N/A |



OCCUPIED BANDWIDTH 99%



XMIT 2020.12.30.0

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

| Description | Manufacturer | Model | ID | Last Cal. | Cal. Due |
|------------------------------|--------------------|------------------------|-----|------------|------------|
| Analyzer - Spectrum Analyzer | Keysight | N9010A | AFN | 2022-01-19 | 2023-01-19 |
| Generator - Signal | Agilent | N5182A | TIF | 2020-08-29 | 2023-08-29 |
| Cable | UtiFlex Micro-Coax | UFD1150A-1-0720-200200 | TXJ | 2021-09-13 | 2022-09-13 |
| Block - DC | Fairview Microwave | SD3379 | AMM | 2021-09-14 | 2022-09-14 |
| Attenuator | Fairview Microwave | SA18E 1913 | TZV | 2021-09-15 | 2022-09-15 |

TEST DESCRIPTION

The 99% occupied bandwidth was measured with the EUT configured for continuous modulated operation.

Per ANSI C63.10:2013, 6.9.3, the spectrum analyzer was configured as follows:

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) of the spectrum analyzer was set to the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) bandwidth was set to at least 3 times the resolution bandwidth. The analyzer sweep time was set to auto to prevent video filtering or averaging. A sample detector was used unless the device was not able to be operated in a continuous transmit mode, in which case a peak detector was used.

The spectrum analyzer occupied bandwidth measurement function was used to sum the power of the transmission in linear terms to obtain the 99% bandwidth.

OCCUPIED BANDWIDTH 99%



TbTx 2021.10.29.2

XMI 2020.12.30.0


| EUT: | Radio Thermostat | Work Order: | F3EN0068 | |
|-------------------------------|------------------------|-------------------|---|--------|
| Serial Number: | DUT 1 | Date: | 10-Feb-22 | |
| Customer: | Quext | Temperature: | 21.3 °C | |
| Attendees: | None | Humidity: | 24% RH | |
| Project: | None | Barometric Pres.: | 1021 mbar | |
| Tested by: | Brandon Hobbs | Power: | 110VAC/60Hz | |
| TEST SPECIFICATIONS | | Test Method | ANSI C63.10:2013 | |
| FCC 15.247:2022 | | | | |
| COMMENTS | None | | | |
| DEVIATIONS FROM TEST STANDARD | | | | |
| None | | | | |
| Configuration # | 3 | Signature |  | |
| | | Value | Limit | Result |
| BLE/GFSK 125 kbps | Low Channel, 2402 MHz | 1.026 MHz | N/A | N/A |
| | Mid Channel, 2440 MHz | 1.027 MHz | N/A | N/A |
| | High Channel, 2480 MHz | 1.027 MHz | N/A | N/A |
| BLE/GFSK 500 kbps | Low Channel, 2402 MHz | 1.015 MHz | N/A | N/A |
| | Mid Channel, 2440 MHz | 1.021 MHz | N/A | N/A |
| | High Channel, 2480 MHz | 1.015 MHz | N/A | N/A |
| BLE/GFSK 1 Mbps | Low Channel, 2402 MHz | 1.038 MHz | N/A | N/A |
| | Mid Channel, 2440 MHz | 1.034 MHz | N/A | N/A |
| | High Channel, 2480 MHz | 1.044 MHz | N/A | N/A |
| BLE/GFSK 2 Mbps | Low Channel, 2402 MHz | 2.024 MHz | N/A | N/A |
| | Mid Channel, 2440 MHz | 2.046 MHz | N/A | N/A |
| | High Channel, 2480 MHz | 2.047 MHz | N/A | N/A |

OCCUPIED BANDWIDTH 99%




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, Low Channel, 2402 MHz | | |
|--|-----------|-------|
| | Value | Limit |
| | 1.026 MHz | N/A |



| BLE/GFSK 125 kbps, Mid Channel, 2440 MHz | | |
|--|-----------|-------|
| | Value | Limit |
| | 1.027 MHz | N/A |




OCCUPIED BANDWIDTH 99%




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, High Channel, 2480 MHz | | |
|---|-----------|-------|
| | Value | Limit |
| | 1.027 MHz | N/A |



| BLE/GFSK 500 kbps, Low Channel, 2402 MHz | | |
|--|-----------|-------|
| | Value | Limit |
| | 1.015 MHz | N/A |




OCCUPIED BANDWIDTH 99%




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 500 kbps, Mid Channel, 2440 MHz | | |
|--|-----------|-------|
| | Value | Limit |
| | 1.021 MHz | N/A |



| BLE/GFSK 500 kbps, High Channel, 2480 MHz | | |
|---|-----------|-------|
| | Value | Limit |
| | 1.015 MHz | N/A |




OCCUPIED BANDWIDTH 99%




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, Low Channel, 2402 MHz | | |
|--|-----------|-------|
| | Value | Limit |
| | 1.038 MHz | N/A |



| BLE/GFSK 1 Mbps, Mid Channel, 2440 MHz | | |
|--|-----------|-------|
| | Value | Limit |
| | 1.034 MHz | N/A |




OCCUPIED BANDWIDTH 99%




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, High Channel, 2480 MHz | | | Value | Limit | Result |
|---|--|--|-----------|-------|--------|
| | | | 1.044 MHz | N/A | N/A |



| BLE/GFSK 2 Mbps, Low Channel, 2402 MHz | | | Value | Limit | Result |
|--|--|--|-----------|-------|--------|
| | | | 2.024 MHz | N/A | N/A |




OCCUPIED BANDWIDTH 99%




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 2 Mbps, Mid Channel, 2440 MHz | | |
|--|-----------|-------|
| | Value | Limit |
| | 2.046 MHz | N/A |



| BLE/GFSK 2 Mbps, High Channel, 2480 MHz | | |
|---|-----------|-------|
| | Value | Limit |
| | 2.047 MHz | N/A |



DTS BANDWIDTH



XMit 2020.12.30.0

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

| Description | Manufacturer | Model | ID | Last Cal. | Cal. Due |
|------------------------------|--------------------|------------------------|-----|------------|------------|
| Attenuator | Fairview Microwave | SA18E 1913 | TZV | 2021-09-15 | 2022-09-15 |
| Block - DC | Fairview Microwave | SD3379 | AMM | 2021-09-14 | 2022-09-14 |
| Cable | UtiFlex Micro-Coax | UFD1150A-1-0720-200200 | TXJ | 2021-09-13 | 2022-09-13 |
| Generator - Signal | Agilent | N5182A | TIF | 2020-08-29 | 2023-08-29 |
| Analyzer - Spectrum Analyzer | Keysight | N9010A | AFN | 2022-01-19 | 2023-01-19 |

TEST DESCRIPTION

The EUT was set to the channels and modes listed in the datasheet.

The 6dB DTS bandwidth was measured using 100 kHz resolution bandwidth and 300 kHz video bandwidth. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

DTS BANDWIDTH



TbTx 2021.10.29.2

XMI 2020.12.30.0


| | | | | |
|-------------------------------|------------------|-------------------|------------------|------|
| EUT: | Radio Thermostat | Work Order: | F3EN0068 | |
| Serial Number: | DUT 1 | Date: | 10-Feb-22 | |
| Customer: | Quext | Temperature: | 22 °C | |
| Attendees: | None | Humidity: | 23.4% RH | |
| Project: | None | Barometric Pres.: | 1021 mbar | |
| Tested by: | Brandon Hobbs | Power: | 110VAC/60Hz | |
| TEST SPECIFICATIONS | | Test Method | ANSI C63.10:2013 | |
| FCC 15.247:2022 | | | | |
| COMMENTS | None | | | |
| DEVIATIONS FROM TEST STANDARD | | | | |
| None | | | | |
| Configuration # | 3 | Signature | | |
| BLE/GFSK 125 kbps | | | | |
| Low Channel, 2402 MHz | | 619.27 kHz | 500 kHz | Pass |
| Mid Channel, 2440 MHz | | 615.093 kHz | 500 kHz | Pass |
| High Channel, 2480 MHz | | 615.482 kHz | 500 kHz | Pass |
| BLE/GFSK 500 kbps | | | | |
| Low Channel, 2402 MHz | | 683.117 kHz | 500 kHz | Pass |
| Mid Channel, 2440 MHz | | 676.264 kHz | 500 kHz | Pass |
| High Channel, 2480 MHz | | 678.839 kHz | 500 kHz | Pass |
| BLE/GFSK 1 Mbps | | | | |
| Low Channel, 2402 MHz | | 556.907 kHz | 500 kHz | Pass |
| Mid Channel, 2440 MHz | | 627.494 kHz | 500 kHz | Pass |
| High Channel, 2480 MHz | | 630.008 kHz | 500 kHz | Pass |
| BLE/GFSK 2 Mbps | | | | |
| Low Channel, 2402 MHz | | 859.079 kHz | 500 kHz | Pass |
| Mid Channel, 2440 MHz | | 863.36 kHz | 500 kHz | Pass |
| High Channel, 2480 MHz | | 855.829 kHz | 500 kHz | Pass |

DTS BANDWIDTH




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, Low Channel, 2402 MHz | | | Limit |
|--|---------|--------|-------|
| Value | (≥) | Result | |
| 619.27 kHz | 500 kHz | Pass | |



| BLE/GFSK 125 kbps, Mid Channel, 2440 MHz | | | Limit |
|--|---------|--------|-------|
| Value | (≥) | Result | |
| 615.093 kHz | 500 kHz | Pass | |




DTS BANDWIDTH




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, High Channel, 2480 MHz | | | Limit |
|---|---------|--------|-------|
| Value | (≥) | Result | |
| 615.482 kHz | 500 kHz | Pass | |



| BLE/GFSK 500 kbps, Low Channel, 2402 MHz | | | Limit |
|--|---------|--------|-------|
| Value | (≥) | Result | |
| 683.117 kHz | 500 kHz | Pass | |




DTS BANDWIDTH




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 500 kbps, Mid Channel, 2440 MHz | | | Value | Limit (≥) | Result |
|--|--|--|-------------|-----------|--------|
| | | | 676.264 kHz | 500 kHz | Pass |



| BLE/GFSK 500 kbps, High Channel, 2480 MHz | | | Value | Limit (≥) | Result |
|---|--|--|-------------|-----------|--------|
| | | | 678.839 kHz | 500 kHz | Pass |




DTS BANDWIDTH




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, Low Channel, 2402 MHz | | | Value | Limit (≥) | Result |
|--|--|--|-------------|-----------|--------|
| | | | 556.907 kHz | 500 kHz | Pass |



| BLE/GFSK 1 Mbps, Mid Channel, 2440 MHz | | | Value | Limit (≥) | Result |
|--|--|--|-------------|-----------|--------|
| | | | 627.494 kHz | 500 kHz | Pass |




DTS BANDWIDTH




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, High Channel, 2480 MHz | | | Value | Limit (≥) | Result |
|---|--|--|-------------|-----------|--------|
| | | | 630.008 kHz | 500 kHz | Pass |



| BLE/GFSK 2 Mbps, Low Channel, 2402 MHz | | | Value | Limit (≥) | Result |
|--|--|--|-------------|-----------|--------|
| | | | 859.079 kHz | 500 kHz | Pass |




DTS BANDWIDTH




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 2 Mbps, Mid Channel, 2440 MHz | | | Value | Limit (≥) | Result |
|--|--|--|------------|-----------|--------|
| | | | 863.36 kHz | 500 kHz | Pass |



| BLE/GFSK 2 Mbps, High Channel, 2480 MHz | | | Value | Limit (≥) | Result |
|---|--|--|-------------|-----------|--------|
| | | | 855.829 kHz | 500 kHz | Pass |



OUTPUT POWER



XMit 2020.12.30.0

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

| Description | Manufacturer | Model | ID | Last Cal. | Cal. Due |
|------------------------------|--------------------|------------------------|-----|------------|------------|
| Block - DC | Fairview Microwave | SD3379 | AMM | 2021-09-14 | 2022-09-14 |
| Generator - Signal | Agilent | N5182A | TIF | 2020-08-29 | 2023-08-29 |
| Analyzer - Spectrum Analyzer | Keysight | N9010A | AFN | 2022-01-19 | 2023-01-19 |
| Cable | UtiFlex Micro-Coax | UFD1150A-1-0720-200200 | TXJ | 2021-09-13 | 2022-09-13 |
| Attenuator | Fairview Microwave | SA18E 1913 | TZV | 2021-09-15 | 2022-09-15 |

TEST DESCRIPTION

The transmit frequency was set to the required channels in each band. The transmit power was set to its default maximum.

Prior to measuring peak transmit power the DTS bandwidth (B) was measured.

The method found in ANSI C63.10:2013 Section 11.9.1.1 was used because the RBW on the analyzer was greater than the DTS Bandwidth of the radio.

OUTPUT POWER



TbTx 2021.10.29.2 XMII 2020.12.30.0


| | | | |
|-------------------------------|------------------|-------------------|------------------|
| EUT: | Radio Thermostat | Work Order: | F3EN0068 |
| Serial Number: | DUT 1 | Date: | 10-Feb-22 |
| Customer: | Quext | Temperature: | 22.1 °C |
| Attendees: | None | Humidity: | 23.3% RH |
| Project: | None | Barometric Pres.: | 1021 mbar |
| Tested by: | Brandon Hobbs | Power: | 110VAC/60Hz |
| TEST SPECIFICATIONS | | Test Method | ANSI C63.10:2013 |
| FCC 15.247:2022 | | | |
| COMMENTS | None | | |
| DEVIATIONS FROM TEST STANDARD | | | |
| None | | | |
| Configuration # | 3 | Signature | |
| BLE/GFSK 125 kbps | | | |
| Low Channel, 2402 MHz | | 5.55 | 30 |
| Mid Channel, 2440 MHz | | 4.872 | 30 |
| High Channel, 2480 MHz | | 5.297 | 30 |
| BLE/GFSK 500 kbps | | | |
| Low Channel, 2402 MHz | | 5.695 | 30 |
| Mid Channel, 2440 MHz | | 4.767 | 30 |
| High Channel, 2480 MHz | | 5.262 | 30 |
| BLE/GFSK 1 Mbps | | | |
| Low Channel, 2402 MHz | | 5.546 | 30 |
| Mid Channel, 2440 MHz | | 4.85 | 30 |
| High Channel, 2480 MHz | | 5.61 | 30 |
| BLE/GFSK 2 Mbps | | | |
| Low Channel, 2402 MHz | | 5.93 | 30 |
| Mid Channel, 2440 MHz | | 4.823 | 30 |
| High Channel, 2480 MHz | | 5.62 | 30 |

OUTPUT POWER




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, Low Channel, 2402 MHz | | | | Out Pwr (dBm) | Limit (dBm) | Result |
|--|--|--|--|---------------|-------------|--------|
| | | | | 5.55 | 30 | Pass |



| BLE/GFSK 125 kbps, Mid Channel, 2440 MHz | | | | Out Pwr (dBm) | Limit (dBm) | Result |
|--|--|--|--|---------------|-------------|--------|
| | | | | 4.872 | 30 | Pass |




OUTPUT POWER




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, High Channel, 2480 MHz | | | | Out Pwr (dBm) | Limit (dBm) | Result |
|---|--|--|--|---------------|-------------|--------|
| | | | | 5.297 | 30 | Pass |



| BLE/GFSK 500 kbps, Low Channel, 2402 MHz | | | | Out Pwr (dBm) | Limit (dBm) | Result |
|--|--|--|--|---------------|-------------|--------|
| | | | | 5.695 | 30 | Pass |




OUTPUT POWER




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 500 kbps, Mid Channel, 2440 MHz | | | |
|--|---------------|-------------|--------|
| | Out Pwr (dBm) | Limit (dBm) | Result |
| | 4.767 | 30 | Pass |



| BLE/GFSK 500 kbps, High Channel, 2480 MHz | | | |
|---|---------------|-------------|--------|
| | Out Pwr (dBm) | Limit (dBm) | Result |
| | 5.262 | 30 | Pass |




OUTPUT POWER




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, Low Channel, 2402 MHz | | | |
|--|------------------|----------------|--------|
| | Out Pwr (dBm) | Limit (dBm) | Result |
| | 5.546 | 30 | Pass |



| BLE/GFSK 1 Mbps, Mid Channel, 2440 MHz | | | |
|--|------------------|----------------|--------|
| | Out Pwr (dBm) | Limit (dBm) | Result |
| | 4.85 | 30 | Pass |




OUTPUT POWER




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, High Channel, 2480 MHz | | | |
|---|------------------|----------------|--------|
| | Out Pwr (dBm) | Limit (dBm) | Result |
| | 5.61 | 30 | Pass |



| BLE/GFSK 2 Mbps, Low Channel, 2402 MHz | | | |
|--|------------------|----------------|--------|
| | Out Pwr (dBm) | Limit (dBm) | Result |
| | 5.93 | 30 | Pass |




OUTPUT POWER




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 2 Mbps, Mid Channel, 2440 MHz | | | |
|--|---------------|-------------|--------|
| | Out Pwr (dBm) | Limit (dBm) | Result |
| | 4.823 | 30 | Pass |



| BLE/GFSK 2 Mbps, High Channel, 2480 MHz | | | |
|---|---------------|-------------|--------|
| | Out Pwr (dBm) | Limit (dBm) | Result |
| | 5.62 | 30 | Pass |



EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)



XMit 2020.12.30.0

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

| Description | Manufacturer | Model | ID | Last Cal. | Cal. Due |
|------------------------------|--------------------|-------------------|-----|------------|------------|
| Attenuator | Fairview Microwave | SA18E 1913 | TZV | 2021-09-15 | 2022-09-15 |
| Block - DC | Fairview Microwave | SD3379 | AMM | 2021-09-14 | 2022-09-14 |
| Cable | UtiFlex Micro-Coax | 01150A-1-0720-200 | TXJ | 2021-09-13 | 2022-09-13 |
| Analyzer - Spectrum Analyzer | Keysight | N9010A | AFN | 2022-01-19 | 2023-01-19 |
| Generator - Signal | Agilent | N5182A | TIF | 2020-08-29 | 2023-08-29 |

TEST DESCRIPTION

The transmit frequency was set to the required channels in each band. The transmit power was set to its default maximum.

Prior to measuring peak transmit power the DTS bandwidth (B) was measured.

The method found in ANSI C63.10:2013 Section 11.9.1.1 was used because the RBW on the analyzer was greater than the DTS Bandwidth of the radio.

Equivalent Isotropic Radiated Power (EIRP) = Max Measured Power + Antenna gain (dBi)

EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)



TbTx 2021.10.29.2 XMII 2020.12.30.0


| EUT: | Radio Thermostat | Work Order: | F3EN0068 | | | | | |
|-------------------------------|------------------|-------------------|------------------|---------------|--------------------|------------|------------------|--------|
| Serial Number: | DUT 1 | Date: | 10-Feb-22 | | | | | |
| Customer: | Quext | Temperature: | 21.5 °C | | | | | |
| Attendees: | None | Humidity: | 23.8% RH | | | | | |
| Project: | None | Barometric Pres.: | 1021 mbar | | | | | |
| Tested by: | Brandon Hobbs | Power: | 110VAC/60Hz | | | | | |
| TEST SPECIFICATIONS | | Test Method | ANSI C63.10:2013 | | | | | |
| FCC 15.247:2022 | | | | | | | | |
| COMMENTS | None | | | | | | | |
| DEVIATIONS FROM TEST STANDARD | | | | | | | | |
| None | | | | | | | | |
| Configuration # | 3 | Signature | | Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result |
| BLE/GFSK 125 kbps | | | | 5.550 | -0.3 | 5.25 | 36 | Pass |
| Low Channel, 2402 MHz | | | | 4.872 | -0.3 | 4.57 | 36 | Pass |
| Mid Channel, 2440 MHz | | | | 5.297 | -0.3 | 5.00 | 36 | Pass |
| High Channel, 2480 MHz | | | | | | | | |
| BLE/GFSK 500 kbps | | | | 5.695 | -0.3 | 5.40 | 36 | Pass |
| Low Channel, 2402 MHz | | | | 4.767 | -0.3 | 4.47 | 36 | Pass |
| Mid Channel, 2440 MHz | | | | 5.262 | -0.3 | 4.96 | 36 | Pass |
| BLE/GFSK 1 Mbps | | | | | | | | |
| Low Channel, 2402 MHz | | | | 5.546 | -0.3 | 5.25 | 36 | Pass |
| Mid Channel, 2440 MHz | | | | 4.850 | -0.3 | 4.55 | 36 | Pass |
| High Channel, 2480 MHz | | | | 5.610 | -0.3 | 5.31 | 36 | Pass |
| BLE/GFSK 2 Mbps | | | | | | | | |
| Low Channel, 2402 MHz | | | | 5.930 | -0.3 | 5.63 | 36 | Pass |
| Mid Channel, 2440 MHz | | | | 4.823 | -0.3 | 4.52 | 36 | Pass |
| High Channel, 2480 MHz | | | | 5.620 | -0.3 | 5.32 | 36 | Pass |

EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, Low Channel, 2402 MHz | | | | | |
|--|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 5.55 | -0.3 | 5.25 | 36 | Pass | |



| BLE/GFSK 125 kbps, Mid Channel, 2440 MHz | | | | | |
|--|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 4.872 | -0.3 | 4.572 | 36 | Pass | |




EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 125 kbps, High Channel, 2480 MHz | | | | | |
|---|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 5.297 | -0.3 | 4.997 | 36 | Pass | |



| BLE/GFSK 500 kbps, Low Channel, 2402 MHz | | | | | |
|--|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 5.695 | -0.3 | 5.395 | 36 | Pass | |




EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)




TbTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 500 kbps, Mid Channel, 2440 MHz | | | | | |
|--|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 4.767 | -0.3 | 4.467 | 36 | Pass | |



| BLE/GFSK 500 kbps, High Channel, 2480 MHz | | | | | |
|---|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 5.262 | -0.3 | 4.962 | 36 | Pass | |




EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, Low Channel, 2402 MHz | | | | | |
|--|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 5.546 | -0.3 | 5.246 | 36 | Pass | |



| BLE/GFSK 1 Mbps, Mid Channel, 2440 MHz | | | | | |
|--|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 4.85 | -0.3 | 4.55 | 36 | Pass | |




EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)




TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 1 Mbps, High Channel, 2480 MHz | | | | | |
|---|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 5.61 | -0.3 | 5.31 | 36 | Pass | |



| BLE/GFSK 2 Mbps, Low Channel, 2402 MHz | | | | | |
|--|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 5.93 | -0.3 | 5.63 | 36 | Pass | |




EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)



TbtTx 2021.10.29.2 XMit 2020.12.30.0

| BLE/GFSK 2 Mbps, Mid Channel, 2440 MHz | | | | | |
|--|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 4.823 | -0.3 | 4.523 | 36 | Pass | |



| BLE/GFSK 2 Mbps, High Channel, 2480 MHz | | | | | |
|---|-----------------------|---------------|---------------------|--------|--|
| Out Pwr (dBm) | Antenna Gain (dBi) | EIRP (dBm) | EIRP Limit (dBm) | Result | |
| 5.62 | -0.3 | 5.32 | 36 | Pass | |

