





# **RF Exposure Evaluation Report**

FCC ID : 2AYS4-AIP6MA

Equipment : SiP Module

Brand Name : AIP

Model Name : SCLCT06M

Applicant : Advanced Semiconductor Engineering, Inc.,

Chung-Li Branch

550, Chung-Hwa Road Section 1, Chung-Li

District, Taoyuan City 32016, Taiwan

Manufacturer : Advanced Semiconductor Engineering, Inc.,

**Chung-Li Branch** 

550, Chung-Hwa Road Section 1, Chung-Li

District, Taoyuan City 32016, Taiwan

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Jan. 21, 2021, and testing was started from Feb. 04, 2021 and completed on Feb. 04, 2021. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 5

FAX: 886-3-327-0973 Issued Date : Feb. 24, 2021

Report Version

: 01

Report Template No.: HE1-A3 Ver2.2 FCC ID: 2AYS4-AIP6MA



: 2 of 5

: Feb. 24, 2021

### **Table of Contents**

1. General Description				
	1.1.	EUT General Information  Testing Location Information	4	
2.	RF	Exposure Evaluation	.5	
	2.1.	Applicable Standard		
	۷.۷.	OAK Ovaldation		

#### Photographs of EUT V01

TEL: 886-3-327-3456 Page Number FAX: 886-3-327-0973 Issued Date

Report Template No.: HE1-A3 Ver2.2 Report Version : 01



# **History of This Test Report**

Report No.	Version	Description	Issued Date
FA111524	01	Initial issue of report	Feb. 24, 2021

Reviewed by: Ben Tseng

Report Producer: Jenny Yang

TEL: 886-3-327-3456 Page Number : 3 of 5
FAX: 886-3-327-0973 Issued Date : Feb. 24, 2021

Report Template No.: HE1-A3 Ver2.2 Report Version : 01



# 1. General Description

#### 1.1. EUT General Information

RF General Information				
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type	
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / π/4-DQPSK / 8DPSK) LE: DSSS (GFSK)	

## 1.2. Testing Location Information

	Testing Location						
$\boxtimes$	HWA YA	ADD :	No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)				
		TEL :	886-3-327-3456 FAX : 886-3-327-0973				
	Test site Designation No. TW1190 with FCC.						
	JHUBEI	ADD :	No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)				
		TEL :	886-3-656-9065 FAX : 886-3-656-9085				
	Test site Designation No. TW0006 with FCC.						
	Wen Shan	ADD :	: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)				
		TEL :	886-3-318-0787 FAX : 886-3-318-0287				
	Test site Designation No. TW1097 with FCC.						

TEL: 886-3-327-3456 Page Number : 4 of 5
FAX: 886-3-327-0973 Issued Date : Feb. 24, 2021

Report Template No.: HE1-A3 Ver2.2 Report Version : 01



#### 2. RF Exposure Evaluation

#### 2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

#### 2.2. SAR evaluation

1. Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]•

 $[\sqrt{f}_{(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Max. Power	Tolerance	Tune-up Max. Power		<b>Test Distance</b>	Frequency	Exclusion
(dBm)	(dB)	(dBm)	(mW)	(mm)	(GHz)	Thresholds
13.02	0.50	13.52	22.49	20	2.402	1.74

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is 1.74 < 3, RF exposure evaluation is not required.

——THE END——

TEL: 886-3-327-3456 Page Number : 5 of 5
FAX: 886-3-327-0973 Issued Date : Feb. 24, 2021

Report Template No.: HE1-A3 Ver2.2 Report Version : 01