Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



Test_Graph_LE125K_ANT1_2402_125Kbps_Lower Band Edge Emissions



Test_Graph_LE125K_ANT1_2480_125Kbps_Higher Band Edge Emissions



Test_Graph_LE500K_ANT1_2402_500Kbps_Lower Band Edge Emissions



Test_Graph_LE500K_ANT1_2480_500Kbps_Higher Band Edge Emissions



Test_Graph_LE1M_ANT1_2402_1Mbps_Lower Band Edge Emissions



Test_Graph_LE1M_ANT1_2480_1Mbps_Higher Band Edge Emissions



Test_Graph_LE2M_ANT1_2402_2Mbps_Lower Band Edge Emissions



Test_Graph_LE2M_ANT1_2480_2Mbps_Higher Band Edge Emissions

11. Radiated Spurious Emission

11.1 Measurement Limit

- FCC Part 15.209 Limit in the below table to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.2 Measurement Procedure

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

8. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
9. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
10. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
11. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP

- **Quasi-Peak Measurements below 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as shown in the table above
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

- **Peak Measurements above 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

- **Average Measurements above 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW ≥ [3 × RBW]
4. Detector = Power averaging (rms)
5. Averaging type = power (i.e., rms)
6. Sweep time = auto
7. Perform a trace average of at least 100 traces.
8. The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the “Input Correction” of the Spectrum Analyzer.

11.3 Measurement Setup (Block Diagram of Configuration)

Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Test setup for radiated emissions of tabletop equipment (30 MHz to 1 GHz)

Radiated Emission Test Setup Above 1000MHz



11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

Radiated Emission Test Results at 30MHz-1GHz			
EUT Name	Portable Power Station	Model Name	Elite 100 V2
Temperature	21.8° C	Relative Humidity	53.3%
Pressure	960hPa	Test Voltage	AC 120V/60Hz
Test Mode	Mode 8	**Antenna Polarity**	Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		38.6160	8.59	13.30	21.89	40.00	-18.11	peak
2		77.8653	11.82	13.04	24.86	40.00	-15.14	peak
3		101.6443	11.78	16.22	28.00	43.50	-15.50	peak
4		451.1349	8.60	24.71	33.31	46.00	-12.69	peak
5		622.8899	7.17	24.93	32.10	46.00	-13.90	peak
6	*	903.3093	5.83	31.34	37.17	46.00	-8.83	peak

Radiated Emission Test Results at 30MHz-1GHz			
EUT Name	Portable Power Station	Model Name	Elite 100 V2
Temperature	21.8° C	Relative Humidity	53.3%
Pressure	960hPa	Test Voltage	AC 120V/60Hz
Test Mode	Mode 8	**Antenna Polarity**	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	43.8119	15.31	16.94	32.25	40.00	-7.75	peak
2		52.3912	14.93	17.02	31.95	40.00	-8.05	peak
3		96.4361	14.08	14.68	28.76	43.50	-14.74	peak
4		451.1349	6.62	25.60	32.22	46.00	-13.78	peak
5		704.2259	7.64	28.25	35.89	46.00	-10.11	peak
6		945.4397	4.58	30.78	35.36	46.00	-10.64	peak

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 8 is the worst case and recorded in the report.

Radiated Emissions Test Results for Above 1GHz

EUT Name	Portable Power Station	Model Name	Elite 100 V2
Temperature	21.8° C	Relative Humidity	53.3%
Pressure	960hPa	Test Voltage	AC 120V/60Hz
Test Mode	Mode 7	**Antenna Polarity**	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804.000	47.94	0.08	48.02	74	-25.98	peak
4804.000	38.42	0.08	38.5	54	-15.5	AVG
7206.000	41.53	2.21	43.74	74	-30.26	peak
7206.000	32.52	2.21	34.73	54	-19.27	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	Elite 100 V2
Temperature	21.8° C	Relative Humidity	53.3%
Pressure	960hPa	Test Voltage	AC 120V/60Hz
Test Mode	Mode 7	**Antenna Polarity**	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804.000	47.62	0.08	47.7	74	-26.3	peak
4804.000	38.45	0.08	38.53	54	-15.47	AVG
7206.000	41.65	2.21	43.86	74	-30.14	peak
7206.000	31.26	2.21	33.47	54	-20.53	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: PASS

Radiated Emissions Test Results for Above 1GHz

EUT Name	Portable Power Station	Model Name	Elite 100 V2
Temperature	21.8° C	Relative Humidity	53.3%
Pressure	960hPa	Test Voltage	AC 120V/60Hz
Test Mode	Mode 8	**Antenna Polarity**	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4880.000	48.62	0.14	48.76	74	-25.24	peak
4880.000	37.12	0.14	37.26	54	-16.74	AVG
7320.000	42.31	2.36	44.67	74	-29.33	peak
7320.000	32.36	2.36	34.72	54	-19.28	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	Elite 100 V2
Temperature	21.8° C	Relative Humidity	53.3%
Pressure	960hPa	Test Voltage	AC 120V/60Hz
Test Mode	Mode 8	**Antenna Polarity**	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4880.000	47.95	0.14	48.09	74	-25.91	peak
4880.000	38.54	0.14	38.68	54	-15.32	AVG
7320.000	42.16	2.36	44.52	74	-29.48	peak
7320.000	31.36	2.36	33.72	54	-20.28	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: Pass

Radiated Emissions Test Results for Above 1GHz

EUT Name	Portable Power Station	Model Name	Elite 100 V2
Temperature	21.8° C	Relative Humidity	53.3%
Pressure	960hPa	Test Voltage	AC 120V/60Hz
Test Mode	Mode 9	**Antenna Polarity**	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.000	47.51	0.22	47.73	74	-26.27	peak
4960.000	38.27	0.22	38.49	54	-15.51	AVG
7440.000	41.94	2.64	44.58	74	-29.42	peak
7440.000	32.55	2.64	35.19	54	-18.81	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	Elite 100 V2
Temperature	21.8° C	Relative Humidity	53.3%
Pressure	960hPa	Test Voltage	AC 120V/60Hz
Test Mode	Mode 9	**Antenna Polarity**	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.000	47.16	0.22	47.38	74	-26.62	peak
4960.000	37.53	0.22	37.75	54	-16.25	AVG
7440.000	42.61	2.64	45.25	74	-28.75	peak
7440.000	31.25	2.64	33.89	54	-20.11	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: Pass

Note:

1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
2. Factor = Antenna Factor + Cable loss – Pre-amplifier gain, Margin =Emission Level-Limit.
3. The “Factor” value can be calculated automatically by software of measurement system.
4. All test modes had been pre-tested. The mode 1Mbps is the worst case and recorded in the report.

Band Edge Emission Test Results for Restricted Bands

EUT Name	Portable Power Station	**Model Name**	Elite 100 V2
Temperature	22℃	**Relative Humidity**	52%
Pressure	960hPa	**Test Voltage**	AC 120V/60Hz

Bluetooth Tx CH00_2402 MHz_125Kbps

Item (Mark)	Freq. MHz	Reading dBμV	Ant. Fac. dB/m	PRM Factor dB	Cable Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Detector	Pol.
1	2390.00	42.56	29.99	30.21	8.35	50.689	74	23.31	Peak	Horizontal
2	2390.00	32.39	29.99	30.21	8.35	40.519	54	13.48	AV[1]	Horizontal
3	2390.00	38.98	29.99	30.21	8.35	47.105	74	26.90	Peak	Vertical
4	2390.00	28.65	29.99	30.21	8.35	36.776	54	17.22	AV[1]	Vertical

Bluetooth Tx CH39_2480 MHz_125Kbps

Item (Mark)	Freq. MHz	Reading dBμV	Ant. Fac. dB/m	PRM Factor dB	Cable Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Detector	Pol.
1	2483.50	50.46	30.25	30.25	8.5	58.963	74	15.04	Peak	Horizontal
2	2483.50	40.45	30.25	30.25	8.5	48.953	54	5.05	AV[1]	Horizontal
3	2483.50	47.00	30.25	30.25	8.5	55.504	74	18.50	Peak	Vertical
4	2483.50	36.47	30.25	30.25	8.5	44.966	54	9.03	AV[1]	Vertical

Bluetooth Tx CH00_2402 MHz_500Kbps

Item (Mark)	Freq. MHz	Reading dBμV	Ant. Fac. dB/m	PRM Factor dB	Cable Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Detector	Pol.
1	2390.00	40.84	29.99	30.21	8.35	48.969	74	25.03	Peak	Horizontal
2	2390.00	30.04	29.99	30.21	8.35	38.173	54	15.83	AV	Horizontal
3	2390.00	36.79	29.99	30.21	8.35	44.916	74	29.08	Peak	Vertical
4	2390.00	27.62	29.99	30.21	8.35	35.747	54	18.25	AV	Vertical

Bluetooth Tx CH39_2480 MHz_500Kbps

Item (Mark)	Freq. MHz	Reading dBμV	Ant. Fac. dB/m	PRM Factor dB	Cable Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Detector	Pol.
1	2483.50	50.63	30.25	30.25	8.5	59.132	74	14.87	Peak	Horizontal
2	2483.50	41.13	30.25	30.25	8.5	49.629	54	4.37	AV	Horizontal
3	2483.50	47.81	30.25	30.25	8.5	56.313	74	17.69	Peak	Vertical
4	2483.50	37.93	30.25	30.25	8.5	46.428	54	7.57	AV	Vertical

Bluetooth Tx CH00_2402 MHz_1Mbps										
Item (Mark)	Freq. MHz	Reading dBµV	Ant. Fac. dB/m	PRM Factor dB	Cable Loss dB	Level dBµV/m	Limit dBµV/m	Margin dB	Detector	Pol.
1	2390.00	42.15	29.99	30.21	8.35	50.281	74	23.72	Peak	Horizontal
2	2390.00	31.79	29.99	30.21	8.35	39.918	54	14.08	AV	Horizontal
3	2390.00	40.22	29.99	30.21	8.35	48.352	74	25.65	Peak	Vertical
4	2390.00	30.45	29.99	30.21	8.35	38.581	54	15.42	AV	Vertical
Bluetooth Tx CH39_2480 MHz_1Mbps										
Item (Mark)	Freq. MHz	Reading dBµV	Ant. Fac. dB/m	PRM Factor dB	Cable Loss dB	Level dBµV/m	Limit dBµV/m	Margin dB	Detector	Pol.
1	2483.50	51.42	30.25	30.25	8.5	59.918	74	14.08	Peak	Horizontal
2	2483.50	41.67	30.25	30.25	8.5	50.167	54	3.83	AV	Horizontal
3	2483.50	47.43	30.25	30.25	8.5	55.926	74	18.07	Peak	Vertical
4	2483.50	37.79	30.25	30.25	8.5	46.292	54	7.71	AV	Vertical

Bluetooth Tx CH00_2402 MHz_2Mbps										
Item (Mark)	Freq. MHz	Reading dBµV	Ant. Fac. dB/m	PRM Factor dB	Cable Loss dB	Level dBµV/m	Limit dBµV/m	Margin dB	Detector	Pol.
1	2390.00	42.51	29.99	30.21	8.35	50.643	74	23.36	Peak	Horizontal
2	2390.00	31.94	29.99	30.21	8.35	40.065	54	13.94	AV	Horizontal
3	2390.00	40.58	29.99	30.21	8.35	48.71	74	25.29	Peak	Vertical
4	2390.00	29.86	29.99	30.21	8.35	37.991	54	16.01	AV	Vertical
Bluetooth Tx CH39_2480 MHz_2Mbps										
Item (Mark)	Freq. MHz	Reading dBµV	Ant. Fac. dB/m	PRM Factor dB	Cable Loss dB	Level dBµV/m	Limit dBµV/m	Margin dB	Detector	Pol.
1	2483.50	52.05	30.25	30.25	8.5	60.546	74	13.45	Peak	Horizontal
2	2483.50	41.89	30.25	30.25	8.5	50.388	54	3.61	AV	Horizontal
3	2483.50	48.77	30.25	30.25	8.5	57.271	74	16.73	Peak	Vertical
4	2483.50	38.67	30.25	30.25	8.5	47.17	54	6.83	AV	Vertical

Remark:
1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. The other emission levels were very low against the limit.
3. Margin = Limit - Emission Level.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=3MHz/Sweep time=Auto/Detector=Average.

RESULT: Pass

12. AC Power Line Conducted Emission Test

12.1 Measurement Limit

Frequency	Maximum RF Line Voltage	
	Q.P. (dBμV)	Average (dBμV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

12.2 Measurement Setup (Block Diagram of Configuration)



12.3 Preliminary Procedure of Line Conducted Emission Test

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipment received AC120V/60Hz power from a LISN, if any.
5. The EUT received AC120V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side).
7. Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
8. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
9. During the above scans, the emissions were maximized by cable manipulation.
10. The test mode(s) were scanned during the preliminary test.
11. Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 Final Procedure of Line Conducted Emission Test

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
3. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
4. The test data of the worst case condition(s) was reported on the Summary Data page.
5. A conducted emission is calculated by the following equation:
   - Measurement Level (dBμV) = Receiver reading (dBμV) + Transd (dB)
   - Transd (dB)= AMN Factor(dB)+Cable Loss(dB)+Attenuation(dB)
   - Margin= Limit-Level

12.5 Measurement Result

AC Power Line Conducted Emission Test			
Test Mode	Mode 1	LISN Line	Neutral Side



MEASUREMENT RESULT: "agc_fin"

2025/6/13 9:43

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.154000	55.70	10.3	66	10.1	QP	N
0.446000	44.80	10.3	57	12.1	QP	N
0.622000	44.00	10.3	56	12.0	QP	N
0.978000	43.70	10.4	56	12.3	QP	N
1.334000	43.70	10.4	56	12.3	QP	N
1.510000	40.90	10.4	56	15.1	QP	N

MEASUREMENT RESULT: "agc_fin2"

2025/6/13 9:43

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.446000	42.70	10.3	47	4.2	AV	N
0.622000	41.80	10.3	46	4.2	AV	N
0.802000	41.20	10.4	46	4.8	AV	N
4.006000	43.30	10.7	46	3.7	AV	N
4.186000	41.70	10.7	46	4.3	AV	N
4.362000	41.70	10.7	46	4.3	AV	N

RESULT: PASS

AC Power Line Conducted Emission Test			
Test Mode	Mode 1	LISN Line	Hot Side



MEASUREMENT RESULT: "agc_fin"

2025/6/13 9:39

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000	56.80	10.3	66	9.2	QP	L1
0.446000	45.00	10.3	57	11.9	QP	L1
0.622000	44.30	10.3	56	11.7	QP	L1
0.978000	43.90	10.4	56	12.1	QP	L1
1.186000	39.00	10.4	56	17.0	QP	L1
1.334000	44.10	10.4	56	11.9	QP	L1

MEASUREMENT RESULT: "agc_fin2"

2025/6/13 9:39

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.446000	42.90	10.3	47	4.0	AV	L1
0.622000	42.00	10.3	46	4.0	AV	L1
0.802000	41.40	10.4	46	4.6	AV	L1
4.006000	42.70	10.7	46	3.3	AV	L1
4.186000	41.40	10.7	46	4.6	AV	L1
4.362000	41.80	10.7	46	4.2	AV	L1

RESULT: PASS

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC12447250201AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC12447250201AP02

Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by Company as a result of this application for testing services (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3.The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

-----End of Report-----