

915MHz Copper Spring Antenna

Product Specification



Catalogue

1. Description.....	- 3 -
2. Technical Parameter.....	- 3 -
3. Size.....	- 3 -
4. VSWR Chart.....	- 3 -

Note: Revision History

Revision	Date	Comment
V1.0	2014-12	First release
V2.0	2016-06	Typesetting, measurements revised
V2.1	2017-06	Logo updated
V2.2	2019-6	Update size


1. Description

SW915-TH12, a copper spring antenna, is designed specially for 915MHz wireless communication. It has good VSWR, Compact dimensions, easy installation, stable performance, with good anti-vibration and anti-aging ability.

2. Technical Parameter


- Frequency Range: 915 ± 5 MHz
- VSWR: ≤ 1.5
- Gain: 2.15 dBi
- Input impedance: 50Ω
- Max power: 5 W
- Height: 12.5 ± 1 mm
- Interface form: welding directly
- Antenna Color: copper
- Weight: 1 g
- Wire diameter: 0.8mm

3. Size



4. VSWR Chart

Antennas have been tested under wireless simulated environment by Network Analyzer





PRODUCT SPECIFICATION

TITLE

2.4GHZ MID SMT ANTENNA

TABLE OF CONTENTS

1.0

SCOPE

2.0

PRODUCT DESCRIPTION

3.0

APPLICABLE DOCUMENTS

4.0

GENERAL SPECIFICATION

5.0

ANTENNA SPECIFICATION

6.0

MECHANICAL REQUIREMENTS

7.0

ENVIRONMENTAL SPECIFICATION

8.0

RECOMMENDED REFLOW CONDITION

9.0

RECOMMENDED FOOTPRINT ON PCB FOR SOLDERING

10.0

PACKING

11.0

OTHER MOLEX ANTENNA PRODUCTS

12.0

CHANGED HISTORY

REVISION:	ECR/ECN INFORMATION:	TITLE:	SHEET No.
G	EC No: 738181 DATE: 2023/02/15	2.4GHZ MID SMT Antenna Product Specification	1 of 11
DOCUMENT NUMBER:	CREATED / REVISED BY:	CHECKED BY:	APPROVED BY:
PS-479480001	Kang Cheng	Cooper Zhou	Horace Ma