



Test Report No.:  
FCC2025-0006-RF1

## TEST REPORT

**FCC ID** : 2AYXT61100003  
**Applicant** : Eight Sleep Inc  
**Product Name** : Pod Hub  
**Model No.** : 11504

**CVC Testing Technology Co., Ltd.**

<b>Product Name</b>	Pod Hub					
<b>Type/Model</b>	11504	<b>Trade Mark</b>	Eight Sleep			
<b>Applicant</b>	Eight Sleep Inc					
<b>Applicant Address</b>	915 Broadway STE 1301 New York, New York 10010					
<b>Manufacturer</b>	BoShiJie Technology Co., Ltd					
<b>Manufacturer Address</b>	Boshijie Industrial Park, No. 1 Huifeng West Third Road, Zhongkai High-tech Zone, Huizhou City, Guangdong, China. 516006					
<b>Factory</b>	BoShiJie Technology Co., Ltd					
<b>Factory Address</b>	Boshijie Industrial Park, No. 1 Huifeng West Third Road, Zhongkai High-tech Zone, Huizhou City, Guangdong, China. 516006					
<b>Sample Identification</b>	1-1	<b>Test Item</b>	See page 9			
<b>Tested According To</b>	FCC CFR47 Part 15C Radio Frequency Devices ANSI C63.10-2020/Cor1-2023 KDB 558074 D01 15.247 Meas Guidance v05r02 KDB 662911 D01 Multiple Transmitter Output v02r01					
<b>Receiving Date</b>	2025-03-19	<b>Completing Date</b>	2025-04-16			
<b>Test conclusion</b>	<p>The equipment under test was found to comply with the requirements of the standards applied.</p> <p>Final Verdict: Pass.</p>					
	Seal of CVC					
	Date of issue: <b>2025-04-30</b>					
Abbreviations: / Pass= passed Fail = failed N/A= not applicable						
This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.						


Approved by:

Chen Huawen



Reviewed by:

Xu Zhenfei



Tested by:

Lu Weiji



## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>4</b>
<b>1. GENERAL PRODUCT INFORMATION .....</b>	<b>5</b>
1.1 GENERAL INFORMATION .....	5
<b>2. TEST SITES .....</b>	<b>6</b>
2.1 TEST FACILITIES .....	6
2.2 DESCRIPTION OF NON-STANDARD METHOD AND DEVIATIONS .....	6
2.3 LIST OF TEST AND MEASUREMENT INSTRUMENTS .....	6
<b>3. TEST CONFIGURATION .....</b>	<b>7</b>
3.1 TEST MODE .....	7
3.2 DUTY CYCLE .....	9
<b>4. SUMMARY OF MEASUREMENT RESULTS .....</b>	<b>10</b>
<b>5. MEASUREMENT PROCEDURE .....</b>	<b>11</b>
5.1 CONDUCTED EMISSION .....	11
5.2 RADIATED EMISSION .....	17
5.3 MAXIMUM CONDUCTED OUTPUT POWER .....	35
5.4 MINIMUM 6 DB BANDWIDTH .....	38
5.5 OCCUPIED CHANNEL BANDWIDTH .....	40
5.6 BAND EDGE MEASUREMENT .....	42
5.7 MAXIMUM POWER SPECTRAL DENSITY .....	44
5.8 SPURIOUS RF CONDUCTED EMISSIONS .....	46
<b>6. APPENDIX X .....</b>	<b>49</b>

**RELEASE CONTROL RECORD**

<b>ISSUE NO.</b>	<b>REASON FOR CHANGE</b>	<b>DATE ISSUED</b>
FCC2025-0006-RF1	Original release	April.30,2025

# 1. General Product Information

## 1.1 General information

Product Name	Pod Hub
Model No.	11504
Additional model	/
Power Supply	110-240V AC 50-60Hz
Serial Number(SN)	/
specific power settings	Bluetooth(LE_1M, LE_2M): Default IEEE 802.11b: 14 IEEE 802.11g: 16 IEEE 802.11n(HT20&HT40): 16
Antenna Type	Bluetooth:Internal antenna WIFI2.4GHz:Internal antenna
Antenna Gain	WIFI: Ant1:-2.21 dBi, Ant2:-3.02 dBi (provided by client) Bluetooth: -1.27 dBi (provided by client)
Beamforming gain	Unsupported (provided by client)
Frequency Range	Bluetooth(LE_1M, LE_2M): 2402~2480MHz IEEE 802.11b/g/n(HT20): 2412~2462MHz IEEE 802.11n(HT40): 2422~2452MHz
Channel Number	Bluetooth(LE_1M, LE_2M):40 Channels IEEE 802.11b/g/n (HT20): 11 Channels IEEE 802.11n (HT40): 7 Channels
Type of Modulation	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM GFSK for BT-LE
Max. Conducted Power	Bluetooth(LE): 3.19 dBm WIFI2.4G:22.58dBm
Operate Temp.Range	-10°C~+70°C

**Note:**

1. The information of the EUT is declared by the manufacturer.
2. The laboratory is not responsible for the product technical specification provided by the client.
3. The product models of this application are: 11504. All the tests carried out on model 11504.
4. EUT photo refer to report (Report NO.:FCC2025-0006-EUT).
5. There are two power supplies, from different manufacturers.

Power supply information		
No.	Manufacturer	MODEL
1	Meanwell	LOP-400-12
2	Megmeet	MAP400-12
6. This time, the main engine+bedspread was used for testing, and the test results covered other combinations..		
7. There are four ways to sell this product in combination:1)Host+Bed cover,2)Host+Pillow,3)Host+Bed cover+Pillow,4)Host+Bed cover+blanket.		

## 2. Test Sites

### 2.1 Test Facilities

The tests and measurements refer to this report were performed by RF testing Lab. of CVC Testing Technology Co., Ltd.

Add.: No.3, Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou, Guangdong, 510663, People's Republic of China

Telephone : +86-20-32293888

Fax : +86-20-32293889

FCC(Test firm designation number: CN1282)

IC(Test firm CAB identifier number: CN0103)

CNAS(Test firm designation number: L0095)

### 2.2 Description of Non-standard Method and Deviations

The testing and measurement methods used in this report are applied by all standard methods. Not any non-standard method or deviation from the used standards was used.

### 2.3 List of Test and Measurement Instruments

Refer to **Appendix X**.

## 3. Test Configuration

### 3.1 Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Test Mode	Antenna Delivery	Test Channel
Bluetooth(LE_1M)	1TX / 1RX	0,19,39
Bluetooth(LE_2M)	1TX / 1RX	0,19,39
IEEE 802.11b	1TX / 1RX	1,6,11
IEEE 802.11g	1TX / 1RX	1,6,11
IEEE 802.11n 20 MIMO	2TX / 2RX	1,6,11
IEEE 802.11n 40 MIMO	2TX / 2RX	3,6,9

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate and different channels. Preliminary tests have been done on all the configurations for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates and channels are shown as following table.

Test Mode	Data Rate		
	Antenna 1	Antenna 2	MIMO
Bluetooth(LE_1M)	1	/	/
Bluetooth(LE_2M)	2	/	/
IEEE 802.11b	1	1	/
IEEE 802.11g	6	6	/
IEEE 802.11n 2.4GHz 20MHz	MCS 0	MCS 0	MCS 8
IEEE 802.11n 2.4GHz 40MHz	MCS 0	MCS 0	MCS 8

Test Items	Test Antennas	Test Modes	Test Channels
Radiated Emissions	Antenna 1, Antenna 2	IEEE 802.11n 20 Bluetooth(LE_2M)	1/ 0
Radiated Emissions (Band Edge)	Antenna 1, Antenna 2	IEEE 802.11n 20 Bluetooth(LE_2M)	1,6,11/ 0,19,39
Maximum conducted output power	Antenna 1, Antenna 2	Bluetooth(LE_1M)/ Bluetooth(LE_2M)/ IEEE 802.11b/ IEEE 802.11g/ IEEE 802.11n 20/ IEEE 802.11n 40	0,19,39/ 0,19,39/ 1,6,11/ 1,6,11/ 1,6,11/ 3,6,9
Minimum 6 dB bandwidth	Antenna 1, Antenna 2	Bluetooth(LE_1M)/ Bluetooth(LE_2M)/ IEEE 802.11b/ IEEE 802.11g/ IEEE 802.11n 20/ IEEE 802.11n 40	0,19,39/ 0,19,39/ 1,6,11/ 1,6,11/ 1,6,11/ 3,6,9
Occupied Channel Bandwidth	Antenna 1, Antenna 2	Bluetooth(LE_1M)/ Bluetooth(LE_2M)/ IEEE 802.11b/ IEEE 802.11g/ IEEE 802.11n 20/ IEEE 802.11n 40	0,19,39/ 0,19,39/ 1,6,11/ 1,6,11/ 1,6,11/ 3,6,9
Band Edge Measurement	Antenna 1, Antenna 2	Bluetooth(LE_1M)/ Bluetooth(LE_2M)/ IEEE 802.11b/ IEEE 802.11g/ IEEE 802.11n 20/ IEEE 802.11n 40	0,39/ 0,39/ 1,11/ 1,11/ 1,11/ 3,9
Maximum Power spectral density	Antenna 1, Antenna 2	Bluetooth(LE_1M)/ Bluetooth(LE_2M)/ IEEE 802.11b/ IEEE 802.11g/ IEEE 802.11n 20/ IEEE 802.11n 40	0,19,39/ 0,19,39/ 1,6,11/ 1,6,11/ 1,6,11/ 3,6,9
Spurious RF Conducted Emissions	Antenna 1, Antenna 2	Bluetooth(LE_1M)/ Bluetooth(LE_2M)/ IEEE 802.11b/ IEEE 802.11g/ IEEE 802.11n 20/ IEEE 802.11n 40	0,19,39/ 0,19,39/ 1,6,11/ 1,6,11/ 1,6,11/ 3,6,9

## 3.2 Duty cycle

TestMode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Limit	Verdict
11B	Ant1	2412	8.38	8.41	99.64	---	---
	Ant2	2412	8.38	8.41	99.64	---	---
	Ant1	2437	8.39	8.42	99.64	---	---
	Ant2	2437	8.38	8.41	99.64	---	---
	Ant1	2462	8.38	8.41	99.64	---	---
	Ant2	2462	8.37	8.40	99.64	---	---
11G	Ant1	2412	1.39	1.43	97.20	---	---
	Ant2	2412	1.39	1.43	97.20	---	---
	Ant1	2437	1.39	1.43	97.20	---	---
	Ant2	2437	1.39	1.43	97.20	---	---
	Ant1	2462	1.39	1.43	97.20	---	---
	Ant2	2462	1.39	1.43	97.20	---	---
11N20MIMO	Ant1	2412	1.29	1.33	96.99	---	---
	Ant2	2412	1.30	1.33	97.74	---	---
	Ant1	2437	1.30	1.34	97.01	---	---
	Ant2	2437	1.30	1.34	97.01	---	---
	Ant1	2462	1.30	1.34	97.01	---	---
	Ant2	2462	1.30	1.34	97.01	---	---
11N40MIMO	Ant1	2422	0.65	0.69	94.20	---	---
	Ant2	2422	0.65	0.68	95.59	---	---
	Ant1	2437	0.65	0.68	95.59	---	---
	Ant2	2437	0.65	0.68	95.59	---	---
	Ant1	2452	0.65	0.69	94.20	---	---
	Ant2	2452	0.65	0.69	94.20	---	---
BLE_1M	Ant1	2402	0.39	0.63	61.90	---	---
		2440	0.39	0.63	61.90	---	---
		2480	0.39	0.63	61.90	---	---
BLE_2M	Ant1	2402	1.08	1.88	57.45	---	---
		2440	1.08	1.88	57.45	---	---
		2480	1.08	1.88	57.45	---	---

## 4. Summary of measurement results

Summary of measurements of results	Clause in FCC rules	Verdict	Note
Conducted Emissions	15.207	PASS	/
Radiated Emissions	15.247(d),15.205,15.209	PASS	/
Maximum conducted output power	15.247(b)(3)	PASS	Appendix C of WIFI2.4G_diagram and Appendix C of BLE_diagram
Minimum 6 dB bandwidth	15.247(a)(2)	PASS	Appendix A of WIFI2.4G_diagram and Appendix A of BLE_diagram
Occupied Channel Bandwidth	15.247(a)(2)	PASS	Appendix B of WIFI2.4G_diagram and Appendix B of BLE_diagram
Band Edge Measurement	15.247(d)	PASS	Appendix E of WIFI2.4G_diagram and Appendix E of BLE_diagram
Maximum Power spectral density	15.247(e)	PASS	Appendix D of WIFI2.4G_diagram and Appendix D of BLE_diagram
Spurious RF Conducted Emissions	15.247(d)	PASS	Appendix F of WIFI2.4G_diagram and Appendix F of BLE_diagram
Antenna Requirement	15.203	PASS	See note 1

Note 1: According to 15.203, it is considered sufficient to comply with the provisions of this section.

## 5. Measurement procedure

### 5.1 Conducted Emission

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.2kPa

Method of Measurement:

The EUT was setup according to ANSI C63.10-2020/Cor1-2023 for compliance to FCC 47CFR 15.247 requirements. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs) Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.


Limits:

Frequency (MHz)	Conducted Limits(dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

## Test Setup:



## Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

### Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Level =Reading + Factor.

## Measurement Uncertainty:


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .  $U = 3.12$  dB.

## Test Results:


### WIFI:

During the test, the Conducted Emission from 150kHz to 30MHz was carried out in 2 power modes, in all modes of WIFI, on all channels and all antennas. Power supply 1#, 802.11n20, Channel 1, MIMO are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Radiates Emission		150k~30MHz						
Power Line		L						
Test channel		Worst-Case						
<b>Suspected List</b>								
Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Detector	Type	Pass/Fail
0.16575	10.20	40.97	51.17	65.17	14.00	QP	L	PASS
0.4785	10.22	17.42	27.64	56.37	28.73	QP	L	PASS
18.84075	11.50	21.41	32.91	60.00	27.09	QP	L	PASS
0.16575	10.20	26.71	36.91	55.17	18.26	AV	L	PASS
0.4785	10.22	9.14	19.36	46.37	27.01	AV	L	PASS
16.6245	11.68	16.59	28.27	50.00	21.73	AV	L	PASS



Radiates Emission	150k~30MHz							
Power Line	N							
Test channel	Worst-Case							
<b>Suspected List</b>								
Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Detector	Type	Pass/Fail
0.16575	10.19	40.75	50.94	65.17	14.23	QP	N	PASS
0.4785	10.21	17.11	27.32	56.37	29.05	QP	N	PASS
19.34025	11.38	21.62	33.00	60.00	27.00	QP	N	PASS
0.16575	10.19	26.53	36.72	55.17	18.45	AV	N	PASS
0.4785	10.21	8.75	18.96	46.37	27.41	AV	N	PASS
16.6245	11.64	17.20	28.84	50.00	21.16	AV	N	PASS




## Test Results:


**Bluetooth(Low Energy):**

During the test, the Conducted Emission from 150kHz to 30MHz was carried out in 2 power modes, in all modes of WIFI, on all channels and all antennas. Power supply 1#,BLE(2Mbps), channel 0, antenna 1 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Radiates Emission	150k~30MHz							
Power Line	L							
Test channel	Worst-Case							
<b>Suspected List</b>								
Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Detector	Type	Pass/Fail
0.15225	10.20	39.61	49.81	65.88	16.07	QP	L	PASS
0.4785	10.22	17.30	27.52	56.37	28.85	QP	L	PASS
18.84075	11.50	21.34	32.84	60.00	27.16	QP	L	PASS
0.177	10.20	25.03	35.23	54.63	19.40	AV	L	PASS
0.4785	10.22	9.25	19.47	46.37	26.90	AV	L	PASS
16.62225	11.68	16.94	28.62	50.00	21.38	AV	L	PASS



Radiates Emission		150k~30MHz						
Power Line		N						
Test channel		Worst-Case						
<b>Suspected List</b>								
Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Detector	Type	Pass/Fail
0.16575	10.19	40.80	50.99	65.17	14.18	QP	N	PASS
0.4785	10.21	17.15	27.36	56.37	29.01	QP	N	PASS
19.70925	11.35	22.10	33.45	60.00	26.55	QP	N	PASS
0.16575	10.19	26.42	36.61	55.17	18.56	AV	N	PASS
0.4785	10.21	8.71	18.92	46.37	27.45	AV	N	PASS
16.62225	11.64	16.85	28.49	50.00	21.51	AV	N	PASS



## 5.2 Radiated Emission

### Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.2kPa

### Method of Measurement:

The EUT was setup and tested according to ANSI C63.10-2020/Cor1-2023.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from Antenna to the EUT was 3 meters.

The Antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the Antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2020/Cor1-2023 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn Antenna will be bended down a little (as horn Antenna has the narrow beamwidth) in order to keeping the Antenna in the “cone of radiation” of EUT.

The 3dB beamwidth is 10~60 degrees for H-plane and 10~90 degrees for E-plane.

### Limits:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).


Frequency	Limit ( $\mu$ V/m )	Limit (dB $\mu$ V/m @3m)	Remark
0.009MHz-0.490MHz	2400/F(kHz)@300m	20lg(24000000/F(kHz))	Quasi-peak Level
0.490MHz~1.705MHz	24000/F(kHz)@30m	20lg(2400000/F(kHz))	Quasi-peak Level
1.705MHz~30.0MHz	30@30m	69.54	Quasi-peak Level
30MHz-88MHz	100@3m	40.0	Quasi-peak Level
88MHz-216MHz	150@3m	43.5	Quasi-peak Level
216MHz-960MHz	200@3m	46.0	Quasi-peak Level
960MHz-1GHz	500@3m	54.0	Quasi-peak Level
Above 1GHz	500@3m	54.0	Average Level
	5000@3m	74.0	Peak Level

Spurious Radiated Emissions are permitted in any of the frequency bands listed below:


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.
12.57675-12.57725	322-335.4	3600-4400	/
13.36-13.41	/	/	/

## Test Setup:


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



## Measurement Data:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Level =Reading - Factor

Factor = Preamplifier Factor – Antenna Factor–Cable Loss

## Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.19 dB
200MHz-1GHz	3.63 dB
Above 1GHz	3.68 dB

## Test Results:

### SPURIOUS EMISSIONS:


#### WIFI:

During the test, radiation emission from 9kHz to 1GHz was carried out in 2 power modes, in all modes of WIFI, on all channels and all antennas. Power supply 1#, 802.11n20, Channel 1, MIMO are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Radiates Emission	9k~1G									
Test channel	Worst-Case									
<b>Suspected List</b>										
Frequency [MHz]	Polarity	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detector	Height [cm]	Angle deg	Pass/Fail
157.5678	Horizontal	9.90	18.43	28.33	43.50	15.17	PK	100	151	PASS
390.003	Horizontal	17.65	9.43	27.08	46.00	18.92	PK	100	360	PASS
584.9925	Horizontal	21.76	9.23	30.99	46.00	15.01	PK	100	1	PASS

Note: 9kHz~30MHz have been test and test data more than 20dB margin.


Final Data List								
Frequency [MHz]	Polarity	Factor [dB]	QP Value [dB $\mu$ V/m]	QP Limit [dB $\mu$ V/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pass/Fail
158.0969	Horizontal	9.90	23.23	43.50	20.27	290	156	PASS
391.1939	Horizontal	17.65	21.56	46.00	24.44	290	258	PASS
584.9501	Horizontal	21.76	26.00	46.00	20.00	350	56	PASS



Radiates Emission	9k~1G									
Test channel	Worst-Case									
<b>Suspected List</b>										
Frequency [MHz]	Polarity	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/Fail
166.9777	Vertical	10.60	22.13	32.73	43.50	10.77	PK	100	3	PASS
244.6825	Vertical	14.09	17.05	31.14	46.00	14.86	PK	100	100	PASS
584.9925	Vertical	21.76	13.14	34.90	46.00	11.10	PK	100	93	PASS

Note: 9kHz~30MHz have been test and test data more than 20dB margin.

<b>Final Data List</b>								
Frequency [MHz]	Polarity	Factor [dB]	QP Value [dB $\mu$ V/m]	QP Limit [dB $\mu$ V/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pass/Fail
166.3929	Vertical	10.60	27.31	43.50	16.19	190	30	PASS
245.111	Vertical	14.09	25.54	46.00	20.46	240	97	PASS
585.7121	Vertical	21.76	26.74	46.00	19.26	340	89	PASS



During the test, the Radiates Emission from 1GHz to 40GHz was carried out in 2 power modes, in all modes of WIFI, on all channels and all antennas. Power supply 1#, 802.11n20, Highest, medium, lowest channels, MIMO are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Radiates Emission	Above 1G								
Test channel	Lowest								
polarization	Horizontal								

#### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
3868.586859	-0.40	38.98	38.58	74.00	35.42	PK	150	310	PASS
6955.89559	7.78	37.18	44.96	74.00	29.04	PK	150	100	PASS
13505.550555	13.50	31.51	45.01	74.00	28.99	PK	150	170	PASS
3868.586859	-0.40	28.72	28.32	54.00	25.68	AV	150	79	PASS
6955.89559	7.78	25.42	33.20	54.00	20.80	AV	150	180	PASS
13505.550555	13.50	21.00	34.50	54.00	19.50	AV	150	10	PASS

Radiates Emission	Above 1G								
Test channel	Lowest								
polarization	Vertical								

#### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
3642.064206	-0.78	39.60	38.82	74.00	35.18	PK	150	50	PASS
6040.80408	4.99	36.74	41.73	74.00	32.27	PK	150	300	PASS
10973.29733	11.66	34.24	45.90	74.00	28.10	PK	150	170	PASS
3642.064206	-0.78	27.85	27.07	54.00	26.93	AV	150	350	PASS
6040.80408	4.99	24.51	29.50	54.00	24.50	AV	150	40	PASS
10973.29733	11.66	23.21	34.87	54.00	19.13	AV	150	10	PASS

Note: The emission levels of other frequencies were greater than 20dB margin.

Radiates Emission		Above 1G							
Test channel		Medium							
polarization		Horizontal							
<b>Suspected List</b>									
Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/Fail
4756.675668	0.42	38.56	38.98	74.00	35.02	PK	150	170	PASS
7387.938794	8.24	36.76	45.00	74.00	29.00	PK	150	140	PASS
12717.971797	12.53	33.42	45.95	74.00	28.05	PK	150	100	PASS
4756.675668	0.42	26.26	26.68	54.00	27.32	AV	150	330	PASS
7387.938794	8.24	22.97	31.21	54.00	22.79	AV	150	210	PASS
12717.971797	12.53	21.34	33.87	54.00	20.13	AV	150	80	PASS
Radiates Emission		Above 1G							
Test channel		Medium							
polarization		Vertical							
<b>Suspected List</b>									
Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/Fail
3726.072607	-0.65	39.21	38.56	74.00	35.44	PK	150	100	PASS
7669.966997	8.37	37.62	45.99	74.00	28.01	PK	150	220	PASS
14491.149115	17.36	29.65	47.01	74.00	26.99	PK	150	300	PASS
3726.072607	-0.65	27.61	26.96	54.00	27.04	AV	150	50	PASS
7669.966997	8.37	25.57	33.94	54.00	20.06	AV	150	79	PASS
14491.149115	17.36	17.65	35.01	54.00	18.99	AV	150	56	PASS

Note: The emission levels of other frequencies were greater than 20dB margin.

Radiates Emission	Above 1G							
Test channel	Highest							
polarization	Horizontal							

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
4896.189619	1.01	37.83	38.84	74.00	35.16	PK	150	330	PASS
7650.465047	8.37	36.23	44.60	74.00	29.40	PK	150	240	PASS
16187.818782	16.80	31.40	48.20	74.00	25.80	PK	150	120	PASS
4896.189619	1.01	27.05	28.06	54.00	25.94	AV	150	120	PASS
7650.465047	8.37	25.47	33.84	54.00	20.16	AV	150	168	PASS
16187.818782	16.80	19.12	35.92	54.00	18.08	AV	150	90	PASS

Radiates Emission	Above 1G							
Test channel	Highest							
polarization	Vertical							

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
3963.09631	-0.21	39.04	38.83	74.00	35.17	PK	150	130	PASS
7629.462946	8.36	36.65	45.01	74.00	28.99	PK	150	170	PASS
16727.872787	18.95	29.31	48.26	74.00	25.74	PK	150	320	PASS
3963.09631	-0.21	27.70	27.49	54.00	26.51	AV	150	10	PASS
7629.462946	8.36	24.46	32.82	54.00	21.18	AV	150	20	PASS
16727.872787	18.95	16.71	35.66	54.00	18.34	AV	150	50	PASS

Note: The emission levels of other frequencies were greater than 20dB margin.


**Bluetooth(Low Energy):**

During the test, the Radiates Emission from 9kHz to 40GHz was carried out in 2 power modes, in all modes of WIFI, on all channels and all antennas. Power supply 1#, BLE(2Mbps), channel 0, antenna 1 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Radiates Emission		9k~1G									
Test channel		Worst-Case									
<b>Suspected List</b>											
Frequency [MHz]	Polarity	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/Fail	
152.6203	Horizontal	9.65	21.05	30.70	43.50	12.80	PK	100	148	PASS	
390.003	Horizontal	17.65	9.62	27.27	46.00	18.73	PK	100	202	PASS	
584.9925	Horizontal	21.76	6.31	28.07	46.00	17.93	PK	100	326	PASS	

Note: 9kHz~30MHz have been test and test data more than 20dB margin.


<b>Final Data List</b>								
Frequency [MHz]	Polarity	Factor [dB]	QP Value [dB $\mu$ V/m]	QP Limit [dB $\mu$ V/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pass/Fail
152.6446	Horizontal	9.65	26.28	43.50	17.22	180	150	PASS
391.1262	Horizontal	17.65	21.88	46.00	24.12	300	204	PASS
587.6254	Horizontal	21.76	24.38	46.00	21.62	350	330	PASS



Radiates Emission	9k~1G									
Test channel	Worst-Case									
<b>Suspected List</b>										
Frequency [MHz]	Polarity	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/Fail
166.0076	Vertical	10.52	21.97	32.49	43.50	11.01	PK	100	360	PASS
390.003	Vertical	17.65	12.78	30.43	46.00	15.57	PK	100	79	PASS
584.9925	Vertical	21.76	14.66	36.42	46.00	9.58	PK	100	286	PASS

Note: 9kHz~30MHz have been test and test data more than 20dB margin.

<b>Final Data List</b>								
Frequency [MHz]	Polarity	Factor [dB]	QP Value [dB $\mu$ V/m]	QP Limit [dB $\mu$ V/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pass/Fail
166.1686	Vertical	10.52	27.08	43.50	16.42	340	13	PASS
390.6916	Vertical	17.65	21.44	46.00	24.56	270	84	PASS
584.002	Vertical	21.76	27.26	46.00	18.74	200	291	PASS



During the test, the Radiates Emission from 1GHz to 40GHz was carried out in 2 power modes, in all modes of WIFI, on all channels and all antennas. Power supply 1#, BLE(2Mbps), Highest, medium, lowest channels, antenna 1 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Radiates Emission	Above 1G								
Test channel	Lowest								
polarization	Horizontal								
<b>Suspected List</b>									
Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
4933.693369	1.17	38.01	39.18	74.00	34.82	PK	150	170	PASS
7633.963396	8.36	36.03	44.39	74.00	29.61	PK	150	110	PASS
14524.152415	17.34	29.21	46.55	74.00	27.45	PK	150	230	PASS
4933.693369	1.17	26.73	27.90	54.00	26.10	AV	150	50	PASS
7633.963396	8.36	24.38	32.74	54.00	21.26	AV	150	20	PASS
14524.152415	17.34	20.21	37.55	54.00	16.45	AV	150	10	PASS
Radiates Emission	Above 1G								
Test channel	Lowest								
polarization	Vertical								
<b>Suspected List</b>									
Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
4092.109211	-0.23	38.94	38.71	74.00	35.29	PK	150	140	PASS
7006.90069	8.01	36.16	44.17	74.00	29.83	PK	150	70	PASS
13552.055206	13.60	33.05	46.65	74.00	27.35	PK	150	130	PASS
4092.109211	-0.23	26.89	26.66	54.00	27.34	AV	150	20	PASS
7006.90069	8.01	24.87	32.88	54.00	21.12	AV	150	30	PASS
13552.055206	13.60	20.41	34.01	54.00	19.99	AV	150	10	PASS

Note: The emission levels of other frequencies were greater than 20dB margin.

Radiates Emission	Above 1G							
Test channel	Medium							
polarization	Horizontal							

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
3879.087909	-0.38	39.05	38.67	74.00	35.33	PK	150	50	PASS
6981.39814	7.91	36.44	44.35	74.00	29.65	PK	150	130	PASS
13505.550555	13.50	32.48	45.98	74.00	28.02	PK	150	200	PASS
3840.084008	-0.46	29.01	28.55	54.00	25.45	AV	150	198	PASS
7165.916592	8.06	25.29	33.35	54.00	20.65	AV	150	236	PASS
13628.562856	13.78	22.88	36.66	54.00	17.34	AV	150	10	PASS

Radiates Emission	Above 1G							
Test channel	Medium							
polarization	Vertical							

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
4095.109511	-0.24	39.16	38.92	74.00	35.08	PK	150	50	PASS
7000.90009	8.01	35.51	43.52	74.00	30.48	PK	150	220	PASS
12822.982298	12.84	32.57	45.41	74.00	28.59	PK	150	90	PASS
4095.109511	-0.24	26.63	26.39	54.00	27.61	AV	150	230	PASS
7000.90009	8.01	24.16	32.17	54.00	21.83	AV	150	180	PASS
12822.982298	12.84	22.19	35.03	54.00	18.97	AV	150	20	PASS

Note: The emission levels of other frequencies were greater than 20dB margin.

Radiates Emission	Above 1G							
Test channel	Highest							
polarization	Horizontal							

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
4935.193519	1.18	38.29	39.47	74.00	34.53	PK	150	210	PASS
7635.463546	8.36	36.89	45.25	74.00	28.75	PK	150	10	PASS
16120.312031	16.62	31.61	48.23	74.00	25.77	PK	150	120	PASS
4935.193519	1.18	26.64	27.82	54.00	26.18	AV	150	350	PASS
7635.463546	8.36	25.26	33.62	54.00	20.38	AV	150	10	PASS
16120.312031	16.62	20.74	37.36	54.00	16.64	AV	150	10	PASS

Radiates Emission	Above 1G							
Test channel	Highest							
polarization	Vertical							

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
4125.112511	-0.27	39.53	39.26	74.00	34.74	PK	150	150	PASS
9279.627963	10.59	34.74	45.33	74.00	28.67	PK	150	330	PASS
16631.863186	18.32	29.75	48.07	74.00	25.93	PK	150	80	PASS
4125.112511	-0.27	26.89	26.62	54.00	27.38	AV	150	170	PASS
9279.627963	10.59	22.69	33.28	54.00	20.72	AV	150	169	PASS
16631.863186	18.32	18.68	37.00	54.00	17.00	AV	150	160	PASS

Note: The emission levels of other frequencies were greater than 20dB margin.

**Band Edge:**

During the test, the Band Edge was performed in WIFI all modes with all channels and all antennas. Power supply 1#, 802.11n20, MIMO are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Test mode	802.11n20								
Test channel	Lowest channel								
polarization	Horizontal								

**Suspected List**

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
2371.7371	-5.10	53.29	48.19	74.00	25.81	PK	150	58	PASS
2381.9381	-5.07	59.95	54.88	74.00	19.12	PK	150	189	PASS
2390.1390	-5.04	61.83	56.79	74.00	17.21	PK	150	65	PASS
2371.7371	-5.10	38.92	33.82	54.00	20.18	AV	150	124	PASS
2382.1382	-5.07	41.21	36.14	54.00	17.86	AV	150	158	PASS
2390.1390	-5.04	44.68	39.64	54.00	14.36	AV	150	214	PASS

Test mode	802.11n20								
Test channel	Lowest channel								
polarization	Vertical								

**Suspected List**

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
2373.7373	-5.09	45.16	40.07	74.00	33.93	PK	150	91	PASS
2382.1382	-5.07	45.59	40.52	74.00	33.48	PK	150	104	PASS
2390.1390	-5.04	50.36	45.32	74.00	28.68	PK	150	97	PASS
2373.7373	-5.09	31.55	26.46	54.00	27.54	AV	150	97	PASS
2382.1382	-5.07	31.74	26.67	54.00	27.33	AV	150	104	PASS
2390.1390	-5.04	36.09	31.05	54.00	22.95	AV	150	111	PASS

Test mode	802.11n20							
Test channel	Highest channel							
polarization	Horizontal							

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detector	Height [cm]	Angle deg	Pass/ Fail
2483.5483	-4.79	60.16	55.37	74.00	18.63	PK	150	28	PASS
2487.9487	-4.77	58.39	53.62	74.00	20.38	PK	150	8	PASS
2494.1494	-4.75	54.61	49.86	74.00	24.14	PK	150	21	PASS
2483.5483	-4.79	45.10	40.31	54.00	13.69	AV	150	359	PASS
2487.9487	-4.77	41.94	37.17	54.00	16.83	AV	150	359	PASS
2494.1494	-4.75	37.51	32.76	54.00	21.24	AV	150	136	PASS

Test mode 802.11n20

Test channel Highest channel

polarization Vertical

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detector	Height [cm]	Angle deg	Pass/ Fail
2483.5483	-4.79	56.56	51.77	74.00	22.23	PK	150	103	PASS
2489.9489	-4.76	52.74	47.98	74.00	26.02	PK	150	337	PASS
2496.5496	-4.75	48.59	43.84	74.00	30.16	PK	150	298	PASS
2483.5483	-4.79	42.92	38.13	54.00	15.87	AV	150	169	PASS
2489.9489	-4.76	36.60	31.84	54.00	22.16	AV	150	360	PASS
2496.5496	-4.75	34.45	29.70	54.00	24.30	AV	150	351	PASS

During the test, the Band Edge was performed in BLE all modes with all channels and all antennas. Power supply 1#,BLE(2Mbps), Antenna 1 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Test mode	BLE(2Mbps)								
Test channel	Lowest channel								
polarization	Horizontal								

#### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
2360.9360	-5.12	43.18	38.06	74.00	35.94	PK	150	253	PASS
2373.9373	-5.09	45.92	40.83	74.00	33.17	PK	150	253	PASS
2390.1390	-5.04	39.57	34.53	74.00	39.47	PK	150	31	PASS
2360.9360	-5.12	28.80	23.68	54.00	30.32	AV	150	44	PASS
2373.9373	-5.09	28.50	23.41	54.00	30.59	AV	150	259	PASS
2390.1390	-5.04	28.41	23.37	54.00	30.63	AV	150	31	PASS

Test mode	BLE(2Mbps)								
Test channel	Lowest channel								
polarization	Vertical								

#### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
2320.9320	-5.26	42.64	37.38	74.00	36.62	PK	150	328	PASS
2359.1359	-5.14	41.34	36.20	74.00	37.80	PK	150	26	PASS
2390.1390	-5.04	39.14	34.10	74.00	39.90	PK	150	32	PASS
2320.9320	-5.26	29.32	24.06	54.00	29.94	AV	150	158	PASS
2359.1359	-5.14	28.76	23.62	54.00	30.38	AV	150	243	PASS
2390.1390	-5.04	27.95	22.91	54.00	31.09	AV	150	360	PASS

Test mode	BLE(2Mbps)								
Test channel	Highest channel								
polarization	Horizontal								

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
2483.5483	-4.79	52.07	47.28	74.00	26.72	PK	150	170	PASS
2487.1487	-4.77	50.90	46.13	74.00	27.87	PK	150	150	PASS
2490.1490	-4.76	49.92	45.16	74.00	28.84	PK	150	230	PASS
2483.5483	-4.79	38.29	33.50	54.00	20.50	AV	150	180	PASS
2487.1487	-4.77	29.87	25.10	54.00	28.90	AV	150	120	PASS
2490.1490	-4.76	28.86	24.10	54.00	29.90	AV	150	49	PASS

Test mode	BLE(2Mbps)								
Test channel	Highest channel								
polarization	Vertical								

### Suspected List

Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detect or	Height [cm]	Angle deg	Pass/ Fail
2483.54835	-4.79	44.85	40.06	74.00	33.94	PK	150	142	PASS
2490.94909	-4.76	44.20	39.44	74.00	34.56	PK	150	249	PASS
2493.74937	-4.76	44.37	39.61	74.00	34.39	PK	150	155	PASS
2483.54835	-4.79	32.85	28.06	54.00	25.94	AV	150	225	PASS
2490.94909	-4.76	28.48	23.72	54.00	30.28	AV	150	354	PASS
2493.74937	-4.76	28.58	23.82	54.00	30.18	AV	150	296	PASS

## 5.3 Maximum conducted output power

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.2kPa

Method of Measurement:

a. A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor and set the detector to PEAK. Record the power level.

Limits:

Average Output Power	≤ 1W (30dBm)
----------------------	--------------

Note: the conducted output power limit specified above is based on the use the antennas with directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated Levels above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Frequency(MHz)	Antenna Gain(dBi)		Directional gain	Limit(dBm)
	Antenna 1	Antenna 2		
2412-2462	-2.21	-3.02	0.4	30.00

WiFi Antenna:

ANT1:Internal antenna with gain-2.21dBi

ANT2:Internal antenna with gain-3.02dBi

BLE Antenna:

Internal antenna with gain-1.27dBi


The maximum peak gain of the transmit antenna less than 6dBi

Directional gain is to be computed as follows:

transmit signals are correlated, then

Directional gain =  $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$  dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

## Test Setup:



## Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.44$  dB.

## Test Results:

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	17.37	≤30.00	PASS
	Ant2	2412	15.41	≤30.00	PASS
	Ant1	2437	16.66	≤30.00	PASS
	Ant2	2437	15.76	≤30.00	PASS
	Ant1	2462	16.18	≤30.00	PASS
	Ant2	2462	15.68	≤30.00	PASS
11G	Ant1	2412	21.23	≤30.00	PASS
	Ant2	2412	20.22	≤30.00	PASS
	Ant1	2437	20.28	≤30.00	PASS
	Ant2	2437	19.35	≤30.00	PASS
	Ant1	2462	20.50	≤30.00	PASS
	Ant2	2462	19.46	≤30.00	PASS
11N20SISO	Ant1	2412	19.15	≤30.00	PASS
	Ant2	2412	18.08	≤30.00	PASS
	total	2412	21.66	≤30.00	PASS
	Ant1	2437	18.93	≤30.00	PASS
	Ant2	2437	18.70	≤30.00	PASS
	total	2437	21.83	≤30.00	PASS
	Ant1	2462	18.91	≤30.00	PASS
	Ant2	2462	18.97	≤30.00	PASS
	total	2462	21.95	≤30.00	PASS
11N40SISO	Ant1	2422	19.61	≤30.00	PASS
	Ant2	2422	19.53	≤30.00	PASS
	total	2422	22.58	≤30.00	PASS
	Ant1	2437	18.95	≤30.00	PASS
	Ant2	2437	19.46	≤30.00	PASS
	total	2437	22.22	≤30.00	PASS
	Ant1	2452	19.58	≤30.00	PASS
	Ant2	2452	18.47	≤30.00	PASS
	total	2452	22.07	≤30.00	PASS
BLE_1M	Ant1	2402	2.47	≤30.00	PASS
	Ant1	2440	2.97	≤30.00	PASS
	Ant1	2480	2.99	≤30.00	PASS
BLE_2M	Ant1	2402	2.7	≤30.00	PASS
	Ant1	2440	3.19	≤30.00	PASS
	Ant1	2480	3.05	≤30.00	PASS

Note: WIFI has MIMO function, Directional gain needs to be considered.

## 5.4 Minimum 6 dB Bandwidth

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.2kPa

Method of Measurement:

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable. Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz; VBW is set to greater than 3 times RBW on spectrum analyzer.


Detector=Peak, Trace mode=Max hold.

Limits:

Rule Part 15.247 (a) (2) specifies that "Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz."

Minimum 6dB Bandwidth	$\geq 500$ kHz
-----------------------	----------------

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 936$  Hz.

## Test Results:

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.36	2407.36	2416.72	$\geq 0.5$	PASS
	Ant2	2412	9.32	2407.32	2416.64	$\geq 0.5$	PASS
	Ant1	2437	9.36	2432.32	2441.68	$\geq 0.5$	PASS
	Ant2	2437	9.24	2432.40	2441.64	$\geq 0.5$	PASS
	Ant1	2462	9.20	2457.40	2466.60	$\geq 0.5$	PASS
	Ant2	2462	9.40	2457.32	2466.72	$\geq 0.5$	PASS
11G	Ant1	2412	16.00	2404.12	2420.12	$\geq 0.5$	PASS
	Ant2	2412	16.32	2403.84	2420.16	$\geq 0.5$	PASS
	Ant1	2437	16.16	2429.00	2445.16	$\geq 0.5$	PASS
	Ant2	2437	16.16	2428.92	2445.08	$\geq 0.5$	PASS
	Ant1	2462	16.16	2453.92	2470.08	$\geq 0.5$	PASS
	Ant2	2462	16.20	2453.92	2470.12	$\geq 0.5$	PASS
11N20MIMO	Ant1	2412	17.16	2403.44	2420.60	$\geq 0.5$	PASS
	Ant2	2412	17.24	2403.44	2420.68	$\geq 0.5$	PASS
	Ant1	2437	17.40	2428.40	2445.80	$\geq 0.5$	PASS
	Ant2	2437	17.36	2428.40	2445.76	$\geq 0.5$	PASS
	Ant1	2462	17.52	2453.32	2470.84	$\geq 0.5$	PASS
	Ant2	2462	16.16	2453.76	2469.92	$\geq 0.5$	PASS
11N40MIMO	Ant1	2422	34.56	2404.32	2438.88	$\geq 0.5$	PASS
	Ant2	2422	35.92	2403.92	2439.84	$\geq 0.5$	PASS
	Ant1	2437	35.84	2419.24	2455.08	$\geq 0.5$	PASS
	Ant2	2437	34.16	2419.56	2453.72	$\geq 0.5$	PASS
	Ant1	2452	35.20	2434.32	2469.52	$\geq 0.5$	PASS
	Ant2	2452	35.76	2434.40	2470.16	$\geq 0.5$	PASS
BLE_1M	Ant1	2402	0.66	2401.67	2402.33	$\geq 0.5$	PASS
		2440	0.72	2439.64	2440.36	$\geq 0.5$	PASS
		2480	0.73	2479.63	2480.36	$\geq 0.5$	PASS
BLE_2M	Ant1	2402	1.26	2401.36	2402.62	$\geq 0.5$	PASS
		2440	1.20	2439.39	2440.59	$\geq 0.5$	PASS
		2480	1.31	2479.33	2480.64	$\geq 0.5$	PASS

## 5.5 Occupied Channel Bandwidth

Ambient condition:


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.2kPa

Method of Measurement:

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable. RBW is set to 1% to 5% of the OBW; video bandwidth (VBW) shall be at least three times RBW on spectrum analyzer.

Detector=Peak, Trace mode=Max hold.

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 936$  Hz.

## Test Results:

TestMode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant2	2412	13.227	---	---
	Ant1	2437	13.546	---	---
	Ant2	2437	13.307	---	---
	Ant1	2462	13.107	---	---
	Ant2	2462	13.147	---	---
	Ant1	2412	13.626	---	---
11G	Ant2	2412	16.783	---	---
	Ant1	2437	16.823	---	---
	Ant2	2437	16.783	---	---
	Ant1	2462	16.903	---	---
	Ant2	2462	16.663	---	---
	Ant1	2412	16.863	---	---
11N20MIMO	Ant2	2412	17.742	---	---
	Ant1	2437	17.742	---	---
	Ant2	2437	17.822	---	---
	Ant1	2462	17.822	---	---
	Ant2	2462	17.662	---	---
	Ant1	2422	17.742	---	---
11N40MIMO	Ant2	2422	35.964	---	---
	Ant1	2437	36.444	---	---
	Ant2	2437	36.284	---	---
	Ant1	2452	36.044	---	---
	Ant2	2452	36.044	---	---
	Ant2	2412	36.124	---	---
BLE_1M	Ant1	2402	1.043	---	---
		2440	1.015	---	---
		2480	1.031	---	---
BLE_2M	Ant1	2402	2.034	---	---
		2440	2.010	---	---
		2480	2.042	---	---

## 5.6 Band Edge Measurement

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.2kPa


Method of Measurement:

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable the band edge of the lowest and highest channels were measured. The peak detector is used and RBW is set to 100 kHz and VBW is set to 300 kHz on spectrum analyzer.

Limits:

Rule Part 15.247(d) specifies that “In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U = 936$  Hz,  $2 \text{ GHz} - 3 \text{ GHz} = 1.407 \text{ dB}$ .

## Test Results:

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	5.26	-39.22	≤-14.74	PASS
	Ant2	Low	2412	3.71	-41.23	≤-16.29	PASS
	Ant1	High	2462	5.45	-49.15	≤-14.55	PASS
	Ant2	High	2462	3.21	-49.36	≤-16.79	PASS
11G	Ant1	Low	2412	2.95	-38.46	≤-17.05	PASS
	Ant2	Low	2412	1.72	-37.59	≤-18.28	PASS
	Ant1	High	2462	2.48	-46.67	≤-17.52	PASS
	Ant2	High	2462	1.37	-47.54	≤-18.63	PASS
11N20MIMO	Ant1	Low	2412	1.21	-41.72	≤-18.79	PASS
	Ant2	Low	2412	-0.42	-37.25	≤-20.42	PASS
	Ant1	High	2462	0.16	-46.63	≤-19.84	PASS
	Ant2	High	2462	-0.20	-48.91	≤-20.2	PASS
11N40MIMO	Ant1	Low	2422	-1.49	-40.96	≤-21.49	PASS
	Ant2	Low	2422	-2.44	-39.21	≤-22.44	PASS
	Ant1	High	2452	-1.63	-43.07	≤-21.63	PASS
	Ant2	High	2452	-2.67	-43.26	≤-22.67	PASS
BLE_1M	Ant1	Low	2402	1.26	-49.66	≤-18.74	PASS
		High	2480	0.38	-48.63	≤-19.62	PASS
BLE_2M	Ant1	Low	2402	1.07	-31.75	≤-18.93	PASS
		High	2480	-0.60	-48.32	≤-20.6	PASS

## 5.7 Maximum Power Spectral Density

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.2kPa

Method of Measurement:

During the process of the testing, The EUT was connected to Spectrum Analyzer with a known loss. The EUT is max power transmission with proper modulation. The Peak detector is used. The conducted Power is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically.

Limits:

Rule Part 15.247(e) specifies that" For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


Maximum Power Spectral Density	$\leq 8 \text{ dBm} / 3\text{kHz}$
--------------------------------	------------------------------------

Frequency(MHz)	Antenna Gain(dBi)		Directional gain	Limit(dBm)
	Antenna 1	Antenna 2		
2412-2462	-2.21	-3.02	0.4	8.00

Directional gain is to be computed as follows:  
 transmit signals are correlated, then  

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{\text{ANT}}] \text{ dBi}$$
 [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.75 \text{ dB}$ .

## Test Results:

TestMode	Antenna	Channel	Result [dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-8.23	≤8.00	PASS
	Ant2	2412	-8.33	≤8.00	PASS
	Ant1	2437	-7.87	≤8.00	PASS
	Ant2	2437	-7.98	≤8.00	PASS
	Ant1	2462	-7.74	≤8.00	PASS
	Ant2	2462	-8.76	≤8.00	PASS
11G	Ant1	2412	-9.98	≤8.00	PASS
	Ant2	2412	-11.07	≤8.00	PASS
	Ant1	2437	-10.86	≤8.00	PASS
	Ant2	2437	-10.46	≤8.00	PASS
	Ant1	2462	-10.79	≤8.00	PASS
	Ant2	2462	-10.67	≤8.00	PASS
11N20MIMO	Ant1	2412	-12.24	≤8.00	PASS
	Ant2	2412	-11.67	≤8.00	PASS
	total	2412	-8.94	≤8.00	PASS
	Ant1	2437	-11.38	≤8.00	PASS
	Ant2	2437	-11.25	≤8.00	PASS
	total	2437	-8.30	≤8.00	PASS
	Ant1	2462	-10.83	≤8.00	PASS
	Ant2	2462	-12.92	≤8.00	PASS
	total	2462	-8.74	≤8.00	PASS
11N40MIMO	Ant1	2422	-13.39	≤8.00	PASS
	Ant2	2422	-15.42	≤8.00	PASS
	total	2422	-11.28	≤8.00	PASS
	Ant1	2437	-15.53	≤8.00	PASS
	Ant2	2437	-14.40	≤8.00	PASS
	total	2437	-11.92	≤8.00	PASS
	Ant1	2452	-14.88	≤8.00	PASS
	Ant2	2452	-16.43	≤8.00	PASS
	total	2452	-12.58	≤8.00	PASS
BLE_1M	Ant1	2402	-15.36	≤8.00	PASS
		2440	-14.95	≤8.00	PASS
		2480	-14.56	≤8.00	PASS
BLE_2M	Ant1	2402	-11.10	≤8.00	PASS
		2440	-10.52	≤8.00	PASS
		2480	-11.17	≤8.00	PASS

## 5.8 Spurious RF Conducted Emissions

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.2kPa

Method of Measurement:

The EUT was connected to the spectrum analyzer with a known loss. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. Set RBW to 100kHz and VBW to 300 kHz, Sweep is set to AUTO .The test is in transmitting mode.

Limits:

Rule Part 15.247(d) pacifies that “In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-26GHz	1.407 dB

## Test Results:

TestMode	Antenna	Channel	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	Reference	3.49	3.49	---	PASS
			30~1000	3.49	-60.36	≤-16.51	PASS
			1000~26500	3.49	-48.69	≤-16.51	PASS
	Ant2	2412	Reference	0.49	0.49	---	PASS
			30~1000	0.49	-60.51	≤-19.51	PASS
			1000~26500	0.49	-49.8	≤-19.51	PASS
	Ant1	2437	Reference	2.03	2.03	---	PASS
			30~1000	2.03	-60.72	≤-17.97	PASS
			1000~26500	2.03	-48.84	≤-17.97	PASS
	Ant2	2437	Reference	1.73	1.73	---	PASS
			30~1000	1.73	-60.19	≤-18.27	PASS
			1000~26500	1.73	-49.04	≤-18.27	PASS
11G	Ant1	2462	Reference	2.55	2.55	---	PASS
			30~1000	2.55	-60.34	≤-17.45	PASS
			1000~26500	2.55	-48.59	≤-17.45	PASS
	Ant2	2462	Reference	1.31	1.31	---	PASS
			30~1000	1.31	-60.71	≤-18.69	PASS
			1000~26500	1.31	-49.3	≤-18.69	PASS
	Ant1	2412	Reference	-0.54	-0.54	---	PASS
			30~1000	-0.54	-60.33	≤-20.54	PASS
			1000~26500	-0.54	-48.57	≤-20.54	PASS
	Ant2	2412	Reference	-1.46	-1.46	---	PASS
			30~1000	-1.46	-60.37	≤-21.46	PASS
			1000~26500	-1.46	-48.91	≤-21.46	PASS
11N20MIMO	Ant1	2437	Reference	-1.58	-1.58	---	PASS
			30~1000	-1.58	-60.59	≤-21.58	PASS
			1000~26500	-1.58	-48.91	≤-21.58	PASS
	Ant2	2437	Reference	1.41	1.41	---	PASS
			30~1000	1.41	-60.4	≤-18.59	PASS
			1000~26500	1.41	-49.18	≤-18.59	PASS
	Ant1	2462	Reference	0.43	0.43	---	PASS
			30~1000	0.43	-60.6	≤-19.57	PASS
			1000~26500	0.43	-47.89	≤-19.57	PASS
	Ant2	2462	Reference	-2.28	-2.28	---	PASS
			30~1000	-2.28	-60.34	≤-22.28	PASS
			1000~26500	-2.28	-48.28	≤-22.28	PASS
11N40MIMO	Ant1	2412	Reference	-2.13	-2.13	---	PASS
			30~1000	-2.13	-60.11	≤-22.13	PASS
			1000~26500	-2.13	-49.09	≤-22.13	PASS
	Ant2	2412	Reference	-2.13	-2.13	---	PASS
			30~1000	-2.13	-59.57	≤-22.13	PASS
			1000~26500	-2.13	-47.88	≤-22.13	PASS
	Ant1	2437	Reference	-2.87	-2.87	---	PASS
			30~1000	-2.87	-60.27	≤-22.87	PASS
			1000~26500	-2.87	-48.59	≤-22.87	PASS
	Ant2	2437	Reference	-2.73	-2.73	---	PASS
			30~1000	-2.73	-60.46	≤-22.73	PASS
			1000~26500	-2.73	-48.93	≤-22.73	PASS
	Ant1	2462	Reference	-2.16	-2.16	---	PASS
			30~1000	-2.16	-59.82	≤-22.16	PASS
			1000~26500	-2.16	-49.37	≤-22.16	PASS
	Ant2	2462	Reference	-2.99	-2.99	---	PASS
			30~1000	-2.99	-60.71	≤-22.99	PASS
			1000~26500	-2.99	-48.85	≤-22.99	PASS
11N40MIMO	Ant1	2422	Reference	-3.31	-3.31	---	PASS
			30~1000	-3.31	-60.03	≤-23.31	PASS
	Ant2	2422	Reference	-5.68	-5.68	---	PASS
			30~1000	-5.68	-60.66	≤-25.68	PASS

TestMode	Antenna	Channel	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	2437	1000~26500	-5.68	-48.67	≤-25.68	PASS
			Reference	-5.32	-5.32	---	PASS
			30~1000	-5.32	-60.04	≤-25.32	PASS
			1000~26500	-5.32	-48.06	≤-25.32	PASS
	Ant2	2437	Reference	-5.07	-5.07	---	PASS
			30~1000	-5.07	-60.36	≤-25.07	PASS
			1000~26500	-5.07	-48.54	≤-25.07	PASS
	Ant1	2452	Reference	-3.42	-3.42	---	PASS
			30~1000	-3.42	-60.38	≤-23.42	PASS
			1000~26500	-3.42	-48.89	≤-23.42	PASS
	Ant2	2452	Reference	-4.70	-4.70	---	PASS
			30~1000	-4.70	-60.69	≤-24.7	PASS
			1000~26500	-4.70	-49.27	≤-24.7	PASS
BLE_2M	Ant1	2402	Reference	-1.05	-1.05	---	PASS
			30~1000	-1.05	-59.71	≤-21.05	PASS
			1000~26500	-1.05	-48.66	≤-21.05	PASS
		2440	Reference	0.40	0.40	---	PASS
			30~1000	0.40	-60.04	≤-19.6	PASS
			1000~26500	0.40	-48.62	≤-19.6	PASS
		2480	Reference	-1.45	-1.45	---	PASS
			30~1000	-1.45	-60	≤-21.45	PASS
			1000~26500	-1.45	-48.88	≤-21.45	PASS
	Ant1	2402	Reference	-2.04	-2.04	---	PASS
			30~1000	-2.04	-60.27	≤-22.04	PASS
			1000~26500	-2.04	-48.53	≤-22.04	PASS
	2440	Reference	-1.36	-1.36	---	PASS	
		30~1000	-1.36	-60.45	≤-21.36	PASS	
		1000~26500	-1.36	-48.34	≤-21.36	PASS	
	2480	Reference	-1.51	-1.51	---	PASS	
		30~1000	-1.51	-60.1	≤-21.51	PASS	
		1000~26500	-1.51	-48.92	≤-21.51	PASS	

## 6. Appendix X

Test Equipment	Type/Mode	SERIAL NO.	Equipment No.	Manufacturer	Cal. Due
Communication Shielded Room 2	4m*3m*3m	CRTDSWKS44301	/	CRT	2027/04/22
Spectrum Analyzer	FSV40	101580	DZ-000238-3	R&S	2026/03/27
Power Meter	JS0806-2	19H9080187	DZ-000241	Tonscend	2026/03/27
Programmable DC Power Supply	E3644A	MY58036222	DZ-000178	KEYSIG HT	2026/04/10
5m Semi-Anechoic Chamber	SAC-5	SAC-5-2.0	EM-000557	COMTES T	2027/02/01
Spectrum Analyzer	N9010B	MY57470323	DZ-000174	KEYSIG HT	2026/01/01
EMI Test Receiver	N9038A-508	MY532290079	EM-000397	Agilent	2025/12/26
EMI Test Receiver	ESR7	102235	EM-000574	R&S	2026/01/05
loop antenna	HLA 6121	540046	EM-000546	TESEQ	2025/06/04
Broadband Antenna	VULB 9163	9163-530	EM-000342	SCHWAR ZBECK	2025/06/09
Waveguide Horn Antenna	HF906	360306/008	EM-000093	R&S	2025/12/26
Waveguide Horn Antenna	BBHA9170	00949	DZ-000209-2	SCHWAR ZBECK	2025/08/03
Preamplifier	BBV 9721	9721-050	DZ-000209-1	SCHWAR ZBECK	2025/06/02
Bandstop Filters	SW-BSF-2400-100-7-A1	/	EM-000495	/	2025/08/29
5.8GHz band resistance	ZBSF6-C5725-5850-1627	1232740	DZ-000399-2	Tonscend	2025/05/30
Preamplifier	BBV 9721	9721-050	DZ-000209-1	SCHWAR ZBECK	2025/06/03
Temperature and humidity meter	MHO-C201	/	DZ-000249-2	Seconds test	2025/07/28
Temperature and humidity meter	MHO-C201	/	DZ-000249-5	Seconds test	2025/07/28

Dynacomm	Software Release	Software Developer
TS1120-3 Test System(Conduction test)	3.3.38	Tonscend
TS+ (5m,Radiation test)	JS32-RE 5.0.0	Tonscend

————— No Body Text Below —————

## Important

1. The test report is invalid without the official stamp of CVC;
2. Any part photocopies of the test report are forbidden without the written permission from CVC;
3. The test report is invalid without the signatures of Author and Reviewer;
4. The test report is invalid if altered;
5. Objections to the test report must be submitted to CVC within 15 days;
6. Generally, commission test is responsible for the tested samples only;
7. As for the test result, “—” or “N/A” means “not applicable”, “/” means “not testing”, “P” means “pass” and “F” means “fail”.

Address: No.3,Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou, China (Test location)

Post Code: 510663 Tel: 020-32293888

FAX: 020 32293889 E-mail: [office@cvc.org.cn](mailto:office@cvc.org.cn)