



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020



EMC TEST REPORT

Applicant:	Hestan Smart Cooking Inc
Address:	1 Meyer Plaza Vallejo, CA 94590 USA

Manufacturer or Supplier:	Hestan Smart Cooking Inc
Address:	1 Meyer Plaza Vallejo, CA 94590 USA
Product:	Hestan Cue Smart Probe
Brand Name:	Hestan Cue
Model Name:	41701-C
FCC ID:	2AYY4-41701
Date of tests:	Mar. 01, 2021 ~ Mar. 08, 2021

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

FCC Part 15, Subpart B, Class A
 FCC Part 15, Subpart B, Class B
 ANSI C63.4:2014

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department

Date: Mar.17, 2021

Date: Mar. 17, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION	4
1.1 GENERAL DESCRIPTION OF EUT	4
1.2 SUMMARY OF TEST RESULTS	5
1.3 MEASUREMENT UNCERTAINTY	6
1.4 DESCRIPTION OF TEST MODES	7
1.5 DESCRIPTION OF SUPPORT UNITS.....	7
2 EMISSION TEST.....	8
2.1 RADIATED EMISSION MEASUREMENT.....	8
2.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	8
2.1.2 TEST INSTRUMENTS.....	10
2.1.3 TEST PROCEDURE.....	11
2.1.4 DEVIATION FROM TEST STANDARD	12
2.1.5 TEST SETUP	13
2.1.6 EUT OPERATING CONDITIONS	14
2.1.7 TEST RESULTS	14
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	18



**BUREAU
VERITAS**

Test Report No.: FVHKO-W7L-P21030020

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FVHKO-W7L-P21030020	Original release	Mar. 17, 2021



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Hestan Cue Smart Probe	
BRAND NAME	Hestan Cue	
MODEL NAME	41701-C	
NOMINAL VOLTAGE	3V	
MODULATION TYPE	BT_LE	GFSK
OPERATING FREQUENCY	Bluetooth/BT_LE	2402MHz ~ 2480MHz
HW VERSION	0	
SW VERSION	0	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Related submittal/Grant:Part 15.247 DTS submission with FCC ID: 2AYY4-41701



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Test lab*
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	N/A	N/A
	Radiated Emission Test (30MHz ~ 1GHz)	Compliance	A
	Radiated Emission Test (Above 1GHz)	Compliance	A

NOTE: N/A - EUT power by battery

*Test Lab Information Reference

Lab A:

BV 7Layers Communications Technology (Shenzhen) Co. Ltd



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	±2.70dB
Radiated emissions	30MHz~1GHz	±4.98dB
	1GHz ~6GHz	±4.70dB
	6GHz ~18GHz	±4.60dB



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
Radiated emission test	
1	BT Link+ Mobile phone

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR ALL TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Mobile phone	HUA WEI	HWI-AL00	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

2 EMISSION TEST

2.1 RADIATED EMISSION MEASUREMENT

2.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dB μ V/m)		
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B
30-88	39	29.5
88-216	43.5	33.1
216-230		
230-960	46.4	35.6
960-1000	49.5	43.5

Radiated Emissions Limits at 3 meters (dB μ V/m)		
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B
1000-3000	Avg: 60	Avg: 54
3000+	Peak: 80	Peak: 74



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_uV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. QP detector shall be applied if not specified.



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

2.1.2 TEST INSTRUMENTS

Frequency range below 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 28,21	Feb. 27,22
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 28,21	Feb. 27,22
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 02 ,20	Jun. 01 ,21

NOTE: 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRRG/CHINA and NIM/CHINA.
2. The test was performed in Dongguan 10m Semi-anechoic Chamber

Frequency range above 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Horn Antenna	ETS-LINDGREN	3117	00168728	Feb. 28,21	Feb. 27,22
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 28,21	Feb. 27,22
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 02,20	Jun. 01,21

NOTE: 1. The test was performed in 3m chamber.
2. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

2.1.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Emission level – Limit value.



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
5. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
6. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier)
7. Margin value = Emission level – Limit value.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.




BUREAU
VERITAS


Test Report No.: FVHKO-W7L-P21030020

2.1.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

depends on the EUT height and the antenna 3dB bandwidth both, refer to section 7.3 of CISPR 16-2-3.



BUREAU
VERITAS

Test Report No.: FVHKO-W7L-P21030020

2.1.6 EUT OPERATING CONDITIONS

Same as item 1.4.


2.1.7 TEST RESULTS

TEST VOLTAGE	Data Transmission Input DC 3V		FREQUENCY RANGE		30-1000 MHz	
ENVIRONMENTAL CONDITIONS	23deg. C, 53 %RH		DETECTOR FUNCTION & RESOLUTION BANDWIDTH		Quasi-Peak, 120 kHz	
TESTED BY	Ray					

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
31.94	24.26	40.95	40	-15.74	19.93	0.8	37.42	200	360	Peak
183.26	15.66	40.66	43.5	-27.84	9.92	1.71	36.63	200	360	Peak
270.56	14.92	35.96	46	-31.08	13.54	2.11	36.69	200	360	Peak
422.85	25.65	42.47	46	-20.35	17.35	2.7	36.87	200	360	Peak
562.53	21.41	35.9	46	-24.59	19.64	3.1	37.23	200	360	Peak
703.18	24.39	35.57	46	-21.61	22.82	3.54	37.54	200	360	Peak

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above equipment noise floor are reported.



BUREAU
VERITAS


Test Report No.: FVHKO-W7L-P21030020

TEST VOLTAGE	Data Transmission Input DC 3V	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 53 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Ray		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
31.94	22.02	38.71	40	-17.98	19.93	0.8	37.42	100	360	Peak
118.27	22.02	49.94	43.5	-21.48	7.73	1.44	37.09	100	360	Peak
189.08	17.56	42.47	43.5	-25.94	9.95	1.74	36.6	100	360	Peak
229.82	17.07	39.65	46	-28.93	12.09	1.94	36.61	100	360	Peak
422.85	23.3	40.12	46	-22.7	17.35	2.7	36.87	100	360	Peak
486.87	22.9	38.06	46	-23.1	18.88	2.94	36.98	100	360	Peak

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above equipment noise floor are reported.





BUREAU
VERITAS


Test Report No.: FVHKO-W7L-P21030020

TEST VOLTAGE	Data Transmission Input DC 3V	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Jace Hu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
3601	49.88	58.13	74	-24.12	33.18	4.95	46.38	200	360	Peak
3601	29.05	37.3	54	-24.95	33.18	4.95	46.38	200	360	Average
5845	45.58	49.77	74	-28.42	34.11	7.85	46.15	200	360	Peak
5845	30.88	35.07	54	-23.12	34.11	7.85	46.15	200	360	Average
9755	49.25	47	74	-24.75	36.7	10.76	45.21	200	360	Peak
9755	34.99	32.74	54	-19.01	36.7	10.76	45.21	200	360	Average

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 18GHz.
4. Only emissions significantly above equipment noise floor are reported.





BUREAU
VERITAS


Test Report No.: FVHKO-W7L-P21030020

TEST VOLTAGE	Data Transmission Input DC 3V	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Jace Hu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2326	45.86	55.37	74	-28.14	32.05	4.81	46.37	100	360	Peak
2326	25.76	35.27	54	-28.24	32.05	4.81	46.37	100	360	Average
3601	50.74	58.18	74	-23.26	33.99	4.95	46.38	100	360	Peak
3601	28.73	36.17	54	-25.27	33.99	4.95	46.38	100	360	Average
5913	48.46	49.92	74	-25.54	36.75	7.92	46.13	100	360	Peak
5913	32	33.46	54	-22	36.75	7.92	46.13	100	360	Average

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 18GHz.
4. Only emissions significantly above equipment noise floor are reported.





**BUREAU
VERITAS** Test Report No.: FVHKO-W7L-P21030020

3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---