

Test Report No.:
RZCE2021-0124-R

RF Test Report

EUT : module
MODEL : YGC-C302
BRAND NAME : N/A
CLIENT : HANGZHOU YAGUAN
TECHNOLOGY CO.,LTD
Classification Of Test : Commission Test

Vkan Certification & Testing Co., Ltd.



Test Report No.:RZCE2021-0124-R		Page 2 of 82	
Client		Name : HANGZHOU YAGUAN TECHNOLOGY CO.,LTD Address :33rd Floor, T4 US Center, European and American Financial City, Yuhang District, Hangzhou, Zhejiang, China	
Manufacturer		Name :Shenzhen Sibo Zhilian Technology Co., Ltd Address :903,building8,Chuangxin Valley, Dashi 2nd Road,Nanshan District, Shenzhen	
Equipment Under Test		Name :module Model/Type:YGC-C302 Trade mark :N/A SerialNO.:N/A Sampe NO.:1-1	
Date of Receipt.	2021.02.24	Date of Testing	2021.02.24~2021.03.11
Test Specification		Test Result	
FCC Part 15, Subpart C, Section 15.247		PASS	
Evaluation of Test Result		The equipment under test was found to comply with the requirements of the standards applied. Issue Date: 2021.03.11	
Tested by: RobertCheng Name Signature		Reviewed by: Andy Zhu Name Signature	Approved by: Sam Tung Name Signature
Other Aspects: NONE.			
Abbreviations:OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			
This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.			



TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	4
1 GENERAL INFORMATION.....	5
1.1 GENERAL PRODUCT INFORMATION.....	5
1.2 OTHER INFORMATION.....	6
1.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	7
1.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	9
1.5 DESCRIPTION OF SUPPORT UNITS.....	9
2 SUMMARY OF TEST RESULTS.....	10
2.1 LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	10
2.2 MEASUREMENT UNCERTAINTY.....	10
2.3 TEST LOCATION.....	10
3 TEST TYPES AND RESULTS.....	11
3.1 CONDUCTED EMISSION MEASUREMENT.....	11
3.1.1 Limit.....	11
3.1.2 Measurement procedure.....	11
3.1.3 Test setup.....	11
3.1.4 Test results.....	12
3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	14
3.2.1 Limit.....	14
3.2.2 Measurement procedure.....	14
3.2.3 Test setup.....	15
3.2.4 Test results.....	17
3.3 6dB BANDWIDTH MEASUREMENT.....	61
3.3.1 Limits.....	61
3.3.2 Measurement procedure.....	61
3.3.3 Test setup.....	61
3.3.4 Test result.....	62
3.4 CONDUCTED OUTPUT POWER.....	66
3.4.1 Limits.....	66
3.4.2 Measurement procedure.....	66
3.4.3 Test setup.....	66
3.4.4 Test result.....	67
3.5 POWER SPECTRAL DENSITY MEASUREMENT.....	68
3.5.1 Limits.....	68
3.5.2 Measurement procedure.....	68
3.5.3 Test setup.....	68
3.5.4 Test result.....	69
3.6 OUT OF BAND EMISSION MEASUREMENT.....	73
3.6.1 Limits.....	73
3.6.2 Measurement procedure.....	73
3.6.3 Test setup.....	73
3.6.4 Test result.....	74
4 PHOTOGRAPHS OF TEST SETUP.....	80
APPENDIX A.....	81



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RZCE2021-0124-R	Original release	2021.03.11



1 GENERAL INFORMATION

1.1 GENERAL PRODUCT INFORMATION

PRODUCT	module
BRAND	N/A
MODEL	YGC-C302
ADDITIONAL MODEL	N/A
FCC ID	2AYYQ-YGC-C302
POWER SUPPLY	DC 3.3V
MODULATIONTECHNOLOGY	DSSS, OFDM, DTS
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM GFSK for DTS
OPERATING FREQUENCY	2412MHz ~ 2462MHz for 11b/g/n(HT20) 2402MHz ~ 2480MHz for BT-LE(GFSK)
NUMBER OF CHANNEL	802.11b/g/n (HT20): 11 BT-LE GFSK (1 Mbps): 40
PeakOutPut POWER	WLAN: 22.79dBm (Maximum) BT-LE: 9.98dBm (Maximum)
ANTENNA TYPE	PCB Antenna, 2dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

Remark:

1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: RZCE2021-0124) for detailed product photo.
4. The EUT have SISO function, provides 1 completed transmitter and 1 receiver.

MODULATION MODE	TX FUNCTION
802.11b	1TX/1RX
802.11g	1TX/1RX
802.11n (HT20)	1TX/1RX



1.2 OTHER INFORMATION

Operating frequency of each channel

2.4G WIFI					
802.11b/g/n (HT20)					
CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

BT-LE(1 Mbps)							
CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note:

1. The channels which were indicated in bold type of the above channel list were selected as representative test channel. Therefore only the data of the test channels were recorded in this report.

1.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, xyz axis and antenna ports

EUT CONFIGURE MODE	APPLICABLE TEST ITEMS				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	√	2.4G WIFI Function
B	√	√	√	√	BT-LE Function

Where **RE<1G**: Radiated Emission below 1GHz**RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission**APCM**: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ The worst case was found when positioned on x axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	6	DSSS	DBPSK	6.0
B	BT-LE	0 to 39	19	DTS	GFSK	1.0

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ The worst case was found when positioned on x axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n(HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
B	BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1.0

**POWER LINE CONDUCTED EMISSION TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CONDITION
-	BT Link+ WIFI (2.4G) Link

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n(HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
B	BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	25deg. C, 55%RH	DC 3.3V	Robert Cheng
RE≥1G	25deg. C, 55%RH	DC 3.3V	Robert Cheng
PLC	N/A	N/A	N/A
APCM	25deg. C, 60%RH	DC 3.3V	Robert Cheng



1.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC PART 15, Subpart C. Section 15.247
KDB 558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support Equipment							
NO	Description	Brand	Model No.	Serial Number	Supplied by		
1	Power Supply	Rohde&Schwarz	HMC8041	101206	Lab		
Support Cable							
NO	Description	Quantity (Number)	Length (cm)	Detachable (Yes/ No)	Shielded (Yes/ No)	Cores (Number)	Supplied by
1	AC Mains	1	1	Y	N	0	Lab

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

PPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Meet the requirement of limit.

2.1 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Refer to Appendix A.

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

No.	ITEM	FREQUENCY	UNCERTAINTY
1	Conducted emissions	9kHz~30MHz	2.7dB
2	Radiated emissions	9KHz ~ 30MHz	5.6dB
		30MHz ~ 1GMHz	4.6dB
		1GHz ~ 18GHz	4.4dB
		18GHz ~ 40GHz	4.6dB

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

2.3 TEST LOCATION

The tests and measurements refer to this report were performed by EMC testing Lab. of Vkan Certification & Testing Co., Ltd.

Address: No.3,TiantaiyiRoad,KaitaiAvenue,ScienceCity,Guangzhou,China

Post Code: 510663

Tel: 020-32293888

FAX: 020-32293889

E-mail: office@cvc.org.cn

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 Limit


Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
NOTE: 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.2 Measurement procedure


- The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the Test photographs) Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source. The equipment under test shall be placed on a support of non-metallic material, the height of which shall be 1.5m above the ground,
- The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
- Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

3.1.3 Test setup



3.1.4 Test results


Test Mode	BT Link+ WIFI (2.4G) Link	Channel	CH 39
Frequency Range	150KHz ~ 30MHz	PHASE	Line (L)



NO.	Frequency (MHz)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Corr. (dB)	Remark
1	0.557	38.8	56.0	17.2	19.6	QP
2	0.625	39.3	56.0	16.7	19.6	QP
3	0.782	25.0	46.0	21.0	19.6	AVG
4	0.796	40.0	56.0	16.0	19.6	QP
5	0.875	24.5	46.0	21.5	19.6	AVG
6	4.119	23.5	46.0	22.5	19.6	AVG

Remark: The emission levels of other frequencies were very low against the limit.

Test Mode	BT Link+ WIFI (2.4G) Link	Channel	CH 39
Frequency Range	150KHz ~ 30MHz	PHASE	Line (N)



NO.	Frequency (MHz)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Corr. (dB)	Remark
1	0.479	38.9	56.4	17.5	19.6	QP
2	0.625	38.7	56.0	17.3	19.6	QP
3	0.715	25.0	46.0	21.0	19.6	AVG
4	0.782	25.6	46.0	20.4	19.6	AVG
5	0.859	38.7	56.0	17.3	19.6	QP
6	0.875	26.0	46.0	20.0	19.6	AVG

Remark: The emission levels of other frequencies were very low against the limit.

3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.2.1 Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (Microvolts/Meter)	MEASUREMENT DISTANCE (Meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE: 1. The lower limit shall apply at the transition frequencies.

NOTE: 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

NOTE: 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.2.2 Measurement procedure


- The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

3.2.3 Test setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:




3.2.4 Test results

BELOW 1GHz WORST-CASE DATA:

Worst Test Mode	802.11b	Worst Test Channel	CH 6
Frequency Range	9KHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Horizontal




NO.	Frequency (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Azimuth (deg)	Remark
1	42.610	21.7	40.0	18.3	100.0	213.0	QP
2	77.918	21.6	40.0	18.4	100.0	68.0	QP
3	167.934	25.1	43.5	18.4	100.0	79.0	QP
4	239.908	25.9	46.0	20.1	100.0	85.0	QP
5	309.748	24.4	46.0	21.6	100.0	351.0	QP
6	359.994	25.4	46.0	20.6	100.0	109.0	QP

Remark: 1. 9KHz~30MHz have been test and test data more than 20dB margin.

2. The emission levels of other frequencies were greater than 20dB margin.

Worst Test Mode	802.11b	Worst Test Channel	CH 6
Frequency Range	9KHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Vertical




NO.	Frequency (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Azimuth (deg)	Remark
1	40.961	31.9	40.0	8.1	100.0	146.0	QP
2	49.206	34.5	40.0	5.5	200.0	122.0	QP
3	55.996	31.4	40.0	8.6	100.0	218.0	QP
4	120.016	25.8	43.5	17.8	100.0	134.0	QP
5	148.825	26.7	43.5	16.8	200.0	86.0	QP
6	216.046	25.5	46.0	20.5	300.0	152.0	QP

Remark: 1. 9KHz~30MHz have been test and test data more than 20dB margin.

2. The emission levels of other frequencies were greater than 20dB margin.

Test Mode	BT-LE (GFSK)	Worst Test Channel	CH 19
Frequency Range	9KHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Horizontal




NO.	Frequency (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Azimuth (deg)	Remark
1	42.707	21.3	40.0	18.7	100.0	297.0	QP
2	48.527	20.9	40.0	19.1	100.0	77.0	QP
3	76.075	19.1	40.0	20.9	100.0	95.0	QP
4	215.949	28.1	43.5	15.4	100.0	119.0	QP
5	297.623	24.8	46.0	21.2	100.0	119.0	QP
6	375.029	32.1	46.0	13.9	100.0	143.0	QP

Remark: 1. 9KHz~30MHz have been test and test data more than 20dB margin.

2. The emission levels of other frequencies were greater than 20dB margin.

Test Mode	BT-LE (GFSK)	Worst Test Channel	CH 19
Frequency Range	9KHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Vertical



NO.	Frequency (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Azimuth (deg)	Remark
1	33.977	31.0	40.0	9.0	100.0	343.0	QP
2	42.707	30.8	40.0	9.2	200.0	38.0	QP
3	48.624	32.9	40.0	7.1	100.0	349.0	QP
4	55.705	32.8	40.0	7.2	100.0	0.0	QP
5	63.174	27.4	40.0	12.6	200.0	326.0	QP
6	148.728	26.5	43.5	17.0	300.0	8.0	QP


Remark: 1. 9KHz~30MHz have been test and test data more than 20dB margin.

2. The emission levels of other frequencies were greater than 20dB margin.

ABOVE 1GHz DATA


Test Mode	802.11b	Channel	CH 1
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4823.300	57.3	74.00	16.7	100	246.0	6.9	Peak
2	4823.300	51.3	54.00	2.7	100	246.0	6.9	Avg
3	7237.300	49.6	54.00	4.4	100	65.0	10.2	Avg
4	7239.000	57.2	74.00	16.8	100	65.0	10.2	Peak

Test frequency range :18G-25G




Remark: The emission levels of other frequencies were greater than 10dB margin.




Test Mode	802.11b	Channel	CH 1
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK)

Test frequency range :2300 MHz-2430MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2300 MHz-2430MHz




Test Mode	802.11b	Channel	CH 1
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4823.300	49.7	54.00	4.3	100	298.0	6.9	Avg
2	4823.300	56.4	74.00	17.6	100	298.0	6.9	Peak
3	7235.600	49.6	54.00	4.4	100	57.0	10.2	Avg
4	7235.600	57.5	74.00	16.5	100	57.0	10.2	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11b	Channel	CH 1
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK)

Test frequency range :2300 MHz-2430MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2300 MHz-2430MHz




Test Mode	802.11b	Channel	CH 6
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4872.600	58.4	74.00	15.6	200.0	342.0	6.9	Peak
2	4874.300	49.1	54.00	4.9	200.0	342.0	6.9	Avg
3	7312.100	51.8	54.00	2.2	100.0	63.0	9.9	Avg
4	7312.100	58.4	74.00	15.6	100.0	63.0	9.9	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11b	Channel	CH 6
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4872.600	56.3	74.00	17.7	100.0	59.0	6.9	Peak
2	4874.300	46.0	54.00	8.0	100.0	66.0	6.9	Avg
3	7310.400	57.7	74.00	16.3	100.0	59.0	9.9	Peak
4	7312.100	51.7	54.00	2.3	100.0	59.0	9.9	Avg


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11b	Channel	CH 11
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4923.600	51.8	54.0	2.2	100.0	50.0	7.1	Avg
2	4923.600	57.6	74.0	16.4	100.0	50.0	7.1	Peak
3	7386.900	49.6	54.0	4.4	100.0	35.0	10.1	Avg
4	7386.900	56.6	74.0	17.4	100.0	35.0	10.1	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11b	Channel	CH 11
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK)

Test frequency range :2440 MHz-2500MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2440 MHz-2500MHz




Test Mode	802.11b	Channel	CH 11
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4923.600	51.9	54.0	2.1	100.0	60.0	7.1	Avg
2	4923.600	58.2	74.0	15.8	100.0	60.0	7.1	Peak
3	7383.500	57.4	74.0	16.6	100.0	109.0	10.0	Peak
4	7385.200	50.0	54.0	4.0	100.0	102.0	10.1	Avg


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11b	Channel	CH 11
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK)

Test frequency range :2440 MHz-2500MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2440 MHz-2500MHz




Test Mode	802.11g	Channel	CH 1
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4819.900	46.2	54.0	7.8	100.0	249.0	6.9	Avg
2	4831.800	55.9	74.0	18.1	100.0	318.0	6.9	Peak
3	7239.000	47.8	54.0	6.2	100.0	55.0	10.2	Avg
4	7249.200	59.0	74.0	15.0	100.0	62.0	10.2	Peak

Test frequency range :18G-25G




Remark: The emission levels of other frequencies were greater than 10dB margin.




Test Mode	802.11g	Channel	CH 1
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK)

Test frequency range :2300 MHz-2430MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2300 MHz-2430MHz




Test Mode	802.11g	Channel	CH 1
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4821.600	44.9	54.0	9.1	100.0	288.0	6.9	Avg
2	4821.600	55.1	74.0	18.9	100.0	288.0	6.9	Peak
3	7237.300	48.0	54.0	6.0	100.0	65.0	10.2	Avg
4	7237.300	57.8	74.0	16.2	100.0	65.0	10.2	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11g	Channel	CH 1
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK)

Test frequency range :2300 MHz-2430MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2300 MHz-2430MHz




Test Mode	802.11g	Channel	CH 6
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4876.000	46.0	54.0	8.0	100.0	240.0	6.9	Avg
2	4877.700	55.3	74.0	18.7	100.0	351.0	6.9	Peak
3	7307.000	48.1	54.0	5.9	100.0	46.0	9.9	Avg
4	7310.400	58.3	74.0	15.7	100.0	61.0	9.9	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11g	Channel	CH 6
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4876.000	55.8	74.0	18.2	100.0	92.0	6.9	Peak
2	4877.700	46.1	54.0	7.9	100.0	92.0	6.9	Avg
3	7312.100	59.7	74.0	14.3	100.0	62.0	9.9	Peak
4	7312.100	49.1	54.0	4.9	100.0	62.0	9.9	Avg


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11g	Channel	CH 11
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4923.600	47.1	54.0	6.9	100.0	59.0	7.1	Avg
2	4927.000	57.4	74.0	16.6	100.0	350.0	7.1	Peak
3	7386.900	48.6	54.0	5.4	100.0	59.0	10.1	Avg
4	7386.900	60.3	74.0	13.7	100.0	59.0	10.1	Peak

Test frequency range :18G-25G




Remark: The emission levels of other frequencies were greater than 10dB margin.




Test Mode	802.11g	Channel	CH 11
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK)

Test frequency range :2440 MHz-2500MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2440 MHz-2500MHz




Test Mode	802.11g	Channel	CH 11
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4925.300	61.9	74.0	12.1	200.0	306.0	7.1	Avg
2	4928.700	48.3	54.0	5.7	200.0	298.0	7.1	Peak
3	7386.900	48.4	54.0	5.6	200.0	337.0	10.1	Peak
4	7386.900	59.3	74.0	14.7	200.0	337.0	10.1	Avg

Test frequency range :18G-25G




Remark: The emission levels of other frequencies were greater than 10dB margin.




Test Mode	802.11g	Channel	CH 11
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK)

Test frequency range :2440 MHz-2500MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2440 MHz-2500MHz




Test Mode	802.11n(HT20)	Channel	CH 1
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4825.000	45.0	54.0	9.0	100.0	238.0	6.9	Avg
2	4831.800	54.4	74.0	19.6	100.0	247.0	6.9	Peak
3	7235.600	47.8	54.0	6.2	100.0	63.0	10.2	Avg
4	7242.400	57.3	74.0	16.7	100.0	318.0	10.2	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11n(HT20)	Channel	CH 1
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK)

Test frequency range :2300 MHz-2430MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2300 MHz-2430MHz




Test Mode	802.11n(HT20)	Channel	CH 1
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4825.000	56.9	74.0	17.1	100.0	107.0	6.9	Avg
2	4825.000	44.3	54.0	9.7	100.0	107.0	6.9	Peak
3	7237.300	48.0	54.0	6.0	100.0	68.0	10.2	Avg
4	7247.500	57.4	74.0	16.6	100.0	52.0	10.2	Peak

Test frequency range :18G-25G




Remark: The emission levels of other frequencies were greater than 10dB margin.




Test Mode	802.11n(HT20)	Channel	CH 1
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK)

Test frequency range :2300 MHz-2430MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2300 MHz-2430MHz




Test Mode	802.11n(HT20)	Channel	CH 6
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4874.300	56.6	74.0	17.4	100.0	65.0	6.9	Peak
2	4876.000	45.8	54.0	8.2	200.0	342.0	6.9	Avg
3	7303.600	57.2	74.0	16.8	100.0	65.0	9.9	Peak
4	7307.000	48.1	54.0	5.9	100.0	65.0	9.9	Avg


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11n(HT20)	Channel	CH 6
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4879.400	56.8	74.0	17.2	100.0	66.0	6.9	Avg
2	4881.100	45.7	54.0	8.3	100.0	66.0	6.9	Peak
3	7307.000	48.8	54.0	5.2	100.0	58.0	9.9	Avg
4	7317.200	58.3	74.0	15.7	200.0	82.0	9.9	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11n(HT20)	Channel	CH 11
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4920.200	57.3	74.0	16.7	100.0	348.0	7.1	Peak
2	4927.000	47.5	54.0	6.5	200.0	57.0	7.1	Avg
3	7383.500	57.7	74.0	16.3	200.0	49.0	10.0	Peak
4	7385.200	47.4	54.0	6.6	100.0	49.0	10.1	Avg

Test frequency range :18G-25G




Remark: The emission levels of other frequencies were greater than 10dB margin.




Test Mode	802.11n(HT20)	Channel	CH 11
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK)

Test frequency range :2440 MHz-2500MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2440 MHz-2500MHz




Test Mode	802.11n(HT20)	Channel	CH 11
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4927.000	62.7	74.0	11.3	200.0	301.0	7.1	Peak
2	4927.000	48.7	54.0	5.3	200.0	301.0	7.1	Avg
3	7385.200	59.8	74.0	14.2	100.0	232.0	10.1	Peak
4	7392.000	47.6	54.0	6.4	100.0	215.0	10.1	Avg


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	802.11n(HT20)	Channel	CH 11
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK)

Test frequency range :2440 MHz-2500MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2440 MHz-2500MHz




Test Mode	BT-LE (GFSK)	Channel	CH 0
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4802.900	51.3	54.0	2.7	100.0	223.0	6.9	Avg
2	4802.900	58.7	74.0	15.3	100.0	223.0	6.9	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	BT-LE (GFSK)	Channel	CH 0
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK)

Test frequency range :2300 MHz-2410MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2300 MHz-2410MHz




Test Mode	BT-LE (GFSK)	Channel	CH 0
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4802.900	48.0	54.0	6.0	300.0	230.0	6.9	Avg
2	4802.900	56.7	74.0	17.3	100.0	72.0	6.9	Peak

Test frequency range :18G-25G




Remark: The emission levels of other frequencies were greater than 10dB margin.




Test Mode	BT-LE (GFSK)	Channel	CH 0
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK)

Test frequency range :2300 MHz-2410MHz



Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------


Test frequency range :2300 MHz-2410MHz






Test Mode	BT-LE (GFSK)	Channel	CH 19
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4879.400	57.2	74.0	16.8	100.0	208.0	6.9	Peak
2	4879.400	51.1	54.0	2.9	100.0	208.0	6.9	Avg


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	BT-LE (GFSK)	Channel	CH 19
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4879.400	48.5	54.0	5.5	200.0	279.0	6.9	Avg
2	4879.400	55.9	74.0	18.1	100.0	69.0	6.9	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	BT-LE (GFSK)	Channel	CH 39
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4959.300	50.1	54.0	3.9	100.0	216.0	7.0	Avg
2	4959.300	56.8	74.0	17.2	100.0	216.0	7.0	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	BT-LE (GFSK)	Channel	CH 39
Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Peak (PK)

Test frequency range :2470 MHz-2500MHz




Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2470 MHz-2500MHz




Test Mode	BT-LE (GFSK)	Channel	CH 39
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK) Average (AV)

Test frequency range :1G-18G



NO.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Remark
1	4959.300	49.1	54.0	4.9	300.0	256.0	7.0	Avg
2	4959.300	56.4	74.0	17.6	300.0	256.0	7.0	Peak


Test frequency range :18G-25G



Remark: The emission levels of other frequencies were greater than 10dB margin.


Test Mode	BT-LE (GFSK)	Channel	CH 39
Antenna Polarity & Test Distance	Vertical at 3m	Detector Function	Peak (PK)

Test frequency range :2470 MHz-2500MHz



Antenna Polarity & Test Distance	Horizontal at 3m	Detector Function	Average (AV)
----------------------------------	------------------	-------------------	--------------

Test frequency range :2470 MHz-2500MHz



3.3 6dB BANDWIDTH MEASUREMENT


3.3.1 Limits

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 Measurement procedure

- Set resolution bandwidth (RBW) = 100KHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3.3.3 Test setup



3.3.4 Test result

802.11b


Channel	Channel Frequency (MHz)	6dB BANDWIDTH (MHz)	Measured Frequencies		MINIMUM LIMIT (MHz)	Verdict
			FL (MHz)	FH (MHz)		
1	2412	9.160	2407.400	2416.560	0.5	PASS
6	2437	9.120	2432.440	2441.560	0.5	PASS
11	2462	9.160	2457.400	2466.560	0.5	PASS





802.11g


Channel	Channel Frequency (MHz)	6dB BANDWIDTH (MHz)	Measured Frequencies		MINIMUM LIMIT (MHz)	Verdict
			FL (MHz)	FH (MHz)		
1	2412	16.400	2403.800	2420.200	0.5	PASS
6	2437	16.440	2428.760	2445.200	0.5	PASS
11	2462	16.400	2453.800	2470.200	0.5	PASS






802.11n(HT20)

Channel	Channel Frequency (MHz)	6dB BANDWIDTH (MHz)	Measured Frequencies		MINIMUM LIMIT (MHz)	Verdict
			FL (MHz)	FH (MHz)		
1	2412	17.120	2403.440	2420.560	0.5	PASS
6	2437	17.160	2428.400	2445.560	0.5	PASS
11	2462	17.160	2453.400	2470.560	0.5	PASS



**BT-LE (GFSK)**

Channel	Channel Frequency (MHz)	6dB BANDWIDTH (MHz)	Measured Frequencies		MINIMUM LIMIT (MHz)	Verdict
			FL (MHz)	FH (MHz)		
0	2402	0.692	2401.608	2402.300	0.5	PASS
19	2440	0.696	2439.608	2440.304	0.5	PASS
39	2480	0.688	2479.608	2480.296	0.5	PASS



3.4 CONDUCTED OUTPUT POWER


3.4.1 Limits

Forsystems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm).

3.4.2 Measurement procedure

- A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor and set the detector to PEAK. Record the power level.
- An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and set the detector to AVERAGE. Record the power level.

3.4.3 Test setup





3.4.4 Test result

MAXIMUM PEAK OUTPUT POWER

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	VERDICT
802.11b					
1	2412	16.01	39.902	1	PASS
6	2437	16.32	42.855	1	PASS
11	2462	16.15	41.210	1	PASS
802.11g					
1	2412	22.63	183.231	1	PASS
6	2437	22.79	190.108	1	PASS
11	2462	22.47	176.604	1	PASS
802.11n(HT20)					
1	2412	22.45	175.792	1	PASS
6	2437	22.63	183.231	1	PASS
11	2462	22.29	169.434	1	PASS
BT-LE (GFSK)					
0	2402	9.68	9.290	1	PASS
19	2440	9.98	9.954	1	PASS
39	2480	9.03	7.998	1	PASS

Average Output Power (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

CHANNEL	CHANNEL FREQUENCY(MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
802.11b			
1	2412	12.51	17.824
6	2437	12.82	19.143
11	2462	12.63	18.323
802.11g			
1	2412	14.56	28.576
6	2437	14.6	28.840
11	2462	14.36	27.290
802.11n(HT20)			
1	2412	14.33	27.102
6	2437	14.42	27.669
11	2462	14.2	26.303
BT-LE (GFSK)			
0	2402	6.19	4.159
19	2440	6.44	4.406
39	2480	5.52	3.565



3.5 POWER SPECTRAL DENSITY MEASUREMENT


3.5.1 Limits

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 Measurement procedure

- Set instrument center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set RBW to: 3KHz
- Set VBW $\geq 3 \times$ RBW.
- Detector = peak
- Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- Sweep time = auto couple.
- Use the peak marker function to determine the maximum amplitude level.


3.5.3 Test setup



3.5.4 Test result

802.11b


CHANNEL	CHANNEL FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	VERDICT
1	2412	-9.58	8	PASS
6	2437	-9.07	8	PASS
11	2462	-8.91	8	PASS





802.11g


CHANNEL	CHANNEL FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	VERDICT
1	2412	-10.36	8	PASS
6	2437	-9.71	8	PASS
11	2462	-10.16	8	PASS





802.11n(HT20)


CHANNEL	CHANNEL FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	VERDICT
1	2412	-9.94	8	PASS
6	2437	-9.42	8	PASS
11	2462	-9.58	8	PASS





BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	VERDICT
0	2402	-8.19	8	PASS
19	2440	-7.88	8	PASS
39	2480	-8.46	8	PASS





3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 Limits

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 Measurement procedure


Measurement Procedure -Reference Level

- Set the RBW = 100 kHz.
- Set the VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHzband segment within the fundamental EBW.

Measurement Procedure –Unwanted Emission Level

- Set RBW = 100 kHz.
- Set VBW $\geq$ 300 kHz.
- Set span to encompass the spectrum to be examined
- Detector = peak.
- Trace Mode = max hold.
- Sweep = auto couple.


3.6.3 Test setup



3.6.4 Test result


Conducted Spurious Emission

802.11b






802.11g






802.11n(HT20)




BT-LE (GFSK)




Band edge

802.11b




802.11g






802.11n(HT20)



BT-LE (GFSK)





4 PHOTOGRAPHS OF TEST SETUP

Please refer to the attached file (Test Setup Photo).

,

Appendix A

Radiated Emission Test - 10M Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Due	Used
EMI Test Receiver	Rohde&Schwarz	ESR 26	101718	2021.5.19	☒
Loop antenna	Rohde&Schwarz	HFH2-Z2E	100951	2021.5.16	☒
Rod antenna	Rohde&Schwarz	HFH2-Z6E	101268	2021.5.24	☒
Double cone antenna	Rohde&Schwarz	HK116E	10359	2021.5.24	☒
Log periodic antenna	Rohde&Schwarz	HL223	100936	2021.5.24	☒
antenna(30MHz~1000MHz)	SCHWARZBECK	VULB 9168	1132	2021.5.16	☒
Horn antenna(1GHz-6GHz)	SCHWARZBECK	BBHA 9120E	947	2023.5.19	☒
Horn antenna(1GHz-18GHz)	ETS	3117	227634	2022.1.14	☒
Horn antenna(18GHz-40GHz)	SCHWARZBECK	BBHA 9170	1003	2021.5.16	☒
10m anechoic chamber	Albatross	P25904	P25904	2024.06.30	☒
LISN (single-phase)	Rohde&Schwarz	ESH3-Z6	102152/102156	2021.5.21	☒
Preamplifier	Rohde&Schwarz	SCU-01F	100298	2021.5.19	☒
Preamplifier	Rohde&Schwarz	SCU-18F	100799	2021.5.19	☒

Antenna Port Conducted Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Due	Used
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 40	101898	2021.5.19	☒
Wideband radio communication tester	Rohde&Schwarz	CMW 500	168778	2021.5.19	☐
Automatic control unit(RSE)	Rohde&Schwarz	OSP220	101742	2021.5.19	☐
Filter group(RSE-BT/WiFi)	Rohde&Schwarz	WiFi /BT Variant 1	100820	2021.5.19	☒
Filter group(RSE-Cellular)	Rohde&Schwarz	Cellular Variant 1	100768	2021.5.19	☒
Signal&Spectrum Analyzer	Rohde&Schwarz	FSVA 3044	101013	2021.5.19	☒
signal Generator(100kHz~40GHz)	Rohde&Schwarz	SMB 100A	CS0300015	2021.05.19	☐
signal Generator(100kHz~12.75GHz)	Rohde&Schwarz	SMB 100A	CS0300016	2021.5.19	☐



Important

- (1) The test report is valid with the official seal of the laboratory and the signatures of Test engineer, Author and Reviewer simultaneously.
- (2) The test report is invalid if altered.
- (3) Any photocopies or part photocopies in the test report are forbidden without the written permission from the laboratory.
- (4) Objections to the test report must be submitted to the laboratory within 15 days.
- (5) Generally, commission test is responsible for the tested samples only.

Address of the laboratory:

Vkan Certification & Testing Co., Ltd.

Address: No.3, Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou, China

Post Code: 510663

Tel: 020-32293888

FAX: 020-32293889

E-mail: office@cvc.org.cn