



Report No.: PTC23052207602E-FC03

# FCC TEST REPORT

## FCC ID: 2AZ2V-ZEN72

|                                                                                |   |                      |
|--------------------------------------------------------------------------------|---|----------------------|
| Product                                                                        | : | DIMMER SWITCH 800    |
| Model Name                                                                     | : | ZEN72 800LR          |
| Brand                                                                          | : | ZOOZ                 |
| Report No.                                                                     | : | PTC23052207602E-FC03 |
| <b>Prepared for</b>                                                            |   |                      |
| Lorenz High Definition LLC                                                     |   |                      |
| 230 Rt 206 STE 401, Flanders, NJ 07836, United States                          |   |                      |
| <b>Prepared by</b>                                                             |   |                      |
| Precise Testing & Certification Co., Ltd.                                      |   |                      |
| Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China. |   |                      |



Report No.: PTC23052207602E-FC03

## TEST RESULT CERTIFICATION

Applicant's name : Lorenz High Definition LLC

Address : 230 Rt 206 STE 401, Flanders, NJ 07836, United States

Manufacture's name : Lorenz High Definition LLC

Address : 230 Rt 206 STE 401, Flanders, NJ 07836, United States

Product name : DIMMER SWITCH 800

Model name : ZEN72 800LR

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Apr. 18, 2023 to Jun. 06, 2023

Date of Issue : Jun. 06, 2023

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu / Engineer

Technical Manager:

A handwritten signature in black ink that reads "Ronnie Liu".

Ronnie Liu / Manager



## Contents

|                                       | <b>Page</b> |
|---------------------------------------|-------------|
| <b>2 TEST SUMMARY.....</b>            | <b>4</b>    |
| <b>3 GENERAL INFORMATION.....</b>     | <b>5</b>    |
| 3.1 GENERAL DESCRIPTION OF E.U.T..... | 5           |
| <b>4 RF EXPOSURE.....</b>             | <b>6</b>    |
| 4.1 REQUIREMENTS.....                 | 6           |
| 4.2 THE PROCEDURES / LIMIT.....       | 6           |
| 4.3 MPE CALCULATION METHOD.....       | 7           |
| 4.4 RF OUTPUT POWER.....              | 7           |
| 4.5 TEST RESULT.....                  | 8           |



Report No.: PTC23052207602E-FC03

## 2 Test Summary

| Test Items                                                        | Test Requirement | Result |
|-------------------------------------------------------------------|------------------|--------|
| Maximum Permissible Exposure<br>(Exposure of Humans to RF Fields) | 15.247 (i)       | PASS   |
| Remark:                                                           |                  |        |
| N/A: Not Applicable                                               |                  |        |



### 3 General Information

#### 3.1 General Description of E.U.T.

|                      |   |                                                                                                          |
|----------------------|---|----------------------------------------------------------------------------------------------------------|
| Product Name         | : | DIMMER SWITCH 800                                                                                        |
| Model Name           | : | ZEN72 800LR                                                                                              |
| Additional model     | : | N/A                                                                                                      |
| Operation Frequency  | : | 908.40MHz<br>908.42MHz<br>916.00MHz<br>912 MHz<br>920 MHz                                                |
| Type of Modulation   | : | 2FSK for 908.40MHz<br>2FSK for 908.42MHz<br>2GFSK for 916.00MHz<br>DSSS OQPSK LR for 912 MHz and 920 MHz |
| Antenna installation | : | Internal permanent Antenna                                                                               |
| Antenna Gain         | : | -3.90 dBi                                                                                                |
| Power supply         | : | AC 125V/60Hz 500W                                                                                        |
| Hardware Version     | : | 1.0                                                                                                      |
| Software Version     | : | 1.0                                                                                                      |



## 4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

### 4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

### 4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

| Frequency Range | Electric Field | Magnetic Field | Power Density (S) | Averaging Time |
|-----------------|----------------|----------------|-------------------|----------------|
| 0.3-3.0         | 614            | 1.63           | (100)*            | 6              |
| 3.0-30          | 1842 / f       | 4.89 / f       | (900 / f)*        | 6              |
| 30-300          | 61.4           | 0.163          | 1.0               | 6              |
| 300-1500        |                |                | F/300             | 6              |
| 1500-100,000    |                |                | 5                 | 6              |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range | Electric Field | Magnetic Field | Power Density (S) | Averaging Time |
|-----------------|----------------|----------------|-------------------|----------------|
| 0.3-1.34        | 614            | 1.63           | (100)*            | 30             |
| 1.34-30         | 824/f          | 2.19/f         | (180/f)*          | 30             |
| 30-300          | 27.5           | 0.073          | 0.2               | 30             |
| 300-1500        |                |                | F/1500            | 30             |
| 1500-100,000    |                |                | 1.0               | 30             |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density



#### 4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2} \theta \phi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

#### 4.4 RF Output power

| Freq.<br>(MHz)                                                                                                                                                                                                                       | Field strength(max)(dBuV/m) | EIRP (max)<br>(dBm) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------|
| 908.40                                                                                                                                                                                                                               | 89.80                       | -5.40               |
| 908.42                                                                                                                                                                                                                               | 89.41                       | -5.79               |
| 916.00                                                                                                                                                                                                                               | 89.58                       | -5.62               |
| <b>Note:</b> EIRP=E-104.8+20logD,<br>Where<br>E is the electric field strength in dBμV/m.<br>EIRP is the equivalent isotropically radiated power in dBm.<br>d is the specified measurement distance in m.<br>where D=3, EIRP=E-95.2. |                             |                     |



#### 4.5 Test Result

| Mode      | Antenna Gain (numeric) | Max. Peak Output Power (dBm) | Tune up tolerance (dBm) | Max Tune Up Power (mW) | Power Density (mW/cm <sup>2</sup> ) | Limit of Power Density (mW/cm <sup>2</sup> ) | Result |
|-----------|------------------------|------------------------------|-------------------------|------------------------|-------------------------------------|----------------------------------------------|--------|
| 912MHz    | 0.41                   | 0.385                        | 0.4±1                   | 1.380384               | 0.001126                            | 0.608000                                     | Pass   |
| 920MHz    | 0.41                   | 0.537                        | 0.6±1                   | 1.44544                | 0.001179                            | 0.613333                                     | Pass   |
| 908.40MHz | 0.41                   | -5.40                        | -5.00±1                 | 0.398107               | 0.000325                            | 0.605600                                     | Pass   |
| 908.42MHz | 0.41                   | -5.79                        | -5.50±1                 | 0.354813               | 0.000289                            | 0.605613                                     | Pass   |
| 916.00MHz | 0.41                   | -5.62                        | -5.50±1                 | 0.354813               | 0.000289                            | 0.610667                                     | Pass   |

Simultaneous SAR Evaluation:

The device can't support simultaneous transmitter.

**\*\*\*\*\*THE END REPORT\*\*\*\*\***