



Report No.: PTC21110401603E-FC01

# FCC TEST REPORT

## FCC ID: 2AZ43-ET24

|                                                                               |   |                            |
|-------------------------------------------------------------------------------|---|----------------------------|
| Product Name                                                                  | : | Portable Bluetooth speaker |
| Model Name                                                                    | : | ET24                       |
| Brand Name                                                                    | : | N/A                        |
| Report No.                                                                    | : | PTC21110401603E-FC01       |
| <b>Prepared for</b>                                                           |   |                            |
| MOSWS INTERNATIONAL LIMITED                                                   |   |                            |
| FLAT/RM 07 BLK B 5/F KING YIP FACTORY BUILDING 59 KING YIP STREET KWUN TONG   |   |                            |
|                                                                               |   |                            |
| <b>Prepared by</b>                                                            |   |                            |
| Precise Testing & Certification Co., Ltd.                                     |   |                            |
| Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China |   |                            |
|                                                                               |   |                            |



## 1 TEST RESULT CERTIFICATION

Applicant's name : MOSWS INTERNATIONAL LIMITED  
Address : FLAT/RM 07 BLK B 5/F KING YIP FACTORY BUILDING 59 KING YIP STREET KWUN TONG  
Manufacture's name : MOSWS INTERNATIONAL LIMITED  
Address : FLAT/RM 07 BLK B 5/F KING YIP FACTORY BUILDING 59 KING YIP STREET KWUN TONG  
Product name : Portable Bluetooth speaker  
Model name : ET24  
Standards : FCC CFR47 Part 15 Section 15.247  
Test procedure : ANSI C63.10:2013  
Test Date : Dec. 23, 2021 to May 21, 2022  
Date of Issue : May 21, 2022  
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu / Engineer

Technical Manager:

A handwritten signature in black ink that reads "Ronnie Liu".

Ronnie Liu / Manager



## Contents

### Page

|                                                        |           |
|--------------------------------------------------------|-----------|
| <b>1 TEST RESULT CERTIFICATION .....</b>               | <b>2</b>  |
| <b>2 TEST SUMMARY .....</b>                            | <b>5</b>  |
| <b>3 TEST FACILITY .....</b>                           | <b>6</b>  |
| <b>4 GENERAL INFORMATION .....</b>                     | <b>7</b>  |
| 4.1 GENERAL DESCRIPTION OF E.U.T. ....                 | 7         |
| 4.2 TEST MODE .....                                    | 8         |
| <b>5 EQUIPMENT DURING TEST .....</b>                   | <b>10</b> |
| 5.1 EQUIPMENTS LIST .....                              | 10        |
| 5.2 MEASUREMENT UNCERTAINTY .....                      | 12        |
| 5.3 DESCRIPTION OF SUPPORT UNITS .....                 | 13        |
| <b>6 CONDUCTED EMISSION .....</b>                      | <b>14</b> |
| 6.1 E.U.T. OPERATION .....                             | 14        |
| 6.2 EUT SETUP .....                                    | 14        |
| 6.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) ..... | 15        |
| 6.4 MEASUREMENT PROCEDURE: .....                       | 15        |
| 6.5 CONDUCTED EMISSION LIMIT .....                     | 15        |
| 6.6 MEASUREMENT DESCRIPTION .....                      | 15        |
| 6.7 CONDUCTED EMISSION TEST RESULT .....               | 15        |
| <b>7 RADIATED SPURIOUS EMISSIONS .....</b>             | <b>18</b> |
| 7.1 EUT OPERATION .....                                | 18        |
| 7.2 TEST SETUP .....                                   | 19        |
| 7.3 SPECTRUM ANALYZER SETUP .....                      | 20        |
| 7.4 TEST PROCEDURE .....                               | 21        |
| 7.5 SUMMARY OF TEST RESULTS .....                      | 22        |
| <b>8 MAXIMUM PEAK OUTPUT POWER TEST .....</b>          | <b>29</b> |
| 8.1 TEST STANDARD AND LIMIT .....                      | 29        |
| 8.2 TEST SETUP .....                                   | 29        |
| 8.3 TEST PROCEDURE .....                               | 29        |
| 8.4 TEST DATA .....                                    | 29        |



|                                                                     |           |
|---------------------------------------------------------------------|-----------|
| <b>9 20DB OCCUPY BANDWIDTH TEST .....</b>                           | <b>34</b> |
| 9.1 TEST STANDARD .....                                             | 34        |
| 9.2 TEST SETUP .....                                                | 34        |
| 9.3 TEST PROCEDURE .....                                            | 34        |
| 9.4 TEST DATA .....                                                 | 34        |
| <b>10 CARRIER FREQUENCY SEPARATION TEST .....</b>                   | <b>39</b> |
| 10.1 TEST STANDARD AND LIMIT .....                                  | 39        |
| 10.2 TEST SETUP .....                                               | 39        |
| 10.3 TEST PROCEDURE .....                                           | 39        |
| 10.4 TEST DATA .....                                                | 39        |
| <b>11 NUMBER OF HOPPING CHANNEL TEST .....</b>                      | <b>44</b> |
| 11.1 TEST STANDARD AND LIMIT .....                                  | 44        |
| 11.2 TEST SETUP .....                                               | 44        |
| 11.3 TEST PROCEDURE .....                                           | 44        |
| 11.4 TEST DATA .....                                                | 45        |
| <b>12 DWELL TIME TEST .....</b>                                     | <b>47</b> |
| 12.1 TEST STANDARD AND LIMIT .....                                  | 47        |
| 12.2 TEST SETUP .....                                               | 47        |
| 12.3 TEST PROCEDURE .....                                           | 47        |
| 12.4 TEST DATA .....                                                | 48        |
| <b>13 100KHZ BANDWIDTH OF FREQUENCY BAND EDGE REQUIREMENT .....</b> | <b>50</b> |
| 13.1 TEST STANDARD AND LIMIT .....                                  | 50        |
| 13.2 TEST SETUP .....                                               | 50        |
| 13.3 TEST PROCEDURE .....                                           | 50        |
| 13.4 TEST DATA .....                                                | 51        |
| <b>14 ANTENNA REQUIREMENT .....</b>                                 | <b>58</b> |
| 14.1 TEST STANDARD AND REQUIREMENT .....                            | 58        |
| 14.2 ANTENNA CONNECTED CONSTRUCTION .....                           | 58        |
| <b>15 APPENDIX I -- TEST SETUP PHOTOGRAPH .....</b>                 | <b>59</b> |
| <b>16 APPENDIX II -- EXTERNAL PHOTOGRAPH .....</b>                  | <b>61</b> |
| <b>17 APPENDIX III -- INTERNAL PHOTOGRAPH .....</b>                 | <b>65</b> |



## 2 Test Summary

| Test Items                  | Test Requirement                 | Result |
|-----------------------------|----------------------------------|--------|
| Radiated Spurious Emissions | 15.205(a)<br>15.209<br>15.247(d) | PASS   |
| Band edge                   | 15.247(d)<br>15.205(a)           | PASS   |
| Conduct Emission            | 15.207                           | PASS   |
| 20dB Bandwidth              | 15.247(a)(1)                     | PASS   |
| Maximum Peak Output Power   | 15.247(b)(1)                     | PASS   |
| Frequency Separation        | 15.247(a)(1)                     | PASS   |
| Number of Hopping Frequency | 15.247(a)(1)(iii)                | PASS   |
| Dwell time                  | 15.247(a)(1)(iii)                | PASS   |
| Antenna Requirement         | 15.203                           | PASS   |



Report No.: PTC21110401603E-FC01

### **3 TEST FACILITY**

Precise Testing & Certification Co., Ltd.

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A



## 4 General Information

### 4.1 General Description of E.U.T.

|                      |   |                                                    |
|----------------------|---|----------------------------------------------------|
| Product Name         | : | Portable Bluetooth speaker                         |
| Model Name           | : | ET24                                               |
| Additional model     | : | N/A                                                |
| Specification        | : | BT 5.0 BDR+EDR; BLE                                |
| Operation Frequency  | : | 2402-2480MHz for BT                                |
| Number of Channel    | : | 79 channels For BR+EDR;<br>40 channels For BLE     |
| Type of Modulation   | : | GFSK, $\pi/4$ -DQPSK, 8DPSK For DSS; GFSK For BLE; |
| Antenna installation | : | PIFA antenna                                       |
| Antenna Gain         | : | 0 dBi                                              |
| Power supply         | : | 3.7V 5000mAH with lithium battery                  |
| Hardware Version     | : | DCX-517V2.0                                        |
| Software Version     | : | AC692x_SDK_release_V2.6.3                          |



## 4.2 Test Mode

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonics of the highest fundamental frequency or to 40 GHz, whichever is lower).

The EUT has been tested under TX operating condition.

This EUT is a FHSS system, were conducted to determine the final configuration from all possible combinations. We use software control the EUT, Let EUT hopping on and transmit with highest power, all the modes GFSK,  $\pi/4$ -DQPSK, 8DPSK have been tested. 79 Channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel List:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 0       | 2402            | 1       | 2403            | 2       | 2404            | 3       | 2405            |
| 4       | 2406            | 5       | 2407            | 6       | 2408            | 7       | 2409            |
| 8       | 2410            | 9       | 2411            | 10      | 2412            | 11      | 2413            |
| 12      | 2414            | 13      | 2415            | 14      | 2416            | 15      | 2417            |
| 16      | 2418            | 17      | 2419            | 18      | 2420            | 19      | 2421            |
| 20      | 2422            | 21      | 2423            | 22      | 2424            | 23      | 2425            |
| 24      | 2426            | 25      | 2427            | 26      | 2428            | 27      | 2429            |
| 28      | 2430            | 29      | 2431            | 30      | 2432            | 31      | 2433            |
| 32      | 2434            | 33      | 2435            | 34      | 2436            | 35      | 2437            |
| 36      | 2438            | 37      | 2439            | 38      | 2440            | 39      | 2441            |
| 40      | 2442            | 41      | 2443            | 42      | 2444            | 43      | 2445            |
| 44      | 2446            | 45      | 2447            | 46      | 2448            | 47      | 2449            |
| 48      | 2450            | 49      | 2451            | 50      | 2452            | 51      | 2453            |
| 52      | 2454            | 53      | 2455            | 54      | 2456            | 55      | 2457            |
| 56      | 2458            | 57      | 2459            | 58      | 2460            | 59      | 2461            |
| 60      | 2462            | 61      | 2463            | 62      | 2464            | 63      | 2465            |
| 64      | 2466            | 65      | 2467            | 66      | 2468            | 67      | 2469            |
| 68      | 2470            | 69      | 2471            | 70      | 2472            | 71      | 2473            |
| 72      | 2474            | 73      | 2475            | 74      | 2476            | 75      | 2477            |
| 76      | 2478            | 77      | 2479            | 78      | 2480            | -       | -               |



Report No.: PTC21110401603E-FC01

| Channel | Frequency(MHz) |
|---------|----------------|
| 0       | 2402           |
| 39      | 2441           |
| 78      | 2480           |



## 5 Equipment During Test

### 5.1 Equipments List

RF Conducted Test

| Name of Equipment   | Manufacturer | Model   | Serial No.    | Characteristics | Calibration Due |
|---------------------|--------------|---------|---------------|-----------------|-----------------|
| MXG Signal Analyzer | Agilent      | N9020A  | SER MY5111038 | 10Hz-30GHz      | Aug. 21, 2022   |
| Coaxial Cable       | CDS          | 79254   | 46107086      | 10Hz-30GHz      | Aug. 21, 2022   |
| Power Meter         | Anritsu      | ML2495A | 0949003       | 300MHz-40GHz    | Aug. 21, 2022   |
| Power Sensor        | Anritsu      | MA2411B | 0917017       | 300MHz-40GHz    | Aug. 21, 2022   |

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

| Name of Equipment            | Manufacturer  | Model      | Serial No.   | Characteristics | Calibration Due |
|------------------------------|---------------|------------|--------------|-----------------|-----------------|
| EMI Test Receiver            | Rohde&Schwarz | ESCI       | 101417       | 9KHz-3GHz       | Aug. 21, 2022   |
| Loop Antenna                 | Schwarzbeck   | FMZB 1519  | 012          | 9 KHz -30MHz    | Aug. 21, 2022   |
| Bilog Antenna                | SCHWARZBECK   | VULB9160   | 9160-3355    | 25MHz-2GHz      | Aug. 21, 2022   |
| Preamplifier (low frequency) | SCHWARZBECK   | BBV 9475   | 9745-0013    | 1MHz-1GHz       | Aug. 21, 2022   |
| Cable                        | Schwarzbeck   | PLF-100    | 549489       | 9KHz-3GHz       | Aug. 21, 2022   |
| Spectrum Analyzer            | Agilent       | E4407B     | MY45109572   | 9KHz-40GHz      | Aug. 21, 2022   |
| Horn Antenna                 | SCHWARZBECK   | 9120D      | 9120D-1246   | 1GHz-18GHz      | Aug. 21, 2022   |
| Power Amplifier              | LUNAR EM      | LNA1G18-40 | J10100000081 | 1GHz-26.5GHz    | Aug. 21, 2022   |
| Horn Antenna                 | SCHWARZBECK   | BBHA 9170  | 9170-181     | 14GHz-40GHz     | Aug. 21, 2022   |
| Amplifier                    | SCHWARZBECK   | BBV 9721   | 9721-205     | 18GHz-40GHz     | Aug. 21, 2022   |
| Cable                        | H+S           | CBL-26     | N/A          | 1GHz-26.5GHz    | Aug. 21, 2022   |
| RF Cable                     | R&S           | R204       | R21X         | 1GHz-40GHz      | Aug. 21, 2022   |

Conducted Emissions



Report No.: PTC21110401603E-FC01

| Name of Equipment        | Manufacturer  | Model  | Serial No. | Characteristics | Calibration Due |
|--------------------------|---------------|--------|------------|-----------------|-----------------|
| EMI Test Receiver        | Rohde&Schwarz | ESCI   | 101417     | 9KHz-3GHz       | Aug. 19, 2022   |
| Artificial Mains Network | Rohde&Schwarz | ENV216 | 102453     | 9KHz-300MHz     | Aug. 19, 2022   |
| Artificial Mains Network | Rohde&Schwarz | ENV216 | 101342     | 9KHz-300MHz     | Aug. 19, 2022   |



## 5.2 Measurement Uncertainty

| Parameter                          | Uncertainty              |
|------------------------------------|--------------------------|
| RF output power, conducted         | $\pm 1.0\text{dB}$       |
| Power Spectral Density, conducted  | $\pm 2.2\text{dB}$       |
| Radio Frequency                    | $\pm 1 \times 10^{-6}$   |
| Bandwidth                          | $\pm 1.5 \times 10^{-6}$ |
| Time                               | $\pm 2\%$                |
| Duty Cycle                         | $\pm 2\%$                |
| Temperature                        | $\pm 1^\circ\text{C}$    |
| Humidity                           | $\pm 5\%$                |
| DC and low frequency voltages      | $\pm 3\%$                |
| Conducted Emissions (150kHz~30MHz) | $\pm 3.64\text{dB}$      |
| Radiated Emission(9KHz~30MHz)      | $\pm 4.5\text{dB}$       |
| Radiated Emission(30MHz~1GHz)      | $\pm 5.03\text{dB}$      |
| Radiated Emission(1GHz~25GHz)      | $\pm 4.74\text{dB}$      |



Report No.: PTC21110401603E-FC01

### 5.3 Description of Support Units

| Equipment | Information  | Model No.. |
|-----------|--------------|------------|
| Adapter   | AC 120V 60Hz | N/A        |

## 6 Conducted Emission

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Test Requirement: | : FCC CFR 47 Part 15 Section 15.207             |
| Test Method:      | : ANSI C63.10:2013                              |
| Test Result:      | : PASS                                          |
| Frequency Range:  | : 150kHz to 30MHz                               |
| Class/Severity:   | : Class B                                       |
| Detector:         | : Peak for pre-scan (9kHz Resolution Bandwidth) |


### 6.1 E.U.T. Operation

Operating Environment :


|                       |                |
|-----------------------|----------------|
| Temperature:          | : 23.2°C       |
| Humidity:             | : 51 % RH      |
| Atmospheric Pressure: | : 101.12 kPa   |
| Test Voltage          | : AC 120V/60Hz |

### 6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10: 2013



### 6.3 Test SET-UP (Block Diagram of Configuration)



### 6.4 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

### 6.5 Conducted Emission Limit

#### Conducted Emission

| Frequency(MHz) | Quasi-peak | Average |
|----------------|------------|---------|
| 0.15-0.5       | 66-56      | 56-46   |
| 0.5-5.0        | 56         | 46      |
| 5.0-30.0       | 60         | 50      |

#### Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 6.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


### 6.7 Conducted Emission Test Result

Pass

Conducted emission at both 120V & 240V is assessed, and emission at 120V represents the worst case. All the modulation modes were tested the data of the worst mode (GFSK) are recorded in the following pages and the others modulation methods do not exceed the limits.



Line -120V/60Hz:




| No. | Freq<br>MHz | Cable<br>Loss<br>dB | AMN<br>Factor<br>dB | Receiver<br>Reading<br>dBuV | Emission<br>Level<br>dBuV | Limit<br>dBuV | Over<br>Limit<br>dB | Remark  |
|-----|-------------|---------------------|---------------------|-----------------------------|---------------------------|---------------|---------------------|---------|
| 1.  | 0.170       | 0.24                | 9.59                | 26.09                       | 35.92                     | 54.94         | -19.02              | Average |
| 2.  | 0.170       | 0.24                | 9.59                | 40.41                       | 50.24                     | 64.94         | -14.70              | QP      |
| 3.  | 0.223       | 0.30                | 9.59                | 22.24                       | 32.13                     | 52.70         | -20.57              | Average |
| 4.  | 0.223       | 0.30                | 9.59                | 35.83                       | 45.72                     | 62.70         | -16.98              | QP      |
| 5.  | 0.708       | 0.44                | 9.61                | 26.84                       | 36.89                     | 46.00         | -9.11               | Average |
| 6.  | 0.708       | 0.44                | 9.61                | 36.38                       | 46.43                     | 56.00         | -9.57               | QP      |
| 7.  | 2.167       | 0.47                | 9.61                | 25.82                       | 35.90                     | 46.00         | -10.10              | Average |
| 8.  | 2.167       | 0.47                | 9.61                | 36.79                       | 46.87                     | 56.00         | -9.13               | QP      |
| 9.  | 2.884       | 0.47                | 9.63                | 28.44                       | 38.54                     | 46.00         | -7.46               | Average |
| 10. | 2.884       | 0.47                | 9.63                | 36.34                       | 46.44                     | 56.00         | -9.56               | QP      |
| 11. | 5.058       | 0.50                | 9.68                | 23.45                       | 33.63                     | 50.00         | -16.37              | Average |
| 12. | 5.058       | 0.50                | 9.68                | 30.15                       | 40.33                     | 60.00         | -19.67              | QP      |



Report No.: PTC21110401603E-FC01

Neutral -120V/60Hz:



| No. | Freq<br>MHz | Cable<br>Loss<br>dB | AMN<br>Factor<br>dB | Receiver<br>Reading<br>dBUV | Emission<br>Level<br>dBUV | Limit<br>dBUV | Over<br>Limit<br>dB | Remark  |
|-----|-------------|---------------------|---------------------|-----------------------------|---------------------------|---------------|---------------------|---------|
| 1.  | 0.178       | 0.25                | 9.61                | 25.81                       | 35.67                     | 54.59         | -18.92              | Average |
| 2.  | 0.178       | 0.25                | 9.61                | 38.88                       | 48.74                     | 64.59         | -15.85              | QP      |
| 3.  | 0.214       | 0.29                | 9.61                | 18.33                       | 28.23                     | 53.05         | -24.82              | Average |
| 4.  | 0.214       | 0.29                | 9.61                | 35.04                       | 44.94                     | 63.05         | -18.11              | QP      |
| 5.  | 0.724       | 0.44                | 9.64                | 21.43                       | 31.51                     | 46.00         | -14.49              | Average |
| 6.  | 0.724       | 0.44                | 9.64                | 33.04                       | 43.12                     | 56.00         | -12.88              | QP      |
| 7.  | 1.441       | 0.47                | 9.64                | 21.89                       | 32.00                     | 46.00         | -14.00              | Average |
| 8.  | 1.441       | 0.47                | 9.64                | 35.38                       | 45.49                     | 56.00         | -10.51              | QP      |
| 9.  | 2.167       | 0.47                | 9.64                | 21.91                       | 32.02                     | 46.00         | -13.98              | Average |
| 10. | 2.167       | 0.47                | 9.64                | 33.29                       | 43.40                     | 56.00         | -12.60              | QP      |
| 11. | 2.884       | 0.47                | 9.66                | 21.21                       | 31.34                     | 46.00         | -14.66              | Average |
| 12. | 2.884       | 0.47                | 9.66                | 32.52                       | 42.65                     | 56.00         | -13.35              | QP      |



## 7 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247  
 Test Method : ANSI C63.10:2013  
 Test Result : PASS  
 Measurement Distance : 3m  
 Limit : See the follow table

| Frequency (MHz) | Field Strength        |              | Field Strength Limit at 3m Measurement Dist |                                       |
|-----------------|-----------------------|--------------|---------------------------------------------|---------------------------------------|
|                 | uV/m                  | Distance (m) | uV/m                                        | dBuV/m                                |
| 0.009 ~ 0.490   | $2400/F(\text{kHz})$  | 300          | $10000 * 2400/F(\text{kHz})$                | $20\log^{(2400/F(\text{kHz}))} + 80$  |
| 0.490 ~ 1.705   | $24000/F(\text{kHz})$ | 30           | $100 * 24000/F(\text{kHz})$                 | $20\log^{(24000/F(\text{kHz}))} + 40$ |
| 1.705 ~ 30      | 30                    | 30           | $100 * 30$                                  | $20\log^{(30)} + 40$                  |
| 30 ~ 88         | 100                   | 3            | 100                                         | $20\log^{(100)}$                      |
| 88 ~ 216        | 150                   | 3            | 150                                         | $20\log^{(150)}$                      |
| 216 ~ 960       | 200                   | 3            | 200                                         | $20\log^{(200)}$                      |
| Above 960       | 500                   | 3            | 500                                         | $20\log^{(500)}$                      |

### 7.1 EUT Operation


Operating Environment :

Temperature : 24.5 °C  
 Humidity : 55.5% RH  
 Atmospheric Pressure : 101.3kPa  
 Test Voltage : DC 3.7V


## 7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.





### 7.3 Spectrum Analyzer Setup

| Spectrum Parameter                    | Setting                                          |
|---------------------------------------|--------------------------------------------------|
| Attenuation                           | Auto                                             |
| Start Frequency                       | 1000 MHz                                         |
| Stop Frequency                        | 10th carrier harmonic                            |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |



## 7.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
  - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
  - 2) Change the antenna polarization and repeat 1) with vertical polarization.
  - 3) Make a hardcopy of the spectrum.
  - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
  - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
  - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
  - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
  - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



## 7.5 Summary of Test Results

### Test Frequency: 9KHz-30MHz

| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission Level<br>(dBuV/m) | Limit 3m<br>(dBuV/m) | Over<br>(dB) |
|----------------|-----------------|----------------------------|----------------------|--------------|
| --             | --              | --                         | --                   | >20          |

#### Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance} / \text{test distance})$  (dB);


Limit line = Specific limits (dBuV) + distance extrapolation factor.

### Test Frequency: 30MHz ~ 1GHz

Please refer to the following test plots, Low Channel (2402MHz) Worst case GFSK for record:



Test plot for Horizontal




| No. | Freq<br>MHz | Cable<br>Loss<br>dB | ANT<br>Factor<br>dB/m | Receiver<br>Reading<br>dBuV | Preamp<br>Factor<br>dB | Emission<br>Level<br>dBuV/m | Limit<br>dBuV/m | Over<br>Limit<br>dB | Remark |
|-----|-------------|---------------------|-----------------------|-----------------------------|------------------------|-----------------------------|-----------------|---------------------|--------|
| 1.  | 30.638      | 1.24                | 11.77                 | 41.72                       | 29.89                  | 24.84                       | 40.00           | -15.16              | QP     |
| 2.  | 39.437      | 1.68                | 12.11                 | 33.13                       | 29.91                  | 17.01                       | 40.00           | -22.99              | QP     |
| 3.  | 82.359      | 2.94                | 8.86                  | 30.51                       | 29.97                  | 12.34                       | 40.00           | -27.66              | QP     |
| 4.  | 165.487     | 4.14                | 13.64                 | 42.34                       | 30.03                  | 30.09                       | 43.50           | -13.41              | QP     |
| 5.  | 284.977     | 5.07                | 13.00                 | 24.10                       | 30.28                  | 11.89                       | 46.00           | -34.11              | QP     |
| 6.  | 515.437     | 6.09                | 17.55                 | 23.99                       | 30.92                  | 16.71                       | 46.00           | -29.29              | QP     |

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Test plot for Vertical



| No. | Freq<br>MHz | Cable<br>Loss<br>dB | ANT<br>Factor<br>dB/m | Receiver<br>Reading<br>dBuV | Preamp<br>Factor<br>dB | Emission<br>Level<br>dBuV/m | Limit<br>dBuV/m | Over<br>Limit<br>dB | Remark |
|-----|-------------|---------------------|-----------------------|-----------------------------|------------------------|-----------------------------|-----------------|---------------------|--------|
| 1.  | 39.437      | 1.68                | 12.11                 | 37.49                       | 29.91                  | 21.37                       | 40.00           | -18.63              | QP     |
| 2.  | 50.409      | 2.09                | 12.10                 | 33.83                       | 29.92                  | 18.10                       | 40.00           | -21.90              | QP     |
| 3.  | 95.093      | 3.18                | 9.11                  | 39.46                       | 29.98                  | 21.77                       | 43.50           | -21.73              | QP     |
| 4.  | 167.237     | 4.16                | 13.50                 | 41.38                       | 30.03                  | 29.01                       | 43.50           | -14.49              | QP     |
| 5.  | 274.194     | 5.00                | 12.85                 | 25.14                       | 30.26                  | 12.73                       | 46.00           | -33.27              | QP     |
| 6.  | 480.528     | 5.97                | 16.65                 | 35.84                       | 30.86                  | 27.60                       | 46.00           | -18.40              | QP     |

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



### Test Frequency 1GHz-25GHz

| Test Mode: CH00 |                   |                       |                 |                    | Test channel: Lowest |                |                 |      |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------------|----------------|-----------------|------|
| Peak Value      |                   |                       |                 |                    |                      |                |                 |      |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m)       | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4804            | 49.68             | 34.04                 | 6.58            | 34.09              | 56.21                | 74             | -17.79          | V    |
| 7206            | 47.52             | 37.11                 | 7.73            | 34.5               | 57.86                | 74             | -16.14          | V    |
| 9608            | 43.05             | 39.31                 | 9.23            | 34.79              | 56.8                 | 74             | -17.2           | V    |
| 4804            | 46.67             | 34.04                 | 6.58            | 34.09              | 53.2                 | 74             | -20.8           | H    |
| 7206            | 45.24             | 37.11                 | 7.73            | 34.5               | 55.58                | 74             | -18.42          | H    |
| 9608            | 44.07             | 39.31                 | 9.23            | 34.79              | 57.82                | 74             | -16.18          | H    |
| Average Value   |                   |                       |                 |                    |                      |                |                 |      |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m)       | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4804            | 33.58             | 34.04                 | 6.58            | 34.09              | 40.11                | 54             | -13.89          | V    |
| 7206            | 27.24             | 37.11                 | 7.73            | 34.5               | 37.58                | 54             | -16.42          | V    |
| 9608            | 28.14             | 39.31                 | 9.23            | 34.79              | 41.89                | 54             | -12.11          | V    |
| 4804            | 36.35             | 34.04                 | 6.58            | 34.09              | 42.88                | 54             | -11.12          | H    |
| 7206            | 27.52             | 32.11                 | 7.73            | 34.5               | 32.86                | 54             | -21.14          | H    |
| 9608            | 28.96             | 39.31                 | 9.23            | 34.79              | 42.71                | 54             | -11.29          | H    |



| Test Mode: CH39 |                   |                       |                 |                    | Test channel: Middle |                |                 |      |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------------|----------------|-----------------|------|
| Peak Value      |                   |                       |                 |                    |                      |                |                 |      |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m)       | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4882            | 49.99             | 34.38                 | 6.69            | 34.09              | 56.97                | 74             | -17.03          | V    |
| 7323            | 47.58             | 37.22                 | 7.78            | 34.53              | 58.05                | 74             | -15.95          | V    |
| 9764            | 44.34             | 39.46                 | 9.35            | 34.8               | 58.35                | 74             | -15.65          | V    |
| 4882            | 48.91             | 34.38                 | 6.69            | 34.09              | 55.89                | 74             | -18.11          | H    |
| 7323            | 46.35             | 37.22                 | 7.78            | 34.53              | 56.82                | 74             | -17.18          | H    |
| 9764            | 41.57             | 39.46                 | 9.35            | 34.8               | 55.58                | 74             | -18.42          | H    |
| Average Value   |                   |                       |                 |                    |                      |                |                 |      |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m)       | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4882            | 33.65             | 34.38                 | 6.69            | 34.09              | 40.63                | 54             | -13.37          | V    |
| 7323            | 29.58             | 37.22                 | 7.78            | 34.53              | 40.05                | 54             | -13.95          | V    |
| 9764            | 57.87             | 39.46                 | 9.35            | 34.8               | 71.88                | 54             | 17.88           | V    |
| 4882            | 33.81             | 34.38                 | 6.69            | 34.09              | 40.79                | 54             | -13.21          | H    |
| 7323            | 30.59             | 37.22                 | 7.78            | 34.53              | 41.06                | 54             | -12.94          | H    |
| 9764            | 27.49             | 39.46                 | 9.35            | 34.8               | 41.5                 | 54             | -12.5           | H    |



| Test Mode: CH78 |                   |                       |                 |                    | Test channel: Middle |                |                 |      |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------------|----------------|-----------------|------|
| Peak Value      |                   |                       |                 |                    |                      |                |                 |      |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m)       | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4960            | 49.89             | 34.72                 | 6.79            | 34.09              | 57.31                | 74             | -16.69          | V    |
| 7440            | 48.75             | 37.34                 | 7.82            | 34.57              | 59.34                | 74             | -14.66          | V    |
| 9920            | 43.35             | 39.62                 | 9.46            | 34.81              | 57.62                | 74             | -16.38          | V    |
| 4960            | 47.24             | 34.72                 | 6.79            | 34.09              | 54.66                | 74             | -19.34          | H    |
| 7440            | 46.91             | 37.34                 | 7.82            | 34.57              | 57.5                 | 74             | -16.5           | H    |
| 9920            | 42.58             | 39.62                 | 9.46            | 34.81              | 56.85                | 74             | -17.15          | H    |
| Average Value   |                   |                       |                 |                    |                      |                |                 |      |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m)       | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4960            | 35.26             | 34.72                 | 6.79            | 34.09              | 42.68                | 54             | -11.32          | V    |
| 7440            | 30.24             | 37.34                 | 7.82            | 34.57              | 40.83                | 54             | -13.17          | V    |
| 9920            | 28.15             | 39.62                 | 9.46            | 34.81              | 42.42                | 54             | -11.58          | V    |
| 4960            | 32.26             | 34.72                 | 6.79            | 34.09              | 39.68                | 54             | -14.32          | H    |
| 7440            | 30.91             | 37.34                 | 7.82            | 34.57              | 41.5                 | 54             | -12.5           | H    |
| 9920            | 28.58             | 39.62                 | 9.46            | 34.81              | 42.85                | 54             | -11.15          | H    |

Note: 1. The testing has been conformed to  $10 \times 2480 \text{ MHz} = 24800 \text{ MHz}$ .

2. All other emissions more than 30dB below the limit.

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit



## Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Bluetooth (GFSK, Pi/4-DQPSK, 8DPSK, Hopping)mode have been tested, and the worst result(GFSK, Hopping) was report as below

| Test Mode: Low Channel 2402MHz |                   |                       |                 |                    |                |                |           |              |            |
|--------------------------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------|--------------|------------|
| Frequency (MHz)                | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over (dB) | Polarity H/V | Test Value |
| 2390                           | 51.25             | 29.15                 | 3.41            | 34.01              | 49.8           | 74             | -24.2     | H            | Peak       |
| 2400                           | 58.33             | 29.16                 | 3.43            | 34.01              | 56.91          | 74             | -17.09    | H            | Peak       |
| 2390                           | 45.24             | 29.15                 | 3.41            | 34.01              | 43.79          | 74             | -30.21    | V            | Peak       |
| 2400                           | 58.99             | 29.16                 | 3.43            | 34.01              | 57.57          | 74             | -16.43    | V            | Peak       |
| 2390                           | 37.58             | 29.15                 | 3.41            | 34.01              | 36.13          | 54             | -17.87    | H            | AV         |
| 2400                           | 43.38             | 29.16                 | 3.43            | 34.01              | 41.96          | 54             | -12.04    | H            | AV         |
| 2390                           | 37.24             | 29.15                 | 3.41            | 34.01              | 35.79          | 54             | -18.21    | V            | AV         |
| 2400                           | 42.58             | 29.16                 | 3.43            | 34.01              | 41.16          | 54             | -12.84    | V            | AV         |

| Test Mode: High Channel 2480MHz |                   |                       |                 |                    |                |                |           |              |            |
|---------------------------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------|--------------|------------|
| Frequency (MHz)                 | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over (dB) | Polarity H/V | Test Value |
| 2483.5                          | 57.82             | 30.25                 | 3.53            | 34.03              | 57.57          | 74             | -16.43    | H            | Peak       |
| 2500                            | 43.52             | 28.88                 | 3.56            | 34.03              | 41.93          | 74             | -32.07    | H            | Peak       |
| 2483.5                          | 56.56             | 30.61                 | 3.53            | 34.03              | 56.67          | 74             | -17.33    | V            | Peak       |
| 2500                            | 41.52             | 29.05                 | 3.56            | 34.03              | 40.1           | 74             | -33.9     | V            | Peak       |
| 2483.5                          | 44.91             | 30.28                 | 3.53            | 34.03              | 44.69          | 54             | -9.31     | H            | AV         |
| 2500                            | 39.82             | 29.3                  | 3.56            | 34.03              | 38.65          | 54             | -15.35    | H            | AV         |
| 2483.5                          | 43.79             | 29.28                 | 3.53            | 34.03              | 42.57          | 54             | -11.43    | V            | AV         |
| 2500                            | 39.81             | 29.3                  | 3.56            | 34.03              | 38.64          | 54             | -15.36    | V            | AV         |




## 8 Maximum Peak Output Power Test

### 8.1 Test Standard and Limit

|               |                                    |
|---------------|------------------------------------|
| Test Standard | FCC Part15 C Section 15.247 (b)(3) |
| Test Limit    | 125mW                              |

### 8.2 Test Setup



### 8.3 Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
2. Spectrum Setting:
  - RBW > the 20 dB bandwidth of the emission being measured
  - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
  - VBW  $\geq$  RBW
  - Sweep = auto
  - Detector function = peak
  - Trace = max hold

### 8.4 Test Data

|              |   |                        |             |   |                  |
|--------------|---|------------------------|-------------|---|------------------|
| Test Item    | : | Max. peak output power | Test Mode   | : | CH Low ~ CH High |
| Test Voltage | : | DC 3.7V                | Temperature | : | 24.5°C           |
| Test Result  | : | PASS                   | Humidity    | : | 55%RH            |



Report No.: PTC21110401603E-FC01

| Channel Frequency<br>(MHz) | Peak Power output<br>(dBm) | Limit<br>(dBm) | Results | Modulation |
|----------------------------|----------------------------|----------------|---------|------------|
| 2402                       | 3.854                      | 20.96          | PASS    | BDR        |
| 2441                       | 3.559                      | 20.96          | PASS    | BDR        |
| 2480                       | 3.490                      | 20.96          | PASS    | BDR        |
| 2402                       | 3.904                      | 20.96          | PASS    | EDR        |
| 2441                       | 3.587                      | 20.96          | PASS    | EDR        |
| 2480                       | 3.490                      | 20.96          | PASS    | EDR        |

Remark: The EDR was tested on ( $\pi/4$ DQPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages.



Test Mode: GFSKK ---Low



Report No.: PTC21110401603E-FC01



Test Mode: GFSK ---Middle



Test Mode: GFSK ---High



Report No.: PTC21110401603E-FC01



Test Mode: 8DPSK---Low





Report No.: PTC21110401603E-FC01

Test Mode: 8DPSK ---Middle



Test Mode: 8DPSK ---High




## 9 20DB Occupy Bandwidth Test

### 9.1 Test Standard

|               |                                    |
|---------------|------------------------------------|
| Test Standard | FCC Part15 C Section 15.247 (a)(1) |
|---------------|------------------------------------|

### 9.2 Test Setup



### 9.3 Test Procedure

Using the following spectrum analyzer settings:

1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

### 9.4 Test Data

|              |   |         |             |   |                  |
|--------------|---|---------|-------------|---|------------------|
| Test Item    | : | 20dB BW | Test Mode   | : | CH Low ~ CH High |
| Test Voltage | : | DC 3.7V | Temperature | : | 24.5°C           |
| Test Result  | : | PASS    | Humidity    | : | 55%RH            |



| Channel | Frequency(MHz) | 20dB Down BW(KHz) | Modulation Mode |
|---------|----------------|-------------------|-----------------|
| Low     | 2402           | 859.3             | BDR             |
| Middle  | 2441           | 862.2             | BDR             |
| High    | 2480           | 860.7             | BDR             |
| Low     | 2402           | 1226              | EDR             |
| Middle  | 2441           | 1224              | EDR             |
| High    | 2480           | 1222              | EDR             |


Remark: The EDR was tested on ( $\pi/4$ DQPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages.



Test Mode: GFSK ---Low



Report No.: PTC21110401603E-FC01



Test Mode: GFSK ---Middle




Test Mode: GFSK ---High



Report No.: PTC21110401603E-FC01



Test Mode: 8DPSK---Low



Test Mode: 8DPSK ---Middle



Report No.: PTC21110401603E-FC01



Test Mode: 8DPSK ---High




## 10 Carrier Frequency Separation Test

### 10.1 Test Standard and Limit

|               |                                              |
|---------------|----------------------------------------------|
| Test Standard | FCC Part15 C Section 15.247 (a)(1)           |
| Test Limit    | >25KHz or >two-thirds of the 20 dB bandwidth |

### 10.2 Test Setup



### 10.3 Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

### 10.4 Test Data

|              |   |                      |             |   |                  |
|--------------|---|----------------------|-------------|---|------------------|
| Test Item    | : | Frequency Separation | Test Mode   | : | CH Low ~ CH High |
| Test Voltage | : | DC 3.7V              | Temperature | : | 24.5°C           |
| Test Result  | : | PASS                 | Humidity    | : | 55%RH            |



Report No.: PTC21110401603E-FC01

| Channel | Frequency<br>(MHz) | Separation Read<br>Value (kHz) | Limit<br>(kHz) | Modulation<br>Mode |
|---------|--------------------|--------------------------------|----------------|--------------------|
| Low     | 2402               | 1010                           | 572.867        | BDR                |
| Middle  | 2441               | 1026                           | 574.800        | BDR                |
| High    | 2480               | 1020                           | 573.800        | BDR                |
| Low     | 2402               | 1004                           | 817.333        | EDR                |
| Middle  | 2441               | 1001                           | 816.000        | EDR                |
| High    | 2480               | 994.0                          | 814.667        | EDR                |

Remark: 1. The EDR was tested on ( $\pi/4$ DQPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages.

2. The limit of mode (EDR) is 2/3 of 20dB BW.



Test Mode: GFSK ---Low




Test Mode: GFSK ---Middle




Test Mode: GFSK ---High



Report No.: PTC21110401603E-FC01



Test Mode: 8DPSK---Low



Test Mode: 8DPSK ---Middle



Report No.: PTC21110401603E-FC01



Test Mode: 8DPSK --High




## 11 Number of Hopping Channel Test

### 11.1 Test Standard and Limit

|               |                                    |
|---------------|------------------------------------|
| Test Standard | FCC Part15 C Section 15.247 (a)(1) |
| Test Limit    | >15 channels                       |

### 11.2 Test Setup



### 11.3 Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:


1. Span= the frequency band of operation
2. Set the RBW = 1000kHz.
3. Set the VBW = 1000kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.



## 11.4 Test Data


|              |                               |             |                    |
|--------------|-------------------------------|-------------|--------------------|
| Test Item    | : Number of Hopping Frequency | Test Mode   | : CH Low ~ CH High |
| Test Voltage | : DC 3.7V                     | Temperature | : 24.5°C           |
| Test Result  | : PASS                        | Humidity    | : 55%RH            |

| Hopping Channel Frequency Range             | Quantity of Hopping Channel | Quantity of Hopping Channel |
|---------------------------------------------|-----------------------------|-----------------------------|
| 2402-2480MHz                                | 79                          | > 15                        |
| Remark: The EDR was tested on (8DPSK) modes |                             |                             |





Report No.: PTC21110401603E-FC01






## 12 Dwell Time Test

### 12.1 Test Standard and Limit

|               |                                    |
|---------------|------------------------------------|
| Test Standard | FCC Part15 C Section 15.247 (a)(1) |
| Test Limit    | 0.4 sec                            |

### 12.2 Test Setup



### 12.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:


1. Span= zero span, centered on a hopping channel
2. Set the RBW = 1 MHz.
3. Set the VBW = 1 MHz.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.



## 12.4 Test Data

|              |                     |             |                    |
|--------------|---------------------|-------------|--------------------|
| Test Item    | : Time of Occupancy | Test Mode   | : CH Low ~ CH High |
| Test Voltage | : DC 3.7V           | Temperature | : 24.5°C           |
| Test Result  | : PASS              | Humidity    | : 55%RH            |

| Package Type                                                                                                                    | Pulse width (ms) | Time slot length(ms)                | Dwell time (ms) | Limit (s) | Modulation |
|---------------------------------------------------------------------------------------------------------------------------------|------------------|-------------------------------------|-----------------|-----------|------------|
| 3DH1                                                                                                                            | 0.406            | time slot length *1600/2 /79 * 31.6 | 130.0           | 0.4       | EDR        |
| 3DH3                                                                                                                            | 1.668            | time slot length *1600/4 /79 * 31.6 | 267.0           | 0.4       | EDR        |
| 3DH5                                                                                                                            | 2.910            | time slot length *1600/6 /79 * 31.6 | 310.0           | 0.4       | EDR        |
| Remark: The EDR was tested on ( $\pi/4$ DQPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages. |                  |                                     |                 |           |            |



Test Mode: EDR---3DH1



Report No.: PTC21110401603E-FC01



Test Mode: EDR---3DH3




Test Mode: EDR---  
3DH5

### 3 100kHz Bandwidth of Frequency Band Edge Requirement

#### 13.1 Test Standard and Limit

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Standard | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Test Limit    | in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a). |

#### 13.2 Test Setup



#### 13.3 Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:

1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.




### 13.4 Test Data

Test Item : Band edge  
Test Voltage : DC 3.7V  
Test Result : PASS

Test Mode : CH Low ~ CH High  
Temperature : 24.5°C  
Humidity : 55%RH


Remark: The EDR was tested on ( $\pi/4$ DQPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages.




For GFSK Non-Hopping Mode (Low)



Report No.: PTC21110401603E-FC01




For GFSK Hopping Mode (Low)




For GFSK Non-Hopping Mode (High)



Report No.: PTC21110401603E-FC01




### For GFSK Hopping Mode (High)




### For 8DPSK NonHopping Mode (Low)



Report No.: PTC21110401603E-FC01




For 8DPSK Hopping Mode (Low)



For 8DPSK Non-Hopping Mode (High)




Report No.: PTC21110401603E-FC01



For 8DPSK Hopping Mode (High)




## Conducted Emission Method






Report No.: PTC21110401603E-FC01



Test Mode: EDR---Mid



Test Mode: EDR--High



## 14 Antenna Requirement

### 14.1 Test Standard and Requirement

| Test Standard | FCC Part15 Section 15.203 /247(c)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Requirement   | <p>1) 15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement:</p> <p>Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p> |

### 14.2 Antenna Connected Construction


The antenna is PIFA Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.

## 15 APPENDIX I -- TEST SETUP PHOTOGRAPH

Conducted Emissions




Radiated Emissions  
From 30M-1GHz





Report No.: PTC21110401603E-FC01

Above 1GHz



## 16 APPENDIX II -- EXTERNAL PHOTOGRAPH



















## 17 APPENDIX III -- INTERNAL PHOTOGRAPH











\*\*\*\*\*THE END REPORT\*\*\*\*\*