


What's in box




Product introduction




Download and install APP



First use



Power on




Pairing




Binding APP



Disconnect



Reconnect



Warranty card

Warranty card form with fields for User Name, TEL, Address, Seller, Seller Tel, Seller Add, Date of purchase, Date of expiration, and Maintenance time.

Email: カスタマーサービスのメールアドレス/Email de servicio al cliente
Электронная почта службы поддержки клиентов/
Email: xiaodufanyuyue@163.com parshidmatan palanggan/Email ng
Customer Service
xiaodufanyuyue@163.com

The diagram shows a USB-C cable with a power icon (a circle with a lightning bolt) and a battery level indicator (a battery icon with four segments, three of which are filled). The battery level indicator is labeled "HIGH POWER" and "CHARGING".

The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Xiaodu Technology Limited is under license. Other trademarks and trade names are those of their respective owners.

Product specification	
Do smart buds	XD-S66A16-2321
Model	
Earbuds size:	36*17*13.5mm
Charging case size:	52*54*24mm
Speaker	13mm
Rated power:	
Charging case:	400mAh/5V = 500mAh/3.00V
Earbuds:	35mAh/3.7V = 35mAh/3.6V
Rated impedance:	32Ω
Weight	40g
Bluetooth	5.0
Working temperature	-10℃ ~ +45℃
Working humidity	30% ~ 95%
Working altitude	< 5000m

[illegible][illegible]

Desain awal buku	XD-SWA16A-2121
Numeral no produk	3P1717-248.2mm
Seri terkecil	25-252-248.2mm
Seri terkecil	13mm
Kontak sisi	400mA/5A/5V ~ 300mA/30A/30V
Kontak belakang	250mA/5A/5V ~ 250mA/30A/30V
Impedansi sekunder	250
Berat	250
Blastrofit	50
Suhu kerja	-10 °C ~ +45 °C
Ketahanan beban	10% ~ 95%
Altitude kerja	< 5000m

Espesifikasi yang Produk

Desain awal buku	XD-SWA16A-2121
Numeral no produk	3P1717-248.2mm
Seri terkecil	25-252-248.2mm
Altitude kerja	< 5000m

No-Date no label
 Kaitan pengapung
 Hewan
 No-Date no Impedansi
 Berat
 Blastrofit
 Suhu kerja
 Ketahanan beban
 Altitude kerja

