

## TEST REPORT

**Report No.: 21020728HKG-002**

Duomondi International Development Co., Ltd.

Application For Certification  
(Original Grant)

**FCC ID: 2AZ8Z-DS24**

**IC: 27373-DS24**

Transceiver

**Prepared and Checked by:**

**Approved by:**

Signed On File

Wong Cheuk Ho, Herbert  
Lead Engineer

Wong Kwok Yeung, Kenneth  
Senior Lead Engineer  
Date: July 08, 2021

**TEST REPORT****GENERAL INFORMATION**

<b>Grantee:</b>	Duomondi International Development Co., Ltd.
<b>Grantee Address:</b>	Room D, 19/F., Roxy Industrial Centre, 59-66 Tai Lin Pai Road, Kwai Chung, N.T., Hong Kong.
<b>Contact Person:</b>	Dale Schroeder
<b>Tel:</b>	(852) 24177128
<b>Fax:</b>	(852) 24177138
<b>e-mail:</b>	dale@artsound.com.cn
<b>Brand Name:</b>	DUOMONDI
<b>Model / HVIN:</b>	DS24
<b>PMN:</b>	DS24
<b>Additional Model:</b>	N/A
<b>Type of EUT:</b>	Transceiver
<b>Description of EUT:</b>	Bluetooth Audio Device DUOMONDI DS24
<b>Serial Number:</b>	N/A
<b>FCC ID / IC:</b>	<b>2AZ8Z-DS24 / 27373-DS24</b>
<b>Date of Sample Submitted:</b>	February 11, 2021
<b>Date of Test:</b>	February 11, 2021 to June 04, 2021
<b>Report No.:</b>	21020728HKG-002
<b>Report Date:</b>	July 08, 2021
<b>Environmental Conditions:</b>	Temperature: +10 to 40°C Humidity: 10 to 90%
<b>Conclusion:</b>	Test was conducted by client submitted sample. The submitted sample as received complied with the 47 CFR Part 15 / RSS-210 Issue 10 Certification.

**TEST REPORT****SUMMARY OF TEST RESULT**

Test Specification	Reference	Results
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 8.8	Pass
Radiated Emission	15.249, 15.209 /	Pass
Radiated Emission on the Bandedge	RSS-210 B.10, RSS-210 4.4	
Radiated Emission in Restricted Bands	15.205 / RSS-210 4.1	Pass

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2019 Edition

RSS-210 Issue 10, December 2019

RSS-Gen Issue 5 Amendment 1, March 2019

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.  
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

**TEST REPORT****TABLE OF CONTENTS**

<b>1.0</b>	<b>GENERAL DESCRIPTION</b>	<b>5</b>
1.1	Product Description .....	5
1.2	Related Submittal(s) Grants .....	5
1.3	Test Methodology.....	5
1.4	Test Facility .....	5
<b>2.0</b>	<b>SYSTEM TEST CONFIGURATION</b>	<b>6</b>
2.1	Justification.....	6
2.2	EUT Exercising Software.....	6
2.3	Special Accessories .....	6
2.4	Measurement Uncertainty.....	6
2.5	Support Equipment List and Description.....	6
<b>3.0</b>	<b>EMISSION RESULTS.....</b>	<b>7</b>
3.1	Field Strength Calculation .....	7
3.2	Radiated Emission Configuration Photograph.....	8
3.3	Radiated Emission Data .....	8
3.4	Conducted Emission Configuration Photograph .....	8
3.5	Conducted Emission Data .....	8
<b>4.0</b>	<b>EQUIPMENT PHOTOGRAPHS</b>	<b>17</b>
<b>5.0</b>	<b>PRODUCT LABELLING</b>	<b>17</b>
<b>6.0</b>	<b>TECHNICAL SPECIFICATIONS</b>	<b>17</b>
<b>7.0</b>	<b>INSTRUCTION MANUAL</b>	<b>17</b>
<b>8.0</b>	<b>MISCELLANEOUS INFORMATION</b>	<b>18</b>
8.1	Radiated Emission on the Bandedge.....	18
8.2	Discussion of Pulse Desensitization.....	23
8.3	Calculation of Average Factor .....	23
8.4	Emissions Test Procedures.....	24
8.5	Occupied Bandwidth.....	28
<b>9.0</b>	<b>CONFIDENTIALITY REQUEST</b>	<b>30</b>
<b>10.0</b>	<b>EQUIPMENT LIST</b>	<b>30</b>

## TEST REPORT

### 1.0 GENERAL DESCRIPTION

#### 1.1 Product Description

The Equipment Under Test (EUT) is a Bluetooth Audio Device DUOMONDI DS24. The EUT can accept audio sources including Aux-in and Bluetooth devices. The audio signal is amplified and fed to the passive internal loudspeaker. The EUT is powered by an AC/DC adaptor (24VDC 4.16A output, 100-240VAC 2A 50/60Hz input).

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

#### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **“Justification Section”** of this Application.

#### 1.4 Test Facility

The 3m Chamber and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong SAR, China. This test facility and site measurement data have been placed on file with the FCC and IC No. 2042H.

## TEST REPORT

### 2.0 SYSTEM TEST CONFIGURATION

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by 120VAC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

The EUT exercise program (if any) used during radiated testing was designed to exercise the various system components in a manner similar to a typical use.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Measurement Uncertainty

Decision Rule for compliance: For FCC/IC standard, the measured value must be within the limits of applicable standard without accounting for the measurement uncertainty. For EN/IEC/HKTA/HKTC standard, conformity rules will be used as per standard directly excepted EN/IEC 61000-3-2, EN/IEC 61000-3-3, HKTA1004, HKCA1008, HKTA1019, HKTA1020, HKTA1041 and HKTA1044. For these excepted or not mentioned standards, Cl 4.2.2 of ILAC-G8:09/2019 decision rules will be reference and guard band will be equal to our measurement uncertainty with 95% confidence level (k=2). In case, the measured value is within guard band region, undetermined decision will be used.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

#### 2.5 Support Equipment List and Description

Adaptor (Provided by Applicant)

Model: YHY-24004160

Input: 100-240VAC 2A 50/60Hz

Output: 24VDC 4.16A

## TEST REPORT

### 3.0 EMISSION RESULTS

Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

RA = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

RR = RA - AG - AV in  $\text{dB}\mu\text{V}$

LF = CF + AF in dB

Assume a receiver reading of 52.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V}/\text{m})/20] = 22.4 \mu\text{V}/\text{m}$$

## TEST REPORT

### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 2480.000 MHz

For electronic filing, the worst-case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 0.4 dB

### 3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.384 MHz

For electronic filing, the worst-case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

### 3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by 13.6 dB


## TEST REPORT

### CONDUCTED EMISSION

Model: DS24

Date of Test: June 04, 2021

Worst-Case Operating Mode: Bluetooth Audio Playing



EDIT PEAK LIST (Final Measurement Results)				
Trace1:	CF15MQP			
Trace2:	CF15MAV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dB $\mu$ V	DELTA	LIMIT dB
1	Quasi Peak 150 kHz	47.09	N	-18.90
2	CISPR Average 154.5 kHz	35.35	L1	-20.39
1	Quasi Peak 217.5 kHz	39.09	L1	-23.81
2	CISPR Average 384 kHz	34.56	L1	-13.62
1	Quasi Peak 388.5 kHz	40.80	N	-17.29
2	CISPR Average 411 kHz	32.23	L1	-15.39
1	Quasi Peak 415.5 kHz	36.64	L1	-20.89
1	Quasi Peak 829.5 kHz	30.41	N	-25.58
1	Quasi Peak 1.653 MHz	33.31	N	-22.68
1	Quasi Peak 11.5755 MHz	37.26	N	-22.73

 Note: Measurement Uncertainty is  $\pm 4.2$ dB at a level of confidence 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: DS24

Date of Test: June 04, 2021

Worst-Case Operating Mode: Transmitting (Bluetooth 3.0)

**Table 1**  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement**

Lowest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2402.000	94.0	33	29.4	90.4	94.0	-3.6
V	4804.000	45.9	33	34.9	47.8	54.0	-6.2
H	7206.000	46.5	33	37.9	51.4	54.0	-2.6
H	9608.000	42.8	33	40.4	50.2	54.0	-3.8
H	12010.000	43.1	33	40.5	50.6	54.0	-3.4
V	14412.000	44.2	33	40.0	51.2	54.0	-2.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2402.000	105.8	33	29.4	102.2	114.0	-11.8
V	4804.000	51.3	33	34.9	53.2	74.0	-20.8
H	7206.000	48.3	33	37.9	53.2	74.0	-20.8
H	9608.000	45.0	33	40.4	52.4	74.0	-21.6
H	12010.000	45.9	33	40.5	53.4	74.0	-20.6
V	14412.000	45.5	33	40.0	52.5	74.0	-21.5

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 4.1.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

Model: DS24

Date of Test: June 04, 2021

Worst-Case Operating Mode: Transmitting (Bluetooth 3.0)

**Table 2**  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement**

Middle Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2440.000	94.4	33	29.4	90.8	94.0	-3.2
V	4880.000	46.5	33	34.9	48.4	54.0	-5.6
H	7320.000	46.3	33	37.9	51.2	54.0	-2.8
H	9760.000	43.0	33	40.4	50.4	54.0	-3.6
H	12200.000	43.1	33	40.5	50.6	54.0	-3.4
V	14640.000	45.8	33	38.4	51.2	54.0	-2.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2440.000	106.0	33	29.4	102.4	114.0	-11.6
V	4880.000	50.7	33	34.9	52.6	74.0	-21.4
H	7320.000	48.6	33	37.9	53.5	74.0	-20.5
H	9760.000	45.0	33	40.4	52.4	74.0	-21.6
H	12200.000	44.9	33	40.5	52.4	74.0	-21.6
V	14640.000	47.0	33	38.4	52.4	74.0	-21.6

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 4.1.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

Model: DS24

Date of Test: June 04, 2021

Worst-Case Operating Mode: Transmitting (Bluetooth 3.0)

Table 3  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement**

Highest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2480.000	96.2	33	29.4	92.6	94.0	-1.4
V	4960.000	46.5	33	34.9	48.4	54.0	-5.6
H	7440.000	46.3	33	37.9	51.2	54.0	-2.8
H	9920.000	43.1	33	40.4	50.5	54.0	-3.5
H	12400.000	43.1	33	40.5	50.6	54.0	-3.4
V	14880.000	45.9	33	38.4	51.3	54.0	-2.7

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2480.000	107.8	33	29.4	104.2	114.0	-9.8
V	4960.000	51.9	33	34.9	53.8	74.0	-20.2
H	7440.000	48.5	33	37.9	53.4	74.0	-20.6
H	9920.000	44.8	33	40.4	52.2	74.0	-21.8
H	12400.000	45.9	33	40.5	53.4	74.0	-20.6
V	14880.000	47.0	33	38.4	52.4	74.0	-21.6

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 4.1.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

Model: DS24

Date of Test: June 04, 2021

Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE)

**Table 4**  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement**

Lowest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2402.000	96.0	33	29.4	92.4	94.0	-1.6
V	4804.000	46.3	33	34.9	48.2	54.0	-5.8
H	7206.000	46.5	33	37.9	51.4	54.0	-2.6
H	9608.000	43.0	33	40.4	50.4	54.0	-3.6
H	12010.000	42.9	33	40.5	50.4	54.0	-3.6
V	14412.000	44.2	33	40.0	51.2	54.0	-2.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2402.000	107.8	33	29.4	104.2	114.0	-9.8
V	4804.000	51.3	33	34.9	53.2	74.0	-20.8
H	7206.000	48.5	33	37.9	53.4	74.0	-20.6
H	9608.000	45.4	33	40.4	52.8	74.0	-21.2
H	12010.000	45.9	33	40.5	53.4	74.0	-20.6
V	14412.000	45.8	33	40.0	52.8	74.0	-21.2

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 4.1.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

Model: DS24

Date of Test: June 04, 2021

Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE)

**Table 5**  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement**

Middle Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2440.000	97.1	33	29.4	93.5	94.0	-0.5
V	4880.000	46.3	33	34.9	48.2	54.0	-5.8
H	7320.000	46.3	33	37.9	51.2	54.0	-2.8
H	9760.000	43.0	33	40.4	50.4	54.0	-3.6
H	12200.000	42.9	33	40.5	50.4	54.0	-3.6
V	14640.000	45.8	33	38.4	51.2	54.0	-2.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2440.000	109.0	33	29.4	105.4	114.0	-8.6
V	4880.000	50.3	33	34.9	52.2	74.0	-21.8
H	7320.000	48.5	33	37.9	53.4	74.0	-20.6
H	9760.000	45.2	33	40.4	52.6	74.0	-21.4
H	12200.000	44.9	33	40.5	52.4	74.0	-21.6
V	14640.000	47.0	33	38.4	52.4	74.0	-21.6

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 4.1.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

Model: DS24

Date of Test: June 04, 2021

Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE)

Table 6  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 B10.0 Requirement**

Highest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2480.000	97.2	33	29.4	93.6	94.0	-0.4
V	4960.000	46.3	33	34.9	48.2	54.0	-5.8
H	7440.000	46.3	33	37.9	51.2	54.0	-2.8
H	9920.000	43.4	33	40.4	50.8	54.0	-3.2
H	12400.000	43.1	33	40.5	50.6	54.0	-3.4
V	14880.000	45.8	33	38.4	51.2	54.0	-2.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2480.000	110.4	33	29.4	106.8	114.0	-7.2
V	4960.000	51.3	33	34.9	53.2	74.0	-20.8
H	7440.000	48.5	33	37.9	53.4	74.0	-20.6
H	9920.000	45.4	33	40.4	52.8	74.0	-21.2
H	12400.000	45.9	33	40.5	53.4	74.0	-20.6
V	14880.000	47.2	33	38.4	52.6	74.0	-21.4

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 4.1.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

Model: DS24

Date of Test: June 04, 2021

Worst-Case Operating Mode: Bluetooth Audio Playing

Table 7  
**Pursuant to FCC Part 15 Section 15.209 / RSS-210 4.4 Requirement**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	48.766	40.8	16	11.0	35.8	40.0	-4.2
V	150.498	34.2	16	14.0	32.2	43.5	-11.3
V	383.922	29.6	16	24.0	37.6	46.0	-8.4
V	390.016	24.8	16	25.0	33.8	46.0	-12.2
V	396.232	28.4	16	25.0	37.4	46.0	-8.6
H	914.444	14.4	16	33.0	31.4	46.0	-14.6

NOTES: 1. Quasi-Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 4.1.
6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### 4.0 EQUIPMENT PHOTOGRAPHS

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 PRODUCT LABELLING

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 6.0 TECHNICAL SPECIFICATIONS

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 INSTRUCTION MANUAL

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States and Canada.

## TEST REPORT

### 8.0 MISCELLANEOUS INFORMATION

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).



#### 8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10 (2013) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209 / RSS-210 4.4, whichever is the lesser attenuation, which meet the requirement of part 15.249(d) / RSS-210 B.10.

## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 3.0)



## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 3.0)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=102.2 \text{ dB}\mu\text{V/m} - 51.4 \text{ dB}$$

$$=50.8 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=90.4 \text{ dB}\mu\text{V/m} - 51.4 \text{ dB}$$

$$=39.0 \text{ dB}\mu\text{V/m}$$

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=104.2 \text{ dB}\mu\text{V/m} - 60.9 \text{ dB}$$

$$=43.3 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot



$$=92.6 \text{ dB}\mu\text{V/m} - 60.9 \text{ dB}$$

$$=31.7 \text{ dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in Section 15.209 / RSS-210 4.4, which does not exceed 74 dB $\mu$ V/m (Peak Limit) and 54 dB $\mu$ V/m (Average Limit).

## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE)



## TEST REPORT

### PEAK MEASUREMENT (Bluetooth 4.0 BLE)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=104.2 \text{ dB}\mu\text{V/m} - 52.3 \text{ dB}$$

$$=51.9 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=92.4 \text{ dB}\mu\text{V/m} - 52.3 \text{ dB}$$

$$=40.1 \text{ dB}\mu\text{V/m}$$

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=106.8 \text{ dB}\mu\text{V/m} - 60.2 \text{ dB}$$

$$=46.6 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=93.6 \text{ dB}\mu\text{V/m} - 60.2 \text{ dB}$$

$$=33.4 \text{ dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in Section 15.209 / RSS-210 4.4, which does not exceed 74 dB $\mu$ V/m (Peak Limit) and 54 dB $\mu$ V/m (Average Limit).

## TEST REPORT

### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 625 $\mu$ s for a digital “1” bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 3MHz, so the pulse desensitivity factor is 0dB.

### 8.3 Calculation of Average Factor

N/A.

## TEST REPORT

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

## TEST REPORT

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


## TEST REPORT

### 8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz


## TEST REPORT

### 8.4.2 Conducted Emission Test Procedures

For tabletop equipment, the EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table. For floor-standing equipment, the EUT and all cables were insulated, if required, from the ground plane by up to 12 mm of insulating material. The EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were moved to find the maximum emission.

### 8.4.3 Conducted Emission Test Setup




## TEST REPORT

### 8.5 Occupied Bandwidth

#### Occupied Bandwidth Results: (Bluetooth 3.0)

Bluetooth (MHz)	Occupied Bandwidth (kHz)
Low Channel: 2402	846
Middle Channel: 2440	852
High Channel: 2480	858

The worst case is shown as below




## TEST REPORT

### 8.5 Occupied Bandwidth (Cont'd)

#### Occupied Bandwidth Results: (Bluetooth 4.0 BLE)

Bluetooth (MHz)	Occupied Bandwidth (<Hz)
Low Channel: 2402	1.026
Middle Channel: 2440	1.032
High Channel: 2480	1.038

The worst case is shown as below



## TEST REPORT

### 9.0 CONFIDENTIALITY REQUEST

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

### 10.0 EQUIPMENT LIST

#### 1) Radiated Emissions Test

Equipment	EMI Test Receiver	14m Double Shield RF Cable (20MHz To 6GHz)	RF Cable 14m (1GHz to 26.5GHz)
Registration No.	EW-3156	EW-2074	EW-2781
Manufacturer	ROHDE SCHWARZ	RADIALL	GREATBILLION
Model No.	ESR26	nm / RG142 / sma 14m	SMA m/SHF5MPU /SMA m ra14m,26G
Calibration Date	January 25, 2021	August 29, 2020	November 24, 2020
Calibration Due Date	January 25, 2022	August 29, 2021	November 24, 2021

Equipment	Solid State Low Noise Preamplifier Assembly (1 - 18)GHz	12 metre RF Cable 40GHz	Double Ridged Guide Antenna
Registration No.	EW-3431	EW-2774	EW-0194
Manufacturer	BONN ELEKTRO	GREATBILLION	EMCO
Model No.	BBV 9718 BBV9744 BBV 9721	SMA m-m ra 12m 40G outdoor	3115
Calibration Date	November 18, 2020	September 12, 2020	June 03, 2021
Calibration Due Date	November 18, 2021	September 12, 2021	June 03, 2022

Equipment	Biconical Antenna 20MHz to 200MHz	Active Loop H-field (9kHz to 30MHz)	Spectrum Analyzer
Registration No.	EW-2512	EW-2313	EW-2466
Manufacturer	EMCO	ELECTROMETRI	ROHDE SCHWARZ
Model No.	3104C	EM-6876	FSP30
Calibration Date	June 03, 2020	December 17, 2019	September 05, 2020
Calibration Due Date	December 03, 2021	June 17, 2021	September 05, 2021

## TEST REPORT

### 2) Conducted Emissions Test

Equipment	EMI Test Receiver	RF Cable 80cm (RG142) (9kHz to 30MHz)	Artificial Mains Network
Registration No.	EW-2251	EW-2452	EW-2501
Manufacturer	ROHDE SCHWARZ	RADIALL	ROHDE SCHWARZ
Model No.	ESCI	bnc m st / 142 / bnc m st 80cm	ENV-216
Calibration Date	January 29, 2021	November 10, 2020	September 11, 2020
Calibration Due Date	January 29, 2022	November 10, 2021	September 11, 2021

### 3) Bandedge/Bandwidth Measurement

Equipment	RF Cable (up to 40GHz) 1.5m length	Spectrum Analyzer
Registration No.	EW-2774	EW-2466
Manufacturer	N/A	ROHDE SCHWARZ
Model No.	SMA-M to SMA-M	FSP30
Calibration Date	September 12, 2020	September 05, 2020
Calibration Due Date	September 12, 2021	September 05, 2021

**END OF TEST REPORT**