



RF Exposure Evaluation

For

1311949 Ontario Inc. operating as Jannatec Technologies

In-Vehicle Display Terminal

Test Model: VT-7A

Prepared for : 1311949 Ontario Inc. operating as Jannatec Technologies
Address : 1545 Maley Drive Jannatec Technologies Sudbury, ON P3A 4R7 Canada

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 27, 2025
Number of tested samples : 2
Sample No. : A250526027-1, A250526027-2
Serial number : Prototype
Date of Test : May 27, 2025 ~ June 23, 2025
Date of Report : June 24, 2025





RF Exposure Evaluation	
Report Reference No.	LCSA05265037EH
Date of Issue.....	June 24, 2025
Testing Laboratory Name	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address.....	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure.....	Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>
Applicant's Name	1311949 Ontario Inc. operating as Jannatec Technologies
Address.....	1545 Maley Drive Jannatec Technologies Sudbury, ON P3A 4R7 Canada
Test Specification	
Standard.....	FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091
Test Report Form No.	TRF-4-E-215 A/0
TRF Originator.....	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF.....	Dated 2011-03
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description	In-Vehicle Display Terminal
Trade Mark.....	N/A
Test Model.....	VT-7A
Ratings.....	Please Refer to Page 6
Result	Positive

Compiled by:

Ling Zhu/ Administrator

Supervised by:

Jack Liu / Technique principal

Approved by:

Gavin Liang/ Manager





RF Exposure Evaluation

Test Report No. : LCSA05265037EH	<u>June 24, 2025</u> Date of issue
---	---------------------------------------

EUT.....	: In-Vehicle Display Terminal
Test Model.....	: VT-7A
Applicant.....	: 1311949 Ontario Inc. operating as Jannatec Technologies
Address.....	: 1545 Maley Drive Jannatec Technologies Sudbury, ON P3A 4R7 Canada
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: ZHANGZHOU 3RTABLET TECHNOLOGY CO., LTD.
Address.....	: NO.26 FU QI NORTH ROAD, LONG WEN DISTRICT, ZHANG ZHOU, FU JIAN, CHINA
Telephone.....	: /
Fax.....	: /
Factory.....	: ZHANGZHOU 3RTABLET TECHNOLOGY CO., LTD.
Address.....	: NO.26 FU QI NORTH ROAD, LONG WEN DISTRICT, ZHANG ZHOU, FU JIAN, CHINA
Telephone.....	: /
Fax.....	: /

Test Result	Pass
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	June 24, 2025	Initial Issue	---





TABLE OF CONTENTS

Description	Page
1. Product Information	6
2. Evaluation Method	8
3. Limit	8
4. MPE Calculation Method	9
5. Conducted Power	9
6. Measurement Results	12
7. Conclusion	14
8. Description of Test Facility	14
9. Measurement Uncertainty	14





1. Product Information

EUT	: In-Vehicle Display Terminal
Test Model	: VT-7A
Ratings	: Input: 9-36V $\overline{=}$ 1500mA
Hardware Version	: VT-7A_V003
Software Version	: V1.6.7
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	: V5.0
Antenna Description	: Internal Antenna, 3.81dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 3.81dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 3.54dBi(Max.)
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)





Antenna Description : Internal Antenna, 4.43dBi(Max.)

LTE :

- Support Band : E-UTRA Band 2(U.S.-Band)
- E-UTRA Band 4(U.S.-Band)
- E-UTRA Band 5(U.S.-Band)
- E-UTRA Band 7(U.S.-Band)
- E-UTRA Band 12(U.S.-Band)
- E-UTRA Band 13(U.S.-Band)
- E-UTRA Band 14(U.S.-Band)
- E-UTRA Band 17(U.S.-Band)
- E-UTRA Band 25(U.S.-Band)
- E-UTRA Band 26(U.S.-Band)
- E-UTRA Band 41(U.S.-Band)
- E-UTRA Band 66(U.S.-Band)
- E-UTRA Band 71(U.S.-Band)

LTE Release Version : R11

Type Of Modulation : QPSK/16QAM

- Antenna Description : Internal Antenna
- 3.02dBi (max.) For E-UTRA Band 2
- 3.24dBi (max.) For E-UTRA Band 4
- 1.32dBi (max.) For E-UTRA Band 5
- 1.21dBi (max.) For E-UTRA Band 7
- 1.6dBi (max.) For E-UTRA Band 12
- 1.87dBi (max.) For E-UTRA Band 13
- 1.7dBi (max.) For E-UTRA Band 14
- 1.6dBi (max.) For E-UTRA Band 17
- 3.02dBi (max.) For E-UTRA Band 25
- 1.32dBi (max.) For E-UTRA Band 26
- 1.21dBi (max.) For E-UTRA Band 41
- 3.24dBi (max.) For E-UTRA Band 66
- 1.35dBi (max.) For E-UTRA Band 71

Power Class : Class 3

NFC :

Operating Frequency : 13.56MHz

Modulation Type : ASK

Antenna Description : Internal Antenna, 0dBi(Max.)

Exposure category : General population/uncontrolled environment

EUT Type : Production Unit

Device Type : Mobile Device

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.





2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density





4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)	ANT Max. Tune Up Power (dBm)
GFSK	0	2402	-0.97	0±1.0
	39	2441	-0.71	0±1.0
	78	2480	-1.78	-1.0±1.0
π/4DQPSK	0	2402	0.85	0±1.0
	39	2441	1.08	-1.0±1.0
	78	2480	-0.02	0±1.0
8DPSK	0	2402	1.29	1.0±1.0
	19	2441	1.56	1.0±1.0
	39	2480	0.43	0±1.0

[BT LE 1M]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)	ANT Max. Tune Up Power (dBm)
GFSK	0	2402	1.03	1.0±1.0
	19	2440	0.69	0±1.0
	39	2480	-0.33	0±1.0

[2.4G WIFI Max Peak Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)	ANT Max. Tune Up Power (dBm)
IEEE 802.11b	1	2412	15.05	15.0±1.0
	6	2437	14.47	14.0±1.0
	11	2462	13.99	13.0±1.0
IEEE 802.11g	1	2412	14.21	14.0±1.0
	6	2437	13.52	13.0±1.0
	11	2462	13.34	13.0±1.0
IEEE 802.11n HT20	1	2412	14.78	14.0±1.0
	6	2437	14.19	14.0±1.0
	11	2462	13.98	13.0±1.0
IEEE 802.11n HT40	3	2422	13.47	13.0±1.0
	6	2437	13.36	13.0±1.0
	9	2452	13.97	13.0±1.0





[5.2G WIFI Max Average Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)	ANT Max. Tune Up Power (dBm)
11A	36	5180	12.27	12.0±1.0
	40	5200	11.93	11.0±1.0
	48	5240	11.62	11.0±1.0
11N20 SISO	36	5180	11.61	11.0±1.0
	40	5200	11.6	11.0±1.0
	48	5240	10.69	10.0±1.0
11N40 SISO	38	5190	11.3	11.0±1.0
	46	5230	9.8	9.0±1.0
11AC20 SISO	36	5180	11.51	11.0±1.0
	40	5200	11.59	11.0±1.0
	48	5240	10.85	10.0±1.0
11AC40 SISO	38	5190	11.29	11.0±1.0
	46	5230	9.85	9.0±1.0
11AC80 SISO	42	5210	10.83	10.0±1.0

[5.8G WIFI Max Average Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)	ANT Max. Tune Up Power (dBm)
11A	149	5745	12.49	12.0±1.0
	157	5785	11.56	11.0±1.0
	165	5825	11.94	11.0±1.0
11N20 SISO	149	5745	11.79	11.0±1.0
	157	5785	11.86	11.0±1.0
	165	5825	11.21	11.0±1.0
11N40 SISO	151	5755	11.46	11.0±1.0
	159	5795	10.49	10.0±1.0
11AC20 SISO	149	5745	11.76	11.0±1.0
	157	5785	10.88	10.0±1.0
	165	5825	11.21	11.0±1.0
11AC40 SISO	151	5755	11.43	11.0±1.0
	159	5795	10.47	10.0±1.
11AC80 SISO	155	5775	10.66	10.0±1.





[LTE Max Average Power]

Test Mode	Channel	Max Average Power (dBm)	ANT Max. Tune Up Power (dBm)	
LTE	Band 2	LCH	21.44	21.0±1.0
		MCH	22.0	22.0±1.0
		HCH	22.8	22.0±1.0
	Band 4	LCH	23	23.0±1.0
		MCH	22.73	22.0±1.0
		HCH	23	23.0±1.0
	Band 5	LCH	23.66	23.0±1.0
		MCH	23.33	23.0±1.0
		HCH	23.37	23.0±1.0
	Band 7	LCH	21.7	21.0±1.0
		MCH	22.03	22.0±1.0
		HCH	21.64	21.0±1.0
	Band 12	LCH	23.3	23.0±1.0
		MCH	23.46	23.0±1.0
		HCH	23.16	23.0±1.0
	Band 13	LCH	23.79	23.0±1.0
		MCH	23.74	23.0±1.0
		HCH	23.61	23.0±1.0
	Band 14	LCH	23.34	23.0±1.0
		MCH	23.47	23.0±1.0
		HCH	23.33	23.0±1.0
	Band 17	LCH	23.51	23.0±1.0
		MCH	23.28	23.0±1.0
		HCH	23.11	23.0±1.0
	Band 25	LCH	23.72	23.0±1.0
		MCH	22.23	22.0±1.0
		HCH	22.59	22.0±1.0
	Band 26-A	LCH	23.14	23.0±1.0
		MCH	23.09	23.0±1.0
		HCH	23.3	23.0±1.0
Band 26-B	LCH	23.14	23.0±1.0	
	MCH	23.24	23.0±1.0	
	HCH	22.81	22.0±1.0	
Band 41	LCH	22.22	22.0±1.0	
	MCH	22.32	22.0±1.0	
	HCH	21.73	21.0±1.0	
Band 66	LCH	22.5	22.0±1.0	
	MCH	22.55	22.0±1.0	
	HCH	22.76	22.0±1.0	
Band 71	LCH	23.38	23.0±1.0	
	MCH	23.49	23.0±1.0	
	HCH	23.47	23.0±1.0	

Test Procedure

TX frequency range: 13.56MHz

Device category: Portable device (Distance: 20cm)

Field Strength: 40.8dBuV/m @3m

EIRP=E-104.8+20logD=40.8-104.8+20log3=-54.46dBm

Maximum Conducted Output Power:-54.46dBm

Turn-up: -54±1





6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
GFSK	1.0	1.2589	3.81	2.4044	0.0006	1.0000	0.0006
$\pi/4$ -DQPSK	1.0	1.2589	3.81	2.4044	0.0006	1.0000	0.0006
8-DPSK	0	1.0000	3.81	2.4044	0.0005	1.0000	0.0005

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
BT LE 1M	2.0	1.5849	3.81	2.4044	0.0008	1.0000	0.0008

[2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
IEEE 802.11b	16.0	39.8107	3.81	2.4044	0.0191	1.0000	0.0191
IEEE 802.11g	15.0	31.6228	3.81	2.4044	0.0151	1.0000	0.0151
IEEE 802.11n HT20	15.0	31.6228	3.81	2.4044	0.0151	1.0000	0.0151
IEEE 802.11n HT40	14.0	25.1189	3.81	2.4044	0.0120	1.0000	0.0120

[5.2G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
IEEE 802.11a	13.0	19.9526	3.54	2.2594	0.0090	1.0000	0.0090
IEEE 802.11n HT20	12.0	15.8489	3.54	2.2594	0.0071	1.0000	0.0071
IEEE 802.11n HT40	12.0	15.8489	3.54	2.2594	0.0071	1.0000	0.0071
IEEE 802.11ac VHT20	12.0	15.8489	3.54	2.2594	0.0071	1.0000	0.0071
IEEE 802.11ac VHT40	12.0	15.8489	3.54	2.2594	0.0071	1.0000	0.0071
IEEE 802.11ac VHT80	11.0	12.5893	3.54	2.2594	0.0057	1.0000	0.0057





[5.8G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
IEEE 802.11a	13.0	19.9526	4.43	2.7733	0.0110	1.0000	0.0110
IEEE 802.11n HT20	12.0	15.8489	4.43	2.7733	0.0087	1.0000	0.0087
IEEE 802.11n HT40	12.0	15.8489	4.43	2.7733	0.0087	1.0000	0.0087
IEEE 802.11ac VHT20	12.0	15.8489	4.43	2.7733	0.0087	1.0000	0.0087
IEEE 802.11ac VHT40	12.0	15.8489	4.43	2.7733	0.0087	1.0000	0.0087
IEEE 802.11ac VHT80	11.0	12.5893	4.43	2.7733	0.0069	1.0000	0.0069

[LTE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios2
	dBm	mW					
Band 2	23	199.5262	3.02	2.0045	0.0796	1.0000	0.0796
Band 4	24	251.1886	3.24	2.1086	0.1054	1.0000	0.1054
Band 5	24	251.1886	-1.32	0.7379	0.0369	0.5493	0.0672
Band 7	23	199.5262	1.21	1.3213	0.0525	1.0000	0.0525
Band 12	24	251.1886	-1.6	0.6918	0.0346	0.4660	0.0742
Band 13	24	251.1886	-1.87	0.6501	0.0325	0.4973	0.0654
Band 14	24	251.1886	-1.7	0.6761	0.0338	0.5053	0.0669
Band 17	24	251.1886	-1.6	0.6918	0.0346	0.4693	0.0737
Band 25	24	251.1886	3.02	2.0045	0.1002	0.5427	0.1846
Band 26-A	24	251.1886	-1.32	0.7379	0.0369	0.5427	0.0680
Band 26-B	24	251.1886	-1.44	0.7178	0.0359	0.5493	0.0654
Band 41	23	199.5262	1.21	1.3213	0.0525	1.0000	0.0525
Band 66	23	199.5262	3.24	2.1086	0.0837	1.0000	0.0837
Band 71	24	251.1886	-1.35	0.7328	0.0366	0.4113	0.0890

[NFC]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
ASK	-53	0.000005	0	1.9953	0.000000001	0.9789

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.





6.2 Simultaneous Transmission MPE Evaluation

The sample support one BT&BLE&2.4GWLAN&5GWIFI, another one LTE transmit antenna and one NFC antenna so need consider simultaneous transmission.

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations.

$$TER = \sum_{k=1}^{N_s} \left(\frac{SAR_k}{SAR_{lim}} \right) + \sum_{k=1}^{N_f} \left(\frac{MPE_{field,k}}{MPE_{field,lim}} \right)^2 + \sum_{k=1}^{N_{pd}} \left(\frac{MPE_{PD,k}}{MPE_{PD,lim}} \right)$$

ΣΣ of MPE ratios ≤ 1.0

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

Mode	MPE1 Max.	MPE2 Max.	MPE3 Max.	Σ MPE ratios	Limit	Results
BT+LTE+NFC	0.0006	0.1846	0.000000001	0.1852	1.000	PASS
BLE+LTE+NFC	0.0008	0.1846	0.000000001	0.1854	1.000	PASS
2.4GWIFI+LTE+NFC	0.0191	0.1846	0.000000001	0.2037	1.000	PASS
5.2GWIFI+ LTE+NFC	0.0090	0.1846	0.000000001	0.1936	1.000	PASS
5.8GWIFI+LTE+NFC	0.0110	0.1846	0.000000001	0.1956	1.000	PASS

8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

9. Measurement Uncertainty

NFC/BT/BLE/2.4GWIFI/5GWIFI:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	±0.57dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----

