



April 13, 2021

TUV SUD America Inc.
10 Centennial Drive
Peabody, MA 01960
USA

Attention: Director of Certification

RE: Analysis of RF Exposure for Mobile and Portable Device per KDB 447498 D01 General RF Exposure Guidance v06, RSS-102 Issue 5 March 2015 and AS/NZS 2772.2:2016.

FCC ID: 2AZ9Q-LTSN

1. Limits:

Limits for General Population/Uncontrolled Exposure (Title 47 Subpart J §2.1091 and KDB 447498 D01 referring to limits under §1.1310)

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Electric Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,000	-	-	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

Limits for Devices Used by the General Public (Uncontrolled Environment (RSS-102 Issue 5 March 2015)

Frequency Range (MHz)	Electric Field Strength (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003 - 10 ²¹	83	90	-	Instantaneous
0.1 - 10	-	0.73/f	-	6**
1.1 - 10	87/f ^{0.5}	-	-	6**
10 - 20	27.46	0.0728	2	6
20 - 48	-58.07/f ^{0.25}	0.1540/f ^{0.25}	8.944/f ^{0.5}	6
48 - 300	22.06	0.05852	1.291	6
300 - 6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000 - 15000	61.4	0.163	10	6
15000 - 150000	61.4	0.163	10	616000/f ^{1.2}
150000 - 300000	0.158f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/f ^{1.2}

f is frequency in MHz

*Based on nerve stimulation (NS)

** Based on specific absorption rate (SAR)



2. Mobile MPE Calculation Summary using a 20cm separation distance:

Mode	Field Strength / Conducted Power	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	IC Limit (mW/cm ²)	FCC MPE Ratio (MPE/Limit)	IC MPE Ratio (MPE/Limit)
ISM	14 dBm *	0.0079	0.601	0.2740	0.013145	0.028883

*Output power declared by manufacturer.

3. Co-Located Transmitters transmission table:

Transmitter type	Transmitter type that can transmit at the same time
ISM 900 MHz	-

4. Mobile MPE Calculation using a 20cm separation distance (900 MHz radio):

Using Power Density formula:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to isotropic

R = distance to the center of radiation of the antenna



5. ISM 900 MHz at 20 cm Separate Distance:

Maximum peak output power at antenna input terminal:	14.00	(dBm)
Maximum peak output power at antenna input terminal:	25.12	(mW)
Antenna gain(typical):	2	(dBi)
Maximum antenna gain:	1.585	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	902.2	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	0.601	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	0.2740	(mW/cm ²)
Power density at prediction frequency:	0.0079	(mW/cm ²)
Power density at prediction frequency:	0.079	(W/m ²)
FCC Margin of Compliance:	-18.80	(dB)
ISED Margin of Compliance:	-15.4	(dB)

Sincerely,

A handwritten signature in black ink, appearing to read "Omar Castillo", written over a horizontal line.

Omar Castillo

Name

Authorized Signatory

Title: EMC Test Engineer