



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

Test Report

Report No.: CQASZ20210300302E-01

Applicant: Shenzhen Teamgee Electronics Co.,Ltd

Address of Applicant: No. 2807, Chuanghui Building, Wuhe Community, Bantian Street, Longgang District, Shenzhen, Guang Dong, China

Equipment Under Test (EUT):

EUT Name: Electric skateboard

Model No.: h5, h20, h20T, h20mini, h20pro, H20x, H9, H6, H8

Test Model No.: H9

Brand Name: N/A

FCC ID: 2AZCW-H9

Standards: 47 CFR Part 15, Subpart C

Date of Receipt: 2021-3-17

Date of Test: 2021-3-17 to 2021-4-7

Date of Issue: 2021-4-7

Test Result : PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Jun Li

(Jun Li)

Reviewed By:

Ares Liu

(Ares Liu)

Approved By:

Sheek Luo

(Sheek Luo)





Shenzhen Huaxia Testing Technology Co., Ltd

Report No.: CQASZ20210300302E-01

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210300302E-01	Rev.01	Initial report	2021-4-7

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10 (2013)	PASS
Conducted Emission (150KHz to 30MHz)	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Field Strength of the Fundamental Signal	47 CFR Part 15, Subpart C Section 15.231 (b)	ANSI C63.10 (2013)	PASS
Spurious Emissions	47 CFR Part 15, Subpart C Section 15.231 (b)/15.209	ANSI C63.10 (2013)	PASS
20dB Bandwidth	47 CFR Part 15, Subpart C Section 15.231 (c)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.231 (a)	ANSI C63.10 (2013)	PASS

3 Contents

	Page
1 VERSION.....	2
2 TEST SUMMARY.....	3
3 CONTENTS.....	4
4 GENERAL INFORMATION.....	5
4.1 CLIENT INFORMATION.....	5
4.2 GENERAL DESCRIPTION OF EUT.....	5
4.3 TEST ENVIRONMENT AND MODE.....	6
4.4 DESCRIPTION OF SUPPORT UNITS.....	6
4.5 TEST LOCATION.....	6
4.6 TEST FACILITY.....	7
4.7 STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	7
4.8 DEVIATION FROM STANDARDS.....	7
4.9 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
4.11 EQUIPMENT LIST.....	8
5 TEST RESULTS AND MEASUREMENT DATA.....	9
5.1 ANTENNA REQUIREMENT.....	9
5.2 CONDUCTED EMISSIONS.....	10
5.3 SPURIOUS EMISSIONS.....	14
5.3.1 <i>Duty Cycle</i>	14
5.3.2 <i>Spurious Emissions</i>	17
5.4 20dB BANDWIDTH.....	25
5.5 DWELL TIME.....	27
6 PHOTOGRAPHS - EUT TEST SETUP.....	29
6.1 RADIATED EMISSION.....	29
6.2 CONDUCTED EMISSION TEST SETUP.....	31
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	32

4 General Information

4.1 Client Information

Applicant:	Shenzhen Teamgee Electronics Co.,Ltd
Address of Applicant:	No. 2807, Chuanghui Building, Wuhe Community, Bantian Street, Longgang District, Shenzhen, Guang Dong, China
Manufacturer:	Shenzhen Teamgee Electronics Co.,Ltd
Address of Manufacturer:	No. 2807, Chuanghui Building, Wuhe Community, Bantian Street, Longgang District, Shenzhen, Guang Dong, China
Factory:	Shenzhen Teamgee Electronics Co.,Ltd
Address of Factory:	No. 2807, Chuanghui Building, Wuhe Community, Bantian Street, Longgang District, Shenzhen, Guang Dong, China

4.2 General Description of EUT

Product Name:	Electric skateboard
All Model No.:	h5, h20, h20T, h20mini, h20pro, H20x, H9, H6, H8
Test Model No.:	H9
Trade Mark:	N/A
Hardware Version:	2.0
Software Version:	2.0
Sample Type:	portable production
Operation Frequency:	433.92MHz
Channel Numbers:	1
Modulation Type:	GFSK
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	Battery Voltage/Capacity:3.7V/300MAH DC 5V 1-2A by Adapter

Note:

All model: h5, h20, h20T, h20mini, h20pro, H20x, H9, H6, H8

Only the model H9 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being appearance, product name, trademarks and models.

4.3 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	24.7 °C
Humidity:	56 % RH
Atmospheric Pressure:	1001 mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with modulation.

4.4 Description of Support Units

The EUT has been tested independently.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.5 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.7 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

Test	Range	Uncertainty	Notes
Radiated Emission	Below 1GHz	±5.12dB	(1)
Radiated Emission	Above 1GHz	±4.60dB	(1)
Conducted Disturbance	0.15~30MHz	±3.34dB	(1)

(1)This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2020/9/26	2021/9/25
Spectrum analyzer	R&S	FSU26	CQA-038	2020/10/28	2021/10/27
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2020/9/26	2021/9/25
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2020/11/2	2021/11/1
Loop antenna	Schwarzbeck	FMZB1516	CQA-065	2019/10/28	2021/10/27
Bilog Antenna	R&S	HL562	CQA-011	2019/9/26	2021/9/25
Horn Antenna	R&S	HF906	CQA-012	2019/9/26	2021/9/25
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2020/9/26	2021/9/25
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2020/9/26	2021/9/25
Antenna Connector	CQA	RFC-01	CQA-080	2020/9/26	2021/9/25
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2020/9/26	2021/9/25
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2020/9/26	2021/9/25

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
EUT Antenna:	
<p>The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.</p>	

5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
			Quasi-peak
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
Test Procedure:	5-30	60	50
	* Decreases with the logarithm of the frequency.		
	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 		
	 <p>The diagram illustrates the test setup for conducted emissions. It shows a 'Shielding Room' containing an 'EUT' (Equipment Under Test) and an 'AE' (Antenna Equipment). The EUT is connected to an 'AC Mains' through a 'LISN1'. The AE is connected to a 'Test Receiver' which is also connected to an 'AC Mains'. A 'Ground Reference Plane' is shown at the bottom, with vertical ground reference planes bonded to the horizontal ground reference plane. The distance between the LISN 1 and the EUT is 0.8m, and the LISN 1 is 0.8m from the boundary of the unit under test.</p>		




Shenzhen Huaxia Testing Technology Co., Ltd

Report No.: CQASZ20210300302E-01

Test Mode:	Transmitting with GFSK modulation. Charge +Transmitting mode.
Final Test Mode:	below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

Live line:




Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz			dB	dBuV		
1	0.180	23.98	9.49	33.47	54.49	-21.02	Average Line
2	0.180	27.99	9.49	37.48	64.49	-27.01	QP Line
3	0.275	21.90	9.49	31.39	50.97	-19.58	Average Line
4	0.275	25.86	9.49	35.35	60.97	-25.62	QP Line
5	0.385	19.40	9.50	28.90	48.17	-19.27	Average Line
6	0.385	24.19	9.50	33.69	58.17	-24.48	QP Line
7	PP	0.720	9.85	32.31	46.00	-13.69	Average Line
8	QP	0.720	9.85	41.17	56.00	-14.83	QP Line
9	1.490	19.43	9.52	28.95	46.00	-17.05	Average Line
10	1.490	27.62	9.52	37.14	56.00	-18.86	QP Line
11	16.705	12.52	9.96	22.48	50.00	-27.52	Average Line
12	16.705	24.74	9.96	34.70	60.00	-25.30	QP Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz			dBuV	dB		
1	0.150	22.93	9.48	32.41	56.00	-23.59	Average
2	0.150	28.59	9.48	38.07	66.00	-27.93	QP
3	0.250	21.11	9.48	30.59	51.76	-21.17	Average
4	0.250	26.40	9.48	35.88	61.76	-25.88	QP
5	0.685	27.69	9.82	37.51	46.00	-8.49	Average
6	0.685	32.40	9.82	42.22	56.00	-13.78	QP
7	PP	0.720	9.83	39.22	46.00	-6.78	Average
8	QP	0.720	9.83	43.46	56.00	-12.54	QP
9	1.345	22.44	9.72	32.16	46.00	-13.84	Average
10	1.345	27.94	9.72	37.66	56.00	-18.34	QP
11	16.775	13.94	9.97	23.91	50.00	-26.09	Average
12	16.775	26.39	9.97	36.36	60.00	-23.64	QP

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Spurious Emissions

5.3.1 Duty Cycle

Test Requirement:	47 CFR Part 15C Section 15.35 (c)
Test Method:	ANSI C63.10:2013
Test Setup:	
Limit:	N/A
Test Mode:	Transmitting mode
Test Results:	Pass


Duty cycle numbers	T period (ms)	T on time (ms)	Duty cycle
4	374.10	38.47	0.103

Note: $T_{on\ time} = 24.04 \times 1 + 4.81 \times 3 = 38.47\text{ms}$,


Duty cycle = $T_{on\ time} / T_{period}$

Test plot as follows:


Duty cycle numbers



T period:



T on time:



5.3.2 Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.231(b) and 15.209				
Test Method:	ANSI C63.10: 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Spurious Emissions)	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi- peak	3
	88MHz-216MHz	150	43.5	Quasi- peak	3
	216MHz-960MHz	200	46.0	Quasi- peak	3
	960MHz-1GHz	500	54.0	Quasi- peak	3
	Above 1GHz	500	54.0	Average	3
	<p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p>				
Limit: (Field strength of the fundamental signal)	433.92MHz	Frequency	Limit (dBuV/m @3m)	Remark	
			80.8	Average Value	
			100.8	Peak Value	
Test Procedure:	<p>a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>Note: For the radiated emission test above 1GHz:</p>				

	<p>Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <ul style="list-style-type: none"> b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. The radiation measurements are performed in X, Y, Z axis positioning. And found the Z axis positioning which is worse case, Only the test worst case mode is recorded in the report.
Test Setup:	




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Mode:	Transmitting mode
Test Results:	Pass

Measurement Data
5.3.2.1 Field Strength Of The Fundamental Signal

Average value:	
Calculate Formula:	Average value=Peak value + PDCF
	PDCF=20 log(Duty cycle)
	Duty cycle= T on time / T period
Test data:	T on time =38.47ms
	T period =374.10ms
	PDCF= -19.76

Antenna polarization: Horizontal						
Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
433.92	58.87	25.17	84.04	108.8	-24.76	Peak
433.92	-	-	64.28	80.8	-16.52	Average

Antenna polarization: Vertical						
Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
433.92	54.36	25.17	79.53	108.8	-29.27	Peak
433.92	-	-	59.77	80.8	-21.03	Average

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

5.3.2.2 Spurious Emissions


9KHz-30MHz

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

Below 1GHz (30MHz-1GHz)


Horizontal



Freq	Read		Limit	Over	Remark	Pol/Phase
	Level	Factor				
	MHz	dB _{UV}	dB/m	dB _{UV} /m	dB _{UV} /m	dB
1	30.53	4.39	28.12	32.51	40.00	-7.49 Peak HORIZONTAL
2	128.11	0.01	20.30	20.31	43.50	-23.19 Peak HORIZONTAL
3	265.68	6.15	20.51	26.66	46.00	-19.34 Peak HORIZONTAL
4	365.54	11.26	23.25	34.51	46.00	-11.49 Peak HORIZONTAL
5	387.99	13.20	23.79	36.99	46.00	-9.01 Peak HORIZONTAL
6 pp	869.13	9.78	30.39	40.17	46.00	-5.83 Peak HORIZONTAL


Vertical


Freq	Read			Limit		Over Limit	Remark	Pol/Phase
	Freq	Level	Factor	Level	Line			
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1 pp	30.64	8.49	28.08	36.57	40.00	-3.43	Peak	VERTICAL
2	40.28	3.84	24.54	28.38	40.00	-11.62	Peak	VERTICAL
3	55.80	7.84	16.63	24.47	40.00	-15.53	Peak	VERTICAL
4	107.13	1.95	20.21	22.16	43.50	-21.34	Peak	VERTICAL
5	465.60	7.74	26.15	33.89	46.00	-12.11	Peak	VERTICAL
6	869.13	10.41	30.39	40.80	46.00	-5.20	Peak	VERTICAL

Above 1GHz(1GHz-5GHz)
Horizontal


Freq	Read		Level	Limit	Over	Remark	Pol/Phase
	MHz	dB _{uV}	dB/m	dB _{uV/m}	dB _{uV/m}	dB	
1	2045.00	46.76	-8.00	38.76	74.00	-35.24	Peak HORIZONTAL
2	2570.00	46.51	-8.04	38.47	74.00	-35.53	Peak HORIZONTAL
3	3150.00	44.58	-5.25	39.33	74.00	-34.67	Peak HORIZONTAL
4	3545.00	45.46	-4.31	41.15	74.00	-32.85	Peak HORIZONTAL
5	4035.00	43.99	-1.70	42.29	74.00	-31.71	Peak HORIZONTAL
6 pp	4605.00	44.44	-1.80	42.64	74.00	-31.36	Peak HORIZONTAL

Vertical:




Freq	Read			Limit	Over	Remark	Pol/Phase
	MHz	Level	Factor		Line		
1	2470.00	46.65	-8.72	37.93	74.00	-36.07	Peak VERTICAL
2	2665.00	46.32	-8.08	38.24	74.00	-35.76	Peak VERTICAL
3	3215.00	45.72	-5.03	40.69	74.00	-33.31	Peak VERTICAL
4	3825.00	43.48	-2.41	41.07	74.00	-32.93	Peak VERTICAL
5	4300.00	43.99	-2.30	41.69	74.00	-32.31	Peak VERTICAL
6 pp	4905.00	45.21	-0.68	44.53	74.00	-29.47	Peak VERTICAL

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 2) The disturbance above 5GHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 3) As shown in this section, for frequencies above 1GHz, the field the strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits. Specified above by more than 20dB under any condition of modulation. So, only the peak measurements were show in the report.


5.4 20dB Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.231 (c)
Test Method:	ANSI C63.10:2013
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Setup:	
Test Mode:	Transmitting mode
Test Results:	Pass


Measurement Data

20dB bandwidth (MHz)	Limit (MHz)	Results
0.123	1.0849	PASS

Test plot as follows:



5.5 Dwell time

Test Requirement:	47 CFR Part 15C Section 15.231 (a)
Test Method:	ANSI C63.10:2013
Test Setup:	
Test Mode:	Transmitting mode
Test Results:	Pass

Requirements:

1. Regulation 15.231 (a) The provisions of this Section are restricted to periodic operation within the band 40.66~40.70 MHz and above 70 MHz. Except as shown in paragraph (e) of this Section, the intentional radiator is restricted to the transmission of a control signal such as those used with alarm systems, door openers, remote switches, etc. Radio control of toys is not permitted. Continuous transmissions, such as voice or video, and data transmissions are not permitted. The prohibition against data transmissions does not preclude the use of recognition codes. Those codes are used to identify the sensor that is activated or to identify the particular component as being part of the system.

Result:

The EUT is a remote switch without audio or video transmitted.


The EUT meets the requirements of this section.

2. Regulation 15.231 (a1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Result:

Test item	Limit (MHz)	Results
Transmitting time	≤5S	0.384615385S

Test plot as follows:



3. Regulation 15.231 (a2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

Result:

The EUT does not have automatic transmission.

4. Regulation 15.231 (a3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions to determine system integrity of transmitters used in security or safety applications are allowed if the periodic rate of transmission does not exceed one transmission of not more than one second duration per hour for each transmitter.

Result:

The EUT does not employ periodic transmission.

5. Regulation 15.231 (a4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

Result:

This section is not applicable to the EUT.

6 Photographs - EUT Test Setup

6.1 Radiated Emission

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emission Test Setup



7 Photographs - EUT Constructional Details

Test Model No.: H9



