



FCC RF Test Report

APPLICANT : NOTHING TECHNOLOGY LIMITED
EQUIPMENT : Smart Phone
BRAND NAME : NOTHING
MODEL NAME : A059P
FCC ID : 2AZEQ-24111
STANDARD : FCC Part 15 Subpart C §15.225
CLASSIFICATION : (DXX) Low Power Communication Device Transmitter
TEST DATE(S) : Nov. 30, 2024 ~ Dec. 17, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sportun International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



TABLE OF CONTENTS

TABLE OF CONTENTS	2
REVISION HISTORY	3
SUMMARY OF THE TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software	7
1.8 Applicable Standards	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Descriptions of Test Mode	8
2.2 Connection Diagram of Test System	9
2.3 Table for Supporting Units	10
2.4 EUT Operation Test Setup	10
3. TEST RESULTS	11
3.1 AC Power Line Conducted Emissions Measurement	11
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement	13
3.3 Frequency Stability Measurement	14
3.4 Field Strength of Fundamental Emissions and Mask Measurement	15
3.5 Radiated Emissions Measurement	17
3.6 Antenna Requirements	20
4. LIST OF MEASURING EQUIPMENT	21
5. UNCERTAINTY OF EVALUATION	22

APPENDIX A. TEST RESULTS OF CONDUCTED EMISSION TEST

APPENDIX B. TEST RESULTS OF CONDUCTED TEST ITEMS

B1. Test Result of 20dB Spectrum Bandwidth

B2. Test Result of Frequency Stability

APPENDIX C. TEST RESULTS OF RADIATED TEST ITEMS

C1 Test Result of Field Strength of Fundamental Emissions

C2. Results of Radiated Emissions (9 kHz~30MHz)

C3. Results of Radiated Emissions (30MHz~1GHz)

APPENDIX D. SETUP PHOTOGRAPHS



REVISION HISTORY



SUMMARY OF THE TEST RESULT

Report Section	FCC Rule	Description of Test	Result	Remark
3.1	15.207	AC Power Line Conducted Emissions	Complies	Under limit 9.29 dB at 0.25MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Complies	-
	-	99% OBW Spectrum Bandwidth	Complies	-
3.3	15.225(e)	Frequency Stability	Complies	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	Max level 13.73 dB μ V/m at 13.56 MHz @30m
3.5	15.225(d) & 15.209	Radiated Spurious Emissions	Complies	Under limit 6.33 dB at 41.64MHz
3.6	15.203	Antenna Requirements	Complies	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1. General Description

1.1 Applicant

NOTHING TECHNOLOGY LIMITED

Bedford House, 21A John Street, London, United Kingdom WC1N 2BF

1.2 Manufacturer

NOTHING TECHNOLOGY LIMITED

Bedford House, 21A John Street, London, United Kingdom WC1N 2BF

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	NOTHING
Model Name	A059P
FCC ID	2AZEQ-24111
IMEI Code	Conducted: 353458700043501/353458700043519 Conduction: 353458700043030/353458700043022 Radiation: 353458700043501/353458700043519
HW Version	24111 Pro
SW Version	Nothing OS 3.1
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	13.553 ~ 13.567MHz
Channel Number	1
20dBW	2.567 KHz
99%OBW	2.178 KHz
Antenna Type	loop antenna
Type of Modulation	ASK



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sportun International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sportun International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sportun Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ		
Test Engineer	ZhiQiang Chen		
Temperature	24-26°C	CN1256	421272
Relative Humidity	45-55%		

Test Firm	Sportun International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sportun Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO02-SZ ; 03CH05-SZ		
Test Engineer	Nathon	ZhanShengLiu	
Temperature	22-24°C	23-25°C	CN1256
Relative Humidity	44-50%	48-52%	421272



1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH05-SZ	AUDIX	E3	6.2009-8-24
2.	CO02-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.225
- ANSI C63.10-2013



2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz


The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report. Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.

Test Cases	
AC Conducted Emission	Mode 1: GSM850 Idle + WLAN Link(2.4G) + NFC TX + Adapter + USB Cable + Battery
Remark: For Radiated Test Cases, the tests were performance with Adapter and USB Cable.	



2.2 Connection Diagram of Test System


<Radiated Emission >



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

< AC Conducted Emission >



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.



2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station(LTE)	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	NFC Card	N/A	N/A	N/A	N/A	N/A
3.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 0 cm gap to the EUT.



3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ± 100 ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.



3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225	
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.	
Freq. of Emission (MHz)	Field Strength (μ V/m) at 30m	Field Strength (dB μ V/m) at 30m
1.705~13.110	30	29.5
13.110~13.410	106	40.5
13.410~13.553	334	50.5
13.553~13.567	15848	84.0
13.567~13.710	334	50.5
13.710~14.010	106	40.5
14.010~30.000	30	29.5

3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.
Note: Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
7. The field strength is tested at 3m distance then convert to 30m by adding distance factor $40 \times \log(d_1/d_2)$.

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.



3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

<FCC Limit>

Frequencies (MHz)	Field Strength (μ V/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.




3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Note:

1. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.
2. Tested for radiated below 30 MHz using a loop antenna in accordance with C63.10, the antenna was positioned in three antenna orientations: parallel, perpendicular, and ground-parallel. Pre-scanned the three antenna orientations, the worst case is parallel & perpendicular polarization, and test data of two mode was reported. (Parallel: The loop antenna is placed vertical axis and aligned along the site axis; Perpendicular: The loop antenna is placed vertical axis and orthogonal to the axis; ground-parallel: The loop antenna is placed horizontal axis and parallel with the ground).



3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	102261	9kHz~7GHz	Apr. 09, 2024	Dec. 17, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010B	MY590711 91	10Hz~44GHz	Apr. 09, 2024	Dec. 17, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 29, 2023	Dec. 17, 2024	Dec. 28, 2024	Radiation (03CH05-SZ)
Log-periodic Antenna	SCHWARZBECK	VULB 9168	01001	20MHz~1.5GHz	Jul. 08, 2024	Dec. 17, 2024	Jul. 07, 2025	Radiation (03CH05-SZ)
Amplifier	EM Electronics	EM330	060756	0.01Hz ~3000MHz	Apr. 09, 2024	Dec. 17, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
AC Power Source	APC	AFV-S-600	F11905001 3	N/A	Oct. 14, 2024	Dec. 17, 2024	Oct. 13, 2025	Radiation (03CH05-SZ)
Turn Table	EMEC	T-200-S-1	060925-T	0~360 degree	NCR	Dec. 17, 2024	NCR	Radiation (03CH05-SZ)
Antenna Mast	EMEC	MBS-400-1	060927	1 m~4 m	NCR	Dec. 17, 2024	NCR	Radiation (03CH05-SZ)
EMI Receiver	R&S	ESR7	102297	9kHz~7GHz;	Jul. 03, 2024	Nov. 30, 2024	Jul. 02, 2025	Conduction (CO02-SZ)
AC LISN	R&S	ENV216	101499	9kHz~30MHz	Jul. 03, 2024	Nov. 30, 2024	Jul. 02, 2025	Conduction (CO02-SZ)
AC Power Source	CHROMA	61601	616010002 470	100Vac~250Vac	Dec.25, 2022	Nov. 30, 2024	Dec. 24, 2024	Conduction (CO02-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Dec. 17, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081 803	-40~+150°C	Jul. 03, 2024	Dec. 17, 2024	Jul. 02, 2025	Conducted (TH01-SZ)

NCR: No Calibration Required



5. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Occupied Channel Bandwidth	± 0.012 MHz
Frequency	± 1.3 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	2.5 dB
--	--------

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	2.5 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.2 dB
--	--------

----- THE END -----



Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Nathon	Temperature : 22~24°C																																																																																																																																																					
		Relative Humidity : 44~50%																																																																																																																																																					
Test Voltage :	120Vac / 60Hz	Phase :				Line																																																																																																																																																	
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.																																																																																																																																																						
Site	: C002-SZ																																																																																																																																																						
Condition	: FCC 15C_QP LISN_2024-L-1 LINE																																																																																																																																																						
<table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>Limit Line</th><th>Read Level</th><th>LISN Factor</th><th>Cable Loss</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV</th><th>dB</th><th>dBuV</th><th>dBuV</th><th>dB</th><th>dB</th><th></th></tr></thead><tbody><tr><td>1</td><td>0.25</td><td>40.94</td><td>-10.79</td><td>51.73</td><td>21.20</td><td>9.70</td><td>10.04</td><td>Average</td></tr><tr><td>2</td><td>0.25</td><td>52.44</td><td>-9.29</td><td>61.73</td><td>32.70</td><td>9.70</td><td>10.04</td><td>QP</td></tr><tr><td>3</td><td>0.37</td><td>34.83</td><td>-13.69</td><td>48.52</td><td>15.10</td><td>9.66</td><td>10.07</td><td>Average</td></tr><tr><td>4</td><td>0.37</td><td>45.43</td><td>-13.09</td><td>58.52</td><td>25.70</td><td>9.66</td><td>10.07</td><td>QP</td></tr><tr><td>5</td><td>0.51</td><td>31.33</td><td>-14.67</td><td>46.00</td><td>11.60</td><td>9.62</td><td>10.11</td><td>Average</td></tr><tr><td>6</td><td>0.51</td><td>42.63</td><td>-13.37</td><td>56.00</td><td>22.90</td><td>9.62</td><td>10.11</td><td>QP</td></tr><tr><td>7</td><td>0.66</td><td>24.00</td><td>-22.00</td><td>46.00</td><td>4.20</td><td>9.66</td><td>10.14</td><td>Average</td></tr><tr><td>8</td><td>0.66</td><td>42.20</td><td>-13.80</td><td>56.00</td><td>22.40</td><td>9.66</td><td>10.14</td><td>QP</td></tr><tr><td>9</td><td>0.89</td><td>27.66</td><td>-18.34</td><td>46.00</td><td>7.80</td><td>9.67</td><td>10.19</td><td>Average</td></tr><tr><td>10</td><td>0.89</td><td>40.96</td><td>-15.04</td><td>56.00</td><td>21.10</td><td>9.67</td><td>10.19</td><td>QP</td></tr><tr><td>11 *</td><td>13.56</td><td>50.71</td><td></td><td>30.40</td><td>9.55</td><td>10.76</td><td>Average</td><td></td></tr><tr><td>12 *</td><td>13.56</td><td>51.01</td><td></td><td>30.70</td><td>9.55</td><td>10.76</td><td>QP</td><td></td></tr><tr><td>13</td><td>22.90</td><td>30.40</td><td>-19.60</td><td>50.00</td><td>9.99</td><td>9.68</td><td>10.73</td><td>Average</td></tr><tr><td>14</td><td>22.90</td><td>39.40</td><td>-20.60</td><td>60.00</td><td>18.99</td><td>9.68</td><td>10.73</td><td>QP</td></tr></tbody></table>									Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark		MHz	dBuV	dB	dBuV	dBuV	dB	dB		1	0.25	40.94	-10.79	51.73	21.20	9.70	10.04	Average	2	0.25	52.44	-9.29	61.73	32.70	9.70	10.04	QP	3	0.37	34.83	-13.69	48.52	15.10	9.66	10.07	Average	4	0.37	45.43	-13.09	58.52	25.70	9.66	10.07	QP	5	0.51	31.33	-14.67	46.00	11.60	9.62	10.11	Average	6	0.51	42.63	-13.37	56.00	22.90	9.62	10.11	QP	7	0.66	24.00	-22.00	46.00	4.20	9.66	10.14	Average	8	0.66	42.20	-13.80	56.00	22.40	9.66	10.14	QP	9	0.89	27.66	-18.34	46.00	7.80	9.67	10.19	Average	10	0.89	40.96	-15.04	56.00	21.10	9.67	10.19	QP	11 *	13.56	50.71		30.40	9.55	10.76	Average		12 *	13.56	51.01		30.70	9.55	10.76	QP		13	22.90	30.40	-19.60	50.00	9.99	9.68	10.73	Average	14	22.90	39.40	-20.60	60.00	18.99	9.68	10.73	QP
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark																																																																																																																																															
	MHz	dBuV	dB	dBuV	dBuV	dB	dB																																																																																																																																																
1	0.25	40.94	-10.79	51.73	21.20	9.70	10.04	Average																																																																																																																																															
2	0.25	52.44	-9.29	61.73	32.70	9.70	10.04	QP																																																																																																																																															
3	0.37	34.83	-13.69	48.52	15.10	9.66	10.07	Average																																																																																																																																															
4	0.37	45.43	-13.09	58.52	25.70	9.66	10.07	QP																																																																																																																																															
5	0.51	31.33	-14.67	46.00	11.60	9.62	10.11	Average																																																																																																																																															
6	0.51	42.63	-13.37	56.00	22.90	9.62	10.11	QP																																																																																																																																															
7	0.66	24.00	-22.00	46.00	4.20	9.66	10.14	Average																																																																																																																																															
8	0.66	42.20	-13.80	56.00	22.40	9.66	10.14	QP																																																																																																																																															
9	0.89	27.66	-18.34	46.00	7.80	9.67	10.19	Average																																																																																																																																															
10	0.89	40.96	-15.04	56.00	21.10	9.67	10.19	QP																																																																																																																																															
11 *	13.56	50.71		30.40	9.55	10.76	Average																																																																																																																																																
12 *	13.56	51.01		30.70	9.55	10.76	QP																																																																																																																																																
13	22.90	30.40	-19.60	50.00	9.99	9.68	10.73	Average																																																																																																																																															
14	22.90	39.40	-20.60	60.00	18.99	9.68	10.73	QP																																																																																																																																															

(1) with antenna


Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	Nathon		Temperature :	22~24°C																																																																																																																																																	
Test Voltage :	120Vac / 60Hz		Relative Humidity :	44~50%																																																																																																																																																	
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.			Phase :	Neutral																																																																																																																																																
Site : CO02-SZ Condition : FCC 15C_QP LISN_2024-N-1 NEUTRAL																																																																																																																																																					
<table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>Limit Line</th><th>Read Level</th><th>LISN Factor</th><th>Cable Loss</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV</th><th>dB</th><th>dBuV</th><th>dBuV</th><th>dB</th><th>dB</th><th></th></tr></thead><tbody><tr><td>1</td><td>0.25</td><td>36.51</td><td>-15.13</td><td>51.64</td><td>16.79</td><td>9.68</td><td>10.04</td><td>Average</td></tr><tr><td>2</td><td>0.25</td><td>50.21</td><td>-11.43</td><td>61.64</td><td>30.49</td><td>9.68</td><td>10.04</td><td>QP</td></tr><tr><td>3</td><td>0.41</td><td>29.78</td><td>-17.86</td><td>47.64</td><td>10.00</td><td>9.70</td><td>10.08</td><td>Average</td></tr><tr><td>4</td><td>0.41</td><td>40.08</td><td>-17.56</td><td>57.64</td><td>20.30</td><td>9.70</td><td>10.08</td><td>QP</td></tr><tr><td>5</td><td>0.48</td><td>29.10</td><td>-17.17</td><td>46.27</td><td>9.30</td><td>9.69</td><td>10.11</td><td>Average</td></tr><tr><td>6</td><td>0.48</td><td>39.80</td><td>-16.47</td><td>56.27</td><td>20.00</td><td>9.69</td><td>10.11</td><td>QP</td></tr><tr><td>7</td><td>0.63</td><td>23.93</td><td>-22.07</td><td>46.00</td><td>4.10</td><td>9.69</td><td>10.14</td><td>Average</td></tr><tr><td>8</td><td>0.63</td><td>37.03</td><td>-18.97</td><td>56.00</td><td>17.20</td><td>9.69</td><td>10.14</td><td>QP</td></tr><tr><td>9</td><td>0.82</td><td>22.06</td><td>-23.94</td><td>46.00</td><td>2.21</td><td>9.68</td><td>10.17</td><td>Average</td></tr><tr><td>10</td><td>0.82</td><td>34.86</td><td>-21.14</td><td>56.00</td><td>15.01</td><td>9.68</td><td>10.17</td><td>QP</td></tr><tr><td>11 *</td><td>13.56</td><td>52.45</td><td></td><td>32.10</td><td>9.59</td><td>10.76</td><td>Average</td><td></td></tr><tr><td>12 *</td><td>13.56</td><td>52.65</td><td></td><td>32.30</td><td>9.59</td><td>10.76</td><td>QP</td><td></td></tr><tr><td>13</td><td>22.66</td><td>31.99</td><td>-18.01</td><td>50.00</td><td>11.59</td><td>9.67</td><td>10.73</td><td>Average</td></tr><tr><td>14</td><td>22.66</td><td>40.79</td><td>-19.21</td><td>60.00</td><td>20.39</td><td>9.67</td><td>10.73</td><td>QP</td></tr></tbody></table>							Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark		MHz	dBuV	dB	dBuV	dBuV	dB	dB		1	0.25	36.51	-15.13	51.64	16.79	9.68	10.04	Average	2	0.25	50.21	-11.43	61.64	30.49	9.68	10.04	QP	3	0.41	29.78	-17.86	47.64	10.00	9.70	10.08	Average	4	0.41	40.08	-17.56	57.64	20.30	9.70	10.08	QP	5	0.48	29.10	-17.17	46.27	9.30	9.69	10.11	Average	6	0.48	39.80	-16.47	56.27	20.00	9.69	10.11	QP	7	0.63	23.93	-22.07	46.00	4.10	9.69	10.14	Average	8	0.63	37.03	-18.97	56.00	17.20	9.69	10.14	QP	9	0.82	22.06	-23.94	46.00	2.21	9.68	10.17	Average	10	0.82	34.86	-21.14	56.00	15.01	9.68	10.17	QP	11 *	13.56	52.45		32.10	9.59	10.76	Average		12 *	13.56	52.65		32.30	9.59	10.76	QP		13	22.66	31.99	-18.01	50.00	11.59	9.67	10.73	Average	14	22.66	40.79	-19.21	60.00	20.39	9.67	10.73	QP
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark																																																																																																																																													
	MHz	dBuV	dB	dBuV	dBuV	dB	dB																																																																																																																																														
1	0.25	36.51	-15.13	51.64	16.79	9.68	10.04	Average																																																																																																																																													
2	0.25	50.21	-11.43	61.64	30.49	9.68	10.04	QP																																																																																																																																													
3	0.41	29.78	-17.86	47.64	10.00	9.70	10.08	Average																																																																																																																																													
4	0.41	40.08	-17.56	57.64	20.30	9.70	10.08	QP																																																																																																																																													
5	0.48	29.10	-17.17	46.27	9.30	9.69	10.11	Average																																																																																																																																													
6	0.48	39.80	-16.47	56.27	20.00	9.69	10.11	QP																																																																																																																																													
7	0.63	23.93	-22.07	46.00	4.10	9.69	10.14	Average																																																																																																																																													
8	0.63	37.03	-18.97	56.00	17.20	9.69	10.14	QP																																																																																																																																													
9	0.82	22.06	-23.94	46.00	2.21	9.68	10.17	Average																																																																																																																																													
10	0.82	34.86	-21.14	56.00	15.01	9.68	10.17	QP																																																																																																																																													
11 *	13.56	52.45		32.10	9.59	10.76	Average																																																																																																																																														
12 *	13.56	52.65		32.30	9.59	10.76	QP																																																																																																																																														
13	22.66	31.99	-18.01	50.00	11.59	9.67	10.73	Average																																																																																																																																													
14	22.66	40.79	-19.21	60.00	20.39	9.67	10.73	QP																																																																																																																																													


(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.



(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.

Note:

1. Level(dB μ V) = Read Level(dB μ V) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dB μ V) – Limit Line(dB μ V)



Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56																												
	<p>CF 13.56 MHz 1001 pts Span 10.0 kHz</p> <p>Marker</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>13.55999 MHz</td> <td>6.37 dBm</td> <td>ndB down</td> <td>2.567 kHz</td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td>13.558701 MHz</td> <td>-13.65 dBm</td> <td>ndB</td> <td>20.00 dB</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td>13.561269 MHz</td> <td>-13.48 dBm</td> <td>Q factor</td> <td>5281.5</td> </tr> </tbody> </table>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		13.55999 MHz	6.37 dBm	ndB down	2.567 kHz	T1	1		13.558701 MHz	-13.65 dBm	ndB	20.00 dB	T2	1		13.561269 MHz	-13.48 dBm	Q factor	5281.5		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																									
M1	1		13.55999 MHz	6.37 dBm	ndB down	2.567 kHz																									
T1	1		13.558701 MHz	-13.65 dBm	ndB	20.00 dB																									
T2	1		13.561269 MHz	-13.48 dBm	Q factor	5281.5																									
20dB Bandwidth (kHz)	2.567	99% OccupiedBW(kHz)	2.178																												
Frequency range (MHz)	$f_L > 13.553$ $f_H < 13.567$	13.558701	Test Result																												
		13.561269	Complies																												

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.



B2. Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
HV	13.559985	-20	13.560045
NV	13.559985	-10	13.560040
LV	13.559985	0	13.560035
		10	13.560015
		20	13.559995
		30	13.559970
		40	13.559960
		50	13.559950
Max.Deviation (MHz)	-0.000015	Max.Deviation (MHz)	-0.000050
Max.Deviation (ppm)	-1.1062	Max.Deviation (ppm)	-3.6873
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS





Appendix C. Test Results of Radiated Test Items

C.1 Test Result of Field Strength of Fundamental Emissions

Frequency (MHz)	Level @3m (dBuV/m)	Distance Factor (dB)	Corrected Level @30m (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Remark	Pol/Phase
13.56	53.73	40	13.73	84.0	-70.27	32.55	20.27	0.91	QP	Perpendicular
13.56	48.63	40	8.63	84.0	-75.37	27.45	20.27	0.91	QP	Parallel

Note: The field strength is tested at 3m distance then convert to 30m by adding distance factor $40 \times \log(d1/d2)$.





Note:

1. Level(dB μ V/m) = Read Level(dB μ V) + Antenna Factor(dB/m) + Cable Loss(dB)
2. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
4. Corrected Level = Level @3m (dB μ V/m) - distance extrapolation factor.

**C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)**

Test Mode :		NFC Tx				Polarization :		Perpendicular			
Frequency (MHz)	Level @3m (dB μ V/m)	Distance Factor (dB)	Corrected Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.04898	39.08	80	-40.92	-74.49	33.57	19.34	19.7	0.04	-	-	Average
0.07419	37.78	80	-42.22	-71.67	29.45	18	19.75	0.03	-	-	Average
0.0918	35.37	80	-44.63	-71	26.37	15.44	19.9	0.03	-	-	QP
0.1308	34	80	-46	-70.46	24.46	13.92	20.04	0.04	-	-	Average
1.676	35.32	40	-4.68	-27.75	23.07	14.94	20.17	0.21	-	-	QP
2.21	34.2	40	-5.8	-35.34	29.54	13.43	20.28	0.49	-	-	QP
9.336	33.88	40	-6.12	-35.66	29.54	12.73	20.22	0.93	-	-	QP
19.456	34.08	40	-5.92	-35.46	29.54	12.58	20.4	1.1	-	-	QP
26.9	36.14	40	-3.86	-33.4	29.54	14.43	20.51	1.2	-	-	QP

Test Mode :		NFC Tx				Polarization :		Parallel			
Frequency (MHz)	Level @3m (dB μ V/m)	Distance Factor (dB)	Corrected Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.04847	47.74	80	-32.26	-68.16	35.9	28	19.7	0.04	-	-	Average
0.08472	47.37	80	-32.63	-62.51	29.88	27.6	19.73	0.04	-	-	Average
0.09048	34.42	80	-45.58	-72.47	26.89	14.5	19.89	0.03	-	-	QP
0.13569	30.97	80	-49.03	-74	24.97	10.98	19.95	0.04	-	-	Average
1.669	35.12	40	-4.88	-27.89	23.01	14.74	20.17	0.21	-	-	QP
2.3	35.13	40	-4.87	-34.41	29.54	14.39	20.27	0.47	-	-	QP
10.056	34.96	40	-5.04	-34.58	29.54	13.76	20.31	0.89	-	-	QP
22.282	34.12	40	-5.88	-35.42	29.54	12.74	20.33	1.05	-	-	QP
25.07	34.53	40	-5.47	-35.01	29.54	12.96	20.4	1.17	-	-	QP

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);
3. Corrected Level = Level @3m (dB μ V/m) - distance extrapolation factor.

**C3. Results of Radiated Spurious Emissions (30MHz~1GHz)**

Test Mode :		NFC Tx			Polarization :		Horizontal			
Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
44.55	25.06	-14.94	40	38.42	19.55	1.58	34.49	-	-	Peak
82.38	29.58	-10.42	40	48.34	14.31	1.93	35	-	-	Peak
200.72	26.24	-17.26	43.5	42.24	16.15	2.75	34.9	-	-	Peak
325.85	30.98	-15.02	46	42.63	20.12	3.33	35.1	-	-	Peak
706.09	29.17	-16.83	46	32.31	27.32	3.74	34.2	-	-	Peak
811.82	31.53	-14.47	46	32.06	29	4.39	33.92	-	-	Peak

Test Mode :		NFC Tx			Polarization :		Vertical			
Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
41.64	33.67	-6.33	40	47.3	19.37	1.43	34.43	100	266	QP
76.56	32.99	-7.01	40	50.35	15.59	1.88	34.83	-	-	Peak
207.51	23.29	-20.21	43.5	38.91	16.44	2.79	34.85	-	-	Peak
319.06	25.48	-20.52	46	37.34	19.94	3.3	35.1	-	-	Peak
465.53	27.54	-18.46	46	35.44	23.15	3.44	34.49	-	-	Peak
584.84	29.74	-16.26	46	34.74	25.87	3.56	34.43	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.