



FCC RF Test Report

APPLICANT : NOTHING TECHNOLOGY LIMITED
EQUIPMENT : Smart Phone
BRAND NAME : NOTHING
MODEL NAME : A059P
FCC ID : 2AZEQ-24111
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Nov. 27, 2024 ~ Nov. 28, 2024

We, Sporton International Inc.(ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
3 TEST RESULT	12
3.1 Unwanted Emissions Measurement	12
3.2 Antenna Requirements	17
4 LIST OF MEASURING EQUIPMENT	18
5 MEASUREMENT UNCERTAINTY	19
APPENDIX A. RADIATED SPURIOUS EMISSION	
APPENDIX B. DUTY CYCLE PLOTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR490417-01E	Rev. 01	Initial issue of report	Dec. 17, 2024



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.09 dB at 5149.99 MHz
3.2	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

Remark: This is a variant report for A059P, the change note could be referred to the Product Equality Declaration which is exhibit separately. According to the change, only the related test cases were verified from original report FR490417E.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

NOTHING TECHNOLOGY LIMITED

Bedford House, 21A John Street, London, United Kingdom WC1N 2BF

1.2 Manufacturer

NOTHING TECHNOLOGY LIMITED

Bedford House, 21A John Street, London, United Kingdom WC1N 2BF

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	NOTHING
Model Name	A059P
FCC ID	2AZEQ-24111
IMEI Code	Radiation: 353458700016747/353458700016754
HW Version	24111 Pro
SW Version	Nothing OS 3.1
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
Antenna Type / Gain	<5180 MHz ~ 5240 MHz> <Ant. 5> : Metal frame Antenna with gain -1.82 dBi <Ant. 6> : Metal frame Antenna with gain 0.08 dBi <5260 MHz ~ 5320 MHz> <Ant. 5> : Metal frame Antenna with gain -1.18 dBi <Ant. 6> : Metal frame Antenna with gain 0.69 dBi <5500 MHz ~ 5720 MHz> <Ant. 5> : Metal frame Antenna with gain -0.69 dBi <Ant. 6> : Metal frame Antenna with gain 1.00 dBi <5745 MHz ~ 5825 MHz> <Ant. 5> : Metal frame Antenna with gain -0.83 dBi <Ant. 6> : Metal frame Antenna with gain 0.21 dBi



Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)
---------------------------	--

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH01-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:



1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated:, radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y/Z plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210	50 ^{##}	5250
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290	-	-
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 [#]	5610	128	5640
	-	-	114 ^{##}	5570

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 [#]	5690	144	5720
	142*	5710	-	-

Note:

1. The above Frequency and Channel in "*" are 40MHz bandwidth.
2. The above Frequency and Channel in "[#]" are 80MHz bandwidth.
3. The above Frequency and Channel in "^{##}" are 160MHz bandwidth.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

MIMO Mode

Modulation	Data Rate
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Remark : For Radiated Test Cases, The tests were performance with Adapter and USB Cable.




Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		20M BW	20M BW	20M BW	20M BW
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		40M BW	40M BW	40M BW	40M BW
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		80M BW	80M BW	80M BW	80M BW
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	-	-
Straddle		-	-	138	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		160M BW		160M BW	160M BW
M	Middle	50		114	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

3 Test Result

3.1 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.1.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

- (2) For transmitters operating in the 5.725-5.85 GHz band:
- 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(4) EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.1.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.1.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.1.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.1.7 Duty Cycle

Please refer to Appendix B.

3.1.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix A.



3.2 Antenna Requirements

3.2.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.2.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = GANT + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(\text{NANT}/\text{NSS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $\text{NANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain GANT is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 5	Ant. 6	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
UNII-1	-1.82	0.08	3.00	6.01	0.00	0.01
UNII-2A	-1.18	0.69	3.00	6.01	0.00	0.01
UNII-2C	-0.69	1.00	3.00	6.01	0.00	0.01
UNII-3	-0.83	0.21	3.00	6.01	0.00	0.01

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Dec. 27, 2024	Nov. 27, 2024~Nov. 28, 2024	Dec. 26, 2025	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2024	Nov. 27, 2024~Nov. 28, 2024	Jul. 02, 2025	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 29, 2023	Nov. 27, 2024~Nov. 28, 2024	Dec. 28, 2024	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Oct. 24, 2023	Nov. 27, 2024~Nov. 28, 2024	Oct. 23, 2025	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2024	Nov. 27, 2024~Nov. 28, 2024	Jul. 03, 2025	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 09, 2024	Nov. 27, 2024~Nov. 28, 2024	Apr. 08, 2025	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 09, 2024	Nov. 27, 2024~Nov. 28, 2024	Apr. 08, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 14, 2024	Nov. 27, 2024~Nov. 28, 2024	Oct. 13, 2025	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5GHz	Oct. 14, 2024	Nov. 27, 2024~Nov. 28, 2024	Oct. 13, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2024	Nov. 27, 2024~Nov. 28, 2024	Jul. 02, 2025	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	Oct. 14, 2024	Nov. 27, 2024~Nov. 28, 2024	Oct. 13, 2025	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Nov. 27, 2024~Nov. 28, 2024	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Nov. 27, 2024~Nov. 28, 2024	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.3 dB
---	--------

----- THE END -----



Appendix A Radiated Spurious Emission Test Data

Test Engineer :	Jia Kuang	Relative Humidity :	48~49%
		Temperature :	24-25°C

Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	U-NII-1	5.15-5.25	CDD 5+6	802.11ax HE40	38	5190	MCS0	-	-
Mode 2	U-NII-3	5.725-5.85	CDD 5+6	802.11ax HE80	155	5775	MCS0	-	-
Mode 3	U-NII-1	5.15-5.25	CDD 5+6	802.11ax HE40-LF	38	5190	MCS0	-	-
Mode 4	U-NII-3	5.725-5.85	CDD 5+6	802.11ax HE80-LF	155	5775	MCS0	-	-

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	802.11ax HE40	38	5149.99	50.91	54.00	-3.09	H	AVERAGE	Pass	Band Edge
1	802.11ax HE40	38	10380.00	47.71	68.30	-20.59	H	Peak	Pass	Harmonic
2	802.11ax HE80	155	5645.96	55.70	68.30	-12.60	V	PEAK	Pass	Band Edge
2	802.11ax HE80	155	17325.00	47.83	68.30	-20.47	V	Peak	Pass	Harmonic
3	802.11ax HE40-LF	38	35.82	33.34	40.00	-6.66	V	QP	Pass	LF
4	802.11ax HE80-LF	155	36.79	33.56	40.00	-6.44	V	QP	Pass	LF







Mode	1																																																		
	Band Edge - L																																																		
	U-NII-1_5.15-5.25_802.11ax HE40_CH38_5190MHz																																																		
ANT	CDD 5+6																																																		
Pol.	Horizontal																																																		
Peak	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5147.73</td><td>63.31</td><td>74.00</td><td>-10.69</td><td>49.15</td><td>35.70</td><td>11.09</td><td>32.63</td><td>185</td><td>136</td><td>PEAK</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5147.73	63.31	74.00	-10.69	49.15	35.70	11.09	32.63	185	136	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	5147.73	63.31	74.00	-10.69	49.15	35.70	11.09	32.63	185	136	PEAK																																								
Fundamental	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5190.00</td><td>106.44</td><td>-----</td><td>-----</td><td>92.24</td><td>35.78</td><td>11.06</td><td>32.64</td><td>185</td><td>136</td><td>PEAK</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5190.00	106.44	-----	-----	92.24	35.78	11.06	32.64	185	136	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	5190.00	106.44	-----	-----	92.24	35.78	11.06	32.64	185	136	PEAK																																								
Avg	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5149.99</td><td>50.91</td><td>54.00</td><td>-3.09</td><td>36.76</td><td>35.70</td><td>11.08</td><td>32.63</td><td>185</td><td>136</td><td>AVERAGE</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5149.99	50.91	54.00	-3.09	36.76	35.70	11.08	32.63	185	136	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	5149.99	50.91	54.00	-3.09	36.76	35.70	11.08	32.63	185	136	AVERAGE																																								
	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5190.00</td><td>98.71</td><td>-----</td><td>-----</td><td>84.51</td><td>35.77</td><td>11.07</td><td>32.64</td><td>185</td><td>136</td><td>AVERAGE</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5190.00	98.71	-----	-----	84.51	35.77	11.07	32.64	185	136	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	5190.00	98.71	-----	-----	84.51	35.77	11.07	32.64	185	136	AVERAGE																																								



Mode	1																																																		
	Band Edge - R																																																		
	U-NII-1_5.15-5.25_802.11ax HE40_CH38_5190MHz																																																		
ANT	CDD 5+6																																																		
Pol.	Horizontal						Fundamental																																												
Peak	Date: 2024-11-27 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5361.34</td><td>53.07</td><td>74.00</td><td>-20.93</td><td>38.72</td><td>36.08</td><td>10.94</td><td>32.67</td><td>185</td><td>136</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5361.34	53.07	74.00	-20.93	38.72	36.08	10.94	32.67	185	136	PEAK	Blank				
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	5361.34	53.07	74.00	-20.93	38.72	36.08	10.94	32.67	185	136	PEAK																																								
Avg	Date: 2024-11-27 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5357.02</td><td>42.53</td><td>54.00</td><td>-11.47</td><td>28.17</td><td>36.09</td><td>10.94</td><td>32.67</td><td>185</td><td>136</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5357.02	42.53	54.00	-11.47	28.17	36.09	10.94	32.67	185	136	AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	5357.02	42.53	54.00	-11.47	28.17	36.09	10.94	32.67	185	136	AVERAGE																																								





Mode	1																																																																																																																																																										
	Band Edge - L																																																																																																																																																										
	U-NII-1_5.15-5.25_802.11ax HE40_CH38_5190MHz																																																																																																																																																										
ANT	CDD 5+6																																																																																																																																																										
Pol.	Vertical	Fundamental																																																																																																																																																									
Peak	Level (dBuV/m) Date: 2024-11-27  <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5149.19</td><td>57.72</td><td>74.00</td><td>-16.28</td><td>43.56</td><td>35.70</td><td>11.09</td><td>32.63</td><td>393</td><td>274 PEAK</td></tr></tbody></table> Level (dBuV/m) Date: 2024-11-27  <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5190.00</td><td>104.42</td><td>-----</td><td>-----</td><td>90.22</td><td>35.77</td><td>11.07</td><td>32.64</td><td>393</td><td>274 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5149.19	57.72	74.00	-16.28	43.56	35.70	11.09	32.63	393	274 PEAK		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5190.00	104.42	-----	-----	90.22	35.77	11.07	32.64	393	274 PEAK	Avg	Level (dBuV/m) Date: 2024-11-27  <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5149.93</td><td>47.99</td><td>54.00</td><td>-6.01</td><td>33.83</td><td>35.70</td><td>11.09</td><td>32.63</td><td>393</td><td>274 AVERAGE</td></tr></tbody></table> Level (dBuV/m) Date: 2024-11-27  <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5190.00</td><td>97.48</td><td>-----</td><td>-----</td><td>83.28</td><td>35.77</td><td>11.07</td><td>32.64</td><td>393</td><td>274 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5149.93	47.99	54.00	-6.01	33.83	35.70	11.09	32.63	393	274 AVERAGE		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5190.00	97.48	-----	-----	83.28	35.77	11.07	32.64	393	274 AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																		
1 5149.19	57.72	74.00	-16.28	43.56	35.70	11.09	32.63	393	274 PEAK																																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																		
1 5190.00	104.42	-----	-----	90.22	35.77	11.07	32.64	393	274 PEAK																																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																		
1 5149.93	47.99	54.00	-6.01	33.83	35.70	11.09	32.63	393	274 AVERAGE																																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																		
1 5190.00	97.48	-----	-----	83.28	35.77	11.07	32.64	393	274 AVERAGE																																																																																																																																																		



Mode	1										
	Band Edge - R										
	U-NII-1_5.15-5.25_802.11ax HE40_CH38_5190MHz										
ANT	CDD 5+6										
Pol.	Vertical										Fundamental
Peak											



Mode	1																																																																						
	Harmonic																																																																						
	U-NII-1_5.15-5.25_802.11ax HE40_CH38_5190MHz																																																																						
ANT	CDD 5+6																																																																						
Pol.	Horizontal						Vertical																																																																
Peak Avg																																																																							
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>10380.00</td><td>47.71</td><td>68.30</td><td>-20.59</td><td>46.87</td><td>38.10</td><td>14.16</td><td>51.42</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>15570.00</td><td>46.92</td><td>74.00</td><td>-27.08</td><td>41.70</td><td>40.60</td><td>16.87</td><td>52.25</td><td>---</td><td>---</td><td>Peak</td></tr></table>														Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	10380.00	47.71	68.30	-20.59	46.87	38.10	14.16	51.42	---	---	Peak	2	15570.00	46.92	74.00	-27.08	41.70	40.60	16.87	52.25	---	---	Peak
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																														
1	10380.00	47.71	68.30	-20.59	46.87	38.10	14.16	51.42	---	---	Peak																																																												
2	15570.00	46.92	74.00	-27.08	41.70	40.60	16.87	52.25	---	---	Peak																																																												
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>10380.00</td><td>47.29</td><td>68.30</td><td>-21.01</td><td>46.45</td><td>38.10</td><td>14.16</td><td>51.42</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>15570.00</td><td>47.61</td><td>74.00</td><td>-26.39</td><td>42.39</td><td>40.60</td><td>16.87</td><td>52.25</td><td>---</td><td>---</td><td>Peak</td></tr></table>														Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	10380.00	47.29	68.30	-21.01	46.45	38.10	14.16	51.42	---	---	Peak	2	15570.00	47.61	74.00	-26.39	42.39	40.60	16.87	52.25	---	---	Peak	
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																														
1	10380.00	47.29	68.30	-21.01	46.45	38.10	14.16	51.42	---	---	Peak																																																												
2	15570.00	47.61	74.00	-26.39	42.39	40.60	16.87	52.25	---	---	Peak																																																												



Mode	2																																																																																																																					
	Band Edge - L																																																																																																																					
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_5775MHz																																																																																																																					
ANT	CDD 5+6																																																																																																																					
Pol.	Horizontal	Fundamental																																																																																																																				
Peak	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5646.11</td><td>55.26</td><td>68.30</td><td>-13.04</td><td>39.85</td><td>36.48</td><td>11.69</td><td>32.76</td><td>219</td><td>240</td><td>PEAK</td></tr><tr><td>2</td><td>5650.16</td><td>54.57</td><td>68.41</td><td>-13.84</td><td>39.14</td><td>36.50</td><td>11.69</td><td>32.76</td><td>219</td><td>240</td><td>PEAK</td></tr><tr><td>3</td><td>5707.03</td><td>68.69</td><td>107.17</td><td>-38.48</td><td>53.20</td><td>36.61</td><td>11.66</td><td>32.78</td><td>219</td><td>240</td><td>PEAK</td></tr><tr><td>4</td><td>5720.02</td><td>66.06</td><td>110.83</td><td>-44.77</td><td>50.55</td><td>36.64</td><td>11.66</td><td>32.79</td><td>219</td><td>240</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5646.11	55.26	68.30	-13.04	39.85	36.48	11.69	32.76	219	240	PEAK	2	5650.16	54.57	68.41	-13.84	39.14	36.50	11.69	32.76	219	240	PEAK	3	5707.03	68.69	107.17	-38.48	53.20	36.61	11.66	32.78	219	240	PEAK	4	5720.02	66.06	110.83	-44.77	50.55	36.64	11.66	32.79	219	240	PEAK	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>105.50</td><td>-----</td><td>-----</td><td>90.05</td><td>36.63</td><td>11.63</td><td>32.81</td><td>219</td><td>240</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	105.50	-----	-----	90.05	36.63	11.63	32.81	219	240	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	5646.11	55.26	68.30	-13.04	39.85	36.48	11.69	32.76	219	240	PEAK																																																																																																											
2	5650.16	54.57	68.41	-13.84	39.14	36.50	11.69	32.76	219	240	PEAK																																																																																																											
3	5707.03	68.69	107.17	-38.48	53.20	36.61	11.66	32.78	219	240	PEAK																																																																																																											
4	5720.02	66.06	110.83	-44.77	50.55	36.64	11.66	32.79	219	240	PEAK																																																																																																											
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	5775.00	105.50	-----	-----	90.05	36.63	11.63	32.81	219	240	PEAK																																																																																																											
Avg	Blank	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>96.90</td><td>-----</td><td>-----</td><td>81.43</td><td>36.65</td><td>11.63</td><td>32.81</td><td>219</td><td>240</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	96.90	-----	-----	81.43	36.65	11.63	32.81	219	240	AVERAGE																																																																												
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	5775.00	96.90	-----	-----	81.43	36.65	11.63	32.81	219	240	AVERAGE																																																																																																											



Mode	2																																																																											
	Band Edge - R																																																																											
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_5775MHz																																																																											
ANT	CDD 5+6																																																																											
Pol.	Horizontal					Fundamental																																																																						
Peak	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.17</td><td>60.69</td><td>110.86</td><td>-50.17</td><td>45.50</td><td>36.51</td><td>11.52</td><td>32.84</td><td>219</td><td>240 PEAK</td></tr><tr><td>2</td><td>5855.24</td><td>62.61</td><td>110.73</td><td>-48.12</td><td>47.42</td><td>36.51</td><td>11.52</td><td>32.84</td><td>219</td><td>240 PEAK</td></tr><tr><td>3</td><td>5924.21</td><td>52.82</td><td>68.79</td><td>-15.97</td><td>37.64</td><td>36.65</td><td>11.40</td><td>32.87</td><td>219</td><td>240 PEAK</td></tr><tr><td>4</td><td>5926.48</td><td>53.95</td><td>68.30</td><td>-14.35</td><td>38.77</td><td>36.65</td><td>11.40</td><td>32.87</td><td>219</td><td>240 PEAK</td></tr></table>						Freq	Level	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.17	60.69	110.86	-50.17	45.50	36.51	11.52	32.84	219	240 PEAK	2	5855.24	62.61	110.73	-48.12	47.42	36.51	11.52	32.84	219	240 PEAK	3	5924.21	52.82	68.79	-15.97	37.64	36.65	11.40	32.87	219	240 PEAK	4	5926.48	53.95	68.30	-14.35	38.77	36.65	11.40	32.87	219	240 PEAK	Blank				
	Freq	Level	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																		
1	5854.17	60.69	110.86	-50.17	45.50	36.51	11.52	32.84	219	240 PEAK																																																																		
2	5855.24	62.61	110.73	-48.12	47.42	36.51	11.52	32.84	219	240 PEAK																																																																		
3	5924.21	52.82	68.79	-15.97	37.64	36.65	11.40	32.87	219	240 PEAK																																																																		
4	5926.48	53.95	68.30	-14.35	38.77	36.65	11.40	32.87	219	240 PEAK																																																																		





Mode	2																																																																																																																														
	Band Edge - L																																																																																																																														
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_5775MHz																																																																																																																														
ANT	CDD 5+6																																																																																																																														
Pol.	Vertical						Fundamental																																																																																																																								
Peak	Level (dBuV/m) Date: 2024-11-27 PEAK_BE(B4)_16-24 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5645.96</td><td>55.70</td><td>68.30</td><td>-12.60</td><td>40.29</td><td>36.48</td><td>11.69</td><td>32.76</td><td>369</td><td>64</td><td>PEAK</td></tr><tr><td>2</td><td>5650.16</td><td>54.48</td><td>68.41</td><td>-13.93</td><td>39.05</td><td>36.50</td><td>11.69</td><td>32.76</td><td>369</td><td>64</td><td>PEAK</td></tr><tr><td>3</td><td>5700.03</td><td>64.49</td><td>105.21</td><td>-40.72</td><td>49.01</td><td>36.60</td><td>11.66</td><td>32.78</td><td>369</td><td>64</td><td>PEAK</td></tr><tr><td>4</td><td>5720.02</td><td>64.81</td><td>110.83</td><td>-46.02</td><td>49.30</td><td>36.64</td><td>11.66</td><td>32.79</td><td>369</td><td>64</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5645.96	55.70	68.30	-12.60	40.29	36.48	11.69	32.76	369	64	PEAK	2	5650.16	54.48	68.41	-13.93	39.05	36.50	11.69	32.76	369	64	PEAK	3	5700.03	64.49	105.21	-40.72	49.01	36.60	11.66	32.78	369	64	PEAK	4	5720.02	64.81	110.83	-46.02	49.30	36.64	11.66	32.79	369	64	PEAK	Level (dBuV/m) Date: 2024-11-27 PART 15.407 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>107.63</td><td>-----</td><td>-----</td><td>92.17</td><td>36.64</td><td>11.63</td><td>32.81</td><td>369</td><td>64</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5775.00	107.63	-----	-----	92.17	36.64	11.63	32.81	369	64	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																						
1	5645.96	55.70	68.30	-12.60	40.29	36.48	11.69	32.76	369	64	PEAK																																																																																																																				
2	5650.16	54.48	68.41	-13.93	39.05	36.50	11.69	32.76	369	64	PEAK																																																																																																																				
3	5700.03	64.49	105.21	-40.72	49.01	36.60	11.66	32.78	369	64	PEAK																																																																																																																				
4	5720.02	64.81	110.83	-46.02	49.30	36.64	11.66	32.79	369	64	PEAK																																																																																																																				
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																						
1	5775.00	107.63	-----	-----	92.17	36.64	11.63	32.81	369	64	PEAK																																																																																																																				
Avg	Blank						Level (dBuV/m) Date: 2024-11-27 PART 15.407 AVG <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>97.72</td><td>-----</td><td>-----</td><td>82.25</td><td>36.65</td><td>11.63</td><td>32.81</td><td>369</td><td>64</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	5775.00	97.72	-----	-----	82.25	36.65	11.63	32.81	369	64	AVERAGE																																																																												
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																						
1	5775.00	97.72	-----	-----	82.25	36.65	11.63	32.81	369	64	AVERAGE																																																																																																																				





Mode	2																																																																																		
	Band Edge - R																																																																																		
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_5775MHz																																																																																		
ANT	CDD 5+6																																																																																		
Pol.	Vertical						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2024-11-27 Frequency (MHz) <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5854.99</td><td>59.43</td><td>110.82</td><td>-51.39</td><td>44.24</td><td>36.51</td><td>11.52</td><td>32.84</td><td>369</td><td>64</td><td>PEAK</td></tr><tr><td>2</td><td>5856.81</td><td>61.12</td><td>110.29</td><td>-49.17</td><td>45.93</td><td>36.51</td><td>11.52</td><td>32.84</td><td>369</td><td>64</td><td>PEAK</td></tr><tr><td>3</td><td>5924.99</td><td>52.22</td><td>68.21</td><td>-15.99</td><td>37.04</td><td>36.65</td><td>11.40</td><td>32.87</td><td>369</td><td>64</td><td>PEAK</td></tr><tr><td>4</td><td>5949.91</td><td>53.70</td><td>68.30</td><td>-14.60</td><td>38.52</td><td>36.70</td><td>11.36</td><td>32.88</td><td>369</td><td>64</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5854.99	59.43	110.82	-51.39	44.24	36.51	11.52	32.84	369	64	PEAK	2	5856.81	61.12	110.29	-49.17	45.93	36.51	11.52	32.84	369	64	PEAK	3	5924.99	52.22	68.21	-15.99	37.04	36.65	11.40	32.87	369	64	PEAK	4	5949.91	53.70	68.30	-14.60	38.52	36.70	11.36	32.88	369	64	PEAK	Blank				
	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	5854.99	59.43	110.82	-51.39	44.24	36.51	11.52	32.84	369	64	PEAK																																																																								
2	5856.81	61.12	110.29	-49.17	45.93	36.51	11.52	32.84	369	64	PEAK																																																																								
3	5924.99	52.22	68.21	-15.99	37.04	36.65	11.40	32.87	369	64	PEAK																																																																								
4	5949.91	53.70	68.30	-14.60	38.52	36.70	11.36	32.88	369	64	PEAK																																																																								





Mode	2																																																																						
	Harmonic																																																																						
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_5775MHz																																																																						
ANT	CDD 5+6																																																																						
Pol.	Horizontal						Vertical																																																																
Peak Avg																																																																							
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>11550.00</td><td>47.64</td><td>74.00</td><td>-26.36</td><td>44.83</td><td>38.20</td><td>14.87</td><td>50.26</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>17325.00</td><td>47.67</td><td>68.30</td><td>-20.63</td><td>41.02</td><td>42.28</td><td>17.59</td><td>53.22</td><td>---</td><td>---</td><td>Peak</td></tr></table>														Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	11550.00	47.64	74.00	-26.36	44.83	38.20	14.87	50.26	---	---	Peak	2	17325.00	47.67	68.30	-20.63	41.02	42.28	17.59	53.22	---	---	Peak
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																														
1	11550.00	47.64	74.00	-26.36	44.83	38.20	14.87	50.26	---	---	Peak																																																												
2	17325.00	47.67	68.30	-20.63	41.02	42.28	17.59	53.22	---	---	Peak																																																												
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>11550.00</td><td>47.53</td><td>74.00</td><td>-26.47</td><td>44.72</td><td>38.20</td><td>14.87</td><td>50.26</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>17325.00</td><td>47.83</td><td>68.30</td><td>-20.47</td><td>41.18</td><td>42.28</td><td>17.59</td><td>53.22</td><td>---</td><td>---</td><td>Peak</td></tr></table>														Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	11550.00	47.53	74.00	-26.47	44.72	38.20	14.87	50.26	---	---	Peak	2	17325.00	47.83	68.30	-20.47	41.18	42.28	17.59	53.22	---	---	Peak	
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																														
1	11550.00	47.53	74.00	-26.47	44.72	38.20	14.87	50.26	---	---	Peak																																																												
2	17325.00	47.83	68.30	-20.47	41.18	42.28	17.59	53.22	---	---	Peak																																																												



Mode	3																																																																																																																																																																																																																																	
	LF																																																																																																																																																																																																																																	
	U-NII-1_5.15-5.25_802.11ax HE40-LF_CH38_5190MHz																																																																																																																																																																																																																																	
ANT	CDD 5+6																																																																																																																																																																																																																																	
Pol.	Horizontal						Vertical																																																																																																																																																																																																																											
QP/ Peak																																																																																																																																																																																																																																		
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>30.97</td><td>23.82</td><td>40.00</td><td>-16.18</td><td>29.37</td><td>24.62</td><td>1.03</td><td>31.20</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>92.08</td><td>21.79</td><td>43.50</td><td>-21.71</td><td>35.86</td><td>15.46</td><td>1.75</td><td>31.28</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>199.75</td><td>29.94</td><td>43.50</td><td>-13.56</td><td>42.77</td><td>15.50</td><td>2.57</td><td>30.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>320.03</td><td>30.45</td><td>46.00</td><td>-15.55</td><td>38.25</td><td>19.84</td><td>3.22</td><td>30.86</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>484.93</td><td>29.14</td><td>46.00</td><td>-16.86</td><td>32.39</td><td>23.48</td><td>3.97</td><td>30.70</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>971.87</td><td>33.28</td><td>54.00</td><td>-20.72</td><td>31.35</td><td>27.32</td><td>5.61</td><td>31.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	30.97	23.82	40.00	-16.18	29.37	24.62	1.03	31.20	---	---	Peak	2	92.08	21.79	43.50	-21.71	35.86	15.46	1.75	31.28	---	---	Peak	3	199.75	29.94	43.50	-13.56	42.77	15.50	2.57	30.90	---	---	Peak	4	320.03	30.45	46.00	-15.55	38.25	19.84	3.22	30.86	---	---	Peak	5	484.93	29.14	46.00	-16.86	32.39	23.48	3.97	30.70	---	---	Peak	6	971.87	33.28	54.00	-20.72	31.35	27.32	5.61	31.00	---	---	Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>35.82</td><td>33.34</td><td>40.00</td><td>-6.66</td><td>41.76</td><td>21.68</td><td>1.10</td><td>31.20</td><td>100</td><td>211</td><td>QP</td></tr><tr><td>2</td><td>86.26</td><td>25.37</td><td>40.00</td><td>-14.63</td><td>40.64</td><td>14.38</td><td>1.69</td><td>31.34</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>196.84</td><td>27.15</td><td>43.50</td><td>-16.35</td><td>40.10</td><td>15.41</td><td>2.55</td><td>30.91</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>316.15</td><td>27.28</td><td>46.00</td><td>-18.72</td><td>35.19</td><td>19.76</td><td>3.20</td><td>30.87</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>482.99</td><td>32.86</td><td>46.00</td><td>-13.14</td><td>36.14</td><td>23.46</td><td>3.96</td><td>30.70</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>953.44</td><td>33.50</td><td>46.00</td><td>-12.50</td><td>31.78</td><td>27.14</td><td>5.58</td><td>31.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	35.82	33.34	40.00	-6.66	41.76	21.68	1.10	31.20	100	211	QP	2	86.26	25.37	40.00	-14.63	40.64	14.38	1.69	31.34	---	---	Peak	3	196.84	27.15	43.50	-16.35	40.10	15.41	2.55	30.91	---	---	Peak	4	316.15	27.28	46.00	-18.72	35.19	19.76	3.20	30.87	---	---	Peak	5	482.99	32.86	46.00	-13.14	36.14	23.46	3.96	30.70	---	---	Peak	6	953.44	33.50	46.00	-12.50	31.78	27.14	5.58	31.00	---	---	Peak
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																									
1	30.97	23.82	40.00	-16.18	29.37	24.62	1.03	31.20	---	---	Peak																																																																																																																																																																																																																							
2	92.08	21.79	43.50	-21.71	35.86	15.46	1.75	31.28	---	---	Peak																																																																																																																																																																																																																							
3	199.75	29.94	43.50	-13.56	42.77	15.50	2.57	30.90	---	---	Peak																																																																																																																																																																																																																							
4	320.03	30.45	46.00	-15.55	38.25	19.84	3.22	30.86	---	---	Peak																																																																																																																																																																																																																							
5	484.93	29.14	46.00	-16.86	32.39	23.48	3.97	30.70	---	---	Peak																																																																																																																																																																																																																							
6	971.87	33.28	54.00	-20.72	31.35	27.32	5.61	31.00	---	---	Peak																																																																																																																																																																																																																							
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																									
1	35.82	33.34	40.00	-6.66	41.76	21.68	1.10	31.20	100	211	QP																																																																																																																																																																																																																							
2	86.26	25.37	40.00	-14.63	40.64	14.38	1.69	31.34	---	---	Peak																																																																																																																																																																																																																							
3	196.84	27.15	43.50	-16.35	40.10	15.41	2.55	30.91	---	---	Peak																																																																																																																																																																																																																							
4	316.15	27.28	46.00	-18.72	35.19	19.76	3.20	30.87	---	---	Peak																																																																																																																																																																																																																							
5	482.99	32.86	46.00	-13.14	36.14	23.46	3.96	30.70	---	---	Peak																																																																																																																																																																																																																							
6	953.44	33.50	46.00	-12.50	31.78	27.14	5.58	31.00	---	---	Peak																																																																																																																																																																																																																							




Mode	4																																																																																																																																																																																																																											
	LF																																																																																																																																																																																																																											
	U-NII-3_5.725-5.85_802.11ax HE80-LF_CH155_5775MHz																																																																																																																																																																																																																											
ANT	CDD 5+6																																																																																																																																																																																																																											
Pol.	Horizontal						Vertical																																																																																																																																																																																																																					
QP/ Peak																																																																																																																																																																																																																												
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>30.00</td><td>24.30</td><td>40.00</td><td>-15.70</td><td>29.29</td><td>25.20</td><td>1.01</td><td>31.20</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>92.08</td><td>22.28</td><td>43.50</td><td>-21.22</td><td>36.35</td><td>15.46</td><td>1.75</td><td>31.28</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>199.75</td><td>30.26</td><td>43.50</td><td>-13.24</td><td>43.09</td><td>15.50</td><td>2.57</td><td>30.90</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>322.94</td><td>30.13</td><td>46.00</td><td>-15.87</td><td>37.83</td><td>19.91</td><td>3.24</td><td>30.85</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>483.96</td><td>29.78</td><td>46.00</td><td>-16.22</td><td>33.05</td><td>23.47</td><td>3.96</td><td>30.70</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>793.39</td><td>30.70</td><td>46.00</td><td>-15.30</td><td>30.65</td><td>26.07</td><td>5.06</td><td>31.08</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	cm	deg		1	30.00	24.30	40.00	-15.70	29.29	25.20	1.01	31.20	---	---	---	Peak	2	92.08	22.28	43.50	-21.22	36.35	15.46	1.75	31.28	---	---	---	Peak	3	199.75	30.26	43.50	-13.24	43.09	15.50	2.57	30.90	---	---	---	Peak	4	322.94	30.13	46.00	-15.87	37.83	19.91	3.24	30.85	---	---	---	Peak	5	483.96	29.78	46.00	-16.22	33.05	23.47	3.96	30.70	---	---	---	Peak	6	793.39	30.70	46.00	-15.30	30.65	26.07	5.06	31.08	---	---	---	Peak	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>36.79</td><td>33.56</td><td>40.00</td><td>-6.44</td><td>42.58</td><td>21.06</td><td>1.12</td><td>31.20</td><td>100</td><td>205</td><td>QP</td><td></td></tr><tr><td>2</td><td>90.14</td><td>26.07</td><td>43.50</td><td>-17.43</td><td>40.54</td><td>15.10</td><td>1.73</td><td>31.30</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>197.81</td><td>28.20</td><td>43.50</td><td>-15.30</td><td>41.11</td><td>15.44</td><td>2.56</td><td>30.91</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>314.21</td><td>27.37</td><td>46.00</td><td>-18.63</td><td>35.33</td><td>19.72</td><td>3.19</td><td>30.87</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>491.72</td><td>32.73</td><td>46.00</td><td>-13.27</td><td>35.86</td><td>23.58</td><td>3.99</td><td>30.70</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>870.02</td><td>31.77</td><td>46.00</td><td>-14.23</td><td>30.89</td><td>26.62</td><td>5.29</td><td>31.03</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	cm	deg		1	36.79	33.56	40.00	-6.44	42.58	21.06	1.12	31.20	100	205	QP		2	90.14	26.07	43.50	-17.43	40.54	15.10	1.73	31.30	---	---	---	Peak	3	197.81	28.20	43.50	-15.30	41.11	15.44	2.56	30.91	---	---	---	Peak	4	314.21	27.37	46.00	-18.63	35.33	19.72	3.19	30.87	---	---	---	Peak	5	491.72	32.73	46.00	-13.27	35.86	23.58	3.99	30.70	---	---	---	Peak	6	870.02	31.77	46.00	-14.23	30.89	26.62	5.29	31.03	---	---	---	Peak
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																															
		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																
	1	30.00	24.30	40.00	-15.70	29.29	25.20	1.01	31.20	---	---	---	Peak																																																																																																																																																																																																															
	2	92.08	22.28	43.50	-21.22	36.35	15.46	1.75	31.28	---	---	---	Peak																																																																																																																																																																																																															
	3	199.75	30.26	43.50	-13.24	43.09	15.50	2.57	30.90	---	---	---	Peak																																																																																																																																																																																																															
	4	322.94	30.13	46.00	-15.87	37.83	19.91	3.24	30.85	---	---	---	Peak																																																																																																																																																																																																															
	5	483.96	29.78	46.00	-16.22	33.05	23.47	3.96	30.70	---	---	---	Peak																																																																																																																																																																																																															
	6	793.39	30.70	46.00	-15.30	30.65	26.07	5.06	31.08	---	---	---	Peak																																																																																																																																																																																																															
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																	
1	36.79	33.56	40.00	-6.44	42.58	21.06	1.12	31.20	100	205	QP																																																																																																																																																																																																																	
2	90.14	26.07	43.50	-17.43	40.54	15.10	1.73	31.30	---	---	---	Peak																																																																																																																																																																																																																
3	197.81	28.20	43.50	-15.30	41.11	15.44	2.56	30.91	---	---	---	Peak																																																																																																																																																																																																																
4	314.21	27.37	46.00	-18.63	35.33	19.72	3.19	30.87	---	---	---	Peak																																																																																																																																																																																																																
5	491.72	32.73	46.00	-13.27	35.86	23.58	3.99	30.70	---	---	---	Peak																																																																																																																																																																																																																
6	870.02	31.77	46.00	-14.23	30.89	26.62	5.29	31.03	---	---	---	Peak																																																																																																																																																																																																																



Appendix B. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11ax HE40	99.63	-	-	10Hz
802.11ax HE80	99.19	-	-	10Hz

802.11ax HE40



802.11ax HE80

