

TEST REPORT

Reference No..... : WTX21X03020504W
FCC ID : 2AZEY-AYLAIQ10
Applicant : Shenzhen Rti-Tek Co., Ltd.
Address..... : Room 206, Yangtian Building, Baocheng 72 Block, Bao an District,
Shenzhen
Product Name : Serial-to-Wireless Device Server
Test Model. : AylaiQ 1.0
Standards : FCC Part 15.247
Date of Receipt sample : Mar.16, 2021
Date of Test..... : Mar.16, 2021 to Mar.24, 2021
Date of Issue : Mar.24, 2021
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China


Tel.: +86-755-33663308

Fax.: +86-755-33663309


Tested by:

Reviewed By:

Approved & Authorized By:



Mike Shi / Project Engineer



Lion Cai / RF Manager



Silin Chen / Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	10
3. ANTENNA REQUIREMENT	11
3.1 STANDARD APPLICABLE	11
3.2 EVALUATION INFORMATION	11
4. POWER SPECTRAL DENSITY	12
4.1 STANDARD APPLICABLE	12
4.2 TEST SETUP BLOCK DIAGRAM	12
4.3 TEST PROCEDURE	12
4.4 SUMMARY OF TEST RESULTS/PLOTS	12
5. DTS BANDWIDTH	13
5.1 STANDARD APPLICABLE	13
5.2 TEST SETUP BLOCK DIAGRAM	13
5.3 TEST PROCEDURE	13
5.4 SUMMARY OF TEST RESULTS/PLOTS	13
6. RF OUTPUT POWER	14
6.1 STANDARD APPLICABLE	14
6.2 TEST SETUP BLOCK DIAGRAM	14
6.3 TEST PROCEDURE	14
6.4 SUMMARY OF TEST RESULTS/PLOTS	14
7. FIELD STRENGTH OF SPURIOUS EMISSIONS	15
7.1 STANDARD APPLICABLE	15
7.2 TEST PROCEDURE	15
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	17
7.4 SUMMARY OF TEST RESULTS/PLOTS	17
8. OUT OF BAND EMISSIONS	25
8.1 STANDARD APPLICABLE	25
8.2 TEST PROCEDURE	25
8.3 SUMMARY OF TEST RESULTS/PLOTS	26
9. CONDUCTED EMISSIONS	36
9.1 TEST PROCEDURE	36
9.2 BASIC TEST SETUP BLOCK DIAGRAM	36
9.3 TEST RECEIVER SETUP	36
9.4 SUMMARY OF TEST RESULTS/PLOTS	36
APPENDIX SUMMARY	39
APPENDIX A	40
APPENDIX B	45
APPENDIX C	50
APPENDIX D	55
APPENDIX PHOTOGRAPHS	63

Report version

Version No.	Date of issue	Description
Rev.00	Mar.24, 2021	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Rti-Tek Co., Ltd.
Address of applicant: Room 206, Yangtian Building, Baocheng 72 Block, Bao an District, Shenzhen

Manufacturer: Shenzhen Rti-Tek Co., Ltd.
Address of manufacturer: Room 206, Yangtian Building, Baocheng 72 Block, Bao an District, Shenzhen

General Description of EUT	
Product Name:	Serial-to-Wireless Device Server
Trade Name:	/
Model No.:	AylalQ 1.0
Adding Model(s):	/
Rated Voltage:	DC12-24V
Power Adapter Model:	/
Note: The test data is gathered from a production sample provided by the manufacturer.	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	16.39dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	1.5dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the FCC rules.

662911 D01 Multiple Transmitter Output v02r01: Emissions Testing of Transmitters with Multiple Outputs in the Same Band.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 662911 D01 Multiple Transmitter Output v02r01

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC CABLE	1.5	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	/	AD24BGH120200	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-26GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2020-04-28	2021-04-27
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2020-04-28	2021-04-27
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28	2021-04-27
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	/	/
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	/	/
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	/	/
SEMT-C004	Cable	Zheng DI	2M0RFC	/	/	/
SEMT-C005	Cable	Zheng DI	1M0RFC	/	/	/
SEMT-C006	Cable	Zheng DI	1M0RFC	/	/	/

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has a PCB antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

4.4 Summary of Test Results/Plots


Please refer to Appendix A

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.4 Summary of Test Results/Plots


Please refer to Appendix B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


7.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.


The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



The test setup for emission measurement above 1 GHz..



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=300KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

7.4 Summary of Test Results/Plots


Note: 1.This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case(802.11b_11Mbps) is recorded in this report.

➤ Spurious Emissions Below 1GHz




802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	53.3179	41.20	-12.47	28.73	40.00	-11.27	-	-	QP
2	104.1701	39.10	-13.31	25.79	43.50	-17.71	-	-	QP
3	149.4857	41.97	-15.49	26.48	43.50	-17.02	-	-	QP
4	236.6447	38.02	-11.58	26.44	46.00	-19.56	-	-	QP
5	560.6928	36.69	-3.27	33.42	46.00	-12.58	-	-	QP
6	916.0687	37.14	1.75	38.89	46.00	-7.11	-	-	QP

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.8998	38.07	-11.87	26.20	40.00	-13.80	-	-	QP
2	102.7192	35.10	-13.32	21.78	43.50	-21.72	-	-	QP
3	350.4768	33.21	-7.43	25.78	46.00	-20.22	-	-	QP
4	400.4319	39.03	-6.45	32.58	46.00	-13.42	-	-	QP
5	922.5157	34.51	1.83	36.34	46.00	-9.66	-	-	QP
6	972.3374	36.38	1.46	37.84	54.00	-16.16	-	-	QP

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	52.5753	41.24	-12.25	28.99	40.00	-11.01	-	-	QP
2	68.8721	40.27	-14.47	25.80	40.00	-14.20	-	-	QP
3	104.9033	38.54	-13.32	25.22	43.50	-18.28	-	-	QP
4	152.6641	41.95	-15.47	26.48	43.50	-17.02	-	-	QP
5	234.1684	38.22	-11.70	26.52	46.00	-19.48	-	-	QP
6	922.5157	38.72	1.83	40.55	46.00	-5.45	-	-	QP

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.1202	37.72	-11.84	25.88	40.00	-14.12	-	-	QP
2	116.9495	35.55	-13.99	21.56	43.50	-21.94	-	-	QP
3	239.1473	35.39	-11.46	23.93	46.00	-22.07	-	-	QP
4	417.6411	33.24	-6.05	27.19	46.00	-18.81	-	-	QP
5	768.7482	32.00	-1.14	30.86	46.00	-15.14	-	-	QP
6	982.6200	37.22	1.60	38.82	54.00	-15.18	-	-	QP

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.1616	39.76	-12.30	27.46	40.00	-12.54	-	-	QP
2	52.9453	42.43	-12.36	30.07	40.00	-9.93	-	-	QP
3	102.3597	38.10	-13.31	24.79	43.50	-18.71	-	-	QP
4	148.4410	42.72	-15.57	27.15	43.50	-16.35	-	-	QP
5	235.8164	37.95	-11.62	26.33	46.00	-19.67	-	-	QP
6	916.0687	36.11	1.75	37.86	46.00	-8.14	-	-	QP

Remark: ‘-’Means’ the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps (worst case)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	54.09	-3.87	50.22	74.00	-23.78	H	PK
4824.000	38.84	-3.87	34.97	54.00	-19.03	H	AV
7236.000	46.30	1.14	47.44	74.00	-26.56	H	PK
7236.000	34.98	1.19	36.17	54.00	-17.83	H	AV
4824.000	57.31	-3.86	53.45	74.00	-20.55	V	PK
4824.000	40.50	-3.86	36.64	54.00	-17.36	V	AV
7236.000	49.11	1.10	50.21	74.00	-23.79	V	PK
7236.000	37.44	1.10	38.54	54.00	-15.46	V	AV
Middle Channel-2437MHz							
4874.000	54.74	-3.74	51.00	74.00	-23.00	H	PK
4874.000	39.99	-3.74	36.25	54.00	-17.75	H	AV
7311.000	47.77	1.47	49.24	74.00	-24.76	H	PK
7311.000	33.10	1.47	34.57	54.00	-19.43	H	AV
4874.000	53.97	-3.74	50.23	74.00	-23.77	V	PK
4874.000	40.89	-3.74	37.15	54.00	-16.85	V	AV
7311.000	47.98	1.47	49.45	74.00	-24.55	V	PK
7311.000	34.08	1.47	35.55	54.00	-18.45	V	AV
High Channel-2462MHz							
4924.000	55.82	-3.59	52.23	74.00	-21.77	H	PK
4924.000	41.76	-3.59	38.17	54.00	-15.83	H	AV
7386.000	46.38	1.79	48.17	74.00	-25.83	H	PK
7386.000	34.83	1.79	36.62	54.00	-17.38	H	AV
4924.000	54.94	-3.59	51.35	74.00	-22.65	V	PK
4924.000	42.04	-3.59	38.45	54.00	-15.55	V	AV
7386.000	47.99	1.79	49.78	74.00	-24.22	V	PK
7386.000	35.18	1.79	36.97	54.00	-17.03	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement

KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) $VBW \geq [3 \times RBW]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots


➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.89	-9.66	34.23	54.00	-19.77	Average Detector
	2310.000	57.30	-9.66	47.64	74.00	-26.36	Peak Detector
2	2390.000	50.39	-9.50	40.89	54.00	-13.11	Average Detector
	2390.000	63.76	-9.50	54.26	74.00	-19.74	Peak Detector
3	2400.000	69.14	-9.48	59.66	Delta=38.79dBc		Average Detector
4	2412.840	107.91	-9.46	98.45			Average Detector

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.200	109.04	-9.36	99.68	/	/	Average Detector
	2463.050	113.99	-9.36	104.63	/	/	Peak Detector
2	2483.500	51.98	-9.31	42.67	54.00	-11.33	Average Detector
	2483.500	64.59	-9.31	55.28	74.00	-18.72	Peak Detector
3	2500.000	49.14	-9.28	39.86	54.00	-14.14	Average Detector
	2500.000	62.21	-9.28	52.93	74.00	-21.07	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.67	-9.66	34.01	54.00	-19.99	Average Detector
	2310.000	55.47	-9.66	45.81	74.00	-28.19	Peak Detector
2	2390.000	58.94	-9.50	49.44	54.00	-4.56	Average Detector
	2390.000	79.28	-9.50	69.78	74.00	-4.22	Peak Detector
3	2400.000	72.71	-9.48	63.23	Delta=30.08dBc		Average Detector
4	2416.080	102.77	-9.46	93.31			Average Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2459.600	102.92	-9.36	93.56	/	/	Average Detector
	2459.200	113.47	-9.36	104.11	/	/	Peak Detector
2	2483.500	61.48	-9.31	52.17	54.00	-1.83	Average Detector
	2483.500	80.37	-9.31	71.06	74.00	-2.94	Peak Detector
3	2500.000	48.43	-9.28	39.15	54.00	-14.85	Average Detector
	2500.000	61.46	-9.28	52.18	74.00	-21.82	Peak Detector

802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.80	-9.66	34.14	54.00	-19.86	Average Detector
	2310.000	56.63	-9.66	46.97	74.00	-27.03	Peak Detector
2	2390.000	58.56	-9.50	49.06	54.00	-4.94	Average Detector
	2390.000	79.89	-9.50	70.39	74.00	-3.61	Peak Detector
3	2400.000	69.51	-9.48	60.03	Delta=31.97dBc		Average Detector
4	2415.240	101.46	-9.46	92.00			Average Detector

802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2459.950	100.77	-9.35	91.42	/	/	Average Detector
	2461.400	111.38	-9.36	102.02	/	/	Peak Detector
2	2483.500	59.82	-9.31	50.51	54.00	-3.49	Average Detector
	2483.500	76.95	-9.31	67.64	74.00	-6.36	Peak Detector
3	2500.000	46.94	-9.28	37.66	54.00	-16.34	Average Detector
	2500.000	58.40	-9.28	49.12	74.00	-24.88	Peak Detector

802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	44.68	-9.66	35.02	54.00	-18.98	Average Detector
	2310.000	56.51	-9.66	46.85	74.00	-27.15	Peak Detector
2	2390.000	62.30	-9.50	52.80	54.00	-1.20	Average Detector
	2390.000	77.90	-9.50	68.40	74.00	-5.60	Peak Detector
3	2400.000	66.08	-9.48	56.60	Delta=33.16dBc		Average Detector
4	2425.360	99.18	-9.42	89.76			Average Detector

802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2459.120	97.68	-9.36	88.32	/	/	Average Detector
	2455.130	108.41	-9.37	99.04	/	/	Peak Detector
2	2483.500	58.79	-9.31	49.48	54.00	-4.52	Average Detector
	2483.500	77.78	-9.31	68.47	74.00	-5.53	Peak Detector
3	2500.000	48.73	-9.28	39.45	54.00	-14.55	Average Detector
	2500.000	67.41	-9.28	58.13	74.00	-15.87	Peak Detector

➤ Conducted test

Please refer to Appendix D

9. Conducted Emissions


9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2660	24.46	10.25	34.71	51.24	-16.53	AVG
2*	0.4340	35.77	10.22	45.99	57.18	-11.19	QP
3	0.5340	18.03	10.22	28.25	46.00	-17.75	AVG
4	0.7780	27.69	10.18	37.87	56.00	-18.13	QP
5	1.0660	24.71	10.21	34.92	56.00	-21.08	QP
6	1.0660	16.75	10.21	26.96	46.00	-19.04	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2660	38.65	10.25	48.90	61.24	-12.34	QP
2*	0.2660	33.79	10.25	44.04	51.24	-7.20	AVG
3	0.4620	38.10	10.22	48.32	56.66	-8.34	QP
4	0.5340	25.35	10.22	35.57	46.00	-10.43	AVG
5	1.0660	29.42	10.21	39.63	56.00	-16.37	QP
6	1.0660	21.81	10.21	32.02	46.00	-13.98	AVG

APPENDIX SUMMARY

Project No.	WTX21X03020504W	Test Engineer	Shaw
Start date	2021/3/23	Finish date	2021/2/23
Temperature	24℃	Humidity	48%
RF specifications	WIFI-2.4G		

APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	DTS Bandwidth	Compliant
C	RF Output Power	Compliant
D	Conducted Out of Band Emissions	Compliant

APPENDIX A

Power Spectral Density			
Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_1Mbps	2412	-18.01	8
	2437	-18.04	8
	2462	-18.53	8
802.11g_6Mbps	2412	-20.5	8
	2437	-20.97	8
	2462	-21.53	8
802.11n-HT20_MCS0	2412	-20.96	8
	2437	-21.79	8
	2462	-22.39	8
802.11n-HT40_MCS0	2422	-23.99	8
	2437	-24.75	8
	2452	-24.82	8

802.11b-Low	Agilent R T Ref 0 dBm Atten 10 dB Mkr1 2.41131 GHz -18.01 dBm #Avg Log 10 dB/ Offst 1 dB M1 S2 S3 FC AA Marker 2.411310000 GHz -18.01 dBm Center 2.412 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Peak Search Meas Tools ▾ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11b-Middle	Agilent R T Ref 0 dBm Atten 10 dB Mkr1 2.43628 GHz -18.04 dBm #Avg Log 10 dB/ Offst 1 dB M1 S2 S3 FC AA Marker 2.436280000 GHz -18.04 dBm Center 2.437 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Peak Search Meas Tools ▾ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11b-High	Agilent R T Ref 0 dBm Atten 10 dB Mkr1 2.46131 GHz -18.53 dBm #Avg Log 10 dB/ Offst 1 dB M1 S2 S3 FC AA Marker 2.461310000 GHz -18.53 dBm Center 2.462 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2

802.11g-Low	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.41134 GHz -20.5 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.411340000 GHz -20.5 dBm Center 2.412 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11g-Middle	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.43634 GHz -20.97 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.436340000 GHz -20.97 dBm Center 2.437 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11g-High	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.46104 GHz -21.53 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.461040000 GHz -21.53 dBm Center 2.462 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2


802.11n-HT20-Low	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.41479 GHz -20.96 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.414790000 GHz -20.96 dBm Center 2.412 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11n-HT20-Middle	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.43979 GHz -21.79 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.439790000 GHz -21.79 dBm Center 2.437 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11n-HT20-High	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.46479 GHz -22.39 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.464790000 GHz -22.39 dBm Center 2.462 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts) Span 30 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2




802.11n-HT40-Low	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.41420 GHz -23.99 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.414200000 GHz -23.99 dBm Center 2.422 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 10.85 s (1001 pts) Span 60 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11n-HT40-Middle	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.44042 GHz -24.75 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.440420000 GHz -24.75 dBm Center 2.437 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 10.85 s (1001 pts) Span 60 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11n-HT40-High	Agilent Ref 0 dBm Atten 10 dB Mkr1 2.44420 GHz -24.82 dBm #Avg Log 10 dB/ Offset 1 dB M1 S2 S3 FC AA Marker 2.444200000 GHz -24.82 dBm Center 2.452 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 10.85 s (1001 pts) Span 60 MHz Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2

APPENDIX B

DTS Bandwidth			
Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_1Mbps	2412	10.068	≥500
	2437	10.057	≥500
	2462	10.068	≥500
802.11g_6Mbps	2412	16.424	≥500
	2437	16.467	≥500
	2462	16.481	≥500
802.11n-HT20_MCS0	2412	17.642	≥500
	2437	17.643	≥500
	2462	17.644	≥500
802.11n-HT40_MCS0	2422	36.319	≥500
	2437	36.313	≥500
	2452	36.348	≥500

802.11b-Low	Agilent Ch Freq 2.412 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 14.6434 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 28.965 kHz x dB Bandwidth 10.068 MHz Freq/Channel Center Freq 2.41200000 GHz Start Freq 2.39700000 GHz Stop Freq 2.42700000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
802.11b-Middle	Agilent Ch Freq 2.437 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 14.6226 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -30.576 kHz x dB Bandwidth 10.057 MHz Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.42200000 GHz Stop Freq 2.45200000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
802.11b-High	Agilent Ch Freq 2.462 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 14.6199 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -3.645 kHz x dB Bandwidth 10.068 MHz Freq/Channel Center Freq 2.46200000 GHz Start Freq 2.44700000 GHz Stop Freq 2.47700000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

802.11g-Low	Agilent R T Ch Freq 2.412 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB  Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 30 MHz Occupied Bandwidth 16.4055 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -32.556 kHz x dB Bandwidth 16.424 MHz Trace/View 1 2 3 Trace Clear Write Max Hold Min Hold View Blank More 1 of 2
-------------	---

802.11n-HT20-Low	Agilent R T Ch Freq 2.412 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB  Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 30 MHz Occupied Bandwidth 17.5916 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -11.861 kHz x dB Bandwidth 17.642 MHz Freq/Channel Center Freq 2.4120000 GHz Start Freq 2.3970000 GHz Stop Freq 2.4270000 GHz CF Step 3.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Scale Type Log Lin
802.11n-HT20-Middle	Agilent R T Ch Freq 2.437 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB  Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 30 MHz Occupied Bandwidth 17.5917 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -28.105 kHz x dB Bandwidth 17.643 MHz Freq/Channel Center Freq 2.4370000 GHz Start Freq 2.4220000 GHz Stop Freq 2.4520000 GHz CF Step 3.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Scale Type Log Lin
802.11n-HT20-High	Agilent R T Ch Freq 2.462 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB  Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 30 MHz Occupied Bandwidth 17.5995 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -21.595 kHz x dB Bandwidth 17.644 MHz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2

802.11n-HT40-Low	Agilent Ch Freq 2.422 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB Center 2.422 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 60 MHz Occupied Bandwidth 35.7936 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -1.167 kHz x dB Bandwidth 36.319 MHz Freq/Channel Center Freq 2.42200000 GHz Start Freq 2.39200000 GHz Stop Freq 2.45200000 GHz CF Step 6.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
802.11n-HT40-Middle	Agilent Ch Freq 2.437 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 60 MHz Occupied Bandwidth 35.7990 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -30.430 kHz x dB Bandwidth 36.313 MHz Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.40700000 GHz Stop Freq 2.46700000 GHz CF Step 6.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
802.11n-HT40-High	Agilent Ch Freq 2.452 GHz Trig Free Occupied Bandwidth Ref 20 dBm Atten 30 dB #Peak Log 10 dB/ Offset 1 dB Center 2.452 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 60 MHz Occupied Bandwidth 35.8012 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -22.290 kHz x dB Bandwidth 36.348 MHz Freq/Channel Center Freq 2.45200000 GHz Start Freq 2.42200000 GHz Stop Freq 2.48200000 GHz CF Step 6.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

APPENDIX C

Test Mode	Frequency MHz	Reading dBm	Limit dBm
802.11b _ 1Mbps	2412	16.02	30.00
	2437	16.38	30.00
	2462	16.39	30.00
802.11g_6Mbps	2412	14.34	30.00
	2437	14.98	30.00
	2462	14.18	30.00
802.11n HT20_MCS0	2412	13.51	30.00
	2437	13.30	30.00
	2462	13.19	30.00
802.11n HT40_MCS0	2422	12.71	30.00
	2437	12.75	30.00
	2452	12.46	30.00

802.11b-Low	Agilent Ch Freq 2.412 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.412 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 16.02 dBm / 20.0000 MHz -56.99 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
802.11b-Middle	Agilent Ch Freq 2.437 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.437 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 16.38 dBm / 20.0000 MHz -56.63 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
802.11b-High	Agilent Ch Freq 2.462 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.462 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 16.39 dBm / 20.0000 MHz -56.62 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2




802.11g-Low	Agilent Ch Freq 2.412 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.412 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 14.34 dBm / 20.0000 MHz -58.67 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
802.11g-Middle	Agilent Ch Freq 2.437 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.437 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 14.98 dBm / 20.0000 MHz -58.03 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
802.11g-High	Agilent Ch Freq 2.462 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.462 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 14.18 dBm / 20.0000 MHz -58.83 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2


802.11n-HT20-Low	Agilent Ch Freq 2.412 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.412 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 13.51 dBm / 20.0000 MHz -59.50 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
802.11n-HT20-Middle	Agilent Ch Freq 2.437 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.437 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 13.30 dBm / 20.0000 MHz -59.71 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
802.11n-HT20-High	Agilent Ch Freq 2.462 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.462 GHz #Res BW 300 kHz #VBW 1 MHz Sweep 8 ms (401 pts) Span 30 MHz Channel Power Power Spectral Density 13.19 dBm / 20.0000 MHz -59.82 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2

802.11n-HT40-Low	Agilent Ch Freq 2.422 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.422 GHz #Res BW 1 MHz #VBW 3 MHz Sweep 8 ms (401 pts) Span 60 MHz Channel Power Power Spectral Density 12.71 dBm / 40.0000 MHz -63.31 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
802.11n-HT40-Middle	Agilent Ch Freq 2.437 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.437 GHz #Res BW 1 MHz #VBW 3 MHz Sweep 8 ms (401 pts) Span 60 MHz Channel Power Power Spectral Density 12.75 dBm / 40.0000 MHz -63.27 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
802.11n-HT40-High	Agilent Ch Freq 2.452 GHz Trig Free Channel Power Ref 20 dBm Atten 30 dB #Avg Log 10 dB/ Offset 1 dB Center 2.452 GHz #Res BW 1 MHz #VBW 3 MHz Sweep 8 ms (401 pts) Span 60 MHz Channel Power Power Spectral Density 12.46 dBm / 40.0000 MHz -63.56 dBm/Hz Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2


APPENDIX D

Conducted Out of Band Emissions


802.11b-Low	
	
802.11b-Middle	





802.11g-Low	Agilent Ref 15 dBm Atten 25 dB Mkr1 2.41614 GHz 0.892 dBm #Peak Log 10 dB/ Offset 1 dB DI -29.1 dBm M1 S2 S3 FC AA Display Line -29.11 dBm Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 60 MHz Display Full Screen Display Line -29.11 dBm OnOff Limits Active Fctn Position Bottom Title Preferences
	Agilent Ref 15 dBm Atten 25 dB Mkr1 25.377 GHz 46.33 dBm #Peak Log 10 dB/ Offset 1 dB DI -29.1 dBm M1 S2 S3 FC AA Marker 25.376720000 GHz -46.33 dBm Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.691 s (1001 pts) Stop 26 GHz Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
802.11g-Middle	Agilent Ref 15 dBm Atten 25 dB Mkr1 2.44114 GHz 1.627 dBm #Peak Log 10 dB/ Offset 1 dB DI -28.4 dBm M1 S2 S3 FC AA Display Line -28.37 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Span 60 MHz Display Full Screen Display Line -28.37 dBm OnOff Limits Active Fctn Position Bottom Title Preferences




802.11n-HT20-Low




802.11n-HT20-Middle








802.11n-HT40-Low



802.11n-HT40-Middle





APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

******* END OF REPORT *******