

Sichuan Injet New Energy Co., Ltd.

MPE ASSESSMENT REPORT

Report Type:

FCCC MPE assessment report

Model:

iM3C-19K2A, iM3C-15K6A,
iM3C-11K5A, iM3C-09K6A

REPORT NUMBER:

2309A1183SHA-003

ISSUE DATE:

November 1, 2023

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek



Applicant: Sichuan Injet New Energy Co., Ltd.
The Northeast Corner of Minshan Road and Tumenjiang Road, Economic
and Technological Development Zone, Deyang, Sichuan, China

Manufacturer: Sichuan Injet New Energy Co., Ltd.
The Northeast Corner of Minshan Road and Tumenjiang Road, Economic
and Technological Development Zone, Deyang, Sichuan, China

Factory: Sichuan Injet New Energy Co., Ltd.
The Northeast Corner of Minshan Road and Tumenjiang Road, Economic
and Technological Development Zone, Deyang, Sichuan, China

FCC ID: 2AZGWIM3C-2309

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:**REVIEWED BY:**

Project Engineer
Sky Yang

Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
2309A1183SHA-003	Rev. 01	Initial issue of report	November 1, 2023

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	AC EV Charger
Type/Model:	iM3C-19K2A, iM3C-15K6A, iM3C-11K5A, iM3C-09K6A
Description of EUT:	The EUT is an electric vehicle DC charger. It contains a certified WIFI module and LTE module. The LTE module FCC ID is XMR201909EC25AFX, the WIFI module FCC ID is 2AC7Z-ESPC3WROOM. All models are electric identical except the rated power.
Rating:	iM3C-19K2A: 240VAC, 60Hz, 80A Max iM3C-15K6A: 240VAC, 60Hz, 65A Max iM3C-11K5A: 240VAC, 60Hz, 48A Max iM3C-09K6A: 240VAC, 60Hz, 40A Max
EUT type:	☒ Table top ☐ Floor standing
Software Version:	-
Hardware Version:	-
Sample received date:	September 11, 2023
Date of test:	September 12, 2023 ~ September 27, 2023

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna:	PCB antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: Limit for 13.56MHz is 60.77 V/m

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

TEST REPORT

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = P / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Radiated transmit power in mW

R = distance (cm)

As we can see from the test report 2309A1183SHA-002:

60.6dBuV/m@3m, @20cm=@3m+40log(3/0.2)=107.64dBuV/m=0.241V/m<60.77.

The power for WIFI module refers to certificate of FCC ID: 2AC7Z-ESPC3WROOM

The power for LTE module refers to certificate of FCC ID: XMR201909EC25AFX

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency Range	EIRP		Antenna Gain	R	S	Limits
(MHz)	(dBm)	(mW)	(dBi)	(cm)	(mW/cm ²)	(mW/cm ²)
Bluetooth LE	11.78	15.07	3.26	20	0.003	1
WIFI 2.4G	20.82	120.78	3.26	20	0.024	1
WCDMA Band II	29	794.33	4	20	0.158	1
WCDMA Band IV	29	794.33	4	20	0.158	1
WCDMA Band V	29	794.33	4	20	0.158	0.55
LTE Band 2	29	794.33	4	20	0.158	1
LTE Band 4	29	794.33	4	20	0.158	1
LTE Band 5	29	794.33	4	20	0.158	0.55
LTE Band 12	29	794.33	4	20	0.158	0.47
LTE Band 13	29	794.33	4	20	0.158	0.52
LTE Band 14	29	794.33	4	20	0.158	0.53
LTE Band66	29	794.33	4	20	0.158	1
LTE Band 71	29	794.33	4	20	0.158	0.45

Note: 1 mW/cm² from 1.310 Table 1.

RFID, WIFI and LTE can transmit simultaneously, so the maximum rate of MPE is,
 $0.241/60.77+0.024/1+0.158/0.45=0.379 < 1.0$.

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

*****END*****