



ELEMENT WASHINGTON DC LLC

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
<http://www.element.com>

RF EXPOSURE EVALUATION Maximum Permissible Exposure (MPE)

Applicant Name:

GenXComm Inc
10000 Metric Blvd. Suite 200
Austin, Texas 78758
USA

Date of Testing:

1/29/2024 – 6/24/2024

Test Report Issue Date:

6/28/2024

Test Site/Location:

Element lab., Columbia, MD, USA

Test Report Serial No.:

1M2401260008-04.2AZH6

FCC ID:

2AZH6GXCMEN002

APPLICANT:

GenXComm Inc

EUT Type:

CBRS CPE

FCC Classification:

Category B Citizens Band Radio Devices (CBSD)

FCC Rule Part:

FCC Part 1 (§1.1310) and Part 2 (§2.1091)

Test Procedure(s):

KDB 447498 D01 v06

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in FCC KDB 447498 D01. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



FCC ID: 2AZH6GXCMEN002		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401260008-04.2AZH6	Test Dates: 1/29/2024 – 6/24/2024	EUT Type: CBRS CPE	Page 1 of 5	

TABLE OF CONTENTS

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE) 3

1.1 Introduction3

1.2 EUT Description.....3

1.3 Procedure4

1.4 Summary of Results.....4

2.0 CONCLUSION 5

FCC ID: 2AZH6GXCME002	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401260008-04.2AZH6	Test Dates: 1/29/2024 – 6/24/2024	EUT Type: CBRS CPE	Page 2 of 5

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Introduction

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Table 1-1. Limits for Maximum Permissible Exposure (MPE)

1.2 EUT Description

The **GXC Inc FCC ID: 2AZH6GXCMEN002** is a CBRS CPE mesh node. It has one antenna port which transmits in the 3550 – 3700 MHz Band. Only the highest power mode is assessed for compliance.

FCC ID: 2AZH6GXCMEN002	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401260008-04.2AZH6	Test Dates: 1/29/2024 – 6/24/2024	EUT Type: CBRS CPE	Page 3 of 5

1.3 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this product was initially measured by a power meter or spectrum analyzer and the powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated at a distance of 20cm.

Friis Transmission Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

P_d = Power Density (mW/cm²)

π = 3.1416

P_{out} = output power to antenna (mW)

r = distance between observation point and center of the radiator (cm)

G = gain of antenna in linear scale

Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.

There is no co-location between the electric fields of any two transmitters therefore following power densities are calculated for each individual transmitter by frequency at 20cm spacing:

Frequency	3635	MHz
FCC Limit	1.000	mW/cm ²
EIRP Limit	47.00	dBm/10MHz
Distance	20	cm
Max Power	20.00	dBm
Power	100.00	mW
Max FCC Tx Ant Gain	16.00	dBi
FCC Power Density	0.792	mW/cm ²
Minimum Distance	17.80	cm

Table 1-2. Calculated MPE Data for CBRS Band

FCC ID: 2AZH6GXCME002	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401260008-04.2AZH6	Test Dates: 1/29/2024 – 6/24/2024	EUT Type: CBRS CPE	Page 4 of 5



CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: 2AZH6GXC MEN002	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401260008-04.2AZH6	Test Dates: 1/29/2024 – 6/24/2024	EUT Type: CBRS CPE	Page 5 of 5