



TEST REPORT

ISSUED FOR

Shenzhen ALEX Electronics Co., Ltd.

No.6,5F, A Block, Bld. 1, Jinshun Industrial Park, No.29 Anju Rd., Henggang St., Longgang Dist.,Shenzhen, Guangdong, China

MANUFACTURER	:	Shenzhen ALEX Electronics Co., Ltd.
PRODUCT NAME	:	PCB Antenna
MODEL NAME	:	F052
MAX Gain	:	1.03 dBi
TRADE NAME	:	N/A
Test Standard	:	IEEE149-1979
TEST DATE	:	2022-09-01
ISSUE DATE	:	2022-09-09

Testing Engineer :

Peter peng

Peter peng

Authorized Signatory :

Jim he

Jim he





DIRECTORY

1. Technical Information	3
1.1. Manufacturer and Factory Information	3
1.2. Equipment Under Test (EUT) Description	3
2. Test Results	4
2.1. Applied Reference Documents	4
2.2. Test Conditions	4
2.3. Test Results lists	4
Annex A Photographs	5
Annex B Figures	6
1. 2D Radiation Pattern	6
2. 3D Radiation Pattern	8
Annex C Photographs	10
Annex D General Information	13
1.1 Identification of the Responsible Testing Laboratory	13
1.2 Identification of the Responsible Testing Location	13
1.3 Test Equipments Utilized	13

Change History		
Issue	Date	Reason
1.0	2022-09-09	First edition




1. Technical Information

Note: Provide by manufacturer.

1.1. Equipment Under Test (EUT) Description

Frequency Range(MHZ)	2400-2500
Impedance(Ω)	50 $\pm$ 10
Gain(dBi)	1.03
ReTurnLoss(dB)	$\leq$ -10
VSWR	$\leq$ 1.92
Polarization	omni

1.2. Equipment Under Test (EUT) Specification





2. Test Results

2.1. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	IEEE149-1979	IEEE Standard Test Procedures for Antennas

2.2. Test Conditions

Test Environment Conditions:

Relative Humidity:	15 ... 75 %
Temperature:	+10 °C to +30 °C

2.3. Test Results lists


2.3.1. Gain

Frequency (MHz)	Efficiency (%)	Gain (dBi)
频率	效率	增益
2400	9.4125	-1.05
2410	10.3365	-0.05
2420	11.2108	-0.74
2430	11.9845	0.65
2440	13.5167	1.02
2450	15.3369	0.27
2460	16.0597	0.74
2470	17.1025	-0.11
2480	17.3316	1.03
2490	18.2557	0.89
2500	19.1582	0.51



Annex A Photographs


1. Test Setup




Annex B Figures

1. 2D Radiation Pattern

Phi=0°




Phi=90°







Theta=90°




2. 3D Radiation Pattern



2400MHz



2450MHz



2500MHz

--The end of report--

