



## RF Exposure evaluation

Report Reference No.....: HTT2025061057F02

FCC ID.....: 2AZHW-AK-A101

Compiled by

( position+printed name+signature) .: File administrators

Supervised by

( position+printed name+signature) .: Project Engineer

Approved by

( position+printed name+signature) .: RF Manager

Date of issue .....: Jun. 26, 2025

Testing Laboratory Name.....: Shenzhen HTT Technology Co.,Ltd.

Address.....: 1F, Building B, Huafeng International Robotics Industrial Park,  
Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an  
District, Shenzhen, Guangdong, China

Applicant's name.....: Shenzhen Century Aoke Electronics Co., Ltd.

Address.....: 6705A, floor 67, SEG Plaza, Futian district, Shenzhen, China

Standard.....: 47CFR §1.1310

47CFR §2.1093

KDB447498 D01 General RF Exposure Guidance v06

**Shenzhen HTT Technology Co.,Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HTT Technology Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HTT Technology Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....: **Wireless Audio-Visual Alarm**

Manufacturer .....: Dongguan aoke electronic co.,ltd

Trade Mark .....: Century Aoke

Model/Type reference .....: AK-A101

Rating .....: DC 9.0V From Battery

Result .....: **PASS**

## TEST REPORT

Equipment under Test : Wireless Audio-Visual Alarm

Model /Type : AK-A101

Listed Models : AK-A102, AK-A103, AK-A001, AK-A201, AK-A301, AK-A401,  
AK-A501, AK-A601, AK-A701, AK-A801, AK-A901

Model difference : The PCB board, circuit, structure and internal of these models are the  
same, Only model number is different for these model.

**Applicant** : **Shenzhen Century Aoke Electronics Co., Ltd.**

Address : 6705A, floor 67, SEG Plaza, Futian district, Shenzhen, China

**Manufacturer** : **Dongguan aoke electronic co.,ltd**

Address : 5th Floor, Building 1, Jiaoyitang baoshi RD4, Tangxia, Dongguan,  
Guangdong,China

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of  
the test laboratory.

## Contents

|                 |                                             |                 |
|-----------------|---------------------------------------------|-----------------|
| <b><u>1</u></b> | <b><u>TEST STANDARDS .....</u></b>          | <b><u>4</u></b> |
| <b><u>2</u></b> | <b><u>SUMMARY .....</u></b>                 | <b><u>5</u></b> |
| 2.1             | General Remarks                             | 5               |
| 2.2             | Product Description                         | 5               |
| 2.3             | Special Accessories                         | 5               |
| 2.4             | Modifications                               | 5               |
| <b><u>3</u></b> | <b><u>TEST ENVIRONMENT .....</u></b>        | <b><u>6</u></b> |
| 3.1             | Address of the test laboratory              | 6               |
| 3.2             | Test Facility                               | 6               |
| 3.3             | Statement of the measurement uncertainty    | 6               |
| <b><u>4</u></b> | <b><u>TEST LIMIT .....</u></b>              | <b><u>7</u></b> |
| 4.1             | Requirement                                 | 7               |
| 4.2             | Conducted Power Results                     | 7               |
| 4.3             | Manufacturing tolerance                     | 8               |
| 4.4             | Evaluation Result                           | 8               |
| 4.5             | Simultaneous Transmission for SAR Exclusion | 8               |
| <b><u>5</u></b> | <b><u>CONCLUSION .....</u></b>              | <b><u>8</u></b> |

# **1 TEST STANDARDS**

The tests were performed according to following standards:

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

## 2 SUMMARY

### 2.1 General Remarks

|                                |   |               |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Jun. 20, 2025 |
|                                |   |               |
| Testing commenced on           | : | Jun. 20, 2025 |
|                                |   |               |
| Testing concluded on           | : | Jun. 26, 2025 |

### 2.2 Product Description

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
| Product Name:         | Wireless Audio-Visual Alarm                                            |
| Model/Type reference: | AK-A101                                                                |
| Testing sample ID:    | HTT2025061057-1# (Engineer sample),<br>HTT2025061057-2#(Normal sample) |
| Power supply:         | DC 9.0V From Batter                                                    |
| Modulation:           | ASK                                                                    |
| Operation frequency:  | 434.0125MHz                                                            |
| Channel number:       | 1                                                                      |
| Antenna type:         | Rod Antenna                                                            |
| Antenna gain:         | 5 dBi                                                                  |

### 2.3 Special Accessories

The following is the EUT test of the auxiliary equipment provided by the laboratory:

| Description | Manufacturer | Model | Technical Parameters | Certificate | Provided by |
|-------------|--------------|-------|----------------------|-------------|-------------|
| /           | /            | /     | /                    | /           | /           |

### 2.4 Modifications

No modifications were implemented to meet testing criteria.

### 3 TEST ENVIRONMENT

#### 3.1 Address of the test laboratory

**Shenzhen HTT Technology Co.,Ltd.**

1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 779513 Designation Number: CN1319**

Shenzhen HTT Technology Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA-Lab Cert. No.: 6435.01**

Shenzhen HTT Technology Co.,Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

#### 3.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen HTT Technology Co.,Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen HTT Technology Co.,Ltd. :

| Test Item             | Frequency Range | Measurement Uncertainty | Notes |
|-----------------------|-----------------|-------------------------|-------|
| Radiated Emission     | 9KHz~30MHz      | 3.12 dB                 | (1)   |
| Radiated Emission     | 30~1000MHz      | 4.37 dB                 | (1)   |
| Radiated Emission     | 1~18GHz         | 5.40 dB                 | (1)   |
| Radiated Emission     | 18-40GHz        | 5.45 dB                 | (1)   |
| Conducted Disturbance | 0.15~30MHz      | 2.68 dB                 | (1)   |
| Spectrum bandwidth    | /               | 1.2%                    | (1)   |
| Output Peak power     | 30MHz~18GHz     | 0.57dB                  | (1)   |
| Time                  | /               | ± 10%                   | (1)   |

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 4 Test limit

### 4.1 Requirement

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: “Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.<sup>22</sup> The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.<sup>23</sup> “

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f \text{ (GHz)}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f$  (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### 4.2 Conducted Power Results

| Freq.<br>(MHz)                                                                                                                                                                                                                                                                                          | Field strength(max)(dBuV/m) | EIRP (max)<br>(dBm) | Turn-up Power<br>(dB) | Max tune up<br>power<br>(dBm)<br>[P] |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------|-----------------------|--------------------------------------|
| 434.0125MHz                                                                                                                                                                                                                                                                                             | 58.82                       | -36.44              | -36.0±1               | -35.0                                |
| <b>Note:</b><br>$E = \text{EIRP} - 20\log D + 104.8$<br>where:<br>$E$ = electric field strength in dBμV/m,<br>$\text{EIRP}$ = equivalent isotropic radiated power in dBm<br>$D$ = specified measurement distance in meters.<br><b><math>\text{EIRP} = E - 104.8 + 20\log D</math>, <math>D=3</math></b> |                             |                     |                       |                                      |

### 4.3 Manufacturing tolerance

| Freq.<br>(MHz) | Field strength(max)(dBuV/m) | EIRP (max)<br>(dBm) | Turn-up Power<br>(dB) |
|----------------|-----------------------------|---------------------|-----------------------|
| 434.0125MHz    | 58.82                       | -36.44              | -36.0±1               |

### 4.4 Evaluation Result

#### Evaluation Results

| Band/Mode | f (GHz) | Antenna<br>Distance<br>(mm) | RF output power<br>(including tune-up<br>tolerance) |        | SAR Test<br>Exclusion<br>Threshold | SAR Test<br>Exclusion |
|-----------|---------|-----------------------------|-----------------------------------------------------|--------|------------------------------------|-----------------------|
|           |         |                             | dBm                                                 | mW     |                                    |                       |
| SRD       | 0.434   | 5                           | -35.0                                               | 0.0003 | 0.0000<3.0                         | Yes                   |

### 4.5 Simultaneous Transmission for SAR Exclusion

N/A

## 5 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01v06

\*\*\*\*\* End of Report \*\*\*\*\*