



RADIO TEST REPORT

Applicant	:	NIMBLE FOR GOOD, PBC.
Address of Applicant	:	1008 Brioso Drive Costa Mesa, CA 92627
Manufacturer	:	NIMBLE FOR GOOD, PBC.
Address of Manufacturer	:	1008 Brioso Drive Costa Mesa, CA 92627
Equipment under Test	:	PODIUM 2-IN-1 WIRELESS
Model No.	:	NB-WP-2N1TRY
FCC ID	:	2AZIO-PODIUM2N1
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2013
Report No.	:	DDT-RE25071422-1E01
Issue Date	:	2025/09/09
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	6
2.	General Test Information.....	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT	7
2.3.	Block diagram of EUT configuration for test.....	7
2.4.	Decision of final test mode	7
2.5.	Deviations of test standard	7
2.6.	Test environment conditions	8
2.7.	Test laboratory	8
2.8.	Measurement uncertainty	9
3.	Equipment Used During Conductive Test	10
4	20 dB Bandwidth	11
4.1.	Block diagram of test setup	11
4.2.	Limits	11
4.3.	Test procedure	11
4.4.	Test result.....	12
4.5.	Test graphs	12
5	Antenna Requirements.....	14
5.1.	Limit.....	14
5.2.	Result	14
6.	Radiated Emission	15
6.1.	Test equipment.....	15
6.2.	Block diagram of test setup	16
6.3.	Limits	16
6.4.	Assistant equipment used for test	17
6.5.	Test procedure	17
6.6.	Test result.....	18
6.7.	Test data	25
7.	Power Line Conducted Emissions.....	29
7.1.	Test equipment.....	29
7.2.	Block diagram of test setup	29
7.3.	Limits	29
7.4.	Assistant equipment used for test	29
7.5.	Test procedure	29
7.6.	Test result.....	30
7.7.	Test data	31

8. Test Setup Photograph33

9. Photos of the EUT35

Test Report Declare

Applicant	:	NIMBLE FOR GOOD, PBC.
Address of Applicant	:	1008 Briosso Drive Costa Mesa, CA 92627
Equipment under Test	:	PODIUM 2-IN-1 WIRELESS
Model No.	:	NB-WP-2N1TRY
Manufacturer	:	NIMBLE FOR GOOD, PBC.
Address of Manufacturer	:	1008 Briosso Drive Costa Mesa, CA 92627

Test Standard Used:
FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10:2013

We Declare:
The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE25071422-1E01		
Date of Receipt:	2025/07/25	Date of Test:	2025/07/25 - 2025/09/09

Created: Johnson Huang	Reviewed: Tiger Mo	Approved: Damon Hu
		
2025/08/30	2025/09/09	2025/09/09

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2025/09/09	Damon Hu

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	20 dB Bandwidth	FCC Part 15: 15.215	/	Pass
2	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209	/	Pass
3	Power Line Conducted Emissions	FCC Part 15: 15.207(a)	/	Pass
4	Antenna Requirement	FCC Part 15: 15.203, RSS-Gen Issue 5 clause 6.8	/	Pass

Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.

2. General Test Information

2.1. Description of EUT

EUT Name	: PODIUM 2-IN-1 WIRELESS
Model Number	: NB-WP-2N1TRY
Difference of model number	: /
EUT Function Description	: Please reference user manual of this device
Power Supply	: 5V=3A, 9V=3A, 12V=3A, 15V=3A from USB cable
Wireless charging Operation frequency	: 111-147 kHz, 360 kHz
Antenna Type	: Inductive loop coil antenna


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

For mode 1: Tx mode 111-147kHz (5W load, 7.5W load, 10W load)

For mode 2: Tx mode 111-147kHz, 360kHz (5W load, 7.5W load, 10W load, 25W load)

For mode 3: Standby mode

Note: Scan with mode 1 and mode 2, mode 3, the worst case is mode 2 Tx mode (10W load) and recorded in this report

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$) 1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz) 3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☒ RF Connected Test (RF Measurement System 1#)				
SIGNAL ANALYZER	R&S	FSQ26	101272	2026/03/28
Wideband Radio Communication Tester	R&S	CMW500	120259	2026/03/28
MXG Vector Signal Generator	KEYSIGHT	N5182B	MY59100192	2026/03/28
MXG Vector Signal Generator	Agilent	N5182A	MY19060405	2026/03/28
RF Control Unit	Tonscend	JS0806-2	158060010	2026/03/28
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2026/03/28
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A

4 20 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (2) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (3) Use the following spectrum analyzer settings for the 20 dB bandwidth measurement:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 2 times and 5 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

- (4) Measure and record the results in the report.

Test Engineer:	Chen Haofeng	Test Site:	RF Measurement System 1#
Ambient Condition:	24.5 °C, 55%RH	Test Date:	2025/8/14 - 2025/8/14
Test Power Supply:	AC 120V/60Hz	Sample Number:	S25071422-001

Freq. (kHz)	20 dB bandwidth Result (kHz)	Verdict
124	0.280	Pass

Freq. (kHz)	20 dB bandwidth Result (kHz)	Verdict
127	0.263	Pass
360	0.263	Pass

ANT1 20 dB bandwidth

Ref -18.5 dBm At 5 dB SWT 120 ms


Center 124.2516026 kHz 100 Hz Span 1 kHz

Marker 1 [T1]
-51.83 dBm
124.251602564 kHz

nbs [T1] -20.00 dB
BW/210.44871949 Hz
Temp 1 [T1 nB]
-72.82 dBm
124.112179487 kHz
Temp 2 [T1 nB]
-72.05 dBm
124.392026205 kHz

Date : 14_AUG_2025 22:21:03

ANT 2 20 dB bandwidth_360 kHz



5 Antenna Requirements

5.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

5.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.

6. Radiated Emission

6.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2026/03/28
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/03/28
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

6.2. Block diagram of test setup



6.3. Limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dB(uV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~ 88	3	100	40.0
88~ 216	3	150	43.5

216~ 960	3	200	46.0
960~ 1000	3	500	54.0

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 40\text{Log}(300\text{m}/3\text{m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 80$$

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40$$

6.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

6.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30 MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.


(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

6.6. Test result

PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-09-09 **Tested By:** Lin Guoyuan
EUT: PODIUM 2-IN-1 WIRELESS **Model Number:** NB-WP-2N1TRY
Test Mode: Working Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:26.0°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\38
Memo: Sample Numbler:S25071422-001; ANT1

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.010	70.24	20.50	3.17	-32.50	61.41	127.52	66.11	PK	X
2	0.014	57.16	20.50	3.17	-32.50	48.33	124.58	76.25	PK	X
3	0.035	53.86	20.40	3.18	-32.53	44.91	116.73	71.82	PK	X
4	0.052	51.70	20.40	3.19	-32.55	42.74	113.30	70.56	PK	X
5	0.087	60.00	20.40	3.19	-32.59	51.00	108.84	57.84	PK	X
6	0.113	93.09	20.29	3.19	-32.60	83.97	106.55	22.58	PK	X

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.010	68.86	20.50	3.17	60.03	127.51	67.48	AV	X
2	0.014	49.37	20.50	3.17	40.54	124.55	84.01	AV	X
3	0.035	46.07	20.40	3.18	37.12	116.72	79.60	AV	X
4	0.052	47.5	20.40	3.19	38.54	113.30	74.76	AV	X
5	0.087	55.8	20.40	3.19	46.80	108.84	62.04	AV	X
6	0.113	88.89	20.29	3.19	79.77	106.55	26.78	AV	X

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-09-09 **Tested By:** Lin Guoyuan
EUT: PODIUM 2-IN-1 WIRELESS **Model Number:** NB-WP-2N1TRY
Test Mode: Working Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:26.0°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\39
Memo: Sample Numbler:S25071422-001; ANT1

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.339	63.95	20.21	3.19	-32.60	54.75	97.00	42.25	PK	X
2	0.571	51.70	20.31	3.20	-32.60	42.61	72.47	29.86	PK	X
3	0.793	51.71	20.36	3.20	-32.60	42.67	69.62	26.95	PK	X
4	1.931	49.69	20.40	3.22	-32.57	40.74	69.54	28.80	PK	X
5	5.703	48.41	20.54	3.29	-32.44	39.80	69.54	29.74	PK	X
6	15.557	53.93	20.24	3.47	-32.30	45.34	69.54	24.20	PK	X

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.339	63.66	20.21	3.19	54.46	97.00	42.54	AV	X
2	0.571	51.41	20.31	3.20	42.32	72.47	30.15	QP	X
3	0.793	51.42	20.36	3.20	42.38	69.62	27.24	QP	X
4	1.931	47.77	20.40	3.22	38.82	69.54	30.72	QP	X
5	5.703	46.49	20.54	3.29	37.88	69.54	31.66	QP	X
6	15.557	45.6	20.24	3.47	37.01	69.54	32.53	QP	X

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-09-09 **Tested By:** Lin Guoyuan
EUT: PODIUM 2-IN-1 WIRELESS **Model Number:** NB-WP-2N1TRY
Test Mode: Working Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:26.0°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\40
Memo: Sample Numbler:S25071422-001; ANT2 25W

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.234	55.02	20.15	3.19	-32.60	45.76	100.22	54.46	PK	X
2	0.295	57.98	20.18	3.19	-32.60	48.75	98.19	49.44	PK	X
3	0.359	68.44	20.22	3.19	-32.60	59.25	96.49	37.24	PK	X
4	0.443	62.50	20.27	3.20	-32.60	53.37	94.68	41.31	PK	X
5	0.739	57.18	20.35	3.20	-32.60	48.13	70.24	22.11	PK	X
6	14.293	52.18	20.30	3.44	-32.30	43.62	69.54	25.92	PK	X

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.234	46.12	20.15	3.19	36.86	100.22	63.36	AV	X
2	0.295	49.08	20.18	3.19	39.85	98.19	58.34	AV	X
3	0.359	63.13	20.22	3.19	53.94	96.49	42.55	AV	X
4	0.443	57.19	20.27	3.20	48.06	94.68	46.62	AV	X
5	0.739	51.87	20.35	3.20	42.82	70.24	27.42	QP	X
6	14.293	45.23	20.30	3.44	36.67	69.54	32.87	QP	X

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-09-09 **Tested By:** Lin Guoyuan
EUT: PODIUM 2-IN-1 WIRELESS **Model Number:** NB-WP-2N1TRY
Test Mode: Working Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:26.0°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\41
Memo: Sample Numbler:S25071422-001; ANT2 25W

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.020	57.59	20.50	3.18	-32.51	48.76	121.67	72.91	PK	X
2	0.035	54.47	20.40	3.18	-32.53	45.52	116.72	71.20	PK	X
3	0.098	51.39	20.36	3.18	-32.60	42.33	107.77	65.44	PK	X
4	0.102	53.66	20.34	3.18	-32.60	44.58	107.40	62.82	PK	X
5	0.119	52.80	20.25	3.19	-32.60	43.64	106.07	62.43	PK	X
6	0.148	49.55	20.11	3.19	-32.60	40.25	104.20	63.95	PK	X

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.020	50.25	20.50	3.18	41.42	121.66	80.24	AV	X
2	0.035	45.49	20.40	3.18	36.54	116.72	80.18	AV	X
3	0.098	42.41	20.36	3.18	33.35	107.77	74.42	QP	X
4	0.102	48.27	20.34	3.18	39.19	107.40	68.21	QP	X
5	0.119	47.41	20.25	3.19	38.25	106.07	67.82	AV	X
6	0.148	44.16	20.11	3.19	34.86	104.20	69.34	AV	X

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-09-09 **Tested By:** Lin Guoyuan
EUT: PODIUM 2-IN-1 WIRELESS **Model Number:** NB-WP-2N1TRY
Test Mode: Working Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:26.0°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\42
Memo: Sample Numbler:S25071422-001; ANT2 10W

**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.039	58.37	20.40	3.18	-32.53	49.42	115.84	66.42	PK	X
2	0.066	52.07	20.40	3.19	-32.56	43.10	111.19	68.09	PK	X
3	0.077	57.94	20.40	3.19	-32.57	48.96	109.87	60.91	PK	X
4	0.102	50.79	20.34	3.18	-32.60	41.71	107.40	65.69	PK	X
5	0.115	56.10	20.27	3.19	-32.60	46.96	106.36	59.40	PK	X
6	0.128	93.42	20.21	3.19	-32.60	84.22	105.48	21.26	PK	X

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.039	57.95	20.40	3.18	49.00	115.84	66.84	AV	X
2	0.066	51.65	20.40	3.19	42.68	111.18	68.50	AV	X
3	0.077	55.89	20.40	3.19	46.91	109.87	62.96	AV	X
4	0.102	48.74	20.34	3.18	39.66	107.40	67.74	QP	X
5	0.115	54.05	20.27	3.19	44.91	106.36	61.45	AV	X
6	0.128	84.95	20.21	3.19	75.75	105.48	29.73	AV	X

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-09-09 **Tested By:** Lin Guoyuan
EUT: PODIUM 2-IN-1 WIRELESS **Model Number:** NB-WP-2N1TRY
Test Mode: Working Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:26.0°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\43
Memo: Sample Numble:S25071422-001; ANT2 10W



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.256	69.00	20.16	3.19	-32.60	59.75	99.43	39.68	PK	X
2	0.293	60.97	20.18	3.19	-32.60	51.74	98.26	46.52	PK	X
3	0.383	69.41	20.23	3.19	-32.60	60.23	95.94	35.71	PK	X
4	0.511	64.87	20.30	3.20	-32.60	55.77	73.43	17.66	PK	X
5	0.638	59.55	20.33	3.20	-32.60	50.48	71.50	21.02	PK	X
6	17.113	51.68	20.11	3.50	-32.30	42.99	69.54	26.55	PK	X

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.256	67.52	20.16	3.19	58.27	99.43	41.16	AV	X
2	0.293	59.49	20.18	3.19	50.26	98.26	48.00	AV	X
3	0.383	66.29	20.23	3.19	57.11	95.94	38.83	AV	X
4	0.511	61.75	20.30	3.20	52.65	73.43	20.78	QP	X
5	0.638	50.02	20.33	3.20	40.95	71.50	30.55	QP	X
6	17.113	42.15	20.11	3.50	33.46	69.54	36.08	QP	X


Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

6.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-08-27 **Tested By:** Lin Guoyuan
EUT: PODIUM 2-IN-1 WIRELESS **Model Number:** NB-WP-2N1TRY
Test Mode: WPT Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:26.0°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\34
Memo: Sample Numbler:S25071422-001 ANT1+ANT2



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.014	59.45	20.50	3.17	-32.50	50.62	124.94	74.32	PK	X
2	0.020	57.32	20.50	3.18	-32.51	48.49	121.51	73.02	PK	X
3	0.046	49.61	20.40	3.19	-32.54	40.66	114.43	73.77	PK	X
4	0.079	52.18	20.40	3.19	-32.58	43.19	109.65	66.46	PK	X
5	0.087	51.92	20.40	3.19	-32.59	42.92	108.80	65.88	PK	X
6	0.125	92.27	20.23	3.19	-32.60	83.09	105.68	22.59	PK	X

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.014	58.1	20.50	3.17	49.27	124.93	75.66	AV	X
2	0.020	55.97	20.50	3.18	47.14	121.53	74.39	AV	X
3	0.046	41.84	20.40	3.19	32.89	114.44	81.55	AV	X
4	0.079	44.41	20.40	3.19	35.42	109.65	74.23	AV	X
5	0.087	42.52	20.40	3.19	33.52	108.80	75.28	AV	X
6	0.125	90.59	20.23	3.19	81.41	105.68	24.27	AV	X

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-08-27 **Tested By:** Lin Guoyuan
EUT: PODIUM 2-IN-1 WIRELESS **Model Number:** NB-WP-2N1TRY
Test Mode: WPT Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:26.0°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\33
Memo: Sample Numbler:S25071422-001 ANT1+ANT2



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.155	53.83	20.10	3.19	-32.60	44.52	103.78	59.26	PK	X
2	0.252	57.07	20.16	3.19	-32.60	47.82	99.57	51.75	PK	X
3	0.359	71.88	20.22	3.19	-32.60	62.69	96.49	33.80	PK	X
4	0.622	58.89	20.32	3.20	-32.60	49.81	71.73	21.92	PK	X
5	0.870	52.61	20.37	3.20	-32.60	43.58	68.81	25.23	PK	X
6	1.078	51.07	20.40	3.21	-32.60	42.08	66.95	24.87	PK	X

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.155	51.61	20.10	3.19	42.30	103.78	61.48	AV	X
2	0.252	53.22	20.16	3.19	43.97	99.57	55.60	AV	X
3	0.359	68.03	20.22	3.19	58.84	96.49	37.65	AV	X
4	0.622	58.62	20.32	3.20	49.54	71.73	22.19	QP	X
5	0.870	52.34	20.37	3.20	43.31	68.81	25.50	QP	X
6	1.078	44.39	20.40	3.21	35.40	66.95	31.55	QP	X

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-08-23

Tested By:

Li Xiongbín

EUT:

PODIUM 2-IN-1 WIRELESS

Model Number:

NB-WP-2N1TRY

Test Mode:

WPT Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:26.0°C;Humi:54.6%


Test Site:

DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\1

Memo:



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	31.977	35.79	10.89	3.74	18.12	40.00	21.88	QP	Horizontal
2	45.467	27.16	13.21	3.84	11.91	40.00	28.09	QP	Horizontal
3	60.145	32.04	12.40	3.95	16.09	40.00	23.91	QP	Horizontal
4	69.686	48.41	9.95	4.01	30.07	40.00	9.93	QP	Horizontal
5	130.707	47.65	8.85	4.28	28.45	43.50	15.05	QP	Horizontal
6	288.871	37.97	13.10	5.07	23.74	46.00	22.26	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-08-23

Tested By:

Li Xiongbín

EUT:

PODIUM 2-IN-1 WIRELESS

Model Number:

NB-WP-2N1TRY

Test Mode:

WPT Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:26.0°C;Humi:54.6%


Test Site:

DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25071422-2E\FCC Below 1G\2

Memo:



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	34.979	40.94	11.30	3.76	23.70	40.00	16.30	QP	Vertical
2	49.355	44.63	13.53	3.87	29.73	40.00	10.27	QP	Vertical
3	62.875	47.70	12.51	3.96	31.87	40.00	8.13	QP	Vertical
4	68.957	46.69	10.51	4.00	28.90	40.00	11.10	QP	Vertical
5	71.105	48.01	10.51	4.00	30.22	40.00	9.78	QP	Vertical
6	132.089	42.5	8.66	4.28	23.11	43.50	20.39	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.


3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

7. Power Line Conducted Emissions

7.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
EMI Test Receiver	R&S	ESCI	DDT-ZC00235	2026/07/06
Two Line V-Network	R&S	ENV216	DDT-ZC00535	2026/07/06
Artificial mains	R&S	ESH2-Z5	DDT-ZC00538	2026/07/06
Pulse Limiter	SCHWARZBECK	ESH3-Z2	DDT-ZC00539	2026/07/06
CE Cable 1	R&S	ESU8/RF2	DDT-ZC00566	2026/07/06
EMI Test Software	Audix/TW	e3	DDT-ZC01252	/

7.2. Block diagram of test setup



7.3. Limits

Frequency	Quasi-Peak Level dB(mV)	Average Level dB(mV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

7.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

7.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

7.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “-----” means Average detection.


Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

7.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room D:\2025 CE report data\Q25071422-2E\EM6.EM6
Test Date : 2025-08-21 Tested By : Li xiongbin
EUT : PODIUM 2-IN-1 WIRELESS Model Number : NB-WP-2N1TRY
Power Supply : AC 120V/60Hz Test Mode : WPT Mode
Condition : Temp:22.3°C,Humi:51.5% LISN : 2025 1# 216/NEUTRAL
Memo : S25071422-001

Data: 2



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.23	26.23	9.84	0.06	9.86	45.99	62.57	-16.58	QP	NEUTRAL
2	0.23	5.32	9.84	0.06	9.86	25.08	52.57	-27.49	Average	NEUTRAL
3	0.36	25.42	9.90	0.07	9.86	45.25	58.74	-13.49	QP	NEUTRAL
4	0.36	17.60	9.90	0.07	9.86	37.43	48.74	-11.31	Average	NEUTRAL
5	0.46	20.19	9.86	0.08	9.86	39.99	56.76	-16.77	QP	NEUTRAL
6	0.46	1.06	9.86	0.08	9.86	20.86	46.76	-25.90	Average	NEUTRAL
7	0.57	21.94	9.89	0.10	9.86	41.79	56.00	-14.21	QP	NEUTRAL
8	0.57	3.83	9.89	0.10	9.86	23.68	46.00	-22.32	Average	NEUTRAL
9	0.79	18.52	9.81	0.13	9.87	38.33	56.00	-17.67	QP	NEUTRAL
10	0.79	0.61	9.81	0.13	9.87	20.42	46.00	-25.58	Average	NEUTRAL
11	1.08	15.14	9.92	0.15	9.88	35.09	56.00	-20.91	QP	NEUTRAL
12	1.08	9.23	9.92	0.15	9.88	29.18	46.00	-16.82	Average	NEUTRAL

Note:


1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room
Test Date : 2025-08-21
EUT : PODIUM 2-IN-1 WIRELESS
Power Supply : AC 120V/60Hz
Condition : Temp:22.3°C,Humi:51.5%
Memo : S25071422-001

D:\2025 CE report data\Q25071422-2E\EM6.EM6
Tested By : Li xiongbin
Model Number : NB-WP-2N1TRY
Test Mode : WPT Mode
LISN : 2025 1# 216/LINE

Data: 4



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.24	27.98	9.82	0.06	9.86	47.72	62.22	-14.50	QP	LINE
2	0.24	7.22	9.82	0.06	9.86	26.96	52.22	-25.26	Average	LINE
3	0.36	25.60	9.67	0.07	9.86	45.20	58.69	-13.49	QP	LINE
4	0.36	19.26	9.67	0.07	9.86	38.86	48.69	-9.83	Average	LINE
5	0.48	20.37	9.75	0.09	9.86	40.07	56.36	-16.29	QP	LINE
6	0.48	4.43	9.75	0.09	9.86	24.13	46.36	-22.23	Average	LINE
7	0.60	24.07	9.94	0.11	9.87	43.99	56.00	-12.01	QP	LINE
8	0.60	2.22	9.94	0.11	9.87	22.14	46.00	-23.86	Average	LINE
9	0.83	19.97	9.77	0.13	9.87	39.74	56.00	-16.26	QP	LINE
10	0.83	1.07	9.77	0.13	9.87	20.84	46.00	-25.16	Average	LINE
11	1.08	18.98	9.95	0.15	9.88	38.96	56.00	-17.04	QP	LINE
12	1.08	12.54	9.95	0.15	9.88	32.52	46.00	-13.48	Average	LINE

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

9. Photos of the EUT

Please refer to DDT-Q25071422-2E appendix I

-----End Report-----