

Shenzhen Reecoo Electronic Co., Ltd.

EMC TEST REPORT

Report Type:

FCC Part 15B & ICES-003 EMC report

Model:
CH2125

REPORT NUMBER:
220401181SHA-001

ISSUE DATE:
July 1, 2022

DOCUMENT CONTROL NUMBER:
TTRF15b_V1 © 2018 Intertek



Applicant	: Shenzhen Reecoo Electronic Co., Ltd. Building 5-6, ShangLiLang Science and Technology Park, ShangLiLang community, NanWan Street, LongGang district, ShenZhen city, Guangdong province, China
Manufacturer	: Shenzhen Reecoo Electronic Co., Ltd. Building 5-6, ShangLiLang Science and Technology Park, ShangLiLang community, NanWan Street, LongGang district, ShenZhen city, Guangdong province, China
Factory	: Ecovacs Robotics Co., Ltd. No.518 Songwei Road, Wusongjiang industry Park,Guoxiang Street, Wuzhong District, Suzhou,Jiangsu, China
FCC ID	: 2AZMB-CH2125

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2020): Radio Frequency Devices (Subpart B)

ANSI C63.4 (2014): American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

ICES-003 Issue 7 October 2020: Information Technology Equipment (Including Digital Apparatus) —Limits and Methods of Measurement.

PREPARED BY:

Project Engineer
Eric Li**REVIEWED BY:**

Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT**Content**

REVISION HISTORY.....	4
MEASUREMENT RESULT SUMMARY	5
1 GENERAL INFORMATION	6
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST FACILITY	7
2 TEST SPECIFICATIONS.....	8
2.1 STANDARDS OR SPECIFICATION	8
2.2 MODE OF OPERATION DURING THE TEST.....	8
2.3 TEST SOFTWARE LIST	8
2.4 TEST PERIPHERALS LIST	8
2.5 TEST ENVIRONMENT CONDITION:.....	9
2.6 INSTRUMENT LIST	9
2.7 MEASUREMENT UNCERTAINTY	10
3 RADIATED EMISSIONS	11
3.1 LIMIT	11
3.1.1 <i>Limits for radiated disturbance of class A device</i>	11
3.1.2 <i>Limits for radiated disturbance of class B device</i>	12
3.2 BLOCK DIAGRAM AND TEST SET UP	13
3.3 MEASUREMENT PROCEDURE	14
3.4 TEST RESULTS OF RADIATED EMISSIONS	15
4 POWER LINE CONDUCTED EMISSION.....	17
4.1 LIMIT	17
4.1.1 <i>Limits for conducted disturbance voltage at the mains ports of class A device</i>	17
4.1.2 <i>Limits for conducted disturbance voltage at the mains ports of class B device</i>	17
4.2 BLOCK DIAGRAM AND TEST SET UP	18
4.3 MEASUREMENT PROCEDURE	19
4.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION.....	20
APPENDIX I: PHOTOGRAPH OF EQUIPMENT UNDER TEST	22

TEST REPORT**Revision History**

Report No.	Version	Description	Issued Date
220401181SHA-001	Rev. 01	Initial issue of report	July 1, 2022

TEST REPORT**Measurement result summary**

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT
Power line conducted emission	15.107	3.2.1	Pass
Radiated emission	15.109	3.2.2	Pass

Notes: 1: NA =Not Applicable

2: “*” means this test is no need and not performed within this report, and the result can refer to the related base report(s).

TEST REPORT**1 GENERAL INFORMATION****1.1 Description of Equipment Under Test (EUT)**

Product name:	Docking Station
Type/Model:	CH2125
Description of EUT:	The EUT is a docking station which supplies charging function to automatic battery-operated cleaner, we test the EMC items and list the worst results in this report.
Rating:	Input: 100-240V~, 50-60Hz, 0,5A Output: 20V DC, 1A.
Category of EUT:	Class B
EUT type:	<input type="checkbox"/> Table top <input checked="" type="checkbox"/> Floor standing
Highest operating frequency	< 108MHz
Software Version:	/
Hardware Version:	/
Sample received date:	2022.6.13
Date of test:	2022.6.13~2022.6.20

TEST REPORT**1.2 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab Registration code No.: 2042B-1
	VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT**2 TEST SPECIFICATIONS****2.1 Standards or specification**

47CFR Part 15 (2020)

ANSI C63.10 (2014)

ICES-003 Issue 7 October 2020

2.2 Mode of operation during the test

Within this test report, EUT was tested under all available operation modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Brand and Model	Description
1	Automatic battery-operated cleaner	YDTX11	-

TEST REPORT
2.5 Test environment condition:

Test items	Temperature	Humidity
Power line conducted emission	23°C	51% RH
Radiated Emissions	24°C	52% RH

2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCS 30	EC 2107	2022-07-14
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2022-11-29
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2023-01-13
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2022-09-12
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2022-12-10
<input checked="" type="checkbox"/>	Horn antenna	R&S	HF 906	EC 3049	2022-11-17
<input checked="" type="checkbox"/>	Horn antenna	ETS	3117	EC 4792-1	2023-01-09
<input checked="" type="checkbox"/>	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2022-07-09
<input checked="" type="checkbox"/>	Pre-amplifier	R&S	Pre-amp 18	EC5881	2023-06-11
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross project	-	EC 3048	2022-09-15
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3325	2023-04-07
<input checked="" type="checkbox"/>	Pressure meter	YM3	Shanghai Mengde	EC 3320	2022-06-30

TEST REPORT**2.7 Measurement uncertainty**

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Radiated Emissions in restricted frequency bands below 1GHz	± 4.60dB
Radiated Emissions in restricted frequency bands above 1GHz	± 4.40dB
Power line conducted emission	± 2.70dB

TEST REPORT

3 Radiated Emissions

 Test result: **Pass**

3.1 Limit

3.1.1 Limits for radiated disturbance of class A device

FCC

Frequency (MHz)	Permitted limit in dB μ V/m (Quasi-peak) of Measurement Distance 10m
30 – 88	39
88 – 216	43.5
216 – 960	46.4
Above 960	49.5

Note: for the measurement distance other than 3m and 10m, the limit is varied according to 20dB/10 decades.

IC

Frequency (MHz)	Permitted limit in dB μ V/m (Quasi-peak) of Measurement Distance 10m	Permitted limit in dB μ V/m (Quasi-peak) of Measurement Distance 3m
30 ~ 88	40.0	50.0
88 ~ 216	43.5	54.0
216 ~ 230	46.4	56.9
230 ~ 960	47.0	57.0
960 ~ 1000	49.5	60.0

Note: The more stringent limit applies at transition frequencies.

Frequency (GHz)	Permitted limit in dB μ V/m (Peak) of Measurement Distance 3m	Permitted limit in dB μ V/m (Average) of Measurement Distance 3m
1 ~ F _M	80.0	60.0

Note: These limit levels apply for a measurement distance of 3 m. If using a different measurement distance, the measured levels shall be extrapolated to the 3 m limit distance using a factor of 20 dB per decade of distance. The measurement distance shall place the measurement antenna in the far field of the ITE or digital apparatus under test.

TEST REPORT

 3.1.2 Limits for radiated disturbance of class B device
 FCC

Frequency (MHz)	Permitted limit in dB μ V/m (Quasi-peak) of Measurement Distance 3m
30 – 88	40.0
88 – 216	43.5
216 – 960	46.0
Above 960	54.0

Note: for the measurement distance other than 3m and 10m, the limit is varied according to 20dB/10 decades.

IC

Frequency (MHz)	Permitted limit in dB μ V/m (Quasi-peak) of Measurement Distance 10m	Permitted limit in dB μ V/m (Quasi-peak) of Measurement Distance 3m
30 ~ 88	30.0	40.0
88 ~ 216	33.1	43.5
216 ~ 230	35.6	46.0
230 ~ 960	37.0	47.0
960 ~ 1000	43.5	54.0


Note: The more stringent limit applies at transition frequencies.

Frequency (GHz)	Permitted limit in dB μ V/m (Peak) of Measurement Distance 3m	Permitted limit in dB μ V/m (Average) of Measurement Distance 3m
1 ~ F_M	74.0	54.0


Note: These limit levels apply for a measurement distance of 3 m. If using a different measurement distance, the measured levels shall be extrapolated to the 3 m limit distance using a factor of 20 dB per decade of distance. The measurement distance shall place the measurement antenna in the far field of the ITE or digital apparatus under test.

TEST REPORT**3.2 Block diagram and test set up**

For table top equipment



For floor standing equipment



TEST REPORT**3.3 Measurement Procedure**

The measurement was performed in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, the pre-amplifier (and high pass filter if necessary) is equipped just at the output terminal of the antenna.

The distance from EUT to receiving antenna is 3 meters.

Measurement was performed according to clause 4 and clause 5 of ANSI 63.4.

Test procedure was according to clause 8.3 of ANSI 63.4.

EUT arrangement and operate condition were according to clause 6 and clause 8 of ANSI 63.4.

The radiated emission was measured using the test receiver with the resolutions bandwidth set as:

RBW = 100kHz, VBW = 300kHz (30MHz~1GHz)


RBW = 1MHz, VBW = 3MHz (>1GHz for PK)

Highest internal frequency (Fx)	Highest measured frequency F_M for radiated measurement	Measured Bandwidth
$F_x \leq 108 \text{ MHz}$	1 GHz	120kHz
$108 \text{ MHz} < F_x \leq 500 \text{ MHz}$	2 GHz	1MHz
$500 \text{ MHz} < F_x \leq 1 \text{ GHz}$	5 GHz	1MHz
$F_x > 1 \text{ GHz}$	$5 \times F_x$ up to a maximum of 40 GHz	1MHz


Note: 1. Fx is the highest fundamental frequency generated and/or used in the ITE or digital apparatus under test.

TEST REPORT**3.4 Test Results of Radiated Emissions**

Horizontal



Vertical



TEST REPORT
Test data:

Polarization	Frequency (MHz)	Measured level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
H	35.83	25.60	40.00	14.40	PK
	86.37	15.20	40.00	24.80	PK
	169.96	19.70	43.50	23.80	PK
	265.21	24.40	46.00	21.60	PK
	545.13	27.20	46.00	18.80	PK
	871.70	33.30	46.00	12.70	PK
V	33.89	26.20	40.00	13.80	PK
	78.60	18.60	40.00	21.40	PK
	171.90	26.30	43.50	17.20	PK
	183.57	27.10	43.50	16.40	PK
	325.47	29.30	46.00	16.70	PK
	881.42	34.50	46.00	11.50	PK

Above 1GHz

Polarization	Frequency (MHz)	Emission level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB μ V/m)	Detector
Horizontal	1000.00	*	74.0	*	PK
	5000.00	*	74.0	*	PK
	10000.00	*	74.0	*	PK
	15000.00	*	74.0	*	PK
	20000.00	*	74.0	*	PK
	25000.00	*	74.0	*	PK
Vertical	1000.00	*	74.0	*	PK
	5000.00	*	74.0	*	PK
	10000.00	*	74.0	*	PK
	15000.00	*	74.0	*	PK
	20000.00	*	74.0	*	PK
	25000.00	*	74.0	*	PK

Note: * means the emission level is 10dB or more lower than the relevant limit.

Remark:

1. Factor= Antenna Factor + Cable Loss (-Amplifier, is employed)
2. Measured level= Original Receiver Reading + Factor
3. Margin = Limit – Measured level
4. If the PK measured level is lower than AV limit, the AV test can be elided.

TEST REPORT**4 Power line conducted emission****Test result:** **Pass****4.1 Limit****4.1.1 Limits for conducted disturbance voltage at the mains ports of class A device**



Frequency range (MHz)	Limits dB(µV)	
	Quasi-peak	Average
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

Note: If the limit for the measurement with the average detector is met when using a receiver with a quasi-peak detector, the equipment under test shall be deemed to meet both limits and the measurement using the receiver with an average detector need not be carried out.

4.1.2 Limits for conducted disturbance voltage at the mains ports of class B device

Frequency range (MHz)	Limits dB(µV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 ~ 56 *	56 ~ 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

Note: 1. * Means the limit decreasing linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz
2. If the limit for the measurement with the average detector is met when using a receiver with a quasi-peak detector, the equipment under test shall be deemed to meet both limits and the measurement using the receiver with an average detector need not be carried out.

TEST REPORT
4.2 Block diagram and test set up
For table top equipment

For floor standing equipment


TEST REPORT

4.3 Measurement Procedure


Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

TEST REPORT
4.4 Test Results of Power line conducted emission
Test Curve

Test Voltage: AC 120V, 60Hz


Test Data:

Frequency (MHz)	Quasi-peak			Average		
	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)
0.30	33.31	60.20	26.89	30.01	50.20	20.19
0.40	35.81	57.91	22.10	33.21	47.91	14.70
0.43	40.14	57.35	17.21	34.73	47.35	12.62
0.45	43.42	56.88	13.46	38.59	46.88	8.29
0.90	34.40	56.00	21.60	28.82	46.00	17.18
1.40	34.06	56.00	21.94	25.15	46.00	20.85

TEST REPORT

Test Data:

Frequency (MHz)	Quasi-peak			Average		
	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)
0.25	31.44	61.79	30.35	26.59	51.79	25.20
0.35	32.86	59.00	26.14	30.70	49.00	18.30
0.37	36.01	58.51	22.50	33.46	48.51	15.05
0.42	40.88	57.41	16.53	36.50	47.41	10.91
0.44	44.20	56.98	12.78	40.45	46.98	6.53
1.50	30.93	56.00	25.07	23.05	46.00	22.95

Remark: 1. *Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.*
 2. *Corrected Reading = Original Receiver Reading + Correct Factor*
 3. *Margin = Limit - Corrected Reading*
 4. *If the PK Corrected Reading is lower than AV limit, the AV test can be elided.*

TEST REPORT**Appendix I: Photograph of equipment under test**

External and Internal photos refer to the external and internal photos documents

***** END *****