



RF TEST REPORT

Report Reference No..... : MAX25040262P01-R01RF

FCC ID..... : 2AZNY-23030S

Compiled by
(position+printed name+signature)....: Engineer/ Cindy Zheng

Supervised by
(position+printed name+signature)....: Manager/Haley Wen

Approved by
(position+printed name+signature)....: RF Manager/ Vivian Jiang

Date of issue..... : May 20, 2025

Testing Laboratory Name..... : MAXLAB Testing Co.,Ltd.

Address..... : 1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District, Shenzhen, Guangdong, 518052, People's Republic of China

Applicant's name..... : Fujian EastWest Lifewit Technology Co.,LTD

Address..... : Room 1201-1205, Building 18, 2nd Phase of Innovation Park. Avenue, no.7, wulongjiang Middle Avenue, Fuzhou High-tech Zone, Fuzhou, Fujian Province

Test specification..... :

FCC Part 15.236

Standard..... : KDB 447498 D01 V06

ANSI C95.1- 2019

MAXLAB Testing Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Equipment description..... : WIRELESS MICROPHONE

Trade Mark..... : TONOR

Manufacturer..... : EASTWEST ELECTRONIC COMMERCE CO., LIMITED

Model/Type reference..... : TW100

Listed Models : N/A

Modulation : FM

Frequency..... : From 510MHz to 530MHz

Ratings..... : DC 3.7V From Battery or DC 5V by USB port

Result..... : PASS



RF Exposure Evaluation

1. The corresponding SAR Exclusion Threshold condition, listed below:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

➢ $f(\text{GHz})$ is the RF channel transmit frequency in GHz

➢ Power and distance are rounded to the nearest mW and mm before calculation

➢ The result is rounded to one decimal place for comparison

2. CLASSIFICATION

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EUT Specification

Antenna type:	Metal Antenna
Antenna gain (Max)	3.0dBi
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

3. SAR TEST EXCLUSION THRESHOLDS

Frequency	RF Output power	Tolerance	Max Tune Up power		Antenna Gain	min. test separation distance	Result	Limit
(MHz)	(dBm)	(dBm)	(dBm)	(mW)	(dBi)	(mm)		
510.30	4.352	4±1	5	3.162	3.0	5	0.4518	3
519.30	4.526	4±1	5	3.162	3.0	5	0.4558	3
529.30	4.632	4±1	5	3.162	3.0	5	0.4601	3

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.3013 which is <= 3, RF Exposure testing is not required.

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · $\sqrt{f(\text{GHz})}$

f(GHz) is the RF channel transmit frequency in GHz

Distance=5mm

Conclusion: No SAR is required.