


802.11ax(40M) (5.15GHz-5.25GHz)
The Lowest Channel 38: 5190MHz




802.11ax(40M) (5.15GHz-5.25GHz)
The High Channel 46: 5230MHz




802.11ax(40M) (5.725GHz-5.85GHz)
The Lowest Channel 151: 5755MHz




802.11ax(40M) (5.725GHz-5.85GHz)
The High Channel 159: 5795MHz




802.11ac(80M) (5.15GHz-5.25GHz)
The Lowest Channel 42: 5210MHz




802.11ac(80M) (5.725GHz-5.85GHz)
The High Channel 155: 5775MHz



802.11ax(80M) (5.15GHz-5.25GHz)
The Lowest Channel 42: 5210MHz




802.11ax(80M) (5.725GHz-5.85GHz)
The High Channel 155: 5775MHz




8. RADIATED EMISSION MEASUREMENT

8.1. Block diagram of test setup

In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz




In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



Report No.: AAEMT/RF/230604-01-03

In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

9.3.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

9.3.2. FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V/m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V/m}) + 40\text{Log}(30\text{m}/3\text{m})$$

9.3.3. Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 30dB below the fundamental emissions, or comply with 15.209 limits.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and assistant system according clause 2.4 and 7.2
- (3) Test antenna was located 3m(except 18GHz-40GHz was 1m) from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used
9KHz-30MHz	Active Loop antenna
30MHz-1GHz	Bilog Broadband Antenna
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)
18GHz-40GHz	Horn Antenna(18GHz-40GHz)

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (4) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 40GHz:
 - (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)
 - (b) Change work frequency or channel of device if practicable.
 - (c) Change modulation type of device if practicable.
 - (d) new battery is used during testing
 - (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Report No.: AAEMT/RF/230604-01-03

Spectrum frequency from 9KHz to 40GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 40GHz, so below final test was performed with frequency range from 9KHz to 40GHz.

- (5) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.
- (6) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (7) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

- (8) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure (according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure). Peak detector is used for Peak and AV measurement both.

According to KDB 789033 v02r01 section G) 1) (d), for For measurements above 1000 MHz @ 3m distance, the limit of field strength is computed as follows:

$$E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2;$$

For example, if EIRP = -27dBm

$$E[\text{dBuV/m}] = -27 + 95.2 = 68.2\text{dBuV/m}.$$

8.4. Test result(Below 30MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	--	Test Result:	Pass
Test Mode:	Keeping TX mode	Tested By:	Aman

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $20 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

Note: N/A

TEST RESULTS (Between 30MHz – 1000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8x14
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5180MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.2115	-21.84	59.24	37.40	40.00	-2.60	QP
2	53.7558	-14.51	52.17	37.66	40.00	-2.34	QP
3	398.2962	-5.65	48.48	42.83	46.00	-3.17	QP
4	531.2910	-2.04	45.11	43.07	46.00	-2.93	QP
5	562.0143	-1.44	43.84	42.40	46.00	-3.60	QP
6	793.0281	0.32	42.85	43.17	46.00	-2.83	QP

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5180MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	50.1080	-12.29	46.45	34.16	40.00	-5.84	QP
2	54.1349	-12.53	49.59	37.06	40.00	-2.94	QP
3	55.2882	-12.60	47.97	35.37	40.00	-4.63	QP
4	67.7854	-16.09	51.42	35.33	40.00	-4.67	QP
5	793.0281	2.32	37.80	40.12	46.00	-5.88	QP
6	952.0000	4.32	35.35	39.67	46.00	-6.33	QP

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result – Limit

TEST RESULTS (Between 1000MHz – 18000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8x14
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5180MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1743.795	-13.55	49.10	35.55	74.00	-38.45	peak
2	1753.924	-13.62	37.41	23.79	54.00	-30.21	AVG
3	3259.699	-10.16	47.77	37.61	74.00	-36.39	peak
4	3297.681	-10.17	34.24	24.07	54.00	-29.93	AVG
5	5181.120	-7.30	83.41	76.11	74.00	2.11	peak
6	5241.490	-6.93	31.81	24.88	54.00	-29.12	AVG
7	6802.299	-3.70	45.17	41.47	74.00	-32.53	peak
8	6921.535	-3.74	33.39	29.65	54.00	-24.35	AVG
9	14031.456	4.28	43.82	48.10	74.00	-25.90	peak
10	14194.951	2.89	29.04	31.93	54.00	-22.07	AVG
11	17689.916	5.71	44.74	50.45	74.00	-23.55	peak

Note: Markers 5 is the intentional frequency from EUT, Hence considered as pass.

The test result is calculated as the following:

- (4) Result = Reading + Correct Factor
- (5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (6) Margin = Result - Limit

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5180MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1268.056	-12.85	49.48	36.63	74.00	-37.37	peak
2	1275.423	-12.81	38.11	25.30	54.00	-28.70	AVG
3	2954.015	-9.96	47.89	37.93	74.00	-36.07	peak
4	2971.175	-9.82	35.66	25.84	54.00	-28.16	AVG
5	5181.120	-7.30	76.28	68.98	74.00	-5.02	peak
6	5271.939	-6.62	31.37	24.75	54.00	-29.25	AVG
7	11259.286	-1.40	45.88	44.48	74.00	-29.52	peak
8	11324.692	-1.48	29.93	28.45	54.00	-25.55	AVG
9	14031.456	4.28	43.91	48.19	74.00	-25.81	peak
10	14112.966	3.70	31.02	34.72	54.00	-19.28	AVG
11	17792.679	5.85	45.18	51.03	74.00	-22.97	peak
12	17896.039	6.00	32.05	38.05	54.00	-15.95	AVG


Note: Markers 5 is the intentional frequency from EUT, Hence considered as pass.

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

TEST RESULTS (Between 18000MHz – 26500 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8x14
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5180MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18638.905	-15.77	44.92	29.15	74.00	-44.85	peak
2	18653.358	-15.76	31.34	15.58	54.00	-38.42	AVG
3	20345.036	-16.41	42.99	26.58	74.00	-47.42	peak
4	20392.399	-16.33	29.55	13.22	54.00	-40.78	AVG
5	21198.216	-15.84	41.48	25.64	74.00	-48.36	peak
6	21231.103	-15.80	27.69	11.89	54.00	-42.11	AVG
7	22606.784	-14.85	41.55	26.70	74.00	-47.30	peak
8	22641.856	-14.87	28.06	13.19	54.00	-40.81	AVG
9	24108.947	-13.98	41.97	27.99	74.00	-46.01	peak
10	24127.641	-13.99	29.54	15.55	54.00	-38.45	AVG
11	25413.729	-13.57	42.49	28.92	74.00	-45.08	peak
12	25433.435	-13.53	29.24	15.71	54.00	-38.29	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5180MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18595.615	-15.77	44.59	28.82	74.00	-45.18	peak
2	18638.905	-15.77	31.83	16.06	54.00	-37.94	AVG
3	20376.599	-16.36	42.32	25.96	74.00	-48.04	peak
4	20392.399	-16.33	29.55	13.22	54.00	-40.78	AVG
5	21165.381	-15.87	41.00	25.13	74.00	-48.87	peak
6	21181.792	-15.85	29.39	13.54	54.00	-40.46	AVG
7	22589.268	-14.84	39.96	25.12	74.00	-48.88	peak
8	22624.313	-14.87	28.42	13.55	54.00	-40.45	AVG
9	24108.947	-13.98	40.80	26.82	74.00	-47.18	peak
10	24146.349	-14.02	29.25	15.23	54.00	-38.77	AVG
11	25591.632	-13.55	43.12	29.57	74.00	-44.43	peak
12	25651.209	-13.66	27.30	13.64	54.00	-40.36	AVG


The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 26500MHz – 40000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5180MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	27409.975	0.57	40.35	40.92	74.00	-33.08	peak
2	30595.109	1.39	46.35	47.74	74.00	-26.26	peak
3	33344.495	1.87	43.32	45.19	74.00	-28.81	peak
4	35279.440	2.16	45.31	47.47	74.00	-26.53	peak
5	37035.802	2.47	47.27	49.74	74.00	-24.26	peak
6	39508.957	2.87	51.51	54.38	74.00	-19.62	peak
7	27421.262	0.57	28.30	28.87	54.00	-25.13	AVG
8	30658.159	1.40	32.49	33.89	54.00	-20.11	AVG
9	33385.708	1.88	30.39	32.27	54.00	-21.73	AVG
10	35323.044	2.17	32.47	34.64	54.00	-19.36	AVG
11	37112.125	2.49	34.68	37.17	54.00	-16.83	AVG
12	39557.789	2.87	39.20	42.07	54.00	-11.93	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5180MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	27957.073	0.72	38.15	38.87	74.00	-35.13	peak
2	28083.981	0.75	26.80	27.55	54.00	-26.45	AVG
3	29799.426	1.22	28.02	29.24	54.00	-24.76	AVG
4	29836.257	1.23	39.87	41.10	74.00	-32.90	peak
5	33030.217	1.82	42.57	44.39	74.00	-29.61	peak
6	33071.041	1.82	30.75	32.57	54.00	-21.43	AVG
7	35732.625	2.25	45.94	48.19	74.00	-25.81	peak
8	35850.518	2.27	35.79	38.06	54.00	-15.94	AVG
9	37357.418	2.53	45.48	48.01	74.00	-25.99	peak
10	37434.404	2.54	35.52	38.06	54.00	-15.94	AVG
11	38719.851	2.75	37.82	40.57	54.00	-13.43	AVG
12	38735.796	2.76	48.93	51.69	74.00	-22.31	peak

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

TEST RESULTS (Between 30M – 1000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8x14
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE) FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5240MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.6390	-21.41	58.78	37.37	40.00	-2.63	QP
2	48.7190	-15.09	49.43	34.34	40.00	-5.66	QP
3	51.5363	-14.37	48.56	34.19	40.00	-5.81	QP
4	53.3793	-14.48	49.63	35.15	40.00	-4.85	QP
5	67.3108	-17.90	52.67	34.77	40.00	-5.23	QP
6	398.2961	-5.65	46.74	41.09	46.00	-4.91	QP

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8x14
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5240MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.2115	-19.84	50.99	31.15	40.00	-8.85	QP
2	49.0626	-12.88	44.90	32.02	40.00	-7.98	QP
3	54.9010	-12.57	44.00	31.43	40.00	-8.57	QP
4	395.5070	-3.72	41.55	37.83	46.00	-8.17	QP
5	793.0280	2.32	37.94	40.26	46.00	-5.74	QP
6	938.7138	3.31	33.80	37.11	46.00	-8.89	QP


The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 1000MHz – 18000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5240MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5241.490	-6.93	80.17	73.24	74.00	-0.76	peak
2	5271.939	-6.62	31.50	24.88	54.00	-29.12	AVG
3	6841.814	-3.71	46.24	42.53	74.00	-31.47	peak
4	6921.535	-3.74	33.39	29.65	54.00	-24.35	AVG
5	11001.415	-1.10	44.32	43.22	74.00	-30.78	peak
6	11065.323	-1.18	30.77	29.59	54.00	-24.41	AVG
7	12352.648	-1.11	45.66	44.55	74.00	-29.45	peak
8	12496.581	-1.32	33.31	31.99	54.00	-22.01	AVG
9	14031.456	4.28	44.63	48.91	74.00	-25.09	peak
10	14194.951	2.89	29.20	32.09	54.00	-21.91	AVG
11	17689.916	5.71	45.47	51.18	74.00	-22.82	peak
12	17792.679	5.85	32.49	38.34	54.00	-15.66	AVG


Note: Markers 1 is the intentional frequency from EUT, Hence considered as pass.

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8x14
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5240MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1375.171	-14.70	52.04	37.34	74.00	-36.66	peak
2	1383.160	-14.92	38.80	23.88	54.00	-30.12	AVG
3	2454.225	-11.80	54.47	42.67	74.00	-31.33	peak
4	2482.821	-11.41	35.24	23.83	54.00	-30.17	AVG
5	4015.488	-7.17	46.54	39.37	74.00	-34.63	peak
6	4038.814	-7.63	34.68	27.05	54.00	-26.95	AVG
7	5241.490	-6.93	90.75	83.82	74.00	9.82	peak
8	5302.564	-6.37	31.61	25.24	54.00	-28.76	AVG
9	7726.777	-3.92	45.99	42.07	74.00	-31.93	peak
10	7771.663	-3.96	34.31	30.35	54.00	-23.65	AVG
11	14031.456	4.28	44.55	48.83	74.00	-25.17	peak
12	14112.966	3.70	31.02	34.72	54.00	-19.28	AVG


Note: Markers 7 is the intentional frequency from EUT, Hence considered as pass.

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

TEST RESULTS (Between 18000MHz – 26500 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5240MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18581.207	-15.77	44.53	28.76	74.00	-45.24	peak
2	18624.464	-15.77	32.06	16.29	54.00	-37.71	AVG
3	19678.129	-16.51	42.81	26.30	74.00	-47.70	peak
4	19708.658	-16.55	30.14	13.59	54.00	-40.41	AVG
5	21132.596	-15.91	40.55	24.64	74.00	-49.36	peak
6	21181.792	-15.85	29.55	13.70	54.00	-40.30	AVG
7	22624.313	-14.87	39.69	24.82	74.00	-49.18	peak
8	22676.982	-14.88	26.89	12.01	54.00	-41.99	AVG
9	24146.349	-14.02	40.92	26.90	74.00	-47.10	peak
10	24165.072	-14.03	28.75	14.72	54.00	-39.28	AVG
11	25532.193	-13.44	41.35	27.91	74.00	-46.09	peak
12	25591.632	-13.55	29.08	15.53	54.00	-38.47	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5240MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18083.905	-15.44	44.94	29.50	74.00	-44.50	peak
2	18126.005	-15.47	31.70	16.23	54.00	-37.77	AVG
3	19939.136	-16.93	42.63	25.70	74.00	-48.30	peak
4	20001.051	-17.03	28.24	11.21	54.00	-42.79	AVG
5	21165.381	-15.87	41.48	25.61	74.00	-48.39	peak
6	21181.792	-15.85	29.55	13.70	54.00	-40.30	AVG
7	24127.641	-13.99	41.12	27.13	74.00	-46.87	peak
8	24165.072	-14.03	28.58	14.55	54.00	-39.45	AVG
9	25453.156	-13.49	41.67	28.18	74.00	-45.82	peak
10	25472.892	-13.44	28.91	15.47	54.00	-38.53	AVG
11	25870.847	-14.06	42.36	28.30	74.00	-45.70	peak
12	25890.908	-14.10	29.09	14.99	54.00	-39.01	AVG


The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 26500MHz – 40000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5240MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	28339.525	0.82	26.72	27.54	54.00	-26.46	AVG
2	28362.872	0.82	37.78	38.60	74.00	-35.40	peak
3	30784.649	1.43	42.07	43.50	74.00	-30.50	peak
4	30860.794	1.44	32.35	33.79	54.00	-20.21	AVG
5	33166.494	1.84	32.11	33.95	54.00	-20.05	AVG
6	33193.817	1.84	43.29	45.13	74.00	-28.87	peak
7	35264.917	2.15	36.78	38.93	54.00	-15.07	AVG
8	35279.440	2.16	46.81	48.97	74.00	-25.03	peak
9	37265.243	2.52	47.15	49.67	74.00	-24.33	peak
10	37265.243	2.52	35.23	37.75	54.00	-16.25	AVG
11	38481.453	2.72	39.41	42.13	54.00	-11.87	AVG
12	38497.301	2.72	49.59	52.31	74.00	-21.69	peak

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5240MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	27364.869	0.55	37.15	37.70	74.00	-36.30	peak
2	27443.852	0.57	26.38	26.95	54.00	-27.05	AVG
3	30607.708	1.39	39.62	41.01	74.00	-32.99	peak
4	30670.785	1.40	28.60	30.00	54.00	-24.00	AVG
5	33207.487	1.84	42.09	43.93	74.00	-30.07	peak
6	33289.624	1.86	30.47	32.33	54.00	-21.67	AVG
7	35366.702	2.18	45.58	47.76	74.00	-26.24	peak
8	35381.267	2.18	34.52	36.70	54.00	-17.30	AVG
9	37930.885	2.62	37.54	40.16	54.00	-13.84	AVG
10	37946.505	2.63	48.39	51.02	74.00	-22.98	peak
11	39007.878	2.79	50.51	53.30	74.00	-20.70	peak
12	39023.943	2.79	38.48	41.27	54.00	-12.73	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

TEST RESULTS (Between 30M – 1000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE) FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5745MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.0000	-22.05	58.41	36.36	40.00	-3.64	QP
2	49.7571	-14.43	50.51	36.08	40.00	-3.92	QP
3	56.0707	-14.64	50.47	35.83	40.00	-4.17	QP
4	395.5070	-5.72	47.37	41.65	46.00	-4.35	QP
5	531.2910	-2.04	45.33	43.29	46.00	-2.71	QP
6	558.0787	-1.52	44.57	43.05	46.00	-2.95	QP

The test result is calculated as the following:

- (4) Result = Reading + Correct Factor
- (5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (6) Margin = Result - Limit

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5745MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.0000	-20.05	51.83	31.78	40.00	-8.22	QP
2	395.5071	-3.72	40.84	37.12	46.00	-8.88	QP
3	535.0377	0.03	36.28	36.31	46.00	-9.69	QP
4	693.9101	1.38	35.98	37.36	46.00	-8.64	QP
5	793.0281	2.32	39.91	42.23	46.00	-3.77	QP
6	952.0001	4.32	37.15	41.47	46.00	-4.53	QP


The test result is calculated as the following:

- (4) Result = Reading + Correct Factor
- (5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (6) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 1000MHz – 18000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5745MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1268.056	-12.85	49.99	37.14	74.00	-36.86	peak
2	1275.423	-12.81	39.10	26.29	54.00	-27.71	AVG
3	1764.113	-13.68	51.49	37.81	74.00	-36.19	peak
4	1784.669	-13.83	37.25	23.42	54.00	-30.58	AVG
5	2454.225	-11.80	52.63	40.83	74.00	-33.17	peak
6	2482.821	-11.41	35.40	23.99	54.00	-30.01	AVG
7	5750.479	-7.03	82.02	74.99	74.00	0.99	peak
8	5885.269	-6.50	33.59	27.09	54.00	-26.91	AVG
9	14031.456	4.28	43.99	48.27	74.00	-25.73	peak
10	14194.951	2.89	29.20	32.09	54.00	-21.91	AVG
11	17689.916	5.71	45.20	50.91	74.00	-23.09	peak
12	17792.679	5.85	32.70	38.55	54.00	-15.45	AVG


Note: Markers 7 is the intentional frequency from EUT, Hence considered as pass.

The test result is calculated as the following:

- (4) Result = Reading + Correct Factor
- (5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (6) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5745MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2454.225	-11.80	53.14	41.34	74.00	-32.66	peak
2	2482.821	-11.41	34.92	23.51	54.00	-30.49	AVG
3	5750.479	-7.03	90.67	83.64	74.00	9.64	peak
4	5817.483	-6.91	32.66	25.75	54.00	-28.25	AVG
5	7682.150	-3.90	47.11	43.21	74.00	-30.79	peak
6	7726.777	-3.92	34.51	30.59	54.00	-23.41	AVG
7	11456.648	-1.63	45.66	44.03	74.00	-29.97	peak
8	11523.201	-1.64	30.25	28.61	54.00	-25.39	AVG
9	14031.456	4.28	44.05	48.33	74.00	-25.67	peak
10	14112.966	3.70	30.89	34.59	54.00	-19.41	AVG
11	17689.916	5.71	45.50	51.21	74.00	-22.79	peak
12	17792.679	5.85	32.49	38.34	54.00	-15.66	AVG

Note: Markers 3 is the intentional frequency from EUT, Hence considered as pass.

The test result is calculated as the following:

(4) Result = Reading + Correct Factor


(5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator

(6) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 18000MHz – 26500 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5745MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18452.038	-15.76	44.49	28.73	74.00	-45.27	peak
2	18466.346	-15.76	32.16	16.40	54.00	-37.60	AVG
3	19693.387	-16.54	42.23	25.69	74.00	-48.31	peak
4	19723.940	-16.58	29.71	13.13	54.00	-40.87	AVG
5	21181.792	-15.85	40.71	24.86	74.00	-49.14	peak
6	21198.216	-15.84	29.25	13.41	54.00	-40.59	AVG
7	22589.268	-14.84	40.32	25.48	74.00	-48.52	peak
8	22606.784	-14.85	28.41	13.56	54.00	-40.44	AVG
9	24108.947	-13.98	41.08	27.10	74.00	-46.90	peak
10	24165.072	-14.03	28.58	14.55	54.00	-39.45	AVG
11	25413.729	-13.57	41.43	27.86	74.00	-46.14	peak
12	25453.156	-13.49	29.24	15.75	54.00	-38.25	AVG

The test result is calculated as the following:


(4) Result = Reading + Correct Factor

(5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator

(6) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5745MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	25532.193	-13.44	41.32	27.88	74.00	-46.12	peak
2	26072.151	-14.25	42.42	28.17	74.00	-45.83	peak
3	24146.349	-14.02	41.44	27.42	74.00	-46.58	peak
4	22554.277	-14.83	39.73	24.90	74.00	-49.10	peak
5	21165.381	-15.87	41.78	25.91	74.00	-48.09	peak
6	19693.387	-16.54	43.17	26.63	74.00	-47.37	peak
7	19723.940	-16.58	30.00	13.42	54.00	-40.58	AVG
8	21198.216	-15.84	29.25	13.41	54.00	-40.59	AVG
9	22606.784	-14.85	28.41	13.56	54.00	-40.44	AVG
10	24183.810	-14.05	28.06	14.01	54.00	-39.99	AVG
11	25571.803	-13.51	29.54	16.03	54.00	-37.97	AVG
12	26132.846	-14.22	28.41	14.19	54.00	-39.81	AVG


The test result is calculated as the following:

- (4) Result = Reading + Correct Factor
- (5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (6) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 26500MHz – 40000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5745MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	28014.687	0.73	37.58	38.31	74.00	-35.69	peak
2	28083.981	0.75	26.75	27.50	54.00	-26.50	AVG
3	30519.620	1.37	42.58	43.95	74.00	-30.05	peak
4	30557.341	1.38	31.00	32.38	54.00	-21.62	AVG
5	31554.627	1.56	43.53	45.09	74.00	-28.91	peak
6	31593.628	1.57	33.02	34.59	54.00	-19.41	AVG
7	34136.308	1.98	32.31	34.29	54.00	-19.71	AVG
8	34164.430	1.99	43.67	45.66	74.00	-28.34	peak
9	35264.917	2.15	36.78	38.93	54.00	-15.07	AVG
10	35352.144	2.17	44.24	46.41	74.00	-27.59	peak
11	37930.885	2.62	48.17	50.79	74.00	-23.21	peak
12	37977.766	2.63	37.79	40.42	54.00	-13.58	AVG

The test result is calculated as the following:

- (4) Result = Reading + Correct Factor
- (5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (6) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5745MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	27807.832	0.67	37.81	38.48	74.00	-35.52	peak
2	27807.832	0.67	26.10	26.77	54.00	-27.23	AVG
3	30207.081	1.31	39.90	41.21	74.00	-32.79	peak
4	30207.081	1.31	28.19	29.50	54.00	-24.50	AVG
5	33166.494	1.84	29.68	31.52	54.00	-22.48	AVG
6	33207.487	1.84	42.09	43.93	74.00	-30.07	peak
7	35909.610	2.28	48.32	50.60	74.00	-23.40	peak
8	35924.399	2.28	35.84	38.12	54.00	-15.88	AVG
9	37449.820	2.55	35.49	38.04	54.00	-15.96	AVG
10	37465.242	2.55	47.58	50.13	74.00	-23.87	peak
11	38656.134	2.74	49.23	51.97	74.00	-22.03	peak
12	38672.053	2.74	38.00	40.74	54.00	-13.26	AVG

The test result is calculated as the following:

(4) Result = Reading + Correct Factor


(5) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator

(6) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 30M – 1000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE) FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5825MHz		




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.2115	-21.84	59.37	37.53	40.00	-2.47	QP
2	50.8171	-14.33	52.14	37.81	40.00	-2.19	QP
3	51.5363	-14.37	49.09	34.72	40.00	-5.28	QP
4	53.0056	-14.46	48.65	34.19	40.00	-5.81	QP
5	54.5165	-14.55	49.61	35.06	40.00	-4.94	QP
6	398.2961	-5.65	45.75	40.10	46.00	-5.90	QP

The test result is calculated as the following:

- (7) Result = Reading + Correct Factor
- (8) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (9) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8x14
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5825MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.0000	-20.05	52.67	32.62	40.00	-7.38	QP
2	67.3109	-15.90	46.92	31.02	40.00	-8.98	QP
3	395.5071	-3.72	41.17	37.45	46.00	-8.55	QP
4	723.7930	1.62	35.00	36.62	46.00	-9.38	QP
5	793.0281	2.32	38.10	40.42	46.00	-5.58	QP
6	952.0001	4.32	36.85	41.17	46.00	-4.83	QP


The test result is calculated as the following:

- (7) Result = Reading + Correct Factor
- (8) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (9) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 1000MHz – 18000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5825MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1268.056	-12.85	49.98	37.13	74.00	-36.87	peak
2	1275.423	-12.81	39.50	26.69	54.00	-27.31	AVG
3	1571.140	-15.40	51.73	36.33	74.00	-37.67	peak
4	1580.267	-15.29	37.83	22.54	54.00	-31.46	AVG
5	1969.348	-12.99	51.21	38.22	74.00	-35.78	peak
6	2003.868	-12.69	37.44	24.75	54.00	-29.25	AVG
7	2869.689	-11.10	49.61	38.51	74.00	-35.49	peak
8	2886.360	-10.72	36.09	25.37	54.00	-28.63	AVG
9	3992.296	-6.94	45.69	38.75	74.00	-35.25	peak
10	4062.276	-8.08	34.01	25.93	54.00	-28.07	AVG
11	5817.483	-6.91	82.67	75.76	74.00	1.76	peak
12	5885.269	-6.50	33.40	26.90	54.00	-27.10	AVG

Note: Markers 11s is the intentional frequency from EUT, Hence considered as pass.

The test result is calculated as the following:


(7) Result = Reading + Correct Factor

(8) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator

(9) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8x14
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5825MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1275.423	-12.81	49.48	36.67	74.00	-37.33	peak
2	1275.423	-12.81	38.28	25.47	54.00	-28.53	AVG
3	1694.016	-13.35	49.06	35.71	74.00	-38.29	peak
4	1713.754	-13.33	37.62	24.29	54.00	-29.71	AVG
5	2454.225	-11.80	51.51	39.71	74.00	-34.29	peak
6	2497.244	-11.22	35.12	23.90	54.00	-30.10	AVG
7	4015.488	-7.17	45.71	38.54	74.00	-35.46	peak
8	4062.276	-8.08	34.01	25.93	54.00	-28.07	AVG
9	5817.483	-6.91	90.71	83.80	74.00	9.80	peak
10	5885.269	-6.50	33.30	26.80	54.00	-27.20	AVG
11	14031.456	4.28	43.36	47.64	74.00	-26.36	peak
12	14112.966	3.70	31.15	34.85	54.00	-19.15	AVG

Note: Markers 9 is the intentional frequency from EUT, Hence considered as pass.

The test result is calculated as the following:

(7) Result = Reading + Correct Factor


(8) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator

(9) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 18000MHz – 26500 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5825MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	20360.811	-16.39	42.39	26.00	74.00	-48.00	peak
2	20392.399	-16.33	29.70	13.37	54.00	-40.63	AVG
3	21165.381	-15.87	41.12	25.25	74.00	-48.75	peak
4	21181.792	-15.85	29.55	13.70	54.00	-40.30	AVG
5	22676.982	-14.88	40.31	25.43	74.00	-48.57	peak
6	22729.774	-14.91	25.55	10.64	54.00	-43.36	AVG
7	24108.947	-13.98	40.96	26.98	74.00	-47.02	peak
8	24127.641	-13.99	29.54	15.55	54.00	-38.45	AVG
9	25413.729	-13.57	42.07	28.50	74.00	-45.50	peak
10	25433.435	-13.53	29.39	15.86	54.00	-38.14	AVG
11	26031.765	-14.28	42.67	28.39	74.00	-45.61	peak
12	26051.950	-14.26	29.70	15.44	54.00	-38.56	AVG

The test result is calculated as the following:


(7) Result = Reading + Correct Factor

(8) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator

(9) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5825MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18509.335	-15.80	45.33	29.53	74.00	-44.47	peak
2	18523.687	-15.79	32.28	16.49	54.00	-37.51	AVG
3	21165.381	-15.87	41.20	25.33	74.00	-48.67	peak
4	21165.381	-15.87	29.70	13.83	54.00	-40.17	AVG
5	22589.268	-14.84	41.66	26.82	74.00	-47.18	peak
6	22624.313	-14.87	28.59	13.72	54.00	-40.28	AVG
7	22853.434	-14.97	40.99	26.02	74.00	-47.98	peak
8	22871.154	-14.99	28.06	13.07	54.00	-40.93	AVG
9	25532.193	-13.44	41.85	28.41	74.00	-45.59	peak
10	25551.990	-13.47	29.84	16.37	54.00	-37.63	AVG
11	25830.774	-13.99	42.40	28.41	74.00	-45.59	peak
12	25890.908	-14.10	29.25	15.15	54.00	-38.85	AVG


The test result is calculated as the following:

- (7) Result = Reading + Correct Factor
- (8) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (9) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

TEST RESULTS (Between 26500MHz – 40000 MHz)

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Vertical	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5825MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	27398.691	0.57	26.94	27.51	54.00	-26.49	AVG
2	27409.975	0.57	38.85	39.42	74.00	-34.58	peak
3	29348.896	1.10	27.96	29.06	54.00	-24.94	AVG
4	29373.074	1.11	40.79	41.90	74.00	-32.10	peak
5	30860.794	1.44	46.02	47.46	74.00	-26.54	peak
6	30873.503	1.44	31.77	33.21	54.00	-20.79	AVG
7	33344.495	1.87	43.82	45.69	74.00	-28.31	peak
8	33371.965	1.88	31.00	32.88	54.00	-21.12	AVG
9	35264.917	2.15	36.78	38.93	54.00	-15.07	AVG
10	35279.440	2.16	46.81	48.97	74.00	-25.03	peak
11	39023.943	2.79	40.91	43.70	54.00	-10.30	AVG
12	39072.175	2.81	51.61	54.42	74.00	-19.58	peak

The test result is calculated as the following:


(7) Result = Reading + Correct Factor

(8) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator

(9) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	25.4 °C	Relative Humidity:	53%
Distance:	3m	Test Power:	AC 110V/60Hz
Polarization:	Horizontal	Test Result:	Pass
Standard:	(RE)FCC PART 15E	Tested By:	Aman
Test Mode:	Keeping TX mode at 5825MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	27443.852	0.57	37.00	37.57	74.00	-36.43	peak
2	27466.461	0.59	26.53	27.12	54.00	-26.88	AVG
3	29799.426	1.22	28.02	29.24	54.00	-24.76	AVG
4	29836.257	1.23	39.87	41.10	74.00	-32.90	peak
5	33057.427	1.82	41.68	43.50	74.00	-30.50	peak
6	33071.041	1.82	30.75	32.57	54.00	-21.43	AVG
7	34774.684	2.08	44.15	46.23	74.00	-27.77	peak
8	34817.664	2.08	33.02	35.10	54.00	-18.90	AVG
9	36990.083	2.47	46.20	48.67	74.00	-25.33	peak
10	36990.083	2.47	34.89	37.36	54.00	-16.64	AVG
11	39233.380	2.83	37.27	40.10	54.00	-13.90	AVG
12	39249.537	2.83	48.57	51.40	74.00	-22.60	peak

The test result is calculated as the following:

- (7) Result = Reading + Correct Factor
- (8) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (9) Margin = Result - Limit

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor.

Average measurement was not performed if peak level lower than average limit.


No any other emissions level very low which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

9. POWER LINE CONDUCTED EMISSION

9.1. Block diagram of test setup



9.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

9.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

9.4. Test Result


PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “-----” means peak detection; “-----” means average detection

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	24.5 °C	Relative Humidity:	52%
Probe:	Line	Test Power:	AC 110V/60Hz
Test Mode:	TX	Test Result:	Pass
Standard:	(CE)FCC PART 15 E_QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1814	46.04	12.12	58.16	64.42	-6.26	QP
2		0.1814	30.91	12.12	43.03	54.42	-11.39	AVG
3		1.1532	40.76	11.00	51.76	56.00	-4.24	QP
4		1.1532	28.01	11.00	39.01	46.00	-6.99	AVG
5		1.4414	39.18	11.00	50.18	56.00	-5.82	QP
6		1.4637	21.69	11.00	32.69	46.00	-13.31	AVG
7		3.8309	39.48	11.13	50.61	56.00	-5.39	QP
8		3.8309	31.82	11.13	42.95	46.00	-3.05	AVG
9		22.2672	42.04	11.68	53.72	60.00	-6.28	QP
10		22.2672	36.11	11.68	47.79	50.00	-2.21	AVG
11		29.2152	42.59	12.36	54.95	60.00	-5.05	QP
12	*	29.2152	35.67	12.36	48.03	50.00	-1.97	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = (LISN, ISN, PLC or Current Probe) Factor + Cable Loss + Attenuator
- (3) Margin = Result - Limit

Report No.: AAEMT/RF/230604-01-03

EUT:	IO 5 GHz 2 Gbps UBR with Integrated Antenna (27 dBi)	Model Name. :	ion8xl4
Temperature:	24.5 °C	Relative Humidity:	52%
Probe:	Neutral	Test Power:	AC 110V/60Hz
Test Mode:	TX	Test Result:	Pass
Standard:	(CE)FCC PART 15 E_QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1814	48.06	11.92	59.98	64.42	-4.44	QP
2		0.1814	31.63	11.92	43.55	54.42	-10.87	AVG
3		0.4243	39.54	10.77	50.31	57.36	-7.05	QP
4		0.4243	28.95	10.77	39.72	47.36	-7.64	AVG
5	*	1.1532	41.22	10.90	52.12	56.00	-3.88	QP
6		1.1532	28.72	10.90	39.62	46.00	-6.38	AVG
7		3.2820	39.18	10.96	50.14	56.00	-5.86	QP
8		3.3540	24.84	10.96	35.80	46.00	-10.20	AVG
9		4.3125	37.08	10.97	48.05	56.00	-7.95	QP
10		4.3125	25.67	10.97	36.64	46.00	-9.36	AVG
11		29.4540	41.50	11.15	52.65	60.00	-7.35	QP
12		29.6923	33.94	11.15	45.09	50.00	-4.91	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = (LISN, ISN, PLC or Current Probe) Factor + Cable Loss + Attenuator
- (3) Margin = Result – Limit

10. CONDUCTED SPURIOUS EMISSIONS

Test Requirement:

FCC Part 15 C section 15.407

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Test Method:


ANSI C63.10: Clause 12.7

Test Status:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Pre-test the EUT under 2 modes: power-supplied by using the AC adapter and power-supplied by using internal battery. After pre-testing, we found the worst case is the test mode of EUT power-supplied by using internal battery.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.

Report No.: AAEMT/RF/230604-01-03

Result plot as follows:

Antenna 0:



