

Radio Test Report

FCC ID: 2AZTZ-OT55A0KAGC

Original Grant

Report No. : TB-FCC183311
Applicant : Kontech Electronics Co., Ltd.
Equipment Under Test (EUT)
EUT Name : OUTDOOR TV
Model No. : OT55A0KAGC
Series Model No. : Please Refer To Page 5
Brand Name : SYLVOX, ZINVAX, MISTAAD, GOTHOT, VUESTATION, KONTECH
Sample ID : 20210407-13-1#& 20210407-13-2#
Receipt Date : 2021-04-14
Test Date : 2021-04-14 to 2021-08-17
Issue Date : 2021-08-17
Standards : FCC Part 15 Subpart C 15.247
Test Method : ANSI C63.10: 2013
KDB 558074 D01 15.247 Meas Guidance v05r02
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above.

Witness Engineer : *Camille Li* Camille Li
Engineer Supervisor : *Ivan Su* Ivan Su
Engineer Manager : *Ray Lai* Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT.....	5
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test)	5
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units	7
1.6 Description of Test Software Setting	8
1.7 Measurement Uncertainty	8
1.8 Test Facility	9
2. TEST SUMMARY.....	10
3. TEST SOFTWARE.....	10
4. TEST EQUIPMENT.....	11
5. CONDUCTED EMISSION TEST	12
5.1 Test Standard and Limit.....	12
5.2 Test Setup.....	12
5.3 Test Procedure.....	12
5.4 Deviation From Test Standard.....	13
5.5 EUT Operating Mode	13
5.6 Test Data.....	13
6. RADIATED AND CONDUCTED UNWANTED EMISSIONS.....	14
6.1 Test Standard and Limit.....	14
6.2 Test Setup.....	14
6.3 Test Procedure.....	16
6.4 Deviation From Test Standard.....	17
6.5 EUT Operating Mode	17
6.6 Test Data.....	17
7. RESTRICTED BANDS REQUIREMENT	18
7.1 Test Standard and Limit.....	18
7.2 Test Setup.....	18
7.3 Test Procedure.....	19
7.4 Deviation From Test Standard.....	20
7.5 EUT Operating Mode	20
7.6 Test Data.....	20
8. BANDWIDTH TEST.....	21
8.1 Test Standard and Limit.....	21
8.2 Test Setup.....	21
8.3 Test Procedure.....	21
8.4 Deviation From Test Standard.....	22
8.5 EUT Operating Mode	22
8.6 Test Data.....	22

9. PEAK OUTPUT POWER	23
9.1 Test Standard and Limit.....	23
9.2 Test Setup.....	23
9.3 Test Procedure.....	23
9.4 Deviation From Test Standard.....	23
9.5 EUT Operating Mode	23
9.6 Test Data.....	23
10. POWER SPECTRAL DENSITY.....	24
10.1 Test Standard and Limit	24
10.2 Test Setup.....	24
10.3 Test Procedure.....	24
10.4 Deviation From Test Standard.....	24
10.5 Antenna Connected Construction	24
10.6 Test Data.....	24
11. ANTENNA REQUIREMENT.....	25
11.1 Test Standard and Limit	25
11.2 Deviation From Test Standard.....	25
11.3 Antenna Connected Construction	25
11.4 Test Data.....	25
ATTACHMENT A-- CONDUCTED EMISSION TEST DATA	26
ATTACHMENT B--UNWANTED EMISSIONS DATA	28

Revision History

1. General Information about EUT

1.1 Client Information

Applicant	:	Kontech Electronics Co., Ltd.
Address	:	No.30, Langkou Industrial Park, Dalang Street, Longhua New District, Shenzhen, Guangdong, China
Manufacturer	:	Kontech Electronics Co., Ltd.
Address	:	No.30, Langkou Industrial Park, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	OUTDOOR TV
Models No.	:	OT55A0KAGC, OT43#*####, OQ43#*####, OT55#*####, OQ55#*####, OT65#*####, OQ65#*####, OT75#*####, OQ75#*#### (# stands for letters A-Z; * stands for numbers 0-9)
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is size and color.
Brand Name	:	SYLVOX, ZINVAX, MISTAAD, GOTHOT, VUESTATION, KONTECH
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels 802.11n(HT40): 7 channels
	Antenna Gain:	Chain 1: PIFA antenna, 2.00dBi (Max.) Chain 2: PIFA antenna, 2.00dBi (Max.) The Directional Gain is 5.01dBi
	Modulation Type:	802.11b:DSSS(CCK, DQPSK, DBPSK) 802.11g/n:OFDM(BPSK,QPSK,16QAM,64 QAM)
	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n: up to 150Mbps
Power Rating	:	Input: 100-240Vac, 50/60Hz, 4A Max
Software Version	:	N/A
Hardware Version	:	N/A
Remark:		
(1) The antenna gain and adapter provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.		
(2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		
(3) Antenna information provided by the applicant.		

(4) Channel List:


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

Note: CH 01~CH 11 for 802.11b/g/n(HT20)


CH 03~CH 09 for 802.11n(HT40)

1.3 Block Diagram Showing the Configuration of System Tested

Conducted Test



Radiated Test



1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used “√”
Adapter	----	----	----	√
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	Yes	NO	0.4M	Accessory

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Emission Test	
Final Test Mode	Description
Mode 1	Charging with TX b Mode Channel 01
For Radiated and RF Conducted Test	
Final Test Mode	Description
Mode 2	TX Mode b Mode Channel 01/06/11
Mode 3	TX Mode g Mode Channel 01/06/11
Mode 4	TX Mode n(HT20) Mode Channel 01/06/11
Mode 5	TX Mode n(HT40) Mode Channel 03/06/09

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

802.11b Mode: CCK

802.11g Mode: OFDM

802.11n (HT20) Mode: MCS 0

802.11n (HT40) Mode: MCS 0

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.

- (3) The EUT is considered a Mobile device; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

Test Software: MT7603U_QA_Tool			
	Test Mode: Continuously transmitting		
Mode	Data Rate	Channel	Parameters
802.11b	CCK/ 1Mbps	01	20
	CCK/ 1Mbps	06	20
	CCK/ 1Mbps	11	20
802.11g	OFDM/ 6Mbps	01	16
	OFDM/ 6Mbps	06	14
	OFDM/ 6Mbps	11	14
802.11n(HT20)	MCS 0	01	14
	MCS 0	06	14
	MCS 0	11	14
802.11n(HT40)	MCS 0	03	9
	MCS 0	06	9
	MCS 0	09	9

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.50 dB ± 3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F.,Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.

2. Test Summary

Standard Section	Test Item	Test Sample(s)	Judgment	Remark
FCC				
FCC 15.207(a)	Conducted Emission	20210407-13-1#	PASS	N/A
FCC 15.209 & 15.247(d)	Radiated Unwanted Emissions	20210407-13-1#	PASS	N/A
FCC 15.203	Antenna Requirement	20210407-13-2#	PASS	N/A
FCC 15.247(a)(2)	6dB Bandwidth	20210407-13-2#	PASS	N/A
/	99% Occupied bandwidth	20210407-13-2#	PASS	N/A
FCC 15.247(b)(3)	Peak Output Power and E.I.R.P	20210407-13-2#	PASS	N/A
FCC 15.247(e)	Power Spectral Density	20210407-13-2#	PASS	N/A
FCC 15.247(d)	Band Edge Measurements	20210407-13-2#	PASS	N/A
FCC 15.207(a)	Conducted Unwanted Emissions	20210407-13-2#	PASS	N/A
FCC 15.247(d)	Emissions in Restricted Bands	20210407-13-2#	PASS	N/A
/	On Time and Duty Cycle	20210407-13-2#	/	N/A

Note: N/A is an abbreviation for Not Applicable.

3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE
RF Conducted Measurement	MTS-8310	MWRFtest	V2.0.0.0
RF Test System	JS1120	Tonscend	V2.6.88.0336

4. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 02, 2021	Jul. 01, 2022
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 02, 2021	Jul. 01, 2022
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 02, 2021	Jul. 01, 2022
LISN	Rohde & Schwarz	ENV216	101131	Jul. 02, 2021	Jul. 01, 2022
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 02, 2021	Jul. 01, 2022
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 02, 2021	Jul. 01, 2022
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jul. 02, 2021	Jul. 01, 2022
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.01, 2020	Feb. 28, 2022
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.01, 2020	Feb. 28, 2022
Horn Antenna	ETS-LINDGREN	BBHA 9170	BBHA9170582	Mar.01, 2020	Feb. 28, 2022
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 06, 2021	Jul. 05, 2022
Pre-amplifier	Sonoma	310N	185903	Feb. 25, 2021	Feb. 24, 2022
Pre-amplifier	HP	8449B	3008A00849	Feb. 25, 2021	Feb. 24, 2022
Pre-amplifier	SKET	LNPA_1840G-50	SK201904032	Feb. 25, 2021	Feb. 24, 2022
Cable	HUBER+SUHNER	100	SUCOFLEX	Feb. 25, 2021	Feb. 24, 2022
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 02, 2021	Jul. 01, 2022
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jul. 02, 2021	Jul. 01, 2022
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 11, 2020	Sep. 10, 2021
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 11, 2020	Sep. 10, 2021
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 11, 2020	Sep. 10, 2021
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 11, 2020	Sep. 10, 2021
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 11, 2020	Sep. 10, 2021
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 11, 2020	Sep. 10, 2021
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 11, 2020	Sep. 10, 2021

5. Conducted Emission Test

5.1 Test Standard and Limit


5.1.1 Test Standard

FCC Part 15.207

5.1.2 Test Limit

Frequency	Maximum RF Line Voltage (dBμV)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

5.2 Test Setup



5.3 Test Procedure

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- The bandwidth of EMI test receiver is set at 9 kHz, and the test frequency band is from 0.15MHz to 30MHz.

5.4 Deviation From Test Standard

No deviation

5.5 EUT Operating Mode

Please refer to the description of test mode.

5.6 Test Data

Please refer to the Attachment A inside test report.

6. Radiated and Conducted Unwanted Emissions

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.209 & FCC Part 15.247(d)

6.1.2 Test Limit

General field strength limits at frequencies Below 30MHz		
Frequency (MHz)	Field Strength (microvolt/meter)**	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30

Note: 1, The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

General field strength limits at frequencies above 30 MHz		
Frequency (MHz)	Field strength (μ V/m at 3 m)	Measurement Distance (meters)
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

General field strength limits at frequencies Above 1000MHz		
Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54




Note:


- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

6.2 Test Setup

Radiated measurement





6.3 Test Procedure

---Radiated measurement

- The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- Testing frequency range 30MHz-1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection. Testing frequency range 9KHz-150Hz the measuring instrument use VBW=200Hz with Quasi-peak detection. Testing frequency range 9KHz-30MHz the measuring instrument use VBW=9kHz with Quasi-peak detection.
- Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- For the actual test configuration, please see the test setup photo.

--- Conducted measurement**● Reference level measurement**

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to ≥ 1.5 times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

● Emission level measurement

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

6.4 Deviation From Test Standard

No deviation

6.5 EUT Operating Mode

Please refer to the description of test mode.

6.6 Test Data

Radiated measurement please refer to the Attachment B inside test report.

Conducted measurement please refer to the Appendix C section 7.

7. Restricted Bands Requirement

7.1 Test Standard and Limit

7.1.1 Test Standard

FCC Part 15.205 & FCC Part 15.247(d)


7.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
2310 ~2390	74	54
2483.5 ~2500	74	54
	Peak (dBm) _{see 7.3 e)}	Average (dBm) _{see 7.3 e)}
2310 ~2390	-21.20	-41.20
2483.5 ~2500	-21.20	-41.20


Note: According the ANSI C63.10 11.12.2 antenna-port conducted measurements may also be used as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case emissions is required.

7.2 Test Setup

Radiated measurement



Conducted measurement



7.3 Test Procedure

---Radiated measurement

- Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- The Peak Value and average value both need to comply with applicable limit above 1 GHz.
- Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- For the actual test configuration, please see the test setup photo.

--- Conducted measurement

- a) Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 11.12.2.3 through 11.12.2.5 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP (see 11.12.2.6 for guidance on determining the applicable antenna gain).
- c) Add the appropriate maximum ground reflection factor to the EIRP (6 dB for frequencies ≤ 30 MHz; 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive; and 0 dB for frequencies > 1000 MHz).
- d) For MIMO devices, measure the power of each chain and sum the EIRP of all chains in linear terms (i.e., watts and mW).
- e) Convert the resultant EIRP to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log d + 104.8$$

where

E is the electric field strength in dBuV/m

EIRP is the equivalent isotropically radiated power in dBm

d is the specified measurement distance in m

f) Compare the resultant electric field strength level with the applicable regulatory limit.

g) Perform the radiated spurious emission test.

7.4 Deviation From Test Standard

No deviation

7.5 EUT Operating Mode

Please refer to the description of test mode.

7.6 Test Data

Remark: The test uses antenna-port conducted measurements as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements.

Please refer to the Appendix C section 8.

8. Bandwidth Test

8.1 Test Standard and Limit


8.1.1 Test Standard

FCC Part 15.205 & FCC Part 15.247(d)

8.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
-6dB bandwidth (DTS bandwidth)	≥ 500 KHz	2400~2483.5
99% occupied bandwidth	/	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

---DTS bandwidth

● The steps for the first option are as follows:

- a) Set RBW = 100 kHz.
- b) Set the VBW \geq [3*RBW].
- c) Detector = peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.

g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

---occupied bandwidth

● The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding

the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.

- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

8.4 Deviation From Test Standard

No deviation

8.5 EUT Operating Mode

Please refer to the description of test mode.

8.6 Test Data

Please refer to the Appendix C section 3&4.

9. Peak Output Power

9.1 Test Standard and Limit


9.1.1 Test Standard

FCC Part 15.247(b)(3)

9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	not exceed 1 W or 30dBm	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

- The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

9.4 Deviation From Test Standard

No deviation

9.5 EUT Operating Mode

Please refer to the description of test mode.

9.6 Test Data

Please refer to the Appendix C section 2.

10. Power Spectral Density

10.1 Test Standard and Limit


10.1.1 Test Standard

FCC Part 15.247(e)

10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

10.2 Test Setup



10.3 Test Procedure

- The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:
 - a) Set analyzer center frequency to DTS channel center frequency.
 - b) Set the span to 1.5 times the DTS bandwidth.
 - c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
 - d) Set the VBW $\geq [3 * \text{RBW}]$.
 - e) Detector = peak.
 - f) Sweep time = auto couple.
 - g) Trace mode = max hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum amplitude level within the RBW.
 - j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

10.4 Deviation From Test Standard

No deviation

10.5 Antenna Connected Construction

Please refer to the description of test mode.

10.6 Test Data

Please refer to the Appendix C section 5.

11. Antenna Requirement

11.1 Test Standard and Limit

11.1.1 Test Standard

FCC Part 15.203

11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

11.2 Deviation From Test Standard

No deviation

11.3 Antenna Connected Construction


The gains of the antenna used for transmitting is 2dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

11.4 Test Data

The EUT antenna is a PIFA Antenna. It complies with the standard requirement.


Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

Attachment A-- Conducted Emission Test Data

Temperature:	22.5°C	Relative Humidity:	42%					
Test Voltage:	AC 120V/60Hz							
Terminal:	Line							
Test Mode:	Mode 1							
Remark:	Only worse case is reported.							
								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dB	Detector	
1		0.1539	27.96	9.70	37.66	65.78	-28.12	QP
2		0.1539	13.38	9.70	23.08	55.78	-32.70	AVG
3	*	0.5500	30.54	9.70	40.24	56.00	-15.76	QP
4		0.5500	19.99	9.70	29.69	46.00	-16.31	AVG
5		1.3900	22.96	9.76	32.72	56.00	-23.28	QP
6		1.3900	12.05	9.76	21.81	46.00	-24.19	AVG
7		3.1060	21.45	9.90	31.35	56.00	-24.65	QP
8		3.1060	9.83	9.90	19.73	46.00	-26.27	AVG
9		10.2060	26.53	9.81	36.34	60.00	-23.66	QP
10		10.2060	13.65	9.81	23.46	50.00	-26.54	AVG
11		16.0220	22.61	10.00	32.61	60.00	-27.39	QP
12		16.0220	8.83	10.00	18.83	50.00	-31.17	AVG

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = QuasiPeak/Average (dBuV)-Limit (dBuV)



Attachment B--Unwanted Emissions Data

---Radiated Unwanted Emissions

9 KHz~30 MHz


From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB

Below the permissible value has no need to be reported.

30MHz~1GHz

Temperature:	23.9°C	Relative Humidity:	44%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	Mode 2		
Remark:	Only worse case is reported.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Over Detector
1		47.3255	45.93	-22.18	23.75	40.00	-16.25	peak
2	*	81.7833	48.78	-22.35	26.43	40.00	-13.57	peak
3		169.5990	44.31	-20.48	23.83	43.50	-19.67	peak
4		184.4898	46.21	-19.98	26.23	43.50	-17.27	peak
5		295.1469	42.32	-16.39	25.93	46.00	-20.07	peak
6		912.8620	34.24	-4.26	29.98	46.00	-16.02	peak

*:Maximum data x:Over limit !:over margin

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = QuasiPeak (dB μ V/m)-Limit QPK(dB μ V/m)

Temperature:	23.9 °C	Relative Humidity:	44%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	Mode 2		
Remark:	Only worse case is reported.		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		31.9546	44.96	-14.41	30.55	40.00	-9.45 peak
2		47.3255	55.93	-22.18	33.75	40.00	-6.25 peak
3	*	81.2117	57.75	-22.38	35.37	40.00	-4.63 peak
4		175.6516	51.07	-20.28	30.79	43.50	-12.71 peak
5		295.1469	40.26	-16.39	23.87	46.00	-22.13 peak
6	!	804.6028	46.37	-5.67	40.70	46.00	-5.30 peak

*:Maximum data x:Over limit !:over margin

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = QuasiPeak (dB μ V/m)-Limit QPK(dB μ V/m)

Above 1~26.5GHz

Temperature:	23.9°C	Relative Humidity:	44%																																			
Test Voltage:	AC 120V/60HZ																																					
Ant. Pol.	Horizontal																																					
Test Mode:	TX B Mode 2412MHz Antenna 1																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> <th style="text-align: center;">Detector</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">4823.936</td> <td style="text-align: center;">43.63</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">56.79</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-17.21</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">* 4823.966</td> <td style="text-align: center;">35.03</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">48.19</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-5.81</td> </tr> <tr> <td colspan="7" style="text-align: center;">AVG</td></tr> </tbody> </table>				No.	Mk.	Reading Level	Correct Factor	Measure-ment	Limit	Over	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	4823.936	43.63	13.16	56.79	74.00	-17.21	2	* 4823.966	35.03	13.16	48.19	54.00	-5.81	AVG						
No.	Mk.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																
1	4823.936	43.63	13.16	56.79	74.00	-17.21																																
2	* 4823.966	35.03	13.16	48.19	54.00	-5.81																																
AVG																																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1~26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit.																																						

Temperature:	23.9°C	Relative Humidity:	44%																																			
Test Voltage:	AC 120V/60HZ A																																					
Ant. Pol.	Vertical																																					
Test Mode:	TX B Mode 2412MHz Antenna 1																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> <th style="text-align: center;">Detector</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">4823.962</td> <td style="text-align: center;">42.82</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">55.98</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-18.02</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">* 4824.006</td> <td style="text-align: center;">34.47</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">47.63</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-6.37</td> </tr> <tr> <td colspan="7" style="text-align: center;">AVG</td></tr> </tbody> </table>				No.	Mk.	Reading Level	Correct Factor	Measure-ment	Limit	Over	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	4823.962	42.82	13.16	55.98	74.00	-18.02	2	* 4824.006	34.47	13.16	47.63	54.00	-6.37	AVG						
No.	Mk.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																
1	4823.962	42.82	13.16	55.98	74.00	-18.02																																
2	* 4824.006	34.47	13.16	47.63	54.00	-6.37																																
AVG																																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1~26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit.																																						

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Horizontal								
Test Mode:	TX B Mode 2437MHz Antenna 1								
Remark:									
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)									
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)									
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)									
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.									
5. No report for the emission which more than 20dB below the prescribed limit.									

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Vertical								
Test Mode:	TX B Mode 2437MHz Antenna 1								
Remark:									
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)									
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)									
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)									
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.									
5. No report for the emission which more than 20dB below the prescribed limit.									

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Horizontal								
Test Mode:	TX B Mode 2462MHz Antenna 1								
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
	MHz	dB _u V	dB/m	dB _u V/m	dB _u V/m	dB Detector			
1	4923.896	44.34	13.89	58.23	74.00	-15.77 peak			
2	*	32.94	13.89	46.83	54.00	-7.17 AVG			

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m) = Corr. (dB/m) + Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m) - Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Vertical								
Test Mode:	TX B Mode 2462MHz Antenna 1								
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
	MHz	dB _u V	dB/m	dB _u V/m	dB _u V/m	dB Detector			
1	4923.860	45.06	13.89	58.95	74.00	-15.05 peak			
2	*	37.08	13.89	50.97	54.00	-3.03 AVG			

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m) = Corr. (dB/m) + Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m) - Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9 °C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Horizontal								
Test Mode:	TX G Mode 2412MHz Antenna 1								
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			
1	*	4823.606	33.12	13.16	46.28	-7.72			
2		4823.826	41.09	13.16	54.25	AVG			
					-19.75	peak			

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9 °C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Vertical								
Test Mode:	TX G Mode 2412MHz Antenna 1								
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			
1	*	4824.262	34.61	13.16	47.77	-6.23			
2		4824.442	48.80	13.16	61.96	AVG			
					-12.04	peak			

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9°C		Relative Humidity:	44%																																	
Test Voltage:	AC 120V/60HZ																																				
Ant. Pol.	Horizontal																																				
Test Mode:	TX G Mode 2437MHz Antenna 1																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB/m</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td>4874.128</td> <td>41.88</td> <td>13.53</td> <td>55.41</td> <td>74.00</td> <td>-18.59 peak</td> </tr> <tr> <td>2</td> <td>*</td> <td>4874.450</td> <td>34.86</td> <td>13.53</td> <td>48.39</td> <td>54.00</td> <td>-5.61 AVG</td> </tr> </tbody> </table>						No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	1		4874.128	41.88	13.53	55.41	74.00	-18.59 peak	2	*	4874.450	34.86	13.53	48.39	54.00	-5.61 AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																														
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																														
1		4874.128	41.88	13.53	55.41	74.00	-18.59 peak																														
2	*	4874.450	34.86	13.53	48.39	54.00	-5.61 AVG																														
<p>Remark:</p> <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit. 																																					

Temperature:	23.9°C		Relative Humidity:	44%																																		
Test Voltage:	AC 120V/60HZ																																					
Ant. Pol.	Vertical																																					
Test Mode:	TX G Mode 2437MHz Antenna 1																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB/m</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td>4874.352</td> <td>48.43</td> <td>13.53</td> <td>61.96</td> <td>74.00</td> <td>-12.04 peak</td> </tr> <tr> <td>2</td> <td>*</td> <td>4874.378</td> <td>35.03</td> <td>13.53</td> <td>48.56</td> <td>54.00</td> <td>-5.44 AVG</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	1		4874.352	48.43	13.53	61.96	74.00	-12.04 peak	2	*	4874.378	35.03	13.53	48.56	54.00	-5.44 AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																															
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																															
1		4874.352	48.43	13.53	61.96	74.00	-12.04 peak																															
2	*	4874.378	35.03	13.53	48.56	54.00	-5.44 AVG																															
<p>Remark:</p> <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit. 																																						

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Horizontal								
Test Mode:	TX G Mode 2462MHz Antenna 1								
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			
1	4923.810	46.73	13.89	60.62	74.00	-13.38 peak			
2	*	32.26	13.89	46.15	54.00	-7.85 AVG			

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Vertical								
Test Mode:	TX G Mode 2462MHz Antenna 1								
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			
1	*	4924.404	35.68	13.89	49.57	54.00 -4.43 AVG			
2		4924.500	50.06	13.89	63.95	74.00 -10.05 peak			

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Horizontal								
Test Mode:	TX n(HT20) Mode 2412MHz Antenna 1+2								
No. Mk. Freq. Reading Level Correct Factor Measure-ment Limit Over									
		MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB	Detector	
1	*	4823.652	29.25	13.16	42.41	54.00	-11.59	AVG	
2		4824.340	43.35	13.16	56.51	74.00	-17.49	peak	

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Vertical								
Test Mode:	TX n(HT20) Mode 2412MHz Antenna 1+2								
No. Mk. Freq. Reading Level Correct Factor Measure-ment Limit Over									
		MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB	Detector	
1	*	4824.042	32.87	13.16	46.03	54.00	-7.97	AVG	
2		4824.332	48.01	13.16	61.17	74.00	-12.83	peak	

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Horizontal								
Test Mode:	TX n(HT20) Mode 2437MHz Antenna 1+2								
No. Mk. 1 2 *	Freq. 4873.710 4873.880	Reading Level 42.97 29.32	Correct Factor 13.53 13.53	Measure-ment 56.50 42.85	Limit 74.00 54.00	Over -17.50 -11.15 peak AVG			
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit.									

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Vertical								
Test Mode:	TX n(HT20) Mode 2437MHz Antenna 1+2								
No. Mk. 1 2 *	Freq. 4874.368 4874.432	Reading Level 48.65 32.85	Correct Factor 13.53 13.53	Measure-ment 62.18 46.38	Limit 74.00 54.00	Over -11.82 -7.62 peak AVG			
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit.									

Temperature:	23.9 °C		Relative Humidity:	44%																																					
Test Voltage:	AC 120V/60HZ																																								
Ant. Pol.	Horizontal																																								
Test Mode:	TX n(HT20) Mode 2462MHz Antenna 1+2																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB/m</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td>4923.834</td> <td>29.28</td> <td>13.89</td> <td>43.17</td> <td>54.00</td> <td>-10.83</td> <td>AVG</td> </tr> <tr> <td>2</td> <td></td> <td>4923.998</td> <td>42.72</td> <td>13.89</td> <td>56.61</td> <td>74.00</td> <td>-17.39</td> <td>peak</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	*	4923.834	29.28	13.89	43.17	54.00	-10.83	AVG	2		4923.998	42.72	13.89	56.61	74.00	-17.39	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																	
1	*	4923.834	29.28	13.89	43.17	54.00	-10.83	AVG																																	
2		4923.998	42.72	13.89	56.61	74.00	-17.39	peak																																	
<p>Remark:</p> <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit. 																																									

Temperature:	23.9 °C		Relative Humidity:	44%																																					
Test Voltage:	AC 120V/60HZ																																								
Ant. Pol.	Vertical																																								
Test Mode:	TX n(HT20) Mode 2462MHz Antenna 1+2																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB/m</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td>4924.232</td> <td>34.49</td> <td>13.89</td> <td>48.38</td> <td>54.00</td> <td>-5.62</td> <td>AVG</td> </tr> <tr> <td>2</td> <td></td> <td>4924.426</td> <td>49.86</td> <td>13.89</td> <td>63.75</td> <td>74.00</td> <td>-10.25</td> <td>peak</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	*	4924.232	34.49	13.89	48.38	54.00	-5.62	AVG	2		4924.426	49.86	13.89	63.75	74.00	-10.25	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																	
1	*	4924.232	34.49	13.89	48.38	54.00	-5.62	AVG																																	
2		4924.426	49.86	13.89	63.75	74.00	-10.25	peak																																	
<p>Remark:</p> <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit. 																																									

Temperature:	23.9°C		Relative Humidity:	44%																																										
Test Voltage:	AC 120V/60HZ																																													
Ant. Pol.	Horizontal																																													
Test Mode:	TX n(HT40) Mode 2422MHz Antenna 1+2																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center; padding: 2px;">No.</th> <th style="text-align: center; padding: 2px;">Mk.</th> <th style="text-align: center; padding: 2px;">Freq.</th> <th style="text-align: center; padding: 2px;">Reading Level</th> <th style="text-align: center; padding: 2px;">Correct Factor</th> <th style="text-align: center; padding: 2px;">Measure-ment</th> <th style="text-align: center; padding: 2px;">Limit</th> <th style="text-align: center; padding: 2px;">Over</th> </tr> <tr> <th style="text-align: center; padding: 2px;"></th> <th style="text-align: center; padding: 2px;"></th> <th style="text-align: center; padding: 2px;">MHz</th> <th style="text-align: center; padding: 2px;">dBμV</th> <th style="text-align: center; padding: 2px;">dB/m</th> <th style="text-align: center; padding: 2px;">dBμV/m</th> <th style="text-align: center; padding: 2px;">dBμV/m</th> <th style="text-align: center; padding: 2px;">dB</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; padding: 2px;">1</td> <td style="text-align: center; padding: 2px;">*</td> <td style="text-align: center; padding: 2px;">4843.958</td> <td style="text-align: center; padding: 2px;">43.58</td> <td style="text-align: center; padding: 2px;">13.31</td> <td style="text-align: center; padding: 2px;">56.89</td> <td style="text-align: center; padding: 2px;">74.00</td> <td style="text-align: center; padding: 2px;">-17.11</td> </tr> <tr> <td style="text-align: center; padding: 2px;">2</td> <td style="text-align: center; padding: 2px;">*</td> <td style="text-align: center; padding: 2px;">4844.310</td> <td style="text-align: center; padding: 2px;">29.39</td> <td style="text-align: center; padding: 2px;">13.31</td> <td style="text-align: center; padding: 2px;">42.70</td> <td style="text-align: center; padding: 2px;">54.00</td> <td style="text-align: center; padding: 2px;">-11.30</td> </tr> <tr> <td style="text-align: center; padding: 2px;"></td> <td style="text-align: center; padding: 2px;">peak</td> <td style="text-align: center; padding: 2px;">AVG</td> </tr> </tbody> </table>	No.	Mk.	Freq.				Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB	1	*	4843.958	43.58	13.31	56.89	74.00	-17.11	2	*	4844.310	29.39	13.31	42.70	54.00	-11.30							peak	AVG			
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																							
		MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB																																							
1	*	4843.958	43.58	13.31	56.89	74.00	-17.11																																							
2	*	4844.310	29.39	13.31	42.70	54.00	-11.30																																							
						peak	AVG																																							
<p>Remark:</p> <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit. 																																														

Temperature:	23.9°C		Relative Humidity:	44%																																									
Test Voltage:	AC 120V/60HZ																																												
Ant. Pol.	Vertical																																												
Test Mode:	TX n(HT40) Mode 2422MHz Antenna 1+2																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center; padding: 2px;">No.</th> <th style="text-align: center; padding: 2px;">Mk.</th> <th style="text-align: center; padding: 2px;">Freq.</th> <th style="text-align: center; padding: 2px;">Reading Level</th> <th style="text-align: center; padding: 2px;">Correct Factor</th> <th style="text-align: center; padding: 2px;">Measure-ment</th> <th style="text-align: center; padding: 2px;">Limit</th> <th style="text-align: center; padding: 2px;">Over</th> </tr> <tr> <th style="text-align: center; padding: 2px;"></th> <th style="text-align: center; padding: 2px;"></th> <th style="text-align: center; padding: 2px;">MHz</th> <th style="text-align: center; padding: 2px;">dBμV</th> <th style="text-align: center; padding: 2px;">dB/m</th> <th style="text-align: center; padding: 2px;">dBμV/m</th> <th style="text-align: center; padding: 2px;">dBμV/m</th> <th style="text-align: center; padding: 2px;">dB</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; padding: 2px;">1</td> <td style="text-align: center; padding: 2px;">*</td> <td style="text-align: center; padding: 2px;">4844.106</td> <td style="text-align: center; padding: 2px;">44.21</td> <td style="text-align: center; padding: 2px;">13.31</td> <td style="text-align: center; padding: 2px;">57.52</td> <td style="text-align: center; padding: 2px;">74.00</td> <td style="text-align: center; padding: 2px;">-16.48</td> </tr> <tr> <td style="text-align: center; padding: 2px;">2</td> <td style="text-align: center; padding: 2px;">*</td> <td style="text-align: center; padding: 2px;">4844.114</td> <td style="text-align: center; padding: 2px;">30.24</td> <td style="text-align: center; padding: 2px;">13.31</td> <td style="text-align: center; padding: 2px;">43.55</td> <td style="text-align: center; padding: 2px;">54.00</td> <td style="text-align: center; padding: 2px;">peak</td> </tr> <tr> <td style="text-align: center; padding: 2px;"></td> <td style="text-align: center; padding: 2px;">AVG</td> </tr> </tbody> </table>	No.	Mk.	Freq.				Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB	1	*	4844.106	44.21	13.31	57.52	74.00	-16.48	2	*	4844.114	30.24	13.31	43.55	54.00	peak							AVG			
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																						
		MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB																																						
1	*	4844.106	44.21	13.31	57.52	74.00	-16.48																																						
2	*	4844.114	30.24	13.31	43.55	54.00	peak																																						
						AVG																																							
<p>Remark:</p> <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit. 																																													

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Horizontal								
Test Mode:	TX n(HT40) Mode 2437MHz Antenna 1+2								
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
	MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB			
1	4873.726	43.30	13.53	56.83	74.00	-17.17 peak			
2	* 4873.798	29.32	13.53	42.85	54.00	-11.15 AVG			

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9°C		Relative Humidity:	44%					
Test Voltage:	AC 120V/60HZ								
Ant. Pol.	Vertical								
Test Mode:	TX n(HT40) Mode 2437MHz Antenna 1+2								
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
	MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB			
1	* 4874.050	29.12	13.53	42.65	54.00	-11.35 AVG			
2	4874.332	42.88	13.53	56.41	74.00	-17.59 peak			

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9 °C		Relative Humidity:	44%																												
Test Voltage:	AC 120V/60HZ																															
Ant. Pol.	Horizontal																															
Test Mode:	TX n(HT40) Mode 2452MHz Antenna 1+2																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dB_uV</th> <th>dB/m</th> <th>dB_uV/m</th> <th>dB_uV/m</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td>4903.936</td> <td>42.90</td> <td>13.74</td> <td>56.64</td> <td>74.00</td> <td>-17.36 peak</td> </tr> <tr> <td>2</td> <td>*</td> <td>4904.284</td> <td>29.21</td> <td>13.75</td> <td>42.96</td> <td>54.00</td> <td>-11.04 AVG</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dB _u V	dB/m	dB _u V/m	dB _u V/m	dB	1		4903.936	42.90	13.74	56.64	74.00	-17.36 peak	2	*
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																									
		MHz	dB _u V	dB/m	dB _u V/m	dB _u V/m	dB																									
1		4903.936	42.90	13.74	56.64	74.00	-17.36 peak																									
2	*	4904.284	29.21	13.75	42.96	54.00	-11.04 AVG																									

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	23.9 °C		Relative Humidity:	44%																												
Test Voltage:	AC 120V/60HZ																															
Ant. Pol.	Vertical																															
Test Mode:	TX n(HT40) Mode 2452MHz Antenna 1+2																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dB_uV</th> <th>dB/m</th> <th>dB_uV/m</th> <th>dB_uV/m</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td>4903.538</td> <td>42.89</td> <td>13.74</td> <td>56.63</td> <td>74.00</td> <td>-17.37 peak</td> </tr> <tr> <td>2</td> <td>*</td> <td>4904.284</td> <td>29.38</td> <td>13.75</td> <td>43.13</td> <td>54.00</td> <td>-10.87 AVG</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dB _u V	dB/m	dB _u V/m	dB _u V/m	dB	1		4903.538	42.89	13.74	56.63	74.00	-17.37 peak	2	*
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																									
		MHz	dB _u V	dB/m	dB _u V/m	dB _u V/m	dB																									
1		4903.538	42.89	13.74	56.63	74.00	-17.37 peak																									
2	*	4904.284	29.38	13.75	43.13	54.00	-10.87 AVG																									

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

-----END OF REPORT-----