



FCC ID: 2AZUG-BJ608B

## 1. Limit for Portable Equipment Exposure

Frequency	1-g SAR
100MHz-6GHz	3.0

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093

For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

## 2. Estimation Result

Frequency (MHz)	PK Output Power(dBm)	Output Power(mW)	Test Separation Distance (mm)	Measurement Result	1-g SAR
433.92	-18.5	0.014	5	0.0018	3.0

**Note:**

1. use the maximum E-field strength(76.7dBuV/m) for the RF exposure evaluation
2.  $E(\text{dBuV/m}) = \text{EIRP}(\text{dBm}) - 95.2$  for distance 3m  
so the  $\text{EIRP} = 76.7 \text{dBuV/m} - 95.2 = -18.5 \text{dBm}$

-----The End-----