

RF Exposure Evaluation Report

Product : VOICE AMPLIFIER
Trade mark : 
Model/Type reference : S208,S209
Serial Number : N/A
Report Number : EED32N80260101
FCC ID : NA
Date of Issue : May 14, 2021
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Test result : PASS

Prepared for:

ShenZhen WinWin Technology Co.,LTD
327 Wisdom Innovation Center, Xixiang,BaoAn, Shenzhen China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385



Compiled by:

Tom Chen

Reviewed by:

Acron Ma

Approved by:

David Wang

Date:

May 14, 2021

David Wang

Check No.:8406220421

2 Version

Version No.	Date	Description
00	May 14, 2021	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 GENERAL DESCRIPTION OF BT CLASSIC.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 SAR EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 <i>Standard Requirement</i>	6
5.1.2 <i>EUT RF Exposure</i>	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	ShenZhen WinWin Technology Co.,LTD
Address of Applicant:	327 Wisdom Innovation Center, Xixiang,BaoAn, Shenzhen China
Manufacturer:	ShenZhen WinWin Technology Co.,LTD
Address of Manufacturer:	327 Wisdom Innovation Center, Xixiang,BaoAn, Shenzhen China
Factory:	ShenZhen WinWin Technology Co.,LTD
Address of Factory:	327 Wisdom Innovation Center, Xixiang,BaoAn, Shenzhen China

4.2 General Description of EUT

Product Name:	VOICE AMPLIFIER
Mode No.:	S208
Add Model No.:	S209
Trade mark:	
Power Supply:	DC3.7V 2000 mA (Li-on Rechargeable Battery)
Test Voltage:	DC 3.7V
Sample Received Date:	Apr. 22, 2021
Sample tested Date:	Apr. 22, 2021 to May. 07, 2021

Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

Model No.: S208,S209

Only the model S208 was tested.Their electrical circuit design, layout, components used and internal wiring are identical, except only the model name is different.

4.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	2.81dBi

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.2 EUT RF Exposure

1)For BT Classic

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-1.24	-1.5±1	0.5	1.122
Middle(2441MHz)	-4.43	-4.5±1	-3.5	0.447
Highest(2480MHz)	-7.76	-7.5±1	-6.5	0.224
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-1.34	-1.5±1	-0.5	0.891
Middle(2441MHz)	-4.7	-4.5±1	-3.5	0.447
Highest(2480MHz)	-8.14	-8.5±1	-7.5	0.178
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-1.31	-1.5±1	-0.5	0.891
Middle(2441MHz)	-4.72	-4.5±1	-3.5	0.447
Highest(2480MHz)	-7.9	-8.0±1	-7.0	0.200

Worst case:GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-1.24	-1.5±1	0.5	1.122	0.35	3.0
Middle (2441MHz)	-4.43	-4.5±1	-3.5	0.447	0.14	
Highest (2480MHz)	-7.76	-7.5±1	-6.5	0.224	0.07	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: EED32N80260101

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32N80260101 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***