

Dongzhen Electronics Co., Ltd

Shangpin Science and Technology Building, Xinjin Street, Longhu District, Shantou City

Antenna Specification for Approval

Customer Name:

Product Name: 2.4G antenna

Product Name:

Part NO.: 19PIN*0.12TC*OD1.35*60MM

Write By: Mr. zhou

Issued Date: 2022-10-8

customer:

R&D Dept	Business Dept	Approved By

supplier

R&D Dept	Engineer Dept	Approval

Product Specification

A. Electrical Characteristics

Frequency 2400MHz ~2500MHz

VSWR <3.0

Efficiency >26%

Impedance 50 Ohm

Gain 0.54DBi

Polarization mode:linear polarization

B. Material & Mechanical Characteristics

Material of Radiator Cu

Cable Type 1.4 white

Connector Type : NO

Dimension

C. Environmental

Operation Temperature - 30 °C ~ + 80 °C

Storage Temperature - 30 °C ~ + 85 °C

Test Equipment & Conditions



1. Network Analyzers :

Agilent 8753D 5071B

2. Communications Test Set:

Agilent E5515C

3. 3D Chamber Test System




Effiency&Gain


Freq (MHz)	Effi (%)	Gain (dBi)
2400	23. 32	0. 42
2410	23. 01	0. 33
2420	22. 53	0. 45
2430	22. 01	0. 37
2440	21. 17	0. 40
2450	25. 31	0. 48
2460	25. 42	0. 49
2470	26. 28	0. 54
2480	25. 87	0. 51
2490	24. 36	0. 48
2500	24. 53	0. 41

Radiation Pattern


2400.000MHz




2400.000MHz H




2400.000MHz E1




2400.000MHz E2




2450.000MHz




2450.000MHz H




2450.000MHz E1




2450.000MHz E2




2500.000MHz



2500.000MHz H



2500.000MHz E1



2500.000MHz E2

