

TEST REPORT

Applicant: SHANTOU CHENGHAI ZHONGYI TOY CO., LTD

Address of Applicant: 3/F BUILDING NO.7 SOUTH NING TAILIU RD WEST GATE
NEW AREA, CHENGHAI QU, SHANTOU, GUANGDONG,
China

Manufacturer: SHANTOU CHENGHAI ZHONGYI TOY CO., LTD

**Address of
Manufacturer:** 3/F BUILDING NO.7 SOUTH NING TAILIU RD WEST GATE
NEW AREA, CHENGHAI QU, SHANTOU, GUANGDONG,
China

Equipment Under Test (EUT)

Product Name: Remote control series

Model No.: 820, 821, 822, 823, 825, 826, 827, 828, 828A, 829, 830, 831,
832, 833, 835, 836, 837, 838, 838A, 839, 1203A, 1203B,
1203C, 1203D, 1203E, 1203F, 1203G, 1203H, 1203I, 1203J,
1203K, 1203L, 1203M, 1203N, 1203O, 1203P, 1203Q, 1203R,
1203S, 1203T, 1203U, 1203V, 1203W, 1203X, 1203Y, 1203Z,
Y878, 878D, cx-60, MX-08, T17

FCC ID: 2AZVK-ZY1203B

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: May 13, 2024

Date of Test: May 14-27, 2024

Date of report issued: May 28, 2024

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Luo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	May 28, 2024	Original

Prepared By:




Date:

May 28, 2024

Project Engineer

Check By:



Date:

May 28, 2024

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS.....	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
5.6 TEST FACILITY.....	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS.....	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT	10
7.2 RADIATED EMISSION METHOD	11
7.2.1 Field Strength of The Fundamental Signal	13
7.2.2 Spurious emissions.....	14
7.2.3 Bandedge emissions.....	22
7.3 20dB OCCUPY BANDWIDTH	26
8 TEST SETUP PHOTO.....	28
9 EUT CONSTRUCTIONAL DETAILS	28

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10:2013.
2. Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz-30MHz	3.1dB	(1)
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Remote control series
Model No.:	820, 821, 822, 823, 825, 826, 827, 828, 828A, 829, 830, 831, 832, 833, 835, 836, 837, 838, 838A, 839, 1203A, 1203B, 1203C, 1203D, 1203E, 1203F, 1203G, 1203H, 1203I, 1203J, 1203K, 1203L, 1203M, 1203N, 1203O, 1203P, 1203Q, 1203R, 1203S, 1203T, 1203U, 1203V, 1203W, 1203X, 1203Y, 1203Z, Y878, 878D, cx-60, MX-08, T17
Test Model No.:	1203B
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color and model name for commercial purpose.	
Serial No.:	6 971045 311658
Test sample(s) ID:	GTS2024050119-1
Sample(s) Status	Engineered sample
Operation Frequency:	2410MHz~2475MHz
Channel Numbers:	66
Modulation Type:	GFSK
Antenna Type:	PCB Antenna
Antenna gain:	0.54dBi(declare by applicant)
Power supply:	DC 3V(2*1.5V Size“AA” Battery)

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2410	18	2427	35	2444	52	2461
2	2411	19	2428	36	2445	53	2462
3	2412	20	2429	37	2446	54	2463
4	2413	21	2430	38	2447	55	2464
5	2414	22	2431	39	2448	56	2465
6	2415	23	2432	40	2449	57	2466
7	2416	24	2433	41	2450	58	2467
8	2417	25	2434	42	2451	59	2468
9	2418	26	2435	43	2452	60	2469
10	2419	27	2436	44	2453	61	2470
11	2420	28	2437	45	2454	62	2471
12	2421	29	2438	46	2455	63	2472
13	2422	30	2439	47	2456	64	2473
14	2423	31	2440	48	2457	65	2474
15	2424	32	2441	49	2458	66	2475
16	2425	33	2442	50	2459		
17	2426	34	2443	51	2460		

The test frequencies are below:

Channel	Frequency
The lowest channel	2410MHz
The middle channel	2440MHz
The Highest channel	2475MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: New battery is used during all test.	

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	98.25	99.63	97.14

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	June 23, 2021	June 22, 2024
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	April 11, 2024	April 10, 2025
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	March 19, 2023	March 18, 2025
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	April 17, 2023	April 16, 2025
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	April 11, 2024	April 10, 2025
8	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 13, 2023	Nov.12, 2024
9	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	April 11, 2024	April 10, 2025
10	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	April 11, 2024	April 10, 2025
11	Horn Antenna (18-26.5GHz)	/	UG-598A/U	GTS664	Oct. 29, 2023	Oct. 28, 2024
12	Horn Antenna (26.5-40GHz)	A.H Systems	SAS-573	GTS665	Oct. 29, 2023	Oct. 28, 2024
13	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	March 12, 2024	March 11, 2025
14	Amplifier	/	LNA-1000-30S	GTS650	April 11, 2024	April 10, 2025
15	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 08, 2023	Nov.07, 2024
16	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	April 11, 2024	April 10, 2025
17	Thermo meter	JINCHUANG	GSP-8A	GTS643	April 18, 2024	April 17, 2025
18	RE cable 1	GTS	N/A	GTS675	July 31. 2023	July 30. 2024
19	RE cable 2	GTS	N/A	GTS676	July 31. 2023	July 30. 2024
20	RE cable 3	GTS	N/A	GTS677	July 31. 2023	July 30. 2024
21	RE cable 4	GTS	N/A	GTS678	July 31. 2023	July 30. 2024
22	RE cable 5	GTS	N/A	GTS679	July 31. 2023	July 30. 2024
23	RE cable 6	GTS	N/A	GTS680	July 31. 2023	July 30. 2024
24	RE cable 7	GTS	N/A	GTS681	July 31. 2023	July 30. 2024
25	RE cable 8	GTS	N/A	GTS682	July 31. 2023	July 30. 2024

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	April 11, 2024	April 10, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 11, 2024	April 10, 2025
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	April 11, 2024	April 10, 2025
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	April 11, 2024	April 10, 2025
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	April 11, 2024	April 10, 2025
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	April 11, 2024	April 10, 2025
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	April 11, 2024	April 10, 2025
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	April 11, 2024	April 10, 2025
9	Thermo meter	JINCHUANG	GSP-8A	GTS641	April 18, 2024	April 17, 2025


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	April 18, 2024	April 17, 2025


7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is PCB antenna, reference to the appendix II for details.	

7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (uV/m)		Remark
	0.009MHz-0.490MHz		2400/F(kHz) @300m		Quasi-peak Value
	0.490MHz-1.705MHz		24000/F(kHz) @30m		Quasi-peak Value
	1.705MHz-30.0MHz		30 @30m		Quasi-peak Value
	30MHz-88MHz		100 @3m		Quasi-peak Value
	88MHz-216MHz		150 @3m		Quasi-peak Value
	216MHz-960MHz		200 @3m		Quasi-peak Value
	960MHz-1GHz		500 @3m		Quasi-peak Value
	Above 1GHz		500 @3m		Average Value
5000 @3m			Peak Value		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz  For radiated emissions from 30MHz to1GHz				



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments: Refer to section 6.0 for details

Test mode: Refer to section 5.2 for details

Test environment: Temp.: 25 °C Humid.: 52% Press.: 1012mbar

Test voltage: DC 3V

Test results: Pass

Measurement data:

7.2.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2410.00	98.68	27.43	4.57	38.56	92.12	114.00	-21.88	Vertical
2410.00	104.48	27.43	4.57	38.56	97.92	114.00	-16.08	Horizontal
2440.00	100.20	27.55	4.56	38.57	93.74	114.00	-20.26	Vertical
2440.00	106.09	27.55	4.56	38.57	99.63	114.00	-14.37	Horizontal
2475.00	95.83	27.64	4.55	38.58	89.44	114.00	-24.56	Vertical
2475.00	103.56	27.64	4.55	38.58	97.17	114.00	-16.83	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2410.00	87.26	27.43	4.57	38.56	80.70	94.00	-13.30	Vertical
2410.00	93.49	27.43	4.57	38.56	86.93	94.00	-7.07	Horizontal
2440.00	89.27	27.55	4.56	38.57	82.81	94.00	-11.19	Vertical
2440.00	94.85	27.55	4.56	38.57	88.39	94.00	-5.61	Horizontal
2475.00	85.30	27.64	4.55	38.58	78.91	94.00	-15.09	Vertical
2475.00	93.18	27.64	4.55	38.58	86.79	94.00	-7.21	Horizontal

Note: For fundamental frequency , RBW>20dB BW, VBW>=RBW, PK detector for PK value, RMS detector for AV value


7.2.2 Spurious emissions

■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


■ Below 1GHz

Pre-scan all test modes, found worst case at 2410MHz, and so only show the test result of it
Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
45.217	28.96	13.34	0.72	33.70	9.32	40.00	-30.68	QP
93.440	37.49	8.99	1.14	33.60	14.02	43.50	-29.48	QP
129.015	35.04	11.76	1.43	33.31	14.92	43.50	-28.58	QP
257.422	27.13	11.34	2.16	32.74	7.89	46.00	-38.11	QP
478.846	25.45	17.23	3.22	32.06	13.84	46.00	-32.16	QP
734.491	23.24	21.48	4.22	31.48	17.46	46.00	-28.54	QP


Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
45.217	43.07	13.34	0.72	33.70	23.43	40.00	-16.57	QP
93.768	37.94	9.03	1.14	33.60	14.51	43.50	-28.99	QP
116.950	33.73	10.99	1.34	33.42	12.64	43.50	-30.86	QP
321.061	28.97	13.18	2.47	32.61	12.01	46.00	-33.99	QP
519.065	25.24	17.95	3.39	31.96	14.62	46.00	-31.38	QP
682.348	24.93	20.55	4.02	31.63	17.87	46.00	-28.13	QP


■ Above 1GHz

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4820.000	41.92	31.90	7.29	38.36	42.75	54.00	-11.25	Average
4820.000	65.27	31.90	7.29	38.36	66.10	74.00	-7.90	Peak
7230.000	39.71	35.84	9.43	38.97	46.01	54.00	-7.99	Average
7230.000	53.88	35.84	9.43	38.97	60.18	74.00	-13.82	Peak
9640.000	35.43	38.26	10.03	39.69	44.03	54.00	-9.97	Average
9640.000	44.58	38.26	10.03	39.69	53.18	74.00	-20.82	Peak

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4820.000	40.80	31.90	7.29	38.36	41.63	54.00	-12.37	Average
4820.000	58.92	31.90	7.29	38.36	59.75	74.00	-14.25	Peak
7230.000	38.47	35.84	9.43	38.97	44.77	54.00	-9.23	Average
7230.000	50.21	35.84	9.43	38.97	56.51	74.00	-17.49	Peak
9640.000	34.98	38.26	10.03	39.69	43.58	54.00	-10.42	Average
9640.000	44.84	38.26	10.03	39.69	53.44	74.00	-20.56	Peak

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	41.55	32.04	7.04	38.38	42.25	54.00	-11.75	Average
4880.000	64.41	32.04	7.04	38.38	65.11	74.00	-8.89	Peak
7320.000	36.48	36.10	9.18	39.00	42.76	54.00	-11.24	Average
7320.000	51.20	36.10	9.18	39.00	57.48	74.00	-16.52	Peak
9760.000	32.09	38.30	10.27	39.73	40.93	54.00	-13.07	Average
9760.000	44.33	38.30	10.27	39.73	53.17	74.00	-20.83	Peak

Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	40.24	32.04	7.04	38.38	40.94	54.00	-13.06	Average
4880.000	59.00	32.04	7.04	38.38	59.70	74.00	-14.30	Peak
7320.000	36.44	36.10	9.18	39.00	42.72	54.00	-11.28	Average
7320.000	49.25	36.10	9.18	39.00	55.53	74.00	-18.47	Peak
9760.000	34.62	38.30	10.27	39.73	43.46	54.00	-10.54	Average
9760.000	43.82	38.30	10.27	39.73	52.66	74.00	-21.34	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4950.000	43.55	32.19	6.75	38.39	44.10	54.00	-9.90	Average
4950.000	63.42	32.19	6.75	38.39	63.97	74.00	-10.03	Peak
7425.000	39.29	36.39	9.00	39.03	45.65	54.00	-8.35	Average
7425.000	53.05	36.39	9.00	39.03	59.41	74.00	-14.59	Peak
9900.000	35.35	38.36	10.12	39.77	44.06	54.00	-9.94	Average
9900.000	45.25	38.36	10.12	39.77	53.96	74.00	-20.04	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4950.000	38.79	32.19	6.75	38.39	39.34	54.00	-14.66	Average
4950.000	56.46	32.19	6.75	38.39	57.01	74.00	-16.99	Peak
7425.000	35.13	36.39	9.00	39.03	41.49	54.00	-12.51	Average
7425.000	48.22	36.39	9.00	39.03	54.58	74.00	-19.42	Peak
9900.000	32.82	38.36	10.12	39.77	41.53	54.00	-12.47	Average
9900.000	43.67	38.36	10.12	39.77	52.38	74.00	-21.62	Peak


Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. For above 18GHz, no emission found.
4. If the average limit is met when using a Peak detector, the EUT shall be deemed to meet both peak and average limits. And measurement with the average detector is unnecessary.

7.2.3 Bandedge emissions


All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	34.80	26.81	4.60	38.52	27.69	54.00	-26.31	Average
2310.000	45.57	26.81	4.60	38.52	38.46	74.00	-35.54	Peak
2390.000	34.73	27.01	4.65	38.56	27.83	54.00	-26.17	Average
2390.000	47.98	27.01	4.65	38.56	41.08	74.00	-32.92	Peak
2394.840	53.26	27.03	4.66	38.56	46.39	54.00	-7.61	Average
2394.840	65.32	27.03	4.66	38.56	58.45	74.00	-15.55	Peak
2399.670	44.72	27.04	4.66	38.56	37.86	54.00	-16.14	Average
2399.670	59.94	27.04	4.66	38.56	53.08	74.00	-20.92	Peak

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	33.40	26.81	4.60	38.52	26.29	54.00	-27.71	Average
2310.000	46.27	26.81	4.60	38.52	39.16	74.00	-34.84	Peak
2390.000	34.83	27.01	4.65	38.56	27.93	54.00	-26.07	Average
2390.000	46.57	27.01	4.65	38.56	39.67	74.00	-34.33	Peak
2394.210	45.63	27.02	4.66	38.56	38.75	54.00	-15.25	Average
2394.210	59.75	27.02	4.66	38.56	52.87	74.00	-21.13	Peak
2400.000	40.33	27.04	4.66	38.56	33.47	54.00	-20.53	Average
2400.000	55.20	27.04	4.66	38.56	48.34	74.00	-25.66	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	47.73	27.26	4.52	38.59	40.92	54.00	-13.08	Average
2483.500	74.58	27.26	4.52	38.59	67.77	74.00	-6.23	Peak
2500.000	35.39	27.30	4.49	38.60	28.58	54.00	-25.42	Average
2500.000	55.70	27.30	4.49	38.60	48.89	74.00	-25.11	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	40.91	27.26	4.52	38.59	34.10	54.00	-19.90	Average
2483.500	65.08	27.26	4.52	38.59	58.27	74.00	-15.73	Peak
2500.000	34.06	27.30	4.49	38.60	27.25	54.00	-26.75	Average
2500.000	48.18	27.30	4.49	38.60	41.37	74.00	-32.63	Peak

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- For above 18GHz, no emission found


7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	2.509	Pass
Middle	2.495	Pass
Highest	2.485	Pass


Test plot as follows:



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----