

Label Design & Location

CPI by Howden 4410 Greenbriar Dr.
Stafford, TX, 77477

CE **FC** **UK** **ETL**
CA **US**
XXXX Intertek XXXXXXXX

Ex ia[ia] IIC T4 Ga
CLASS I, ZONE 0, AEx ia[ia] IIC T4 Ga
CLASS I, DIV 1, GROUPS A B C D, T4
Ex (1) G Ex ia[ia] IIC T4 Ga

ETL21CA104173915X ITS21UKEX0329X
ETL21ATEX0042X IECEX ETL21.0054X

CERTIFIED TO CSA STDs CONFORMS TO UL STDs
C22.2 #60079-0, 60079-11, 61010-1-12, 61010-1

INPUT: 3.6V (BATTERY), 24VDC --- 50mA
MODEL: PF2 -40° C ≤ Ta ≤ +60° C IP66
FCC ID: 2AZVT-PF2 IC: 30305-PF2

WIRE	CONNECTION	WIRE	CONNECTION
No. 1	ALARM OUTPUT 1	No. 7	MODBUS +
No. 2	ALARM OUTPUT 2	No. 8	MODBUS -
No. 3	24VDC INPUT +	No. 9	MODBUS GROUND
No. 4	24VDC INPUT -	No. 10	WARNING/PULSED OUTPUT 1
No. 5	PULSED INPUT 1	No. 11	WARNING/PULSED OUTPUT 2
No. 6	PULSED INPUT 2	No. 12	GROUND

REFERENCE INSTRUCTION MANUAL FOR ENTITY PARAMETERS AND PRODUCT DETAILS
MANUEL D'INSTRUCTIONS DE RÉFÉRENCE POUR LES PARAMÈTRES DE L'ENTITÉ ET LES DÉTAILS DU PRODUIT
INTRINSICALLY SAFE / SECURITE INTRINSEQUE
WARNING! DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
AVERTISSEMENT! NE PAS OUVRIR EN PRÉSENCE D'UNE ATMOSPHERE EXPLOSIVE

