


SELESTIA®
BREATHING LIGHT



SPECIFICATION

Input: 5V/1.5A (USB type-C)
Battery Capacity: 1500mAh
Bluetooth Distance: 10m (33 ft)
IP Rating: IP20
Dimensions: Ø 95 x 35mm
Firmware Updates: Connect Kaloud® Selestia® via USB to update the firmware.
The update software is only available for Windows.

KEY PARTS



AIR PRESSURE SENSOR
The air pressure sensor is located inside the Opening. Do not cover the Opening.

POWER ON/OFF
Press the power button for 2 seconds to start up Kaloud® Selestia®. Press the power button for 2 seconds to turn off.

MAINTENANCE
Charge Kaloud® Selestia® at least once per month or whenever needed.
Do not use alcohol wipes on the surface of the light.
Do not soak in water or allow water to enter any opening.

CHARGING INSTRUCTIONS
Connect Kaloud® Selestia® with the USB cord to a power source.
The LED at the center will pulse as the Kaloud® Selestia® charges.

● Battery below 30%
● Battery below 50%
● Battery below 85%
● Battery charged

POWER
Press Power Button for 2 seconds to turn on, press for 2 seconds to turn off.

PAIRING
Turn on Bluetooth on your device and inside the Kaloud® App search for your Selestia®.

READY
Once paired, you will be able to select from the Moods available in our App.
You can also change Moods by pressing the power button.

