



好天线·优比造

东莞市优比电子有限公司

Dongguan Youbi Electronics Co., Ltd

Antenna Specification

2.4/5.8G
PIFA Antenna

PN: UB01NP2D1087A

2.4 /5.8GHz Dual-band antenna

Dongguan Youbi Electronics Co.,LTD
Room 101, Building 2, No.9,
Xinfa Road, Lin Village, Tangxia Town
Tel: +86-769-81777126

Hangzhou Youbige Electronics Co.,LTD
Room 106, Building 3, Letong Science Park,
No.500 Qiuyi Road, Binjiang District
Website: www.ubuant.com


Shenzhen Youbi Electronics Co.,LTD
Room 106, Building A, Xinzheng Industrial Park,
57 Liuxian Road, Bao'an District, Shenzhen

Features

1. Size 15 X 7 X 6.19 X 0.4 mm³ steel piece built-in antenna.
2. low energy loss, high antenna efficiency.
3. High stability under temperature and humidity variations.

Applications

1. 2.4 / 5.8GHz band antenna application.
2. Bluetooth, wireless, smart home applications.


Structure**Size**


Three Views	Symbol	Size (mm)
	L	15 ± 0.2
	W	7 ± 0.2
	H	6.19 ± 0.2
	T	0.4 ± 0.1

Electrical Characteristics

UB01NP2D1087A	Specification
Working Frequency	2400-2500MHz 5150-5850MHz
Band Width	>100MHz
Impedance	50 Ω
Gain(dBi)	2
VSWR	<2
Operation Temperature	-40°C~+85°C
Power Capacity	3W


Antenna pads and alignment design






Matching Device Value	Series	22PF
	Shunt 1	NC
	Shunt 2	NC


Antenna test on test board (board thickness 0.6mm)



Antenna S11





Antenna VSWR





Efficiency and radiation maps



The performance such as efficiency, radiation pattern, gain, etc. are obtained based on the test board design. The specification data of the antenna is based on the test PCB size and the test orientation shown in the figure below. The following data were tested in the ETS 3D microwave darkroom.



Gain and efficiency	2.4G-2.5GHz	5.15G-5.85GHz
Peak Gain	2.7dBi	2.59dBi
Average Gain across the band	2.33dBi	2.24dBi
Gain Range across the band	2.07dBi~2.7dBi	1.75dBi~2.59dBi
Peak Efficiency	71.18%	66.78%
Average Efficiency across the band	69.36%	63.64%
Efficiency Range across the band	68.06%~71.18%	61.01%~66.78%





**包装****Storage Environment**

The following conditions should be met when storing the product:

Temperature : -10°C ~ +40°C

Humidity : 30% to 70% relative humidity

The location where the product is placed should not be exposed to corrosive gases, such as sulfur. Chlorine or acid may cause oxidation of product electrodes resulting in poor solderability.

The products should be placed in the tool box and avoid the influence of moisture and dust. Products should be stored in a warehouse and protected from heat, vibration and direct sunlight.

The products should be stored under airtight conditions.