

FCC TEST REPORT

FCC ID:2BA4Q-M12

Report No..... : ZHT-241223137W01-1

Product..... : INSMY M12 Speaker

Trademark..... : INSMY

Model(s)..... : INSMY-M12

Model Difference..... : /

Applicant..... : INSMY (HK) TECHNOLOGY LIMITED

Address..... : FLAT/RM B 5/F GAYLORD COMM BLDG 114-118 LOCKHART RD
HONGKONG

Manufacturer..... : Dongguan Siliang Electronic Technology Co., Ltd

Address..... : Room 101, Building 5, No.30 Dakan Road, Huangjiang Town, Dongguan
City, Guangdong Province

Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address..... : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai
Street, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt..... : Dec. 23, 2024

Date of Test(s)..... : Dec. 23, 2024 to Dec. 25, 2024


Date of Issue..... : Dec. 29, 2024

Test Standard(s)..... : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Test procedure..... : KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2013

In the configuration tested, the EUT complied with the standards specified above.

Tested by:



Kimi Lu/ Engineer

Reviewed by:



Baret Wu/ Director

Approved by:



Levi Lee/ Manager

Note: The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report shall not be reproduced except in full, without prior written approval of ZHT. This document may be altered or revised by ZHT, personnel only, and shall be noted in the revision of the document.

Table of Contents

	Page
1. VERSION	4
2. TEST SUMMARY	5
3. GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 Test Setup Configuration	7
3.3 Support Equipment	8
3.4 Test Mode	8
4. TEST FACILITY AND TEST INSTRUMENT USED	9
4.1 TEST FACILITY	9
4.2 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
4.3 Testing software	10
4.4 MEASUREMENT UNCERTAINTY	11
5. EMC EMISSION TEST	12
5.1 Conducted emissions	12
5.1.1 POWER LINE CONDUCTED EMISSION Limits	12
5.1.2 TEST PROCEDURE	12
5.1.3 DEVIATION FROM TEST STANDARD	12
5.1.4 TEST SETUP	13
5.1.5 EUT OPERATING CONDITIONS	13
5.1.6 Test Result	13
5.2 Radiated emissions	16
5.2.1 Radiated Emission Limits	16
5.2.2 TEST PROCEDURE	16
5.2.3 DEVIATION FROM TEST STANDARD	17
5.2.4 TEST SETUP	17
5.2.5 EUT OPERATING CONDITIONS	18
5.2.6 TEST RESULTS	19
6. RADIATED BAND EMISSION MEASUREMENT	27
6.1 Test Requirement	27
6.2 TEST PROCEDURE	27
6.3 DEVIATION FROM TEST STANDARD	28
6.4 TEST SETUP	28
6.5 EUT OPERATING CONDITIONS	28
6.6 TEST RESULT	29
7. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	31
7.1 Limit	31
7.2 Test Setup	31
7.3 Test procedure	31
7.4 DEVIATION FROM STANDARD	31
7.5 Test Result	32
8. 20DB&99% BANDWIDTH	56
8.1 Test Setup	56
8.2 Limit	56
8.3 Test procedure	56
8.4 DEVIATION FROM STANDARD	56
8.5 Test Result	56
9. MAXIMUM PEAK OUTPUT POWER	67
9.1 Block Diagram Of Test Setup	67
9.2 Limit	67
9.3 Test procedure	67
9.4 DEVIATION FROM STANDARD	67
9.5 Test Result	67
10. HOPPING CHANNEL SEPARATION	73
10.1 Test Setup	73
10.2 Test procedure	73



10.3 DEVIATION FROM STANDARD	73
10.4 Test Result	73
11.NUMBER OF HOPPING FREQUENCY	76
11.1 Test Setup	76
11.2 Test procedure	76
11.3 DEVIATION FROM STANDARD	76
11.4 Test Result	77
12. DWELL TIME	83
12.1 Test Setup	83
12.2 Test procedure	83
12.3 DEVIATION FROM STANDARD	83
12.4 Test Result	84
13. ANTENNA REQUIREMENT	94
14. TEST SETUP PHOTO	95
15. EUT CONSTRUCTIONAL DETAILS	95

1. VERSION

Report No.	Version	Description	Approved
ZHT-241223137W01-1	Rev.01	Initial issue of report	Dec. 29, 2024

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth 99% OCB	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission and Restricted Band	PASS	
15.247(d)	Conducted Unwanted emissions and Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	INSMY M12 Speaker
Test Model No.:	INSMY-M12
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	79
Operation Frequency:	2402MHz-2480MHz
Modulation technology:	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type:	PCB antenna
Antenna gain:	-0.58dBi
Power supply:	Input: 5V $\overline{=}$ 1A or DC 3.7V powered by battery
Sample Number:	241223137YP-001
Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Guangdong Zhonghan Testing Technology Co., Ltd. does not assume any responsibility.	

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 Test Setup Configuration

Conducted Emission

Adapter

EUT

Radiated Emission

EUT

3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Adapter	N/A	HW-059200CHQ	N/A	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) The test software is the Bluetooth RF Test Tool which can set the EUT into the individual test modes.TX Power:7

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

4. TEST FACILITY AND TEST INSTRUMENT USED

4.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

FCC Registration Number:255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

4.2 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	100874	May 10, 2024	May 09, 2025
2	Loop antenna	EMCI	LAP600	272	May 10, 2024	May 09, 2025
3	Amplifier	Schwarzbeck	BBV 9743 B	00378	May 10, 2024	May 09, 2025
4	Amplifier	Schwarzbeck	BBV 9718 B	00040	May 10, 2024	May 09, 2025
5	Bilog Antenna	Schwarzbeck	VULB9162	00498	May 28, 2024	May 27, 2025
6	Horn Antenna	Schwarzbeck	BBHA9120D	02623	May 16, 2024	May 15, 2025
7	Horn Antenna	A.H.SYSTEMS	SAS574	588	May 10, 2024	May 09, 2025
8	Amplifier	AEROFLEX	100KHz-40GHz	097	May 10, 2024	May 09, 2025
9	Spectrum Analyzer	R&S	FSV40	101413	May 16, 2024	May 15, 2025
10	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 10, 2024	May 09, 2025
11	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	109863	May 10, 2024	May 09, 2025
12	Single Generator	Agilent	N5182A	MY48180575	May 10, 2024	May 09, 2025
13	Power Sensor	MWRFTest	MW100-RFCB	/	May 10, 2024	May 09, 2025
14	CABLE	EMToni	DA800-NM-NM-11000MM	/	May 10, 2024	May 09, 2025

Conduction Test equipment

Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
Receiver	R&S	ESCI	100874	May 10, 2024	May 09, 2025
LISN	R&S	ENV216	102794	May 10, 2024	May 09, 2025
ISN CAT 6	Schwarzbeck	NTFM 8158	00318	May 10, 2024	May 09, 2025
ISN CAT 5	Schwarzbeck	CAT5 8158	00343	May 10, 2024	May 09, 2025
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	00101	May 10, 2024	May 09, 2025
Current Transformer Clamp	Schwarzbeck	SW 9605	SW9605 #209	May 10, 2024	May 09, 2025
CABLE	EMToni	G223-NM-BNCM -2000MM	/	May 10, 2024	May 09, 2025

Conducted Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	R&S	FSV40	101413	May 10, 2024	May 09, 2025
2	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 10, 2024	May 09, 2025
3	Power Sensor	MWRFTest	MW100-RFCB	/	May 10, 2024	May 09, 2025

4.3 Testing software

Project	Software name	Edition
RF Conducted	MTS 8310	2.0.0.0
Conducted Emission	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission	EZ-EMC	FA-03A2 RE+

4.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF conducted power	$\pm 0.16\text{dB}$
3	Conducted spurious emissions	$\pm 0.21\text{dB}$
4	All radiated emissions (9k-30MHz)	$\pm 4.68\text{dB}$
5	All radiated emissions (<1G)	$\pm 4.68\text{dB}$
6	All radiated emissions (>1G)	$\pm 4.89\text{dB}$
7	Temperature	$\pm 0.5^{\circ}\text{C}$
8	Humidity	$\pm 2\%$
9	Occupied Bandwidth	$\pm 4.96\text{dB}$

Decision Rule

- ☒ Uncertainty is not included
☐ Uncertainty is included

5. EMC EMISSION TEST

5.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207, RSS-Gen 8.8
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

5.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


5.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.1.3 DEVIATION FROM TEST STANDARD

No deviation

5.1.4 TEST SETUP




5.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

5.1.6 Test Result

Temperature:	24.3℃	Relative Humidity :	53.2%
Pressure:	1010kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1544	32.24	9.89	42.13	65.76	-23.63	QP	P	
2	0.1544	16.41	9.89	26.30	55.76	-29.46	AVG	P	
3	0.1635	30.94	9.90	40.84	65.28	-24.44	QP	P	
4	0.1635	16.86	9.90	26.76	55.28	-28.52	AVG	P	
5	0.1824	29.42	9.90	39.32	64.38	-25.06	QP	P	
6	0.1824	16.38	9.90	26.28	54.38	-28.10	AVG	P	
7	0.2040	28.93	9.91	38.84	63.45	-24.61	QP	P	
8	0.2040	13.42	9.91	23.33	53.45	-30.12	AVG	P	
9	0.3704	24.18	9.98	34.16	58.49	-24.33	QP	P	
10	0.3704	14.12	9.98	24.10	48.49	-24.39	AVG	P	
11 *	0.4560	26.72	10.01	36.73	56.77	-20.04	QP	P	
12	0.4560	15.88	10.01	25.89	46.77	-20.88	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 8DPSK mode(Middle Channel:2441MHz).



Temperature:	24.3℃	Relative Humidity :	53.2%
Pressure:	1010kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1545	32.09	9.89	41.98	65.75	-23.77	QP	P	
2	0.1545	18.11	9.89	28.00	55.75	-27.75	AVG	P	
3	0.3570	24.36	9.97	34.33	58.80	-24.47	QP	P	
4	0.3570	14.27	9.97	24.24	48.80	-24.56	AVG	P	
5	0.4335	25.96	10.00	35.96	57.19	-21.23	QP	P	
6	0.4335	23.01	10.00	33.01	47.19	-14.18	AVG	P	
7	0.4560	25.14	10.01	35.15	56.77	-21.62	QP	P	
8 *	0.4560	23.45	10.01	33.46	46.77	-13.31	AVG	P	
9	11.1750	29.40	10.08	39.48	60.00	-20.52	QP	P	
10	11.1750	19.71	10.08	29.79	50.00	-20.21	AVG	P	
11	15.3465	29.12	10.10	39.22	60.00	-20.78	QP	P	
12	15.3465	19.13	10.10	29.23	50.00	-20.77	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 8DPSK mode(Middle Channel:2441MHz).

5.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209, RSS-Gen 8.9, RSS-Gen 8.10				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	10Hz	Average

5.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.2.3 DEVIATION FROM TEST STANDARD


No deviation

5.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



5.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


5.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	25.2℃	Relative Humidity:	50%
Pressure:	1010kPa	Polarization:	Horizontal
Test Voltage:	DC 3.7 V		



Temperature:	25.2℃	Relative Humidity:	50%
Pressure:	1010kPa	Polarization:	Vertical
Test Voltage:	DC 3.7 V		



Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case 8DPSK mode(Middle Channel:2441MHz).

1GHz~25GHz

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	59.13	30.55	5.77	24.66	59.01	74	-14.99	Pk
V	4804.00	41.2	30.55	5.77	24.66	41.08	54	-12.92	AV
V	7206.00	59.37	30.33	6.32	24.55	59.91	74	-14.09	Pk
V	7206.00	43.21	30.33	6.32	24.55	43.75	54	-10.25	AV
V	9608.00	55.56	30.55	5.77	24.66	55.44	74	-18.56	Pk
V	9608.00	42.38	30.55	5.77	24.66	42.26	54	-11.74	AV
V	12010.00	57.98	30.33	6.32	24.55	58.52	74	-15.48	Pk
V	12010.00	41.63	30.33	6.32	24.55	42.17	54	-11.83	AV
H	4804.00	56.64	30.55	5.77	24.66	56.52	74	-17.48	Pk
H	4804.00	41.93	30.55	5.77	24.66	41.81	54	-12.19	AV
H	7206.00	56.91	30.33	6.32	24.55	57.45	74	-16.55	Pk
H	7206.00	43.3	30.33	6.32	24.55	43.84	54	-10.16	AV
H	9608.00	57.04	30.55	5.77	24.66	56.92	74	-17.08	Pk
H	9608.00	41.05	30.55	5.77	24.66	40.93	54	-13.07	AV
H	12010.00	55.54	30.33	6.32	24.55	56.08	74	-17.92	Pk
H	12010.00	41.71	30.33	6.32	24.55	42.25	54	-11.75	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	58.86	30.55	5.77	24.66	58.74	74	-15.26	Pk
V	4882.00	41.71	30.55	5.77	24.66	41.59	54	-12.41	AV
V	7323.00	56.66	30.33	6.32	24.55	57.2	74	-16.8	Pk
V	7323.00	43.62	30.33	6.32	24.55	44.16	54	-9.84	AV
V	9764.00	56.88	30.55	5.77	24.66	56.76	74	-17.24	Pk
V	9764.00	44.51	30.55	5.77	24.66	44.39	54	-9.61	AV
V	12205.00	55.77	30.33	6.32	24.55	56.31	74	-17.69	Pk
V	12205.00	41.49	30.33	6.32	24.55	42.03	54	-11.97	AV
H	4882.00	59.68	30.55	5.77	24.66	59.56	74	-14.44	Pk
H	4882.00	43.5	30.55	5.77	24.66	43.38	54	-10.62	AV
H	7323.00	57.83	30.33	6.32	24.55	58.37	74	-15.63	Pk
H	7323.00	42.03	30.33	6.32	24.55	42.57	54	-11.43	AV
H	9764.00	55.96	30.55	5.77	24.66	55.84	74	-18.16	Pk
H	9764.00	41.73	30.55	5.77	24.66	41.61	54	-12.39	AV
H	12205.00	57.83	30.33	6.32	24.55	58.37	74	-15.63	Pk
H	12205.00	41.8	30.33	6.32	24.55	42.34	54	-11.66	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	58.41	30.55	5.77	24.66	58.29	74	-15.71	Pk
V	4960.00	41.38	30.55	5.77	24.66	41.26	54	-12.74	AV
V	7440.00	57.72	30.33	6.32	24.55	58.26	74	-15.74	Pk
V	7440.00	41.12	30.33	6.32	24.55	41.66	54	-12.34	AV
V	9920.00	57.93	30.55	5.77	24.66	57.81	74	-16.19	Pk
V	9920.00	42	30.55	5.77	24.66	41.88	54	-12.12	AV
V	12400.00	57.29	30.33	6.32	24.55	57.83	74	-16.17	Pk
V	12400.00	41.45	30.33	6.32	24.55	41.99	54	-12.01	AV
H	4960.00	56.25	30.55	5.77	24.66	56.13	74	-17.87	Pk
H	4960.00	41.97	30.55	5.77	24.66	41.85	54	-12.15	AV
H	7440.00	59.23	30.33	6.32	24.55	59.77	74	-14.23	Pk
H	7440.00	41.78	30.33	6.32	24.55	42.32	54	-11.68	AV
H	9920.00	55.28	30.55	5.77	24.66	55.16	74	-18.84	Pk
H	9920.00	42.54	30.55	5.77	24.66	42.42	54	-11.58	AV
H	12400.00	55.1	30.33	6.32	24.55	55.64	74	-18.36	Pk
H	12400.00	44.56	30.33	6.32	24.55	45.1	54	-8.9	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

$\pi/4$ DQPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	56.28	30.55	5.77	24.66	56.16	74	-17.84	Pk
V	4804.00	41.67	30.55	5.77	24.66	41.55	54	-12.45	AV
V	7206.00	56.69	30.33	6.32	24.55	57.23	74	-16.77	Pk
V	7206.00	41.66	30.33	6.32	24.55	42.2	54	-11.8	AV
V	9608.00	58.78	30.55	5.77	24.66	58.66	74	-15.34	Pk
V	9608.00	42.06	30.55	5.77	24.66	41.94	54	-12.06	AV
V	12010.00	56.47	30.33	6.32	24.55	57.01	74	-16.99	Pk
V	12010.00	42.88	30.33	6.32	24.55	43.42	54	-10.58	AV
H	4804.00	55.11	30.55	5.77	24.66	54.99	74	-19.01	Pk
H	4804.00	41.03	30.55	5.77	24.66	40.91	54	-13.09	AV
H	7206.00	57.51	30.33	6.32	24.55	58.05	74	-15.95	Pk
H	7206.00	43.46	30.33	6.32	24.55	44	54	-10	AV
H	9608.00	56.42	30.55	5.77	24.66	56.3	74	-17.7	Pk
H	9608.00	41.13	30.55	5.77	24.66	41.01	54	-12.99	AV
H	12010.00	58.27	30.33	6.32	24.55	58.81	74	-15.19	Pk
H	12010.00	41.23	30.33	6.32	24.55	41.77	54	-12.23	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	58.01	30.55	5.77	24.66	57.89	74	-16.11	Pk
V	4882.00	41.95	30.55	5.77	24.66	41.83	54	-12.17	AV
V	7323.00	55.51	30.33	6.32	24.55	56.05	74	-17.95	Pk
V	7323.00	42.67	30.33	6.32	24.55	43.21	54	-10.79	AV
V	9764.00	57.21	30.55	5.77	24.66	57.09	74	-16.91	Pk
V	9764.00	44.94	30.55	5.77	24.66	44.82	54	-9.18	AV
V	12205.00	59.96	30.33	6.32	24.55	60.5	74	-13.5	Pk
V	12205.00	43.47	30.33	6.32	24.55	44.01	54	-9.99	AV
H	4882.00	55.95	30.55	5.77	24.66	55.83	74	-18.17	Pk
H	4882.00	44.5	30.55	5.77	24.66	44.38	54	-9.62	AV
H	7323.00	55.59	30.33	6.32	24.55	56.13	74	-17.87	Pk
H	7323.00	42.13	30.33	6.32	24.55	42.67	54	-11.33	AV
H	9764.00	59.1	30.55	5.77	24.66	58.98	74	-15.02	Pk
H	9764.00	41.04	30.55	5.77	24.66	40.92	54	-13.08	AV
H	12205.00	59.17	30.33	6.32	24.55	59.71	74	-14.29	Pk
H	12205.00	41.71	30.33	6.32	24.55	42.25	54	-11.75	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	58.18	30.55	5.77	24.66	58.06	74	-15.94	Pk
V	4960.00	41.17	30.55	5.77	24.66	41.05	54	-12.95	AV
V	7440.00	57.16	30.33	6.32	24.55	57.7	74	-16.3	Pk
V	7440.00	41.5	30.33	6.32	24.55	42.04	54	-11.96	AV
V	9920.00	58.56	30.55	5.77	24.66	58.44	74	-15.56	Pk
V	9920.00	41.53	30.55	5.77	24.66	41.41	54	-12.59	AV
V	12400.00	58.63	30.33	6.32	24.55	59.17	74	-14.83	Pk
V	12400.00	41.66	30.33	6.32	24.55	42.2	54	-11.8	AV
H	4960.00	55.72	30.55	5.77	24.66	55.6	74	-18.4	Pk
H	4960.00	41.9	30.55	5.77	24.66	41.78	54	-12.22	AV
H	7440.00	59.51	30.33	6.32	24.55	60.05	74	-13.95	Pk
H	7440.00	42.91	30.33	6.32	24.55	43.45	54	-10.55	AV
H	9920.00	56.35	30.55	5.77	24.66	56.23	74	-17.77	Pk
H	9920.00	43.73	30.55	5.77	24.66	43.61	54	-10.39	AV
H	12400.00	56.69	30.33	6.32	24.55	57.23	74	-16.77	Pk
H	12400.00	44.78	30.33	6.32	24.55	45.32	54	-8.68	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8DPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	56.48	30.55	5.77	24.66	56.36	74	-17.64	Pk
V	4804.00	42.97	30.55	5.77	24.66	42.85	54	-11.15	AV
V	7206.00	56.27	30.33	6.32	24.55	56.81	74	-17.19	Pk
V	7206.00	41.86	30.33	6.32	24.55	42.4	54	-11.6	AV
V	9608.00	57.12	30.55	5.77	24.66	57	74	-17	Pk
V	9608.00	42.45	30.55	5.77	24.66	42.33	54	-11.67	AV
V	12010.00	57.03	30.33	6.32	24.55	57.57	74	-16.43	Pk
V	12010.00	42.39	30.33	6.32	24.55	42.93	54	-11.07	AV
H	4804.00	58.84	30.55	5.77	24.66	58.72	74	-15.28	Pk
H	4804.00	42	30.55	5.77	24.66	41.88	54	-12.12	AV
H	7206.00	58.43	30.33	6.32	24.55	58.97	74	-15.03	Pk
H	7206.00	41.33	30.33	6.32	24.55	41.87	54	-12.13	AV
H	9608.00	58.93	30.55	5.77	24.66	58.81	74	-15.19	Pk
H	9608.00	41.34	30.55	5.77	24.66	41.22	54	-12.78	AV
H	12010.00	58.82	30.33	6.32	24.55	59.36	74	-14.64	Pk
H	12010.00	41.72	30.33	6.32	24.55	42.26	54	-11.74	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882.00	57.74	30.55	5.77	24.66	57.62	74	-16.38	Pk
V	4882.00	41.96	30.55	5.77	24.66	41.84	54	-12.16	AV
V	7323.00	56.08	30.33	6.32	24.55	56.62	74	-17.38	Pk
V	7323.00	42.04	30.33	6.32	24.55	42.58	54	-11.42	AV
V	9764.00	59.68	30.55	5.77	24.66	59.56	74	-14.44	Pk
V	9764.00	43.48	30.55	5.77	24.66	43.36	54	-10.64	AV
V	12205.00	56.69	30.33	6.32	24.55	57.23	74	-16.77	Pk
V	12205.00	44.55	30.33	6.32	24.55	45.09	54	-8.91	AV
H	4882.00	55.89	30.55	5.77	24.66	55.77	74	-18.23	Pk
H	4882.00	44.71	30.55	5.77	24.66	44.59	54	-9.41	AV
H	7323.00	58.48	30.33	6.32	24.55	59.02	74	-14.98	Pk
H	7323.00	42.1	30.33	6.32	24.55	42.64	54	-11.36	AV
H	9764.00	55.31	30.55	5.77	24.66	55.19	74	-18.81	Pk
H	9764.00	42.46	30.55	5.77	24.66	42.34	54	-11.66	AV
H	12205.00	57.81	30.33	6.32	24.55	58.35	74	-15.65	Pk
H	12205.00	41.21	30.33	6.32	24.55	41.75	54	-12.25	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	56.04	30.55	5.77	24.66	55.92	74	-18.08	Pk
V	4960.00	41.8	30.55	5.77	24.66	41.68	54	-12.32	AV
V	7440.00	56.01	30.33	6.32	24.55	56.55	74	-17.45	Pk
V	7440.00	43.77	30.33	6.32	24.55	44.31	54	-9.69	AV
V	9920.00	58.4	30.55	5.77	24.66	58.28	74	-15.72	Pk
V	9920.00	41.7	30.55	5.77	24.66	41.58	54	-12.42	AV
V	12400.00	58.62	30.33	6.32	24.55	59.16	74	-14.84	Pk
V	12400.00	41.49	30.33	6.32	24.55	42.03	54	-11.97	AV
H	4960.00	55.49	30.55	5.77	24.66	55.37	74	-18.63	Pk
H	4960.00	41.53	30.55	5.77	24.66	41.41	54	-12.59	AV
H	7440.00	55.25	30.33	6.32	24.55	55.79	74	-18.21	Pk
H	7440.00	41.33	30.33	6.32	24.55	41.87	54	-12.13	AV
H	9920.00	58.73	30.55	5.77	24.66	58.61	74	-15.39	Pk
H	9920.00	42.82	30.55	5.77	24.66	42.7	54	-11.3	AV
H	12400.00	56.43	30.33	6.32	24.55	56.97	74	-17.03	Pk
H	12400.00	44.4	30.33	6.32	24.55	44.94	54	-9.06	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

6. RADIATED BAND EMISSION MEASUREMENT

6.1 Test Requirement

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen 8.9, RSS-Gen 8.10				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

6.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

6.3 DEVIATION FROM TEST STANDARD

No deviation

6.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



6.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Margi n (dB)	Detec tor Type	Result
GFSK	Low Channel: 2402MHz										
	H	2390.00	60.37	30.22	4.85	23.98	58.98	74.00	-15.02	PK	PASS
	H	2390.00	47.73	30.22	4.85	23.98	46.34	54.00	-7.66	AV	PASS
	H	2400.00	61.84	30.22	4.85	23.98	60.45	74.00	-13.55	PK	PASS
	H	2400.00	48.38	30.22	4.85	23.98	46.99	54.00	-7.01	AV	PASS
	V	2390.00	61.17	30.22	4.85	23.98	59.78	74.00	-14.22	PK	PASS
	V	2390.00	46.92	30.22	4.85	23.98	45.53	54.00	-8.47	AV	PASS
	V	2400.00	59.82	30.22	4.85	23.98	58.43	74.00	-15.57	PK	PASS
	V	2400.00	47.17	30.22	4.85	23.98	45.78	54.00	-8.22	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	60.83	30.22	4.85	23.98	59.44	74.00	-14.56	PK	PASS
	H	2483.50	48.55	30.22	4.85	23.98	47.16	54.00	-6.84	AV	PASS
	H	2500.00	62.26	30.22	4.85	23.98	60.87	74.00	-13.13	PK	PASS
	H	2500.00	46.53	30.22	4.85	23.98	45.14	54.00	-8.86	AV	PASS
	V	2483.50	61.43	30.22	4.85	23.98	60.04	74.00	-13.96	PK	PASS
	V	2483.50	48.17	30.22	4.85	23.98	46.78	54.00	-7.22	AV	PASS
	V	2500.00	62.85	30.22	4.85	23.98	61.46	74.00	-12.54	PK	PASS
	V	2500.00	46.99	30.22	4.85	23.98	45.60	54.00	-8.40	AV	PASS
$\pi/4$ DQPS K	Low Channel: 2402MHz										
	H	2390.00	61.75	30.22	4.85	23.98	60.36	74.00	-13.64	PK	PASS
	H	2390.00	46.41	30.22	4.85	23.98	45.02	54.00	-8.98	AV	PASS
	H	2400.00	62.03	30.22	4.85	23.98	60.64	74.00	-13.36	PK	PASS
	H	2400.00	47.68	30.22	4.85	23.98	46.29	54.00	-7.71	AV	PASS
	V	2390.00	62.48	30.22	4.85	23.98	61.09	74.00	-12.91	PK	PASS
	V	2390.00	48.66	30.22	4.85	23.98	47.27	54.00	-6.73	AV	PASS
	V	2400.00	62.95	30.22	4.85	23.98	61.56	74.00	-12.44	PK	PASS
	V	2400.00	47.65	30.22	4.85	23.98	46.26	54.00	-7.74	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	61.38	30.22	4.85	23.98	59.99	74.00	-14.01	PK	PASS
	H	2483.50	46.42	30.22	4.85	23.98	45.03	54.00	-8.97	AV	PASS
	H	2500.00	59.68	30.22	4.85	23.98	58.29	74.00	-15.71	PK	PASS
	H	2500.00	47.33	30.22	4.85	23.98	45.94	54.00	-8.06	AV	PASS
	V	2483.50	62.67	30.22	4.85	23.98	61.28	74.00	-12.72	PK	PASS
	V	2483.50	47.41	30.22	4.85	23.98	46.02	54.00	-7.98	AV	PASS
	V	2500.00	61.71	30.22	4.85	23.98	60.32	74.00	-13.68	PK	PASS
	V	2500.00	46.09	30.22	4.85	23.98	44.70	54.00	-9.30	AV	PASS
8DPSK	Low Channel: 2402MHz										
	H	2390.00	60.69	30.22	4.85	23.98	59.30	74.00	-14.70	PK	PASS
	H	2390.00	48.83	30.22	4.85	23.98	47.44	54.00	-6.56	AV	PASS
	H	2400.00	61.57	30.22	4.85	23.98	60.18	74.00	-13.82	PK	PASS
	H	2400.00	47.80	30.22	4.85	23.98	46.41	54.00	-7.59	AV	PASS
	V	2390.00	59.99	30.22	4.85	23.98	58.60	74.00	-15.40	PK	PASS
	V	2390.00	48.16	30.22	4.85	23.98	46.77	54.00	-7.23	AV	PASS
	V	2400.00	59.47	30.22	4.85	23.98	58.08	74.00	-15.92	PK	PASS
	V	2400.00	46.29	30.22	4.85	23.98	44.90	54.00	-9.10	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	59.30	30.22	4.85	23.98	57.91	74.00	-16.09	PK	PASS
	H	2483.50	46.37	30.22	4.85	23.98	44.98	54.00	-9.02	AV	PASS
	H	2500.00	60.00	30.22	4.85	23.98	58.61	74.00	-15.39	PK	PASS
	H	2500.00	48.98	30.22	4.85	23.98	47.59	54.00	-6.41	AV	PASS
	V	2483.50	62.48	30.22	4.85	23.98	61.09	74.00	-12.91	PK	PASS
	V	2483.50	47.55	30.22	4.85	23.98	46.16	54.00	-7.84	AV	PASS



	V	2500.00	60.61	30.22	4.85	23.98	59.22	74.00	-14.78	PK	PASS
	V	2500.00	46.82	30.22	4.85	23.98	45.43	54.00	-8.57	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

7. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d), RSS-247 5.5
Test Method:	ANSI C63.10

7.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

According to RSS-247§5.5 and RSS-Gen§8.9, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) or RSS-Gen is not required.

7.2 Test Setup



7.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Band Edge


Mode	Frequency (MHz)	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	No-Hopping	-35.97	-20	Pass
1-DH5	2480	No-Hopping	-43.71	-20	Pass
2-DH5	2402	No-Hopping	-40.18	-20	Pass
2-DH5	2480	No-Hopping	-41.79	-20	Pass
3-DH5	2402	No-Hopping	-36.81	-20	Pass
3-DH5	2480	No-Hopping	-44.18	-20	Pass



Test Graphs



Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission









Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission





Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission






Band Edge(Hopping)


Mode	Frequency (MHz)	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	Hopping	-56.5	-20	Pass
1-DH5	2480	Hopping	-43.26	-20	Pass
2-DH5	2402	Hopping	-57.68	-20	Pass
2-DH5	2480	Hopping	-44.66	-20	Pass
3-DH5	2402	Hopping	-54.09	-20	Pass
3-DH5	2480	Hopping	-40.79	-20	Pass

Test Graphs


Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission





Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission






Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission




Conducted RF Spurious Emission


Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	-38.63	-20	Pass
1-DH5	2441	-40.36	-20	Pass
1-DH5	2480	-41.39	-20	Pass
2-DH5	2402	-43.11	-20	Pass
2-DH5	2441	-43.45	-20	Pass
2-DH5	2480	-39.17	-20	Pass
3-DH5	2402	-39.71	-20	Pass
3-DH5	2441	-40.4	-20	Pass
3-DH5	2480	-41.48	-20	Pass

Test Graphs


Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission




Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission



8. 20DB&99% BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(1), RSS 247 5.1, RSS-Gen 6.7
Test Method:	ANSI C63.10:2013

8.1 Test Setup



8.2 Limit

According to RSS-247§5.1(a)& §5.1(b), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

8.3 Test procedure

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
8. The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30KHz RBW and 100 KHz VBW record the 99% bandwidth.

8.4 DEVIATION FROM STANDARD


No deviation.

8.5 Test Result


Mode	Test channel	20dB Emission Bandwidth (MHz)	99%Bandwidth (MHz)	Result
GFSK	Lowest	0.951	0.870	Pass
	Middle	0.948	0.862	
	Highest	0.957	0.883	
$\pi/4$ DQPSK	Lowest	1.391	1.296	Pass
	Middle	1.335	1.286	
	Highest	1.316	1.233	
8DPSK	Lowest	1.333	1.268	Pass
	Middle	1.332	1.278	
	Highest	1.322	1.256	



Test Graphs



-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1







-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1















OBW NVNT 1-DH5 2441MHz Ant1







OBW NVNT 2-DH5 2441MHz Ant1




OBW NVNT 2-DH5 2480MHz Ant1




OBW NVNT 3-DH5 2402MHz Ant1



OBW NVNT 3-DH5 2441MHz Ant1





9. Maximum Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1), RSS 247 5.4 (b)
Test Method:	ANSI C63.10:2013

9.1 Block Diagram Of Test Setup



9.2 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W.

9.3 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 2MHz. VBW =6MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

9.4 DEVIATION FROM STANDARD


No deviation.

9.5 Test Result


Mode	Test channel	Peak Output Power (dBm)	Peak Output Power Limit (dBm)	Result
GFSK	Lowest	5.20	21.00	Pass
	Middle	5.52		
	Highest	5.31		
$\pi/4$ DQPSK	Lowest	5.47	21.00	Pass
	Middle	5.81		
	Highest	5.64		
8DPSK	Lowest	5.53	21.00	Pass
	Middle	5.91		
	Highest	5.73		




Peak Power NVNT 1-DH5 2480MHz Ant1




Peak Power NVNT 2-DH5 2402MHz Ant1




Peak Power NVNT 2-DH5 2441MHz Ant1




Peak Power NVNT 2-DH5 2480MHz Ant1




Peak Power NVNT 3-DH5 2402MHz Ant1



Peak Power NVNT 3-DH5 2441MHz Ant1





10. HOPPING CHANNEL SEPARATION

Test Requirement:	FCC Part15 C Section 15.247 (a)(1), RSS 247 5.1
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=300KHz, VBW=300KHz, detector=Peak
Limit:	GFSK, $\pi/4$ -DQPSK & 8DSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

10.1 Test Setup



10.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 300kHz. VBW = 300kHz , Span = 2.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

10.3 DEVIATION FROM STANDARD


No deviation.

10.4 Test Result


Modulation	Separation (MHz)	Limit(MHz)	Result
GFSK	1.01	0.87	PASS
$\pi/4$ DQPSK	1	0.927	PASS
8DPSK	1.006	0.889	PASS


Test Graphs

CFS NVNT 1-DH5 2402MHz Ant1



CFS NVNT 2-DH5 2402MHz Ant1





11.NUMBER OF HOPPING FREQUENCY

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii), RSS-247 5.1
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels

11.1 Test Setup



11.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

11.3 DEVIATION FROM STANDARD


No deviation.

11.4 Test Result


Mode	Antenna	Hopping Number	Limit	Verdict
1-DH5	Ant1	79	15	Pass
2-DH5	Ant1	79	15	Pass
3-DH5	Ant1	79	15	Pass

Test Graphs


Hopping No. NVNT 1-DH5 2402MHz Ant1




Hopping No. NVNT 1-DH5 2441MHz Ant1




Hopping No. NVNT 1-DH5 2480MHz Ant1



Hopping No. NVNT 2-DH5 2402MHz Ant1




Hopping No. NVNT 2-DH5 2441MHz Ant1




Hopping No. NVNT 2-DH5 2480MHz Ant1




Hopping No. NVNT 3-DH5 2402MHz Ant1



Hopping No. NVNT 3-DH5 2441MHz Ant1





12. DWELL TIME

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii), RSS-247 5.1
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second

12.1 Test Setup



12.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0Hz;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

12.3 DEVIATION FROM STANDARD

No deviation.

12.4 Test Result


Mode	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
1-DH1	0.382	120.712	316	31600	400	Pass
1-DH3	1.639	254.045	155	31600	400	Pass
1-DH5	2.887	303.135	105	31600	400	Pass
2-DH1	0.391	195.891	501	31600	400	Pass
2-DH3	1.644	259.752	158	31600	400	Pass
2-DH5	2.886	343.434	119	31600	400	Pass
3-DH1	0.392	125.048	319	31600	400	Pass
3-DH3	1.642	254.51	155	31600	400	Pass
3-DH5	2.894	283.612	98	31600	400	Pass



Test Graphs

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated







Dwell NVNT 1-DH5 2441MHz Ant1 One Burst




Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated







Dwell NVNT 2-DH1 2441MHz Ant1 One Burst




Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated











Dwell NVNT 3-DH1 2441MHz Ant1 One Burst



Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated







13. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4), RSS-Gen 6.8
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the licence-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. Licence-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (EIRP) limits specified in the applicable standard (RSS) for the licence-exempt apparatus. Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.9 When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.	
EUT Antenna:	
The antenna is PCB antenna, the best case gain of the antennas is -0.58dBi, reference to the appendix II for details	

14. Test Setup Photo

Reference to the appendix I for details.

15. EUT Constructional Details

Reference to the appendix II for details.

***** END OF REPORT *****