

2023-07-01

We, NanJing CukTech Electronics Technology Co.,Ltd, hereby declares that the item 2 of the following requirements as listed in the section 5(b) of the KDB680106 D01 RF Exposure Wireless Charging is not satisfied.

(1) Power transfer frequency is less than 1 MHz

Answer: Yes, the frequency range far less than 1MHz

(2) Output power from each primary coil is less than or equal to 15 watts.

Answer: No, the maximum wireless transfer power is up to 20W

(3) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.

Answer: Yes, this device contains one coil only.

(4) Client device is placed directly in contact with the transmitter.

Answer: Yes, Client device is placed directly in contact with the transmitter when in normal use.

(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Answer: Yes, Mobile exposure conditions only.

(6) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.

Answer: Yes, the maximum H-field less than 50% of the applicable MPE limit, refer to EMF Report.



(Signature)

Yang_ Chen
(Print name)

On behalf of:

NanJing CukTech Electronics Technology Co., Ltd.
(Company Name)