

**Shenzhen Sing-E Intl Development Co., Ltd**  
208, Bldg a, Maker center, Enterprise business network, Huarong Road, Dalang, Longhua,  
Shenzhen, China

---

**Date: June 26, 2023**

**FCC ID: 2BA67-JQS1220**

**Model Number: JQS1220, ZQS1317, ZQS1450, ZQS2211**

To: Federal Communication Commission  
Authorization and Evaluation Division 7435 Oakland Mills Road  
Columbia, MD 21048

To Whom It May Concern,

We, **Shenzhen Sing-E Intl Development Co., Ltd** hereby declare that our product  
(**colourful crescent moon Bluetooth speaker**) Model Number: **JQS1220, ZQS1317,**  
**ZQS1450, ZQS2211** meet item 5.2 of KDB 680106v03r01 as follow;

| Requirements of KDB 680106 D01                                                                                                                                                                                                                                                                       | Yes / No | Description                                                                                                                                                                               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power transfer frequency is less than 1 MHz                                                                                                                                                                                                                                                          | Yes      | The device operate in the frequency range is 110.5 KHz – 205 KHz                                                                                                                          |
| Output power from each primary coil is less than or equal to 15 watts.                                                                                                                                                                                                                               | Yes      | The maximum output power of the primary coil is 5W                                                                                                                                        |
| The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.                                                                                                             | Yes      | The transfer system includes single coil that able to detect receiver device                                                                                                              |
| Client device is placed directly in contact with the transmitter.                                                                                                                                                                                                                                    | Yes      | Client device is placed directly in contact with the transmitter                                                                                                                          |
| Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).                                                                                                                                                                                                    | Yes      | Mobile exposure condition only                                                                                                                                                            |
| The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit. | Yes      | The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit. |

Please contact me if you have any question.

***Shenzhen Sing-E Intl Development Co., Ltd***

*208, Bldg a, Maker center, Enterprise business network, Huarong Road, Dalang, Longhua,  
Shenzhen, China*

---

Sincerely,

A handwritten signature in black ink that reads "Vincent". The script is cursive and fluid, with the first letter 'V' being particularly large and stylized.

(Signed)

Name/Title: Vincent Liu / Sales Director & Co-Founder

Company: Shenzhen Sing-E Intl Development Co., Ltd

Address: 208, Bldg a, Maker center, Enterprise business network, Huarong Road, Dalang,  
Longhua, Shenzhen, China

Tel: +86-18565678273

Fax: n/a

E-Mail: [bvincent@ising-e.com](mailto:bvincent@ising-e.com)