




Shenzhen Yingjia Chuang electronic technology Co., LTD

<http://www.szsyjc.com>

APPROVAL SHEET

CUSTOMER NAME		
CUSTOMER P/N		
PART NAME	2.4G onboard antenna	
P/ N		
APPROVAL REV.	A0	
DELIVERY DATE	January 10, 2022	
PREPARED BY	Wu Jiaxiong	
CHECKED BY	Fang Wenfeng	
APPROVED BY	Chauhan	
Customer Approved		
Prepared By	Checked By	Approved By

Address: Building C, Hongyu Guangming Valley, No. 11, Youma Gang Road, Ma Tian Street, Guangming District, Shenzhen
Dongguan Branch: Yingjiachuang Industrial Park, No. 2 Yinhe 3rd Road, Shishuikou, Qiaotou Town, Dongguan City
Hangzhou Office: 212, Building B, Dahua Jianghong International Innovation Park, 369 Internet of Things Street, Binjiang District, Hangzhou
Mianyang Office: No. 4F-34 Wanxiang High-tech International, No. 35 Mianxing East Road, Mianyang High-tech Zone, Sichuan Province
telephone : 0755-27810060 fax : 0755-27810057 website : <http://www.szsyjc.com>

[illegible]




Revise your resume:

edition	Changes and reasons	date	publish
A0	Initial release	January 10, 2022	



Antenna plan:





Antenna technical parameters and environmental testing:

Electrical technical parameter			
Electrical Specifications		Mechanical Specifications	
VSWR	<1.92	Input connector	0P
Input Impedance	50 Ω	Working Temperature	-20℃~+70℃
Direction	All	Working Humidity	20~80%
Gain	2.04dBi		

Environmental performance test:

Project	Test condition	Standard
Storage Conditions	In the absence of specified test temperature, humidity, air pressure is as follows:: 1. Temperature is - 30 °C ~ + 80 °C 2. Relative humidity of 45% to 45% 3. Air pressure is 86 kpa to 106 kpa	Electrical and mechanical performace is normal
High and low temperature test	Between 70 °C and -20 °C for 5 loops, then 1-2 h under normal conditions, check the appearance quality.	Size should meet the requirements and meet the performance of mechinery and electric.
Constant damp and hot resistance test	95 + / - 3% relative humidity, temperature test: 40 °C. Lasts 2 h after, try to take out the determination of electrical properties, within 5 min after try 1-2 h under article normal thing, check the appearance quality	Size should meet the requirements and meet the performance of mechinery and electric.
vibration test	10-55 hz, vibration frequency range of displacement amplitude: 0.35 MM, acceleration amplitude: 50.0 M/S, sweep cycles: 30 times	Electrical and mechanical performace is normal
Fall down test	1 m high altitude in accordance with the perpendicular axis free drop 3 times	Electrical and mechanical performace is normal



Antenna performance test diagram:




2D and 3D test data (2.4G):


Frequency	Efficiency (%)	Gain. (dBi)
2400MHz	44.36	1.7
2410MHz	46.95	1.87
2420MHz	45.27	1.74
2430MHz	47.35	1.82
2440MHz	48.16	1.82
2450MHz	54.1	2.04
2460MHz	52.32	1.93
2470MHz	50.71	1.71
2480MHz	48.42	1.82
2490MHz	47.1	1.75
2500MHz	47.97	1.71




Phi 0 2D 图:




Phi 90 2D 图




Theta 90 2D



3D 2400:



3D 2450:



3D 2500

