



**Above 1GHz**

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Horizontal										
<b>Test Mode:</b>	TX B Mode 2412MHz										
No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector				
1 *	10919.500	44.70	-1.79	42.91	74.00	-31.09	peak				
2	14362.000	42.18	0.73	42.91	74.00	-31.09	peak				

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB<sub>u</sub>V/m)= Corr. (dB/m)+ Read Level (dB<sub>u</sub>V)
3. Margin (dB) = Peak/AVG (dB<sub>u</sub>V/m)-Limit PK/AVG(dB<sub>u</sub>V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Vertical										
<b>Test Mode:</b>	TX B Mode 2412MHz										
No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector				
1	10868.500	44.14	-1.93	42.21	74.00	-31.79	peak				
2 *	13214.500	43.38	-0.20	43.18	74.00	-30.82	peak				

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB<sub>u</sub>V/m)= Corr. (dB/m)+ Read Level (dB<sub>u</sub>V)
3. Margin (dB) = Peak/AVG (dB<sub>u</sub>V/m)-Limit PK/AVG(dB<sub>u</sub>V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.



<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Horizontal										
<b>Test Mode:</b>	TX B Mode 2437MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Vertical										
<b>Test Mode:</b>	TX B Mode 2437MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											



<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Horizontal										
<b>Test Mode:</b>	TX B Mode 2462MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Vertical										
<b>Test Mode:</b>	TX B Mode 2462MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											



<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Horizontal										
<b>Test Mode:</b>	TX G Mode 2412MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Vertical										
<b>Test Mode:</b>	TX G Mode 2412MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											



<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%																											
<b>Test Voltage:</b>	AC 120V/60HZ																														
<b>Ant. Pol.</b>	Horizontal																														
<b>Test Mode:</b>	TX G Mode 2437MHz																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB<sub>u</sub>V)</th> <th>Factor (dB/m)</th> <th>Level (dB<sub>u</sub>V/m)</th> <th>Limit (dB<sub>u</sub>V/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10817.500</td> <td>45.22</td> <td>-2.17</td> <td>43.05</td> <td>74.00</td> <td>-30.95</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>14362.000</td> <td>43.18</td> <td>0.73</td> <td>43.91</td> <td>74.00</td> <td>-30.09</td> <td>peak</td> </tr> </tbody> </table>								No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector	1	10817.500	45.22	-2.17	43.05	74.00	-30.95	peak	2 *	14362.000	43.18	0.73	43.91	74.00	-30.09	peak
No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector																								
1	10817.500	45.22	-2.17	43.05	74.00	-30.95	peak																								
2 *	14362.000	43.18	0.73	43.91	74.00	-30.09	peak																								
<b>Remark:</b> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB <sub>u</sub> V/m)= Corr. (dB/m)+ Read Level (dB <sub>u</sub> V) 3. Margin (dB) = Peak/AVG (dB <sub>u</sub> V/m)-Limit PK/AVG(dB <sub>u</sub> V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit.																															

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%																											
<b>Test Voltage:</b>	AC 120V/60HZ																														
<b>Ant. Pol.</b>	Vertical																														
<b>Test Mode:</b>	TX G Mode 2437MHz																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB<sub>u</sub>V)</th> <th>Factor (dB/m)</th> <th>Level (dB<sub>u</sub>V/m)</th> <th>Limit (dB<sub>u</sub>V/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10843.000</td> <td>44.77</td> <td>-2.04</td> <td>42.73</td> <td>74.00</td> <td>-31.27</td> <td>peak</td> </tr> <tr> <td>2</td> <td>14362.000</td> <td>41.56</td> <td>0.73</td> <td>42.29</td> <td>74.00</td> <td>-31.71</td> <td>peak</td> </tr> </tbody> </table>								No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector	1 *	10843.000	44.77	-2.04	42.73	74.00	-31.27	peak	2	14362.000	41.56	0.73	42.29	74.00	-31.71	peak
No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector																								
1 *	10843.000	44.77	-2.04	42.73	74.00	-31.27	peak																								
2	14362.000	41.56	0.73	42.29	74.00	-31.71	peak																								
<b>Remark:</b> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB <sub>u</sub> V/m)= Corr. (dB/m)+ Read Level (dB <sub>u</sub> V) 3. Margin (dB) = Peak/AVG (dB <sub>u</sub> V/m)-Limit PK/AVG(dB <sub>u</sub> V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit.																															



<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%			
<b>Test Voltage:</b>	AC 120V/60HZ						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX G Mode 2462MHz						
<b>No.</b>	<b>Frequency (MHz)</b>	<b>Reading (dB<sub>u</sub>V)</b>	<b>Factor (dB/m)</b>	<b>Level (dB<sub>u</sub>V/m)</b>	<b>Limit (dB<sub>u</sub>V/m)</b>	<b>Margin (dB)</b>	<b>Detector</b>
1	10817.500	44.62	-2.17	42.45	74.00	-31.55	peak
2 *	13954.000	42.20	0.70	42.90	74.00	-31.10	peak

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB<sub>u</sub>V/m)= Corr. (dB/m)+ Read Level (dB<sub>u</sub>V)
3. Margin (dB) = Peak/AVG (dB<sub>u</sub>V/m)-Limit PK/AVG(dB<sub>u</sub>V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%			
<b>Test Voltage:</b>	AC 120V/60HZ						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX G Mode 2462MHz						
<b>No.</b>	<b>Frequency (MHz)</b>	<b>Reading (dB<sub>u</sub>V)</b>	<b>Factor (dB/m)</b>	<b>Level (dB<sub>u</sub>V/m)</b>	<b>Limit (dB<sub>u</sub>V/m)</b>	<b>Margin (dB)</b>	<b>Detector</b>
1 *	10817.500	45.40	-2.17	43.23	74.00	-30.77	peak
2	14387.500	41.95	0.91	42.86	74.00	-31.14	peak

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB<sub>u</sub>V/m)= Corr. (dB/m)+ Read Level (dB<sub>u</sub>V)
3. Margin (dB) = Peak/AVG (dB<sub>u</sub>V/m)-Limit PK/AVG(dB<sub>u</sub>V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.
5. No report for the emission which more than 20dB below the prescribed limit.



<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Horizontal										
<b>Test Mode:</b>	TX n(HT20) Mode 2412MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Vertical										
<b>Test Mode:</b>	TX n(HT20) Mode 2412MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											



<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Horizontal										
<b>Test Mode:</b>	TX n(HT20) Mode 2437MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing as been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	AC 120V/60HZ										
<b>Ant. Pol.</b>	Vertical										
<b>Test Mode:</b>	TX n(HT20) Mode 2437MHz										
<b>Remark:</b>											
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)											
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)											
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)											
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency.											
5. No report for the emission which more than 20dB below the prescribed limit.											



<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%																											
<b>Test Voltage:</b>	AC 120V/60HZ																														
<b>Ant. Pol.</b>	Horizontal																														
<b>Test Mode:</b>	TX n(HT20) Mode 2462MHz																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB<sub>u</sub>V)</th> <th>Factor (dB/m)</th> <th>Level (dB<sub>u</sub>V/m)</th> <th>Limit (dB<sub>u</sub>V/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10945.000</td> <td>44.32</td> <td>-1.80</td> <td>42.52</td> <td>74.00</td> <td>-31.48</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>13979.500</td> <td>43.02</td> <td>0.54</td> <td>43.56</td> <td>74.00</td> <td>-30.44</td> <td>peak</td> </tr> </tbody> </table>								No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector	1	10945.000	44.32	-1.80	42.52	74.00	-31.48	peak	2 *	13979.500	43.02	0.54	43.56	74.00	-30.44	peak
No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector																								
1	10945.000	44.32	-1.80	42.52	74.00	-31.48	peak																								
2 *	13979.500	43.02	0.54	43.56	74.00	-30.44	peak																								
<b>Remark:</b> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB <sub>u</sub> V/m)= Corr. (dB/m)+ Read Level (dB <sub>u</sub> V) 3. Margin (dB) = Peak/AVG (dB <sub>u</sub> V/m)-Limit PK/AVG(dB <sub>u</sub> V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit.																															

<b>Temperature:</b>	25.5°C		<b>Relative Humidity:</b>	55%																											
<b>Test Voltage:</b>	AC 120V/60HZ																														
<b>Ant. Pol.</b>	Vertical																														
<b>Test Mode:</b>	TX n(HT20) Mode 2462MHz																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB<sub>u</sub>V)</th> <th>Factor (dB/m)</th> <th>Level (dB<sub>u</sub>V/m)</th> <th>Limit (dB<sub>u</sub>V/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10868.500</td> <td>44.45</td> <td>-1.93</td> <td>42.52</td> <td>74.00</td> <td>-31.48</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>13265.500</td> <td>42.95</td> <td>-0.20</td> <td>42.75</td> <td>74.00</td> <td>-31.25</td> <td>peak</td> </tr> </tbody> </table>								No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector	1	10868.500	44.45	-1.93	42.52	74.00	-31.48	peak	2 *	13265.500	42.95	-0.20	42.75	74.00	-31.25	peak
No.	Frequency (MHz)	Reading (dB <sub>u</sub> V)	Factor (dB/m)	Level (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Detector																								
1	10868.500	44.45	-1.93	42.52	74.00	-31.48	peak																								
2 *	13265.500	42.95	-0.20	42.75	74.00	-31.25	peak																								
<b>Remark:</b> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB <sub>u</sub> V/m)= Corr. (dB/m)+ Read Level (dB <sub>u</sub> V) 3. Margin (dB) = Peak/AVG (dB <sub>u</sub> V/m)-Limit PK/AVG(dB <sub>u</sub> V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. 5. No report for the emission which more than 20dB below the prescribed limit.																															

-----END OF THE REPORT-----

