



WLT8016M Antenna specification

ANT Model: WLT8016M

Max. Gain: -0.06dBi

Frequency band: 2400-2500MHz

manufacturer: Wi-linktech Communication Technologies(Shanghai) Co.,Ltd.


最新版本 V1.3

维霖通(上海)通信技术有限公司


COPYRIGHT © 2011 - 2023

1.overview

This antenna specification document describes the RF performance of the WLT8016M module onboard antenna, ensuring that when connected to a 50 ohm source, the VSWR is less than 3 in the 2.4 GHz ISM frequency band, and the gain maps of the antenna in different directions, as well as the antenna efficiency and gain values in different frequency bands.



1- 1 : WLT8016M




WLT8016M Module antenna size

2.Test equipment

测试设备 / Equipment

auden



- Chamber : GTS Rayzone1800
- 网络分析仪 : Agilent E5071C
- 2G/3G综测仪 : Agilent 8960
- LTE综测仪 : Anritsu MT8820
- TD综测仪 : StarPoint SP6010
- WIFI综测仪 : Anritsu MT8860
- GPS信号源 : Agilent E4438C




VS


2

Company Confidential, Auden
Many aspects of this presentation are protected by US, TW, CN and international patents and patent applications

3.Return loss、 VSWR




VSWR




Return loss

4. Direction and gain diagram


Etheta[Unit:dBi]




Ephi[Unit:dBi]



增益: -1.90dBi



增益: -0.72dBi



增益: -0.06dBi

5. Antenna gain table

Frequency / MHz	Efficiency / %	Gain/ dBi
2400	22.29	-1.90
2410	24.61	-1.52
2420	26.72	-1.15
2430	28.62	-0.77
2440	27.97	-0.72
2450	30.65	-0.17
2460	30.04	-0.16
2470	28.77	-0.17
2480	28.70	-0.06
2490	26.38	-0.34
2500	25.77	-0.40