

TEST REPORT

Product Name : SELFIE STICK
Model Number : ONNTR439-BLK, 36014093
FCC ID : 2BA9O-TR439

Prepared for : ZhongShan Junwang Electronic Technology Limited
Address : 5/F, Bldg.B, 146 Tanshen South Rd., Tanzhou,
Zhongshan, Guangdong 528467, China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

TEL:(0755) 26954280
FAX:(0755) 26954282

Report Number : ENS2506260141W00502R
Date of sample receipt : Jun 26, 2025
Date(s) of Tests : Jun 26, 2025 to Jul 18, 2025
Date of issue : Jul 18, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : ZhongShan Junwang Electronic Technology Limited
Address : 5/F, Bldg.B,146 Tanshen South Rd., Tanzhou, Zhongshan, Guangdong 528467, China
Manufacturer : ZhongShan Junwang Electronic Technology Limited
Address : 5/F, Bldg.B,146 Tanshen South Rd., Tanzhou, Zhongshan, Guangdong 528467, China
Factory : LTB Electronic Technology Limited
Address : 5/F,Bldg.B,146 Tanshen South Rd., Tanzhou, Zhongshan, Guangdong 528467, China
EUT : SELFIE STICK
Model Name : ONNTR439-BLK, 36014093
Trademark : onn

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Jun 26, 2025 to Jul 18, 2025

Prepared by : 
Una Yu /Editor

Reviewer : 
Joe Xia/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2506260141W00502R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	SELFIE STICK
Model Number:	ONNTR439-BLK, 36014093 All products are identical except the model numbe.Here we selected ONNTR439-BLK for all the test.
Sample:	2#
Device Type:	BLE
Data Rate:	1Mbps for GFSK modulation
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	40 channels
Transmit Power Max:	1.41 dBm(0.001384 W)
Antenna Type:	PCB Antenna
Antenna Gain:	1.81 dBi
Power supply:	DC 3.0V from battery
Evaluation applied:	☐ MPE Evaluation ☒ SAR Evaluation

3. Test Requirement:

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain:1.81 dBi

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	EIRP (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	Calculation threshold(1-g SAR)
2402	GFSK(1M)	1.41	3.22	3±1	4	0.7786	3
2440	GFSK(1M)	0.87	2.68	2±1	3	0.6233	3
2480	GFSK(1M)	-0.25	1.56	1±1	2	0.4992	3

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

*** End of Report ***

